



BobSim

Suspension Kinematics and Compliance (KnC) Characterization

Heave and Roll Sweeps

Generated: 2026-04-14 18:35

BobDyn

– These results include heave and roll sweeps to evaluate key suspension parameters such as camber, toe, caster, KPI, trail, scrub, motion ratio, and jacking characteristics.

KnC Metrics Summary

Heave Gains

Camber	0.4557	rad/m
Toe	-0.0019	rad/m
Caster	-0.0390	rad/m
KPI	0.4551	rad/m
Trail	-0.0011	m/m
Scrub	0.0018	m/m

Anti & Balance

Anti-Dive	2.5	%
Anti-Squat	-5.3	%
Front Anti-Roll	-0.8	%
Rear Anti-Roll	-0.9	%
Anti Balance (F/R)	0.77	-
LLTD (Front)	52.2	%

Roll Gains

Camber	0.7245	rad/rad
Toe	0.0013	rad/rad
Caster	0.0344	rad/rad
KPI	0.7249	rad/rad
Trail	-0.0015	m/rad
Scrub	0.0026	m/rad

Motion Ratios


Front MR	0.991	-
Rear MR	1.251	-
Front Bar MR	0.127	-
Rear Bar MR	0.155	-

Roll Stiffness


Spring Front	21983	Nm/rad
Spring Rear	12888	Nm/rad
ARB Front	46328	Nm/rad
ARB Rear	49753	Nm/rad
Total Front	68311	Nm/rad
Total Rear	62641	Nm/rad

Camber vs Heave


Front Left




Front Right



Rear Left




Rear Right




Toe vs Heave


Front Left




Front Right



Rear Left




Rear Right




Caster vs Heave


Front Left




Front Right



Rear Left




Rear Right




KPI vs Heave


Front Left




Front Right



Rear Left




Rear Right




Mechanical Trail vs Heave


Front Left




Front Right



Rear Left




Rear Right




Mechanical Scrub vs Heave


Front Left




Front Right



Rear Left




Rear Right




Motion Ratio vs Heave


Front Left




Front Right



Rear Left




Rear Right




Anti vs Heave

Front




Rear




Camber vs Roll


Front Left




Front Right



Rear Left




Rear Right




Toe vs Roll


Front Left




Front Right



Rear Left




Rear Right




Caster vs Roll


Front Left




Front Right



Rear Left




Rear Right




KPI vs Roll


Front Left




Front Right



Rear Left




Rear Right




Mechanical Trail vs Roll


Front Left




Front Right



Rear Left




Rear Right




Mechanical Scrub vs Roll


Front Left




Front Right



Rear Left




Rear Right




Stabar Motion Ratio vs Roll



Front




Rear



Geometric Anti-Roll vs Roll



Anti Balance vs Roll



LLTD vs Roll

