

# CHEAT SHEETS

A Complete Reference for Python Desktop GUIs

- Windows
- Widgets
- Text
- pack · grid · place
- Events & Bindings
- Menus & Dialogs
- ttk Themes & Styles
- Treeview
- Canvas
- Threading
- CustomTkinter
- PyInstaller

## 62 REFERENCE SHEETS

CONTENTS

| FOUNDATIONS |                      | INTERACTION & LOOK |                    | BUILDING APPS |                        |
|-------------|----------------------|--------------------|--------------------|---------------|------------------------|
| 01-03       | Introduction & Setup | 21-26              | Variables & Events | 47-49         | Colors, Fonts & Images |
| 04-06       | Windows              | 27-32              | Menus & Dialogs    | 50-57         | Application Patterns   |
| 07-15       | Classic Widgets      | 33-41              | ttk Themed Widgets | 58-60         | External Libraries     |
| 16-20       | Layout Managers      | 42-46              | Canvas             | 61-62         | Quick Reference        |



|                              |                                |                              |                               |                              |                             |
|------------------------------|--------------------------------|------------------------------|-------------------------------|------------------------------|-----------------------------|
| INTRODUCTION & SETUP01 – 03  |                                |                              | TTK THEMED WIDGETS33 – 41     |                              |                             |
| 01Tkinter Introduction & ... | 02Installation & Setup         | 03First App & Program St...  | 33ttk Introduction & The...   | 34ttk.Style — configure &... | 35ttk Layouts & Elements    |
| WINDOWS04 – 06               |                                |                              | 36ttk Core Widgets & Sta...   | 37Combobox & ttk.Spinb...    | 38Notebook & ttk.Paned...   |
| 04Root Window Setup          | 05Toplevel Windows & Lif...    | 06Window State & Positi...   | 39Progressbar, Separator...   | 40Treeview — Basics          | 41Treeview — Selection, ... |
| CLASSIC WIDGETS07 – 15       |                                |                              | CANVAS42 – 46                 |                              |                             |
| 07Widget Options & Con...    | 08Label & Button               | 09Entry                      | 42Canvas Basics & Shap...     | 43Canvas Items & Tags        | 44Canvas Text, Images & ... |
| 10Text Widget — Basics       | 11Text Widget — Tags, M...     | 12Checkbutton & Radiob...    | 45Canvas Events & Drag...     | 46Canvas Scrolling & Ani...  |                             |
| 13Listbox & Scrollbar        | 14Scale, Spinbox & Optio...    | 15Frame, LabelFrame & P...   |                               |                              |                             |
| LAYOUT MANAGERS16 – 20       |                                |                              | COLORS, FONTS & IMAGES47 – 49 |                              |                             |
| 16pack()                     | 17grid() — Basics              | 18grid() — Resizing & Wei... | 47Colors, Reliefs & Borde...  | 48Fonts                      | 49Images — PhotoImage ...   |
| 19place()                    | 20Layout Patterns & Pitfa...   |                              |                               |                              |                             |
| VARIABLES & EVENTS21 – 26    |                                |                              | APPLICATION PATTERNS50 – 57   |                              |                             |
| 21Control Variables          | 22Command Callbacks            | 23bind() & Event Sequen...   | 50after() & Timers            | 51Threading & Responsiv...   | 52Input Validation          |
| 24The Event Object           | 25Binding Levels & Virtua...   | 26Focus & Keyboard Nav...    | 53Scrollable Frames           | 54Application Architectu...  | 55DPI & Cross-Platform ...  |
| MENUS & DIALOGS27 – 32       |                                |                              | 56Testing & Debugging         | 57Packaging & Distributi...  |                             |
| 27Menu Bars                  | 28Menu Items & Context ...     | 29messagebox                 | EXTERNAL LIBRARIES58 – 60     |                              |                             |
| 30filedialog                 | 31simplifiedialog & colorch... | 32Custom Modal Dialogs       | 58Modern Themes — sv-...      | 59CustomTkinter              | 60Embedding Matplotlib ...  |
|                              |                                |                              | QUICK REFERENCE61 – 62        |                              |                             |
|                              |                                |                              | 61Quick Reference — Wi...     | 62Quick Reference — Eve...   |                             |

## WHAT TKINTER IS

**Tkinter** is Python's standard GUI toolkit: a thin Python layer over **Tcl/Tk**, a cross-platform widget library from the early 1990s. Every Tkinter call is translated into a Tcl command run by an embedded Tcl interpreter. It ships with the official Python installers, so a desktop app needs no third-party packages. Two widget sets live side by side: the **classic** tkinter widgets (fully customizable colors) and the **themed** `tkinter.ttk` widgets (native look per platform).

## NOTES

- › Tk = the widget toolkit; Tcl = the scripting language that drives it
- › `tkinter.ttk` arrived in Python 2.7/3.1 (Tk 8.5)
- › Tk 8.6 is the long-standing baseline; Tk 9.0 shipped in 2024
- › `tkinter.tix` was deprecated in 3.6 and removed in 3.13
- › Docs: [docs.python.org/3/library/tkinter.html](https://docs.python.org/3/library/tkinter.html) and [tkdocs.com](https://tkdocs.com)

## CLASSIC VS THEMED WIDGETS

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.title("Hello Tkinter")

# Classic widget: every color and border is an option
tk.Label(root, text="Classic tk.Label",
         bg="navy", fg="white").pack(padx=10, pady=5)

# Themed widget: look comes from the active ttk theme
ttk.Label(root, text="Themed ttk.Label").pack(padx=10, pady=5)
ttk.Button(root, text="Quit", command=root.destroy).pack(pady=5)

# Peek at the Tcl/Tk underneath
print(tk.TkVersion, tk.TclVersion)      # e.g. 8.6 8.6
print(root.tk.call("info", "patchlevel")) # e.g. 8.6.15

root.mainloop()
```

## CODE EXPLAINED

- `import tkinter as tk` is the conventional alias
- `ttk` widgets replace most classic widgets with themed versions
- `bg / fg` work on classic widgets; `ttk` uses styles instead
- `root.tk.call()` sends a raw Tcl command to the interpreter
- `mainloop()` hands control to Tk until the window closes

## TIMELINE

| YEAR | MILESTONE                               |
|------|-----------------------------------------|
| 1988 | Tcl created by John Ousterhout          |
| 1991 | Tk released on top of Tcl               |
| 1994 | Tkinter added to Python                 |
| 2007 | Tk 8.5 adds the ttk themed widgets      |
| 2012 | Tk 8.6 (Python's long-running baseline) |
| 2024 | Tk 9.0 released                         |

## KEY MODULES

| MODULE                          | PURPOSE                                     |
|---------------------------------|---------------------------------------------|
| <code>tkinter</code>            | Core widgets, <code>Tk()</code> , variables |
| <code>tkinter.ttk</code>        | Themed widgets and Style                    |
| <code>tkinter.messagebox</code> | Standard alert dialogs                      |
| <code>tkinter.filedialog</code> | Open/save file pickers                      |
| <code>tkinter.font</code>       | Font objects and metrics                    |
| <code>tkinter.constants</code>  | END, LEFT, BOTH, ...                        |

## ALTERNATIVES

| TOOLKIT                                          | TRADE-OFF                     |
|--------------------------------------------------|-------------------------------|
| <a href="#">PyQt</a> / <a href="#">PySide</a>    | Rich, large; GPL or LGPL      |
| <a href="#">wxPython</a>                         | Native widgets; extra install |
| <a href="#">Kivy</a>                             | Touch/mobile; custom look     |
| <a href="#">Dear PyGui</a>                       | GPU-drawn, tool-style UIs     |
| <a href="#">Toga</a> ( <a href="#">BeeWare</a> ) | Native, mobile targets        |
| <a href="#">Tkinter</a>                          | Built in, small, simple       |

## △ COMMON MISTAKES

- › Naming your script `tkinter.py`, which shadows the real module
- › Using Python 2 imports: `Tkinter` and `ttk` are gone
- › Expecting `bg=` to recolor `ttk` widgets

## ✓ TIPS &amp; BEST PRACTICES

- › Prefer `ttk` widgets for a native look; drop to classic for full color control
- › Learn from [tkdocs.com](https://tkdocs.com); it covers modern `ttk` usage
- › Check `tk.TkVersion` when a feature depends on Tk 8.6 vs 9.0

## QUICK SUMMARY

- › Python wrapper around Tcl/Tk
- › Ships with Python; no install on Windows/macOS
- › Classic `tk` + themed `ttk` widget sets
- › Event-driven: build widgets, then `mainloop()`

## GETTING TKINTER RUNNING

On **Windows** and **macOS**, the python.org installers include Tcl/Tk, so `import tkinter` works immediately. Most **Linux** distributions split it into a separate package, and Homebrew's Python needs `python-tk`. The fastest health check is `python -m tkinter`, which opens a small demo window showing the Tk version. Inside a virtual environment, Tkinter comes from the base interpreter. It is not on PyPI, so `pip install tkinter` never works.

## NOTES

- › A `ModuleNotFoundError: _tkinter` means Tk libraries are missing
- › pyenv builds need Tk dev headers installed before `pyenv install`
- › conda environments include `tk` by default
- › WSL2 on Windows 11 can show Tk windows through WSLg
- › Headless servers need a display (or Xvfb) to create windows

## CHECK, INSTALL, IMPORT

```
# 1. Health check: opens a demo window with the Tk version
python -m tkinter

# 2. Install when missing
sudo apt install python3-tk          # Debian / Ubuntu
sudo dnf install python3-tkinter    # Fedora
sudo pacman -S tk                   # Arch
brew install python-tk@3.13         # Homebrew Python

# 3. Versions from Python
python -c "import tkinter as tk; print(tk.TkVersion)"
python -c "import tkinter; tkinter._test()"

# 4. Standard imports in your code
# import tkinter as tk
# from tkinter import ttk, messagebox, filedialog
```

## CODE EXPLAINED

- `python -m tkinter` runs the module's built-in test window
- Distro packages add the `_tkinter` C extension and Tk libraries
- Homebrew's formula is versioned to match your Python
- `tk.TkVersion` is a float like `8.6` or `9.0`
- Submodules such as `ttk` must be imported explicitly

## INSTALL BY PLATFORM

| PLATFORM      | HOW                                      |
|---------------|------------------------------------------|
| Windows       | python.org installer (Tcl/Tk box ticked) |
| macOS         | python.org installer includes Tk         |
| Homebrew      | <code>brew install python-tk@3.x</code>  |
| Debian/Ubuntu | <code>apt install python3-tk</code>      |
| Fedora        | <code>dnf install python3-tkinter</code> |
| conda         | Included; <code>conda install tk</code>  |

## IMPORT STYLES

| IMPORT                     | USE                                  |
|----------------------------|--------------------------------------|
| <code>tkinter as tk</code> | Recommended; clear prefix            |
| <code>ttk</code>           | <code>from tkinter import ttk</code> |
| <code>*</code>             | Short demos only                     |
| <code>constants</code>     | END, LEFT, BOTH, ...                 |
| <code>tkinter.font</code>  | <code>import ... as tkfont</code>    |

## VERSION CHECKS

| CHECK                        | RETURNS                   |
|------------------------------|---------------------------|
| <code>tk.TkVersion</code>    | 8.6 (float)               |
| <code>tk.TclVersion</code>   | 8.6 (float)               |
| <code>info patchlevel</code> | Full Tk version, '8.6.15' |
| <code>windowingsystem</code> | win32 / aqua / x11        |

## COMMON MISTAKES

- › Running `pip install tkinter` (it is not on PyPI)
- › Using `from tkinter import *` and then shadowing names like `Image`
- › Forgetting `from tkinter import ttk`; `tk.ttk` is not auto-imported

## TIPS &amp; BEST PRACTICES

- › Run `python -m tkinter` first whenever imports fail
- › Use `import tkinter as tk` so tk vs ttk widgets stay obvious
- › Rebuild pyenv Pythons after installing `tk-dev`

## QUICK SUMMARY

- › Bundled on Windows and macOS installers
- › Separate package on most Linux distros
- › Test with `python -m tkinter`
- › Import as `tk`, plus `ttk` explicitly

## YOUR FIRST APPLICATION

Every Tkinter app follows the same shape: create **one** `Tk()` root window, build widgets with a **parent** (the master they live inside), place each one with a **geometry manager**, then call `mainloop()`. `mainloop()` blocks and processes events until the window closes. For anything past a demo, wrap the UI in a **class**, either subclassing `tk.Tk` for the app or `ttk.Frame` for a reusable panel, so widgets and callbacks share state through `self`.

## NOTES

- › Only one `Tk()` per program; extra windows use `Toplevel`
- › A widget isn't visible until a geometry manager places it
- › Code after `mainloop()` runs only after the window closes
- › `root.destroy()` closes the window and ends `mainloop()`
- › Keep references to widgets you need to read or update later

## CLASS-BASED APP SKELETON

```
import tkinter as tk
from tkinter import ttk

class App(tk.Tk):
    def __init__(self):
        super().__init__()
        self.title("Greeter")
        self.geometry("300x120")

        self.name = tk.StringVar()
        ttk.Label(self, text="Name:").grid(row=0, column=0, padx=8, pady=8)
        ttk.Entry(self, textvariable=self.name).grid(row=0, column=1)
        ttk.Button(self, text="Greet", command=self.greet).grid(
            row=1, column=0, columnspan=2)
        self.out = ttk.Label(self)
        self.out.grid(row=2, column=0, columnspan=2, pady=8)

    def greet(self):
        self.out.config(text=f"Hello, {self.name.get() or 'world'}!")

if __name__ == "__main__":
    App().mainloop()
```

## CODE EXPLAINED

- Subclassing `tk.Tk` makes the app object the root window
- `StringVar` links the Entry text to Python
- Widgets take the parent as their first argument (`self`)
- `command=self.greet` passes the method, not its result
- The `__main__` guard lets the module be imported safely

## APP LIFECYCLE

| STEP          | CALL                                                             |
|---------------|------------------------------------------------------------------|
| Create root   | <code>root = tk.Tk()</code>                                      |
| Configure     | <code>title()</code> , <code>geometry()</code>                   |
| Build widgets | <code>ttk.Button(root, ...)</code>                               |
| Place widgets | <code>pack()</code> / <code>grid()</code> / <code>place()</code> |
| Run           | <code>root.mainloop()</code>                                     |

## STRUCTURE OPTIONS

| PATTERN                             | WHEN               |
|-------------------------------------|--------------------|
| Script, no class                    | Tiny demos         |
| <code>class App(tk.Tk)</code>       | Single-window app  |
| <code>class Panel(ttk.Frame)</code> | Reusable section   |
| App + Frame pages                   | Multi-screen app   |
| Separate model module               | Logic you can test |

## KEY TERMS

| TERM             | MEANING                                                     |
|------------------|-------------------------------------------------------------|
| root             | The main Tk window                                          |
| master / parent  | Widget that contains another                                |
| widget           | Any UI element                                              |
| geometry manager | <code>pack</code> , <code>grid</code> or <code>place</code> |
| event loop       | <code>mainloop()</code> dispatching events                  |

## COMMON MISTAKES

- › Writing `command=self.greet()`, which calls it once at startup
- › Chaining `x = ttk.Entry(...).grid(); x` becomes `None`
- › Creating a second `tk.Tk()` instead of a `Toplevel`

## TIPS &amp; BEST PRACTICES

- › Create and place widgets on separate lines when you keep a reference
- › Put each screen in its own `ttk.Frame` subclass
- › Keep business logic out of callbacks so it can be tested

## QUICK SUMMARY

- › One `Tk()` root per app
- › Create widget → place it → `mainloop()`
- › Subclass `tk.Tk` or `ttk.Frame` for structure
- › Pass callbacks without parentheses

## CONFIGURING THE MAIN WINDOW

The root `Tk()` object is a window with its own set of **window-manager (wm) methods**. They control the title bar, size, position, size limits, icon and stacking. `geometry()` takes a string `"WIDTHxHEIGHT+X+Y"` where any part can be left out. Most of these calls are **requests** to the operating system's window manager, so results can vary slightly between Windows, macOS and Linux desktops.

## NOTES

- › All wm methods also exist on `Toplevel` windows
- › Sizes are in pixels; positions are from the screen's top-left
- › Without `geometry()`, the window sizes itself to fit its widgets
- › `wm_title()` is the long name for `title()`
- › Call with no arguments to read the current value

## ROOT WINDOW SETUP

```
import tkinter as tk

root = tk.Tk()
root.title("Inventory Manager")
root.geometry("640x400+100+80")    # W x H + X + Y
root.minsize(400, 250)             # user can't shrink below this
root.maxsize(1200, 900)
root.resizable(True, False)        # width yes, height no

icon = tk.PhotoImage(file="app.png")
root.iconphoto(True, icon)         # True = default for all windows

root.attributes("-topmost", True)  # keep above other windows
root.configure(bg="#1e1e2e")       # classic background color

print(root.title())                # 'Inventory Manager'
root.update_idletasks()
print(root.winfo_width(), root.winfo_height())

root.mainloop()
```

## CODE EXPLAINED

- `geometry()` sets size and position in one string
- `minsize / maxsize` bound manual resizing
- `resizable(width, height)` takes two booleans
- `iconphoto(True, ...)` applies the icon to future Toplevels too
- `update_idletasks()` makes `winfo_*` report real sizes

## GEOMETRY() STRINGS

| STRING        | EFFECT               |
|---------------|----------------------|
| "640x400"     | Size only            |
| "+100+80"     | Position only        |
| "640x400+0+0" | Size at top-left     |
| "-0-0"        | Bottom-right corner  |
| ""            | Back to natural size |

## WINDOW METHODS

| METHOD                         | PURPOSE               |
|--------------------------------|-----------------------|
| <code>title(s)</code>          | Title bar text        |
| <code>minsize(w, h)</code>     | Smallest size         |
| <code>maxsize(w, h)</code>     | Largest size          |
| <code>resizable(w, h)</code>   | Allow resizing        |
| <code>iconphoto(d, img)</code> | Window icon (PNG/GIF) |
| <code>iconbitmap(f)</code>     | Windows .ico icon     |

## ATTRIBUTES()

| OPTION                   | EFFECT                    |
|--------------------------|---------------------------|
| <code>-topmost</code>    | Stay above others         |
| <code>-alpha</code>      | Opacity 0.0–1.0           |
| <code>-fullscreen</code> | Full screen               |
| <code>-disabled</code>   | Block input (Windows)     |
| <code>-toolwindow</code> | Small title bar (Windows) |
| <code>-type</code>       | Window type hint (X11)    |

## △ COMMON MISTAKES

- › Writing `geometry(640, 400)`; it takes one string
- › Reading `winfo_width()` before the window is drawn (returns 1)
- › Using `.ico` with `iconphoto`; it needs a `PhotoImage`

## ✓ TIPS &amp; BEST PRACTICES

- › Set `minsize` so layouts never collapse
- › Use `iconbitmap('app.ico')` on Windows for the taskbar icon
- › Keep a reference to the icon image object

## QUICK SUMMARY

- › `title`, `geometry`, `minsize`, `resizable`
- › `"WxH+X+Y"` geometry strings
- › `attributes()` for `topmost/alpha/fullscreen`
- › `wm` calls are requests to the OS

## EXTRA WINDOWS WITH TOPLEVEL

A `tk.Toplevel` is an additional window that belongs to the same application and the same event loop as the root. It accepts the same `wm` methods as the root. `transient(parent)` marks it as a child window (no taskbar entry, stays above its parent). `protocol("WM_DELETE_WINDOW", handler)` intercepts the close button, so you can confirm or clean up first. Destroying the **root** destroys every `Toplevel`; destroying a `Toplevel` only removes that window.

## NOTES

- › Never create a second `Tk()`; use `Toplevel`
- › `destroy()` removes a window and all its child widgets
- › `quit()` stops `mainloop()` but leaves windows alive
- › `wininfo_exists()` checks whether a window is still open
- › A `Toplevel` can be reused by hiding it with `withdraw()`

## OPENING AND CLOSING A TOPLEVEL

```
import tkinter as tk
from tkinter import ttk, messagebox

class App(tk.Tk):
    def __init__(self):
        super().__init__()
        self.settings = None
        ttk.Button(self, text="Settings...",
                   command=self.open_settings).pack(padx=20, pady=20)
        self.protocol("WM_DELETE_WINDOW", self.on_close)

    def open_settings(self):
        if self.settings and self.settings.wininfo_exists():
            self.settings.lift()           # already open: bring to front
            return
        self.settings = win = tk.Toplevel(self)
        win.title("Settings")
        win.transient(self)                # child of the main window
        ttk.Label(win, text="Options go here").pack(padx=30, pady=20)
        ttk.Button(win, text="Close", command=win.destroy).pack(pady=8)

    def on_close(self):
        if messagebox.askokcancel("Quit", "Exit the app?", parent=self):
            self.destroy()

App().mainloop()
```

## CODE EXPLAINED

- `wininfo_exists()` prevents opening duplicate windows
- `lift()` raises an existing window instead
- `transient(self)` ties the window to the main one
- `win.destroy` closes only the `Toplevel`
- `protocol` replaces the default close behavior

## LIFECYCLE CALLS

| CALL                          | EFFECT                   |
|-------------------------------|--------------------------|
| <code>Toplevel(parent)</code> | New window               |
| <code>destroy()</code>        | Remove window + children |
| <code>withdraw()</code>       | Hide, keep alive         |
| <code>deiconify()</code>      | Show again               |
| <code>quit()</code>           | Exit mainloop only       |

## PROTOCOL() NAMES

| NAME                          | WHEN                   |
|-------------------------------|------------------------|
| <code>WM_DELETE_WINDOW</code> | Close button clicked   |
| <code>WM_TAKE_FOCUS</code>    | WM gives focus (X11)   |
| <code>WM_SAVE_YOURSELF</code> | Session save (old X11) |

## DESTROY VS QUIT

| ASPECT                | DESTROY() / QUIT()         |
|-----------------------|----------------------------|
| Windows               | Removed / stay open        |
| <code>mainloop</code> | Ends / ends                |
| Widgets usable        | No / yes                   |
| Typical use           | Close app / embedded loops |

## ⚠ COMMON MISTAKES

- › Opening a new `Toplevel` on every click without checking
- › Using `quit()` to close; windows remain on screen
- › Forgetting `self.destroy()` inside a custom close handler

## ✓ TIPS &amp; BEST PRACTICES

- › Store the `Toplevel` on `self` so you can reuse or check it
- › Pass `parent=` to dialogs so they center on the right window
- › Use `transient()` for tool and settings windows

## QUICK SUMMARY

- › `Toplevel` = extra window, same app
- › `transient()` for child windows
- › `protocol("WM_DELETE_WINDOW", fn)` intercepts close
- › `destroy()` removes, `quit()` just stops the loop

## PLACING AND SHOWING WINDOWS

To place a window precisely, ask Tk for the **screen size** with `wininfo_screenwidth()`/`wininfo_screenheight()` and compute the position. A window can be **normal**, **iconic** (minimized), **withdrawn** (hidden, no taskbar entry) or **zoomed** (maximized; Windows and macOS). `overriddenirect(True)` removes the title bar and border, which suits splash screens.

## NOTES

- › Call `update_idletasks()` before measuring a new window
- › On Linux, maximize with `attributes("-zoomed", True)`
- › Frameless windows can't be moved or closed by the user
- › `wininfo_x()` / `wininfo_y()` give the window's current position
- › Multi-monitor setups report the primary or combined screen

## CENTER, MINIMIZE, HIDE, RESTORE

```
import tkinter as tk

def center(win, w, h):
    win.update_idletasks()
    sw, sh = win.wininfo_screenwidth(), win.wininfo_screenheight()
    x, y = (sw - w) // 2, (sh - h) // 3
    win.geometry(f'{w}x{h}+{x}+{y}')

root = tk.Tk()
center(root, 500, 300)

print(root.state())           # 'normal'
root.iconify()                # minimize to taskbar
root.deiconify()              # restore
root.state("zoomed")          # maximize (Windows/macOS)
# Splash screen: no title bar, semi-transparent
splash = tk.Toplevel(root)
splash.overriddenirect(True)
splash.attributes("-alpha", 0.9)
tk.Label(splash, text="Loading...", padx=40, pady=30).pack()
center(splash, 200, 100)
root.withdraw()               # hide main window meanwhile
root.after(1500, lambda: (splash.destroy(), root.deiconify()))
root.mainloop()
```

## CODE EXPLAINED

- Screen size minus window size, halved, gives a centered origin
- Dividing height by 3 sits slightly above center
- `state()` reads or sets normal/iconic/withdrawn/zoomed
- `overriddenirect(True)` removes the window decorations
- `after(1500, ...)` swaps splash for main window

## WINDOW STATES

| STATE()                | MEANING              |
|------------------------|----------------------|
| <code>normal</code>    | Visible, regular     |
| <code>iconic</code>    | Minimized            |
| <code>withdrawn</code> | Hidden entirely      |
| <code>zoomed</code>    | Maximized (Win/mac)  |
| <code>icon</code>      | Shown as icon (rare) |

## SCREEN QUERIES

| METHOD                                              | RETURNS            |
|-----------------------------------------------------|--------------------|
| <code>wininfo_screenwidth()</code>                  | Screen width px    |
| <code>wininfo_screenheight()</code>                 | Screen height px   |
| <code>wininfo_x()</code> , <code>wininfo_y()</code> | Window position    |
| <code>wininfo_rootx()</code>                        | Widget x on screen |
| <code>wininfo_pointerxy()</code>                    | Mouse position     |

## SHOW / HIDE

| CALL                     | EFFECT          |
|--------------------------|-----------------|
| <code>iconify()</code>   | Minimize        |
| <code>deiconify()</code> | Restore / show  |
| <code>withdraw()</code>  | Hide completely |
| <code>lift()</code>      | Raise to front  |
| <code>lower()</code>     | Send behind     |

## △ COMMON MISTAKES

- › Centering before `update_idletasks()`, using 1×1 sizes
- › Calling `state("zoomed")` on Linux, which raises `TclError`
- › Hiding the only window with `withdraw()` and losing the app

## ✓ TIPS &amp; BEST PRACTICES

- › Make `center()` a helper you reuse for dialogs
- › Withdraw the root while a splash or login window is shown
- › Save and restore `geometry()` between sessions

## QUICK SUMMARY

- › `wininfo_screenwidth/height` for positioning
- › `iconify`, `deiconify`, `withdraw`, `state()`
- › `overriddenirect(True)` for frameless windows
- › `-alpha` attribute for transparency

## HOW WIDGET OPTIONS WORK

Every widget is configured through **options** (keyword arguments) such as `text`, `width` or `state`. Set them when you create the widget, change them later with `configure()` (alias `config()`), and read them with `cget()` or dictionary syntax `widget["text"]`. `keys()` lists every option a widget supports. `option_add()` sets app-wide **defaults** through Tk's option database, which saves repeating the same font or color on every widget.

## NOTES

- › `config()` with no arguments returns a dict of all options
- › Values come back as strings or Tcl objects; convert if needed
- › Units: plain ints are pixels; `"2c"`, `"1i"`, `"10p"` also work
- › `width` on text widgets is in characters, not pixels
- › ttk widgets support fewer appearance options (use styles)

## SET, CHANGE AND READ OPTIONS

```
import tkinter as tk

root = tk.Tk()
root.option_add("*Font", "Helvetica 11")           # default for all widgets
root.option_add("*Button.relief", "groove")         # only classic Buttons

btn = tk.Button(root, text="Save", width=12, state="disabled")
btn.pack(padx=10, pady=10)

btn.configure(text="Save now", state="normal")      # change several at once
btn["fg"] = "darkgreen"                            # dict-style set

print(btn.cget("text"))                             # 'Save now'
print(btn["width"])                                 # 12
print(btn.winfo_class())                            # 'Button'
print("command" in btn.keys())                      # True

info = btn.configure("relief")
print(info)    # ('relief', 'relief', 'Relief', <raised>, 'groove')

root.mainloop()
```

## CODE EXPLAINED

- `option_add` patterns: `*Font` for all, `*Button.relief` per class
- `configure()` accepts any number of keyword options
- Item assignment `btn["fg"] = ...` is shorthand for `configure`
- `winfo_class()` gives the class name used in option patterns
- `configure("relief")` returns name, db name, class, default, value

## COMMON OPTIONS

| OPTION                      | MEANING                 |
|-----------------------------|-------------------------|
| <code>text</code>           | Displayed string        |
| <code>width / height</code> | Size (chars or px)      |
| <code>state</code>          | normal / disabled       |
| <code>bg / fg</code>        | Background / text color |
| <code>font</code>           | Font spec               |
| <code>cursor</code>         | Mouse pointer shape     |

## READING &amp; WRITING

| FORM                          | DOES              |
|-------------------------------|-------------------|
| <code>w.configure(k=v)</code> | Set options       |
| <code>w.config(k=v)</code>    | Same (alias)      |
| <code>w["k"] = v</code>       | Set one           |
| <code>w.cget("k")</code>      | Read one          |
| <code>w["k"]</code>           | Read one          |
| <code>w.keys()</code>         | List option names |

## SCREEN UNITS

| VALUE | UNIT             |
|-------|------------------|
| 10    | Pixels           |
| "2c"  | Centimeters      |
| "5m"  | Millimeters      |
| "1i"  | Inches           |
| "12p" | Points (1/72 in) |

## △ COMMON MISTAKES

- › Using `bg=` on ttk widgets (raises `TclError: unknown option`)
- › Comparing `w["width"] == "12"` when it returns an int
- › Misspelling an option; Tk raises instead of ignoring it

## ✓ TIPS &amp; BEST PRACTICES

- › Set fonts and colors once with `option_add` before creating widgets
- › Use `keys()` in the REPL to explore any widget
- › Group related changes in a single `configure()` call

## QUICK SUMMARY

- › Options are keyword args on create
- › `configure()` to change, `cget()` / `[]` to read
- › `option_add()` for app-wide defaults
- › `keys()` lists everything a widget supports

## SHOWING TEXT AND TAKING CLICKS

A Label displays text or an image; it can show a fixed string with `text=` or a live value through `textvariable=`. A Button runs a **callback** when clicked, given by `command=` with no arguments. Both share many options: `image` with `compound` to mix picture and text, `anchor` and `justify` for alignment, `wraplength` for automatic line wrapping, and `underline` to mark a keyboard mnemonic. A disabled Button greys out and ignores clicks.

## NOTES

- › `textvariable` beats `text` when both are given
- › `wraplength` is in screen units (pixels by default)
- › `invoke()` runs a Button's command as if clicked
- › `Message` is an older wrapping label; prefer `wraplength`
- › `ttk.Button` has no `bg`; use a style instead

## LABELS AND BUTTONS TOGETHER

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
count = tk.IntVar(value=0)

ttk.Label(root, text="Clicks:", font=("Segoe UI", 12)).grid(row=0, column=0)
ttk.Label(root, textvariable=count, width=5,
          anchor="e").grid(row=0, column=1)

def add():
    count.set(count.get() + 1)
    reset.config(state="normal")

ttk.Button(root, text="Add", underline=0, command=add).grid(row=1, column=0)
reset = ttk.Button(root, text="Reset", state="disabled",
                  command=lambda: count.set(0))
reset.grid(row=1, column=1)
root.bind("<Alt-a>", lambda e: add())      # Alt+A, matches underline

tk.Label(root, text="A long help message that wraps neatly "
                  "inside two hundred pixels.", wraplength=200,
          justify="left").grid(row=2, column=0, columnspan=2, pady=6)

root.mainloop()
```

## CODE EXPLAINED

- `textvariable=count` updates the label automatically
- `anchor="e"` right-aligns text inside the label's width
- `underline=0` draws the mnemonic but doesn't bind the key
- A `lambda` adapts the bind event argument to `add()`
- `wraplength` plus `justify` controls multi-line text

## LABEL OPTIONS

| OPTION                    | PURPOSE                |
|---------------------------|------------------------|
| <code>text</code>         | Static string          |
| <code>textvariable</code> | Live value             |
| <code>image</code>        | PhotoImage to show     |
| <code>compound</code>     | Image position vs text |
| <code>wraplength</code>   | Wrap width             |

## BUTTON OPTIONS

| OPTION                 | PURPOSE                 |
|------------------------|-------------------------|
| <code>command</code>   | Callback on click       |
| <code>state</code>     | normal / disabled       |
| <code>underline</code> | Mnemonic index          |
| <code>default</code>   | active = default button |
| <code>width</code>     | Width in characters     |

## ANCHOR VALUES

| VALUE                    | POSITION            |
|--------------------------|---------------------|
| <code>n / s</code>       | Top / bottom center |
| <code>e / w</code>       | Right / left middle |
| <code>ne nw se sw</code> | Corners             |
| <code>center</code>      | Middle (default)    |

## △ COMMON MISTAKES

- › Expecting `underline` to bind the key by itself
- › Changing `text` when `textvariable` is also set
- › Using `justify` to align a single line (use `anchor`)

## ✓ TIPS &amp; BEST PRACTICES

- › Prefer `ttk.Label` / `ttk.Button` for native styling
- › Disable buttons until their action makes sense
- › Use `invoke()` to trigger buttons from key bindings

## QUICK SUMMARY

- › Label: `text` or `textvariable`, optional `image`
- › Button: `command=` callback, `state`
- › `anchor` aligns, `justify` aligns lines
- › `wraplength` wraps long text

## SINGLE-LINE TEXT INPUT

An Entry holds one line of editable text. Read it with `get()`, and modify it with `insert(index, text)` and `delete(first, last)`. Indices are character positions, or the names `0`, `"end"` (also `tk.END`), `"insert"` (the cursor) and `"sel.first"/"sel.last"`. Linking a `StringVar` through `textvariable=` is often cleaner than calling `get()`. `show="*"` masks passwords, and `state="readonly"` allows selecting and copying but not editing.

## NOTES

- › `get()` always returns a `str`; convert numbers yourself
- › `delete(0, "end")` clears the whole field
- › `width` is in average characters, not pixels
- › `readonly` keeps the text selectable; `disabled` doesn't
- › Validation on each keystroke is covered on Sheet 52

## READING, EDITING AND MASKING

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
user = tk.StringVar(value="guest")

ttk.Label(root, text="User").grid(row=0, column=0, sticky="w")
name = ttk.Entry(root, textvariable=user, width=24)
name.grid(row=0, column=1, pady=4)

ttk.Label(root, text="Password").grid(row=1, column=0, sticky="w")
pw = ttk.Entry(root, show="•", width=24)
pw.grid(row=1, column=1, pady=4)

def submit(event=None):
    print(user.get(), len(pw.get()))
    pw.delete(0, "end")           # clear password field
    name.select_range(0, "end")   # highlight user name
    name.icursor("end")          # cursor to end
    name.focus_set()

pw.bind("<Return>", submit)
ttk.Button(root, text="Log in", command=submit).grid(row=2, column=1)
name.insert("end", "_01")        # 'guest_01'
root.mainloop()
```

## CODE EXPLAINED

- `textvariable` keeps the Entry and `user` in sync
- `show="•"` displays a mask character instead of the text
- `event=None` lets one function serve both bind and command
- `select_range` + `icursor` mimic native field behavior
- `insert("end", ...)` appends to the current text

## ENTRY METHODS

| METHOD                          | DOES            |
|---------------------------------|-----------------|
| <code>get()</code>              | Current text    |
| <code>insert(i, s)</code>       | Insert at index |
| <code>delete(a, b)</code>       | Remove range    |
| <code>icursor(i)</code>         | Move cursor     |
| <code>select_range(a, b)</code> | Select text     |

## INDEX NAMES

| INDEX                    | POSITION        |
|--------------------------|-----------------|
| <code>0</code>           | Start           |
| <code>"end"</code>       | After last char |
| <code>"insert"</code>    | Cursor position |
| <code>"sel.first"</code> | Selection start |
| <code>"sel.last"</code>  | Selection end   |

## USEFUL OPTIONS

| OPTION                       | EFFECT                   |
|------------------------------|--------------------------|
| <code>show</code>            | Mask character           |
| <code>state</code>           | normal/readonly/disabled |
| <code>justify</code>         | Text alignment           |
| <code>textvariable</code>    | Linked StringVar         |
| <code>exportselection</code> | Share selection (0 = no) |

## △ COMMON MISTAKES

- › Calling `delete(0)` and expecting the field to clear
- › Doing math on `get()` without `int()` / `float()`
- › Setting `state="disabled"` when users still need to copy

## ✓ TIPS &amp; BEST PRACTICES

- › Use a `StringVar` when several widgets show the same value
- › Bind `<Return>` to submit forms
- › Set `exportselection=0` when many Entries share a window

## QUICK SUMMARY

- › `get`, `insert`, `delete(0, "end")`
- › Indices: ints, `"end"`, `"insert"`, `sel.*`
- › `show=` masks, `readonly` locks editing
- › Link with `textvariable=StringVar`

## MULTI-LINE TEXT EDITING

The Text widget edits many lines of text and is powerful enough to build a small editor. Positions are **text indices** written as "line.column" strings: lines start at 1, columns at 0, so the very start is "1.0". "end" is just after the last character, and Text always keeps an extra trailing newline there. Indices accept modifiers such as "insert linestart" or "end-1c". undo=True turns on the built-in undo stack.

## NOTES

- › `get("1.0", "end-1c")` drops the automatic final newline
- › `state="disabled"` makes Text read-only (also blocks `insert()`)
- › Re-enable with `state="normal"` before changing a read-only Text
- › `wrap` can be `"none"`, `"char"` or `"word"`
- › Attach a Scrollbar for long content (Sheet 13)

## INSERT, READ, REPLACE, UNDO

```
import tkinter as tk

root = tk.Tk()
text = tk.Text(root, width=50, height=10, wrap="word",
               undo=True, font=("Consolas", 11))
text.pack(fill="both", expand=True)

text.insert("1.0", "Line one\nLine two\n")
text.insert("end", "Appended line")

content = text.get("1.0", "end-1c")      # everything, no extra \n
first = text.get("1.0", "1.end")        # 'Line one'
lines = int(text.index("end-1c").split(".")[0])

text.delete("2.0", "3.0")               # remove line 2
text.replace("1.5", "1.8", "ONE")       # 'Line ONE'
text.edit_separator()                  # mark an undo step
def log(msg):                          # read-only output pattern
    text.config(state="normal")
    text.insert("end", msg + "\n")
    text.see("end")
    text.config(state="disabled")
root.bind("<Control-z>", lambda e: text.edit_undo())
root.mainloop()
```

## CODE EXPLAINED

- "1.0" is line 1, column 0: the first character
- "end-1c" steps back over the trailing newline
- `index()` converts any index to "line.col" form
- `replace()` (Tk 8.6+) deletes and inserts in one step
- `see("end")` scrolls so the newest line is visible

## INDEX FORMS

| INDEX    | MEANS               |
|----------|---------------------|
| "1.0"    | Line 1, column 0    |
| "3.end"  | End of line 3       |
| "end"    | After final newline |
| "insert" | Cursor position     |
| "@x,y"   | Char under pixel    |

## INDEX MODIFIERS

| MODIFIER  | MOVES         |
|-----------|---------------|
| +5c / -1c | By characters |
| +2l / -1l | By lines      |
| linestart | Start of line |
| lineend   | End of line   |
| wordstart | Start of word |

## UNDO / MODIFIED

| METHOD                        | DOES               |
|-------------------------------|--------------------|
| <code>edit_undo()</code>      | Undo last step     |
| <code>edit_redo()</code>      | Redo               |
| <code>edit_separator()</code> | End an undo step   |
| <code>edit_reset()</code>     | Clear undo stack   |
| <code>edit_modified()</code>  | Get/set dirty flag |

## △ COMMON MISTAKES

- › Using "0.0" or "1.1" as the start (it's "1.0")
- › Saving `get("1.0", "end")` and gaining a newline each time
- › Inserting into a disabled Text and wondering why nothing happens

## ✓ TIPS &amp; BEST PRACTICES

- › Track unsaved changes with `<<Modified>>` and `edit_modified(False)`
- › Use the disable/insert/re-disable pattern for log panes
- › Prefer `wrap="word"` for prose, `"none"` for code

## QUICK SUMMARY

- › Indices are "line.column", from "1.0"
- › `get`, `insert`, `delete`, `replace`
- › "end-1c" excludes the trailing newline
- › `undo=True` enables `edit_undo` / `edit_redo`

## FORMATTING AND FINDING TEXT

**Tags** are named styles applied to ranges of a Text widget: configure a tag's look once with `tag_configure()`, then attach it to ranges with `tag_add()` or as an extra argument to `insert()`. Tags can also receive events through `tag_bind()`, which is how clickable links are made. **Marks** are named positions that float with edits; "insert" and "current" are built-in marks. `search()` finds text (optionally with regex) and returns the index of the match.

## NOTES

- › The "sel" tag is the user's selection
- › Later-created tags win when styles overlap; reorder with `tag_raise()`
- › Marks have gravity: "right" (default) or "left"
- › `search()` returns "" when nothing matches
- › `window_create()` embeds a widget inside the text

## HIGHLIGHT, LINK AND SEARCH

```
import tkinter as tk, webbrowser

text = tk.Text(width=60, height=12); text.pack()
text.tag_configure("h1", font=("Helvetica", 16, "bold"))
text.tag_configure("hit", background="yellow")
text.tag_configure("link", foreground="blue", underline=True)

text.insert("end", "Report\n", "h1")
text.insert("end", "See the docs for details. More docs here.\n")
text.insert("end", "tkdocs.com", ("link",))
text.tag_bind("link", "<Button-1>",
             lambda e: webbrowser.open("https://tkdocs.com"))
def highlight(word):
    text.tag_remove("hit", "1.0", "end")
    start = "1.0"
    while True:
        count = tk.IntVar()
        pos = text.search(word, start, "end", nocase=True, count=count)
        if not pos: break
        end = f"{pos}+{count.get()}c"
        text.tag_add("hit", pos, end)
        start = end
highlight("docs"); text.mark_set("insert", "2.0")
text.mainloop()
```

## CODE EXPLAINED

- Third `insert` argument applies one or more tags
- `tag_bind` makes tagged text respond to clicks
- `search(..., count=var)` reports the match length
- Loop from the end of each match to find the next
- `mark_set("insert", ...)` moves the cursor

## TAG METHODS

| METHOD                           | DOES              |
|----------------------------------|-------------------|
| <code>tag_configure()</code>     | Set tag style     |
| <code>tag_add(t, a, b)</code>    | Apply to range    |
| <code>tag_remove(t, a, b)</code> | Remove from range |
| <code>tag_ranges(t)</code>       | All tagged ranges |
| <code>tag_bind(t, ev, fn)</code> | Events on tag     |

## TAG OPTIONS

| OPTION                  | EFFECT          |
|-------------------------|-----------------|
| <code>font</code>       | Font for range  |
| <code>foreground</code> | Text color      |
| <code>background</code> | Highlight color |
| <code>underline</code>  | Underline       |
| <code>lmargin1</code>   | Left indent     |

## SEARCH() OPTIONS

| OPTION                      | EFFECT            |
|-----------------------------|-------------------|
| <code>nocase=True</code>    | Ignore case       |
| <code>regex=True</code>     | Tcl regex pattern |
| <code>backwards=True</code> | Search upward     |
| <code>count=IntVar</code>   | Match length      |
| <code>stopindex</code>      | Search limit      |

## △ COMMON MISTAKES

- › Forgetting "end" as stopindex, so search wraps forever
- › Passing a tag string where a tuple is needed in loops
- › Expecting Python regex syntax; `regex=True` uses Tcl's

## ✓ TIPS &amp; BEST PRACTICES

- › Clear old highlights with `tag_remove` before re-searching
- › Use tags for syntax highlighting and log levels
- › Change the "current" cursor on <Enter> of link tags

## QUICK SUMMARY

- › Tags = named styles on ranges
- › `tag_bind` for clickable text
- › Marks = floating positions (`insert`, `current`)
- › `search()` returns an index or ""

## BOOLEAN AND CHOICE INPUTS

A **Checkbox** toggles a variable between an **on** and an **off** value (by default 1 and 0; change them with `onvalue/offvalue`). A group of **Radiobuttons** shares **one variable**; each button has its own `value`, and selecting it writes that value to the variable. Because the state lives in the variable, you read the user's choice with `var.get()` rather than querying the widgets, and you can preselect by calling `var.set()`.

## NOTES

- › Use `BooleanVar` for simple on/off checkboxes
- › Radiobuttons are grouped only by sharing a variable
- › Both accept `command=` to react immediately
- › `ttk` versions look native; classic ones allow colors
- › `indicatoron=False` makes classic radios look like toggle buttons

## OPTIONS PANEL

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
dark = tk.BooleanVar(value=False)
size = tk.StringVar(value="M")
level = tk.StringVar(value="beta")

def show():
    print(dark.get(), size.get(), level.get())
    ttk.Checkbutton(root, text="Dark mode", variable=dark,
                    command=show).grid(row=0, column=0, columnspan=3, sticky="w")

for col, (label, val) in enumerate([("Small", "S"), ("Medium", "M"),
                                    ("Large", "L")]):
    ttk.Radiobutton(root, text=label, value=val, variable=size,
                    command=show).grid(row=1, column=col, padx=4)
    ttk.Checkbutton(root, text="Use beta channel", variable=level,
                    onvalue="beta", offvalue="stable").grid(
        row=2, column=0, columnspan=3, sticky="w")
align = tk.StringVar(value="Left")  # classic toolbar-style group
for i, v in enumerate(("Left", "Center", "Right")):
    tk.Radiobutton(root, text=v, value=v, variable=align,
                    indicatoron=False, width=7).grid(row=3, column=i)

root.mainloop()
```

## CODE EXPLAINED

- `BooleanVar` returns `True / False` from `get()`
- All three `Radiobuttons` share `size`, so only one is selected
- The initial `value="M"` preselects Medium
- `onvalue / offvalue` store strings instead of 1/0
- `indicatoron=False` draws push-button style radios

## CHECKBUTTON

| OPTION                           | PURPOSE            |
|----------------------------------|--------------------|
| <code>variable</code>            | Linked var         |
| <code>onvalue</code>             | Value when checked |
| <code>offvalue</code>            | Value when cleared |
| <code>command</code>             | Called on toggle   |
| <code>select()/deselect()</code> | Classic only       |

## RADIOBUTTON

| OPTION                   | PURPOSE                |
|--------------------------|------------------------|
| <code>variable</code>    | Shared group var       |
| <code>value</code>       | This button's value    |
| <code>command</code>     | Called on select       |
| <code>indicatoron</code> | Classic: dot or button |
| <code>state</code>       | normal / disabled      |

## TTK STATE

| CALL                               | MEANING        |
|------------------------------------|----------------|
| <code>instate(['selected'])</code> | Is checked?    |
| <code>state(['!alternate'])</code> | Clear 'mixed'  |
| <code>invoke()</code>              | Toggle in code |
| <code>alternate</code>             | Tri-state look |

## △ COMMON MISTAKES

- › Giving each `Radiobutton` its own variable (they never exclude)
- › Leaving the variable unset, so no radio appears selected
- › Letting a local variable get garbage-collected; keep a reference

## ✓ TIPS &amp; BEST PRACTICES

- › Store vars on `self` in class-based apps
- › Build radio groups from a list of (label, value) pairs
- › Read choices from variables, never from widgets

## QUICK SUMMARY

- › Checkbox: on/off values in one variable
- › Radiobuttons: shared variable, unique `value`
- › Read state with `var.get()`
- › Preselect with `var.set()`

## LISTS AND SCROLLING

A Listbox shows a list of strings the user can select from. Items are addressed by **index** (0-based) or "end", and `curselection()` returns a tuple of selected indices. `selectmode` controls single or multiple selection. Scrollbars connect in **two directions**: the widget's `yscrollcommand` is set to the scrollbar's `set`, and the scrollbar's `command` is set to the widget's `yview`. The same pairing works for Text, Canvas, Entry (horizontal) and Treeview.

## NOTES

- › `listvariable` links a `StringVar` holding a Tcl list
- › `<<ListboxSelect>>` fires when the selection changes
- › `curselection()` may be empty; always check
- › Selections are lost when focus moves unless `exportselection=False`
- › For columns or icons, use `tk.Treeview` instead

## LISTBOX WITH SCROLLBAR

```
import tkinter as tk
from tkinter import ttk

frame = ttk.Frame(tk.Tk(), padding=8)
frame.pack(fill="both", expand=True)

fruits = ["Apple", "Banana", "Cherry", "Date", "Elderberry",
          "Fig", "Grape", "Honeydew", "Kiwi", "Lemon"]
lb = tk.Listbox(frame, height=6, selectmode="extended",
               exportselection=False)
sb = ttk.Scrollbar(frame, orient="vertical", command=lb.yview)
lb.configure(yscrollcommand=sb.set)

lb.grid(row=0, column=0, sticky="nsew")
sb.grid(row=0, column=1, sticky="ns")
frame.rowconfigure(0, weight=1); frame.columnconfigure(0, weight=1)

lb.insert("end", *fruits)
lb.itemconfigure(0, foreground="red")
def on_select(event):
    print([lb.get(i) for i in lb.curselection()])
lb.bind("<<ListboxSelect>>", on_select)
lb.selection_set(2); lb.see(2)           # select and scroll to Cherry
lb.delete("end")                         # remove last item
frame.mainloop()
```

## CODE EXPLAINED

- Scrollbar `command` → `lb.yview` scrolls the list
- `yscrollcommand` → `sb.set` moves the scrollbar thumb
- `sticky="ns"` stretches the scrollbar to full height
- `curselection()` gives indices; `get(i)` gives text
- `selection_set` + `see` select in code and scroll into view

## SELECTMODE

| MODE                  | BEHAVIOR                |
|-----------------------|-------------------------|
| <code>browse</code>   | One item, drag moves it |
| <code>single</code>   | One item                |
| <code>multiple</code> | Click toggles items     |
| <code>extended</code> | Shift/Ctrl ranges       |

## LISTBOX METHODS

| METHOD                             | DOES             |
|------------------------------------|------------------|
| <code>insert(i, *items)</code>     | Add items        |
| <code>delete(a, b)</code>          | Remove items     |
| <code>get(a, b)</code>             | Text of items    |
| <code>curselection()</code>        | Selected indices |
| <code>selection_clear(a, b)</code> | Deselect         |

## SCROLL WIRING

| SIDE                    | SETTING                             |
|-------------------------|-------------------------------------|
| <code>Widget</code>     | <code>yscrollcommand=sb.set</code>  |
| <code>Scrollbar</code>  | <code>command=w.yview</code>        |
| <code>Horizontal</code> | <code>xscrollcommand / xview</code> |
| <code>Scrollbar</code>  | <code>orient="horizontal"</code>    |

## △ COMMON MISTAKES

- › Wiring only one direction, so the thumb never moves
- › Indexing `curselection()[0]` when nothing is selected
- › Losing the selection when clicking into another Entry

## ✓ TIPS &amp; BEST PRACTICES

- › Use `grid` with weights so the list grows with the window
- › Prefer `ttk.Scrollbar` for a native look
- › Use `<<ListboxSelect>>` instead of `<Button-1>`

## QUICK SUMMARY

- › Listbox: index-based string list
- › `curselection()` → tuple of indices
- › `selectmode` for single vs multi
- › Scrollbars wire both directions

## NUMERIC SLIDERS AND CHOOSERS

A Scale is a slider for numbers between `from_` and `to` (note the trailing underscore, because `from` is a Python keyword). A Spinbox is an Entry with up/down arrows that steps through a numeric range or a fixed list of values. An OptionMenu is a classic drop-down built from a variable and a list of choices; `ttk.Combobox` (Sheet 37) is the modern alternative. All three can share a Tk variable so the current value is always one `get()` away.

## NOTES

- › `Scale` passes the new value as a **string** to its `command`
- › `resolution` sets the Scale step; `tickinterval` adds labels
- › Spinbox `wrap=True` loops past the ends
- › OptionMenu takes the default value and choices positionally
- › `ttk.Scale` has no `resolution`; round the value yourself

## VOLUME, QUANTITY AND SIZE

```
import tkinter as tk

root = tk.Tk()
vol = tk.DoubleVar(value=50)
qty = tk.IntVar(value=1)
size = tk.StringVar(value="Medium")

tk.Scale(root, from_=0, to=100, resolution=5, orient="horizontal",
        label="Volume", tickinterval=25, length=240,
        variable=vol, command=lambda v: print("vol", float(v))
        ).pack(padx=10, pady=4)
tk.Spinbox(root, from_=1, to=10, increment=1, width=5,
        textvariable=qty, wrap=True).pack(pady=4)

tk.Spinbox(root, values=("XS", "S", "M", "L", "XL"),
        state="readonly", width=6).pack(pady=4)

opts = ["Small", "Medium", "Large"]
menu = tk.OptionMenu(root, size, size.get(), *opts,
        command=lambda v: print("size", v))
menu.config(width=10); menu.pack(pady=4)
def reset():
    vol.set(50); qty.set(1); size.set("Medium")
tk.Button(root, text="Reset", command=reset).pack(pady=6)
root.mainloop()
```

## CODE EXPLAINED

- `from_ / to` set the range; `resolution=5` snaps to steps
- `command` receives the value as text, so convert it
- Spinbox with `values=` cycles through a fixed list
- OptionMenu args: master, var, default, \*choices
- Setting each variable resets every linked widget

## SCALE OPTIONS

| OPTION                    | PURPOSE               |
|---------------------------|-----------------------|
| <code>from_ / to</code>   | Range ends            |
| <code>resolution</code>   | Step size             |
| <code>orient</code>       | horizontal / vertical |
| <code>tickinterval</code> | Labelled ticks        |
| <code>length</code>       | Pixel length          |

## SPINBOX OPTIONS

| OPTION                  | PURPOSE        |
|-------------------------|----------------|
| <code>from_ / to</code> | Numeric range  |
| <code>increment</code>  | Step per click |
| <code>values</code>     | Fixed list     |
| <code>wrap</code>       | Loop at ends   |
| <code>format</code>     | e.g. "%05.2f"  |

## WHICH TO USE

| NEED              | WIDGET       |
|-------------------|--------------|
| Rough number      | Scale        |
| Exact small int   | Spinbox      |
| Pick from list    | Combobox     |
| Few fixed choices | Radiobuttons |
| Classic dropdown  | OptionMenu   |

## ⚠ COMMON MISTAKES

- › Writing `from=0`, a syntax error (use `from_`)
- › Doing math on the Scale callback value without `float()`
- › Passing the choices as one list to OptionMenu without `*`

## ✓ TIPS &amp; BEST PRACTICES

- › Show the live number in a Label via the same variable
- › Use `readonly` Spinboxes to prevent invalid typing
- › Prefer `ttk.Combobox` for long choice lists

## QUICK SUMMARY

- › Scale: slider, `from_ / to / resolution`
- › Spinbox: arrows over range or `values`
- › OptionMenu: classic drop-down
- › Share one Tk variable per value

## CONTAINERS FOR GROUPING

Container widgets group other widgets so they can be laid out and styled as one unit. A Frame is an invisible (or bordered) box. A LabelFrame adds a titled border, which suits form sections. A PanedWindow splits space between children with **draggable sashes**, like a file browser's sidebar. Containers are the key to good layouts: each Frame can use its own geometry manager independently of its parent, which is how complex screens are built from simple pieces.

## NOTES

- › `padding=` on ttk Frames adds inner space
- › Classic Frames use `padx / pady`, `relief`, `borderwidth`
- › PanedWindow children are added with `add()`, not `pack/grid`
- › A Frame shrinks to fit its children unless propagation is off
- › `ttk.Panedwindow` is the themed version (Sheet 38)

## FRAMES, LABELFRAME AND PANES

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk(); root.geometry("520x260")
panes = tk.PanedWindow(root, orient="horizontal", sashwidth=6,
                        sashrelief="raised")
panes.pack(fill="both", expand=True)

sidebar = ttk.Frame(panes, padding=6)
for name in ("Inbox", "Sent", "Archive"):
    ttk.Button(sidebar, text=name).pack(fill="x", pady=2)

main = ttk.Frame(panes, padding=8)
info = ttk.LabelFrame(main, text="Contact", padding=8)
info.pack(fill="x")
ttk.Label(info, text="Name").grid(row=0, column=0, sticky="w")
ttk.Entry(info).grid(row=0, column=1, sticky="ew", padx=4)
info.columnconfigure(1, weight=1)
box = tk.Frame(main, relief="sunken", borderwidth=2, height=60)
box.pack(fill="x", pady=8)
panes.add(sidebar, minsize=100)
panes.add(main, stretch="always")
root.mainloop()
```

## CODE EXPLAINED

- The PanedWindow fills the window; sash is draggable
- Sidebar Frame uses `pack`, the LabelFrame inside uses `grid`
- `columnconfigure(1, weight=1)` lets the Entry stretch
- `relief="sunken"` draws a classic inset border
- `add(..., minsize=100)` keeps the sidebar from vanishing

## CONTAINERS

| WIDGET       | USE                    |
|--------------|------------------------|
| Frame        | Invisible grouping box |
| LabelFrame   | Titled border group    |
| PanedWindow  | Resizable split        |
| Toplevel     | Separate window        |
| ttk.Notebook | Tabbed pages           |

## FRAME OPTIONS

| OPTION         | EFFECT                          |
|----------------|---------------------------------|
| padding        | Inner space (ttk)               |
| relief         | flat/raised/sunken/groove/ridge |
| borderwidth    | Border thickness                |
| width / height | Size if not propagating         |
| labelanchor    | LabelFrame title spot           |

## PANEDWINDOW

| CALL                             | DOES          |
|----------------------------------|---------------|
| <code>add(w, ...)</code>         | Add a pane    |
| <code>forget(w)</code>           | Remove a pane |
| <code>sash_coord(i)</code>       | Sash position |
| <code>sash_place(i, x, y)</code> | Move a sash   |
| <code>paneconfigure()</code>     | Pane options  |

## ⚠ COMMON MISTAKES

- › Packing children into a PanedWindow instead of `add()`
- › Setting Frame `width / height` and seeing no effect (propagation)
- › Mixing `pack` and `grid` inside the same Frame

## ✓ TIPS &amp; BEST PRACTICES

- › One Frame per logical region of the screen
- › Use LabelFrames to group related form fields
- › Set `minsize` on panes the user shouldn't collapse

## QUICK SUMMARY

- › Frame groups, LabelFrame adds a title
- › PanedWindow gives draggable splits
- › Each container has its own geometry manager
- › Nest frames to build complex layouts

## STACKING WIDGETS WITH PACK()

`pack()` places widgets one after another against a **side** of the remaining space in their parent: top (default), bottom, left or right. Each packed widget claims a full-width (or full-height) **parcel**. `fill` stretches the widget within its parcel, and `expand=True` lets the parcel grab leftover space when the window grows. Packing **order matters**: widgets packed first get space first and are the last to shrink, so pack toolbars and status bars before the main content.

## NOTES

- › `fill` = grow inside the parcel; `expand` = grow the parcel
- › `padx` / `pady` add space outside; `ipadx` / `ipady` inside
- › `pack_forget()` hides a widget and discards its pack options
- › `before=` / `after=` insert relative to an already packed widget
- › Best for simple rows, columns and edge-docked bars

## TOOLBAR, STATUS BAR, CONTENT

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.geometry("420x260")

toolbar = ttk.Frame(root, padding=4)
toolbar.pack(side="top", fill="x")
for name in ("New", "Open", "Save"):
    ttk.Button(toolbar, text=name).pack(side="left", padx=2)
    ttk.Button(toolbar, text="Help").pack(side="right")

status = ttk.Label(root, text="Ready", relief="sunken", anchor="w")
status.pack(side="bottom", fill="x")           # packed before content

sidebar = tk.Listbox(root, width=14)
sidebar.pack(side="left", fill="y")

editor = tk.Text(root)
editor.pack(side="left", fill="both", expand=True, padx=(4, 0))

status.pack_forget()                          # hide status bar
status.pack(side="bottom", fill="x", before=sidebar) # show again
root.mainloop()
```

## CODE EXPLAINED

- Toolbar docks to the top and stretches horizontally
- Buttons pack left-to-right; Help sits at the far right
- Status bar is packed before content so it never gets squeezed
- Only the editor has `expand=True`, so it absorbs extra space
- `before=sidebar` restores the bar's original packing slot

## PACK() OPTIONS

| OPTION                                  | EFFECT                      |
|-----------------------------------------|-----------------------------|
| <code>side</code>                       | top / bottom / left / right |
| <code>fill</code>                       | none / x / y / both         |
| <code>expand</code>                     | Claim extra space           |
| <code>anchor</code>                     | Position in parcel          |
| <code>padx</code> / <code>pady</code>   | Outer spacing               |
| <code>ipadx</code> / <code>ipady</code> | Inner spacing               |

## FILL VS EXPAND

| SETTING                  | RESULT                       |
|--------------------------|------------------------------|
| <code>neither</code>     | Natural size                 |
| <code>fill="x"</code>    | Stretches across parcel      |
| <code>expand=True</code> | Parcel grows, widget doesn't |
| <code>both</code>        | Widget grows with window     |

## PACK METHODS

| METHOD                                     | DOES                  |
|--------------------------------------------|-----------------------|
| <code>pack_forget()</code>                 | Unmap, forget options |
| <code>pack_info()</code>                   | Current options       |
| <code>pack_slaves()</code>                 | Packed children       |
| <code>pack_propagate()</code>              | Parent auto-size      |
| <code>before=</code> / <code>after=</code> | Insert position       |

## ⚠ COMMON MISTAKES

- › Using `expand=True` without `fill`, then wondering why it doesn't stretch
- › Packing the status bar last, so it gets cut off when shrinking
- › Mixing `pack` and `grid` for children of the same parent

## ✓ TIPS &amp; BEST PRACTICES

- › Pack edge bars first, the flexible area last
- › Use a Frame per row when you need several horizontal groups
- › Tuple padding `padx=(4, 0)` pads one side only

## QUICK SUMMARY

- › Widgets stack against a side
- › `fill` stretches, `expand` claims space
- › Order of packing decides priority
- › Great for bars and simple stacks

## ROWS AND COLUMNS WITH GRID()

`grid()` places widgets in a table of **rows** and **columns** inside their parent. Rows and columns are created on demand and size themselves to the largest widget they hold. A widget can span several cells with `colspan`/`rowspan`. Inside its cell, a widget is centered unless `sticky` pins it to edges using compass letters: "w" aligns left, "ew" stretches horizontally, "nsew" fills the cell. `grid` is the go-to manager for forms and anything aligned in columns.

## NOTES

- › Empty rows/columns take no space
- › Row and column numbers needn't be consecutive
- › `grid_remove()` hides but remembers options; `grid_forget()` doesn't
- › `sticky` only stretches within the cell, not the cell itself
- › Cell growth needs `columnconfigure` / `rowconfigure` (Sheet 18)

## A CLASSIC FORM

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
form = ttk.Frame(root, padding=10)
form.grid(row=0, column=0, sticky="nsew")

fields = ["First name", "Last name", "Email"]
entries = {}
for r, label in enumerate(fields):
    ttk.Label(form, text=label + ":", grid(row=r, column=0,
                                         sticky="e", padx=(0, 6), pady=3)

    e = ttk.Entry(form, width=30)
    e.grid(row=r, column=1, sticky="ew", pady=3)
    entries[label] = e

ttk.Label(form, text="Notes:", grid(row=3, column=0, sticky="ne", pady=3)
tk.Text(form, width=30, height=4).grid(row=3, column=1, pady=3)

buttons = ttk.Frame(form)
buttons.grid(row=4, column=0, colspan=2, sticky="e", pady=(8, 0))
tk.Button(buttons, text="Cancel").grid(row=0, column=0, padx=4)
tk.Button(buttons, text="Save").grid(row=0, column=1)
entries["Email"].grid_remove()      # hide...
entries["Email"].grid()             # ...and restore with old options
root.mainloop()
```

## CODE EXPLAINED

- Labels in column 0 align right with `sticky="e"`
- Entries fill their cell width with `sticky="ew"`
- `sticky="ne"` keeps the Notes label at the top of its tall row
- A nested Frame spanning both columns holds the buttons
- `grid()` with no args re-shows a `grid_remove` d widget

## GRID() OPTIONS

| OPTION       | EFFECT            |
|--------------|-------------------|
| row / column | Cell position     |
| rowspan      | Span rows         |
| colspan      | Span columns      |
| sticky       | Edges to stick to |
| padx / pady  | Outer spacing     |

## STICKY VALUES

| VALUE     | RESULT               |
|-----------|----------------------|
| ""        | Centered             |
| "w" / "e" | Left / right         |
| "n" / "s" | Top / bottom         |
| "ew"      | Stretch horizontally |
| "ns"      | Stretch vertically   |

## HIDE &amp; INSPECT

| METHOD                         | DOES               |
|--------------------------------|--------------------|
| <code>grid_remove()</code>     | Hide, keep options |
| <code>grid_forget()</code>     | Hide, drop options |
| <code>grid_info()</code>       | Current options    |
| <code>grid_size()</code>       | (columns, rows)    |
| <code>grid_slaves(r, c)</code> | Widgets in a cell  |

## △ COMMON MISTAKES

- › Writing `sticky="left"`; it uses compass letters
- › Expecting `sticky="ew"` to widen a column with no weight
- › Calling `.grid()` inline and storing the `None` it returns

## ✓ TIPS &amp; BEST PRACTICES

- › Build forms in a loop over field names
- › Put button rows in their own Frame
- › Use `grid_remove` for widgets you toggle often

## QUICK SUMMARY

- › Rows × columns, created on demand
- › `colspan` / `rowspan` merge cells
- › `sticky` pins or stretches in the cell
- › Ideal for forms and aligned layouts

## MAKING GRIDS RESIZE PROPERLY

By default, grid rows and columns stay at their natural size when the window grows. To let them grow, give them a **weight** with `columnconfigure(index, weight=n)` and `rowconfigure(index, weight=n)` on the **parent**. Extra space is shared in proportion to the weights. `minsize` sets a minimum pixel size, `pad` adds space, and `uniform` forces columns in the same group to equal width. Remember to configure the root too, or the frame inside it never grows.

## NOTES

- › Weight 0 (default) = fixed size
- › Configure the parent of the widgets, not the widgets
- › A list of indices configures several at once
- › Widgets still need `sticky` to fill the growing cell
- › `uniform="grp"` + equal weights = equal columns

## A RESIZABLE TWO-PANE LAYOUT

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.geometry("500x300")
root.columnconfigure(0, weight=1)      # let the frame grow
root.rowconfigure(0, weight=1)

frame = ttk.Frame(root, padding=6)
frame.grid(row=0, column=0, sticky="nsew")

frame.columnconfigure(0, weight=1, minsize=120)  # sidebar
frame.columnconfigure(1, weight=3)              # main: 3x share
frame.rowconfigure(1, weight=1)                  # content row grows
ttk.Label(frame, text="Folders").grid(row=0, column=0, sticky="w")
ttk.Label(frame, text="Messages").grid(row=0, column=1, sticky="w")
tk.Listbox(frame).grid(row=1, column=0, sticky="nsew", padx=(0, 4))
tk.Text(frame).grid(row=1, column=1, sticky="nsew")
bar = ttk.Frame(frame)
bar.grid(row=2, column=0, colspan=2, sticky="ew", pady=(6, 0))
bar.columnconfigure((0, 1, 2), weight=1, uniform="btn")
for i, t in enumerate(("Reply", "Forward", "Delete")):
    ttk.Button(bar, text=t).grid(row=0, column=i, sticky="ew", padx=2)
root.mainloop()
```

## CODE EXPLAINED

- Root weights let the outer frame follow the window size
- Columns share extra width 1:3 (sidebar:main)
- Only row 1 grows; header and button rows stay fixed
- `sticky="nsew"` makes widgets fill their growing cells
- `uniform="btn"` keeps the three buttons the same width

## CONFIGURE OPTIONS

| OPTION               | EFFECT                 |
|----------------------|------------------------|
| <code>weight</code>  | Share of extra space   |
| <code>minsize</code> | Minimum size (px)      |
| <code>pad</code>     | Extra space in row/col |
| <code>uniform</code> | Equal-size group name  |

## WEIGHT EXAMPLES

| WEIGHTS | EXTRA SPACE     |
|---------|-----------------|
| 0, 0    | None; fixed     |
| 1, 0    | All to first    |
| 1, 1    | Split evenly    |
| 1, 3    | 25% / 75%       |
| 2, 1, 1 | 50% / 25% / 25% |

## CHECKLIST

| STEP         | CALL                                      |
|--------------|-------------------------------------------|
| Parent grows | root weights                              |
| Frame fills  | <code>sticky="nsew"</code>                |
| Column grows | <code>columnconfigure(i, weight=1)</code> |
| Row grows    | <code>rowconfigure(i, weight=1)</code>    |
| Widget fills | <code>sticky</code> on widget             |

## △ COMMON MISTAKES

- › Configuring weights on the child widget instead of its parent
- › Forgetting root weights, so nothing below it can grow
- › Giving weights but no `sticky`, leaving widgets centered

## ✓ TIPS &amp; BEST PRACTICES

- › Resize the window while developing to test weights
- › Use `minsize` to keep sidebars readable
- › Use `uniform` for toolbars of equal buttons

## QUICK SUMMARY

- › Weights distribute extra space
- › Set on the parent with `columnconfigure` / `rowconfigure`
- › `minsize` and `uniform` for limits and equality
- › Pair weights with `sticky`

## EXACT POSITIONING WITH PLACE()

`place()` positions a widget by **coordinates** inside its parent, either absolute pixels (`x`, `y`, `width`, `height`) or **relative** fractions of the parent size (`relx`, `rely`, `relwidth`, `relheight` from 0.0 to 1.0). The two can be combined: relative values are computed first, then the absolute ones are added as offsets. `anchor` chooses which point of the widget lands on the coordinates. `place` ignores other widgets entirely, so overlapping is possible and sometimes the point.

## NOTES

- › `place` doesn't resize the parent to fit children
- › Relative values make overlays follow window resizing
- › Placed widgets stack in creation order; use `lift()` to raise
- › Good for overlays, badges, splash screens and games
- › Poor for forms: no automatic alignment or resizing

## OVERLAY, BADGE AND CENTERED BOX

```
import tkinter as tk

root = tk.Tk()
root.geometry("400x260")

bg = tk.Label(root, bg="#2b3a55")
bg.place(x=0, y=0, relwidth=1, relheight=1)    # full background

box = tk.Frame(root, bg="white", padx=12, pady=12)
box.place(relx=0.5, rely=0.5, anchor="center") # always centered
tk.Label(box, text="Sign in", bg="white",
          font=("Helvetica", 14)).pack()
tk.Entry(box).pack(pady=6)

badge = tk.Label(root, text="3", bg="red", fg="white", width=2)
badge.place(relx=1.0, x=-10, y=10, anchor="ne") # 10 px from top-right

bar = tk.Frame(root, bg="#ffcc00", height=4)
bar.place(relx=0, rely=1.0, relwidth=0.6, anchor="sw") # progress strip
def grow():
    w = float(bar.place_info()["relwidth"])
    bar.place_configure(relwidth=min(1.0, w + 0.1))
root.bind("<space>", lambda e: grow())
root.mainloop()
```

## CODE EXPLAINED

- `relwidth=1, relheight=1` stretches the background
- `relx=0.5, rely=0.5, anchor="center"` centers the box
- `relx=1.0, x=-10` = right edge minus 10 pixels
- `anchor="sw"` pins the strip's bottom-left corner
- `place_info()` returns strings; convert before math

## PLACE() OPTIONS

| OPTION                            | MEANING            |
|-----------------------------------|--------------------|
| <code>x / y</code>                | Pixel position     |
| <code>relx / rely</code>          | Fraction of parent |
| <code>width / height</code>       | Pixel size         |
| <code>relwidth / relheight</code> | Fraction size      |
| <code>anchor</code>               | Widget point used  |

## COMMON RECIPES

| GOAL        | OPTIONS                                      |
|-------------|----------------------------------------------|
| Fill parent | <code>relwidth=1, relheight=1</code>         |
| Center      | <code>relx=.5, rely=.5, anchor=center</code> |
| Top-right   | <code>relx=1, anchor=ne</code>               |
| Bottom bar  | <code>rely=1, relwidth=1, anchor=sw</code>   |
| Inset       | <code>x=10, y=10</code>                      |

## PLACE METHODS

| METHOD                                     | DOES            |
|--------------------------------------------|-----------------|
| <code>place_configure()</code>             | Change options  |
| <code>place_forget()</code>                | Remove          |
| <code>place_info()</code>                  | Current options |
| <code>place_slaves()</code>                | Placed children |
| <code>lift()</code> / <code>lower()</code> | Stacking order  |

## △ COMMON MISTAKES

- › Building whole forms with `place` and hard-coded pixels
- › Expecting the parent to grow around placed children
- › Mixing up `anchor` with the position it applies to

## ✓ TIPS &amp; BEST PRACTICES

- › Combine `relx` with `x` for offsets from edges
- › Use `place` for overlays on top of a grid layout
- › Keep pixel values in constants for HiDPI scaling

## QUICK SUMMARY

- › Absolute `x / y` or relative `relx / rely`
- › `anchor` picks the widget's reference point
- › Can overlap; no auto layout
- › Best for overlays and special effects

## BUILDING REAL LAYOUTS

Real screens are built by **nesting Frames**, each with the geometry manager that suits its contents: pack for bars and simple stacks, grid for forms and tables, place for overlays. The one hard rule is: **\*\*never use pack and grid for children of the same parent\*\***; Tk 8.6 raises a TclError, and older versions could freeze as both managers fought over the parent's size. Containers normally shrink to fit their children; turn that off with pack\_propagate(False) or grid\_propagate(False) to keep a fixed size.

## NOTES

- › Different managers in different Frames are fine
- › Propagation off = honor the Frame's width / height
- › Sketch the screen as nested boxes before coding
- › One Frame per region keeps code easy to change
- › wininfo\_children() lists a container's widgets

## APP SHELL: TOOLBAR, FORM, STATUS

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.geometry("520x300")

top = ttk.Frame(root, padding=4)                # pack in root
body = ttk.Frame(root, padding=10)
status = ttk.Label(root, text="Ready", anchor="w", padding=(6, 2))
top.pack(fill="x"); status.pack(side="bottom", fill="x")
body.pack(fill="both", expand=True)
for t in ("New", "Open", "Save"):              # pack in toolbar
    ttk.Button(top, text=t).pack(side="left")
body.columnconfigure(1, weight=1)              # grid in body
for r, lbl in enumerate(("Title", "Author", "Year")):
    ttk.Label(body, text=lbl).grid(row=r, column=0, sticky="w", pady=2)
    ttk.Entry(body).grid(row=r, column=1, sticky="ew", pady=2)
preview = tk.Frame(body, width=120, height=80, bg="#ddd")
preview.grid(row=0, column=2, rowspan=3, padx=(10, 0))
preview.grid_propagate(False)                  # keep 120x80
tk.Label(preview, text="Cover", bg="#ddd").place(relx=.5, rely=.5,
                                                  anchor="center")

root.mainloop()
```

## CODE EXPLAINED

- Root children all use pack: toolbar, status, body
- The toolbar's buttons use pack inside their own Frame
- The body uses grid for an aligned form
- grid\_propagate(False) keeps the preview at 120x80
- place centers a label inside the fixed preview

## CHOOSING A MANAGER

| CONTENT                | MANAGER |
|------------------------|---------|
| Toolbar / status bar   | pack    |
| Vertical stack         | pack    |
| Form fields            | grid    |
| Table-like layout      | grid    |
| Overlay / centered box | place   |

## PROPAGATION

| CALL                  | EFFECT            |
|-----------------------|-------------------|
| pack_propagate(False) | Fixed size (pack) |
| grid_propagate(False) | Fixed size (grid) |
| width / height        | Used when off     |
| Default True          | Shrink to fit     |

## LAYOUT DEBUGGING

| TRICK              | SHOWS                 |
|--------------------|-----------------------|
| bg="red" on Frames | Region bounds         |
| wininfo_geometry() | Actual size/pos       |
| grid_size()        | Rows and columns used |
| pack_info()        | Applied options       |
| update_idletasks() | Force layout now      |

## △ COMMON MISTAKES

- › pack and grid in the same parent (TclError in Tk 8.6)
- › Setting Frame width / height without disabling propagation
- › One giant grid for the whole window, hard to change later

## ✓ TIPS &amp; BEST PRACTICES

- › Name frames after regions: toolbar, sidebar, body
- › Color frames temporarily to see their bounds
- › Wrap each region in its own class as it grows

## QUICK SUMMARY

- › Nest Frames; one manager per parent
- › pack for bars, grid for forms, place for overlays
- › Propagation off for fixed-size containers
- › Debug with colors and wininfo\_\*

## TK VARIABLES LINK DATA AND WIDGETS

**Control variables** (`StringVar`, `IntVar`, `DoubleVar`, `BooleanVar`) are values held inside the Tcl interpreter that widgets can watch. Connect one through `textvariable=` or `variable=`, and every widget using it updates when you call `set()`; every user edit is visible through `get()`. `trace_add()` registers a callback that fires when the variable is **written**, **read** or **unset**, which is how you build live previews and dependent fields.

## NOTES

- › Create variables after `Tk()` exists (or pass `master=`)
- › `IntVar.get()` raises `TclError` if the text isn't a valid int
- › Trace callbacks receive `(name, index, mode)` strings
- › `trace_add` replaces the deprecated `trace` / `trace_variable`
- › Keep a reference: an unreferenced variable is deleted

## LIVE TOTAL WITH TRACES

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
price = tk.DoubleVar(value=9.99)
qty = tk.IntVar(value=1)
total = tk.StringVar()

def update_total(*_):
    try:
        total.set(f"Total: ${price.get() * qty.get():.2f}")
    except tk.TclError:          # empty or invalid field
        total.set("Total: -")

for v in (price, qty):
    v.trace_add("write", update_total)
update_total()
ttk.Entry(root, textvariable=price, width=8).grid(row=0, column=0)
ttk.Spinbox(root, from_=1, to=99, textvariable=qty,
             width=4).grid(row=0, column=1, padx=4)
ttk.Label(root, textvariable=total).grid(row=1, column=0, columnspan=2)
tid = qty.trace_add("write", lambda *a: print("qty", qty.get()))
qty.trace_remove("write", tid)    # stop watching
print(qty.trace_info())           # [(['write',), 'name...']]
root.mainloop()
```

## CODE EXPLAINED

- `*_` absorbs the three trace arguments
- `try / except TclError` handles half-typed numbers
- The same callback traces both inputs
- `textvariable=` links Entry, Spinbox and Label
- `trace_add` returns an id needed by `trace_remove`

## VARIABLE TYPES

| CLASS                   | GET() RETURNS |
|-------------------------|---------------|
| <code>StringVar</code>  | str           |
| <code>IntVar</code>     | int           |
| <code>DoubleVar</code>  | float         |
| <code>BooleanVar</code> | bool          |
| <code>Variable</code>   | Raw Tcl value |

## VARIABLE METHODS

| METHOD                           | DOES              |
|----------------------------------|-------------------|
| <code>get()</code>               | Read value        |
| <code>set(v)</code>              | Write value       |
| <code>trace_add(mode, f)</code>  | Watch; returns id |
| <code>trace_remove(m, id)</code> | Stop watching     |
| <code>trace_info()</code>        | List traces       |

## TRACE MODES

| MODE    | FIRES WHEN       |
|---------|------------------|
| "write" | Value changes    |
| "read"  | Value read       |
| "unset" | Variable deleted |
| "array" | Tcl array access |

## △ COMMON MISTAKES

- › Creating a `StringVar()` before `Tk()` with no `master`
- › Letting `IntVar.get()` crash on an empty Entry
- › Writing to the same variable inside its write trace (recursion)

## ✓ TIPS &amp; BEST PRACTICES

- › Use variables for any value shown in more than one place
- › Wrap numeric `get()` calls in `try / except tk.TclError`
- › Give variables a `name=` to debug traces

## QUICK SUMMARY

- › `String/Int/Double/BooleanVar`
- › `get()` / `set()` sync all linked widgets
- › `trace_add("write", fn)` reacts to changes
- › Keep references so they aren't deleted

## WIRING BUTTONS TO FUNCTIONS

`command=` expects a **callable that takes no arguments**. To pass data, wrap the call in a `lambda` or `functools.partial`. The classic trap is **late binding** in loops: a `lambda` looks up loop variables when it runs, not when it's created, so every button ends up using the last value. Fix it by binding the current value as a **default argument** (`lambda n=n: ...`) or with `partial`. Bound methods (`self.save`) are the cleanest choice in class-based apps.

## NOTES

- › `command=f()` calls `f` once immediately; drop the parentheses
- › `partial` freezes arguments at creation time
- › Callbacks run on the main thread and block the UI while running
- › A callback's return value is ignored for `command=`
- › Exceptions print to `stderr`; the app keeps running

## PASSING ARGUMENTS SAFELY

```
import tkinter as tk
from functools import partial

root = tk.Tk()
display = tk.StringVar(value="")
tk.Entry(root, textvariable=display, justify="right",
         font=("Consolas", 14)).grid(row=0, column=0, columnspan=3)

def press(key):
    display.set(display.get() + key)
# WRONG: all buttons would type "9" (late binding)
# for i, k in enumerate("123456789"):
#     tk.Button(root, text=k, command=lambda: press(k))
for i, k in enumerate("123456789"):           # default-arg capture
    tk.Button(root, text=k, width=4,
              command=lambda k=k: press(k)).grid(row=1 + i // 3,
                                                  column=i % 3)

tk.Button(root, text="0", width=4,
          command=partial(press, "0")).grid(row=4, column=1)
tk.Button(root, text="C", width=4,
          command=lambda: display.set("")).grid(row=4, column=0)
tk.Button(root, text="=", width=4,
          command=lambda: display.set(str(eval(display.get() or "0")))).grid(row=4, column=2)

root.mainloop()
```

## CODE EXPLAINED

- `press(key)` needs an argument, so it can't go in `command` bare
- The commented loop shows the late-binding bug
- `k=k` copies the current value into the `lambda`
- `partial(press, "0")` is the import-based alternative
- Demo only: never `eval` untrusted input in real apps

## CALLBACK FORMS

| FORM                           | USE               |
|--------------------------------|-------------------|
| <code>command=f</code>         | No arguments      |
| <code>command=self.save</code> | Method in a class |
| <code>lambda: f(1)</code>      | Fixed arguments   |
| <code>lambda x=x: f(x)</code>  | Loop values       |
| <code>partial(f, x)</code>     | Freeze arguments  |

## LATE BINDING

| CODE                          | EACH BUTTON GETS                 |
|-------------------------------|----------------------------------|
| <code>lambda: f(i)</code>     | Last <code>i</code>              |
| <code>lambda i=i: f(i)</code> | Its own <code>i</code>           |
| <code>partial(f, i)</code>    | Its own <code>i</code>           |
| <code>def make(i)</code>      | Its own <code>i</code> (closure) |

## COMMAND VS BIND

| ASPECT         | COMMAND / BIND            |
|----------------|---------------------------|
| Arguments      | none / event              |
| Trigger        | widget action / any event |
| Keyboard       | space on focus / any key  |
| Return "break" | n/a / stops chain         |

## △ COMMON MISTAKES

- › `command=save()` runs at startup, not on click
- › Loop lambdas capturing the loop variable by reference
- › Doing slow work in a callback and freezing the window

## ✓ TIPS &amp; BEST PRACTICES

- › Prefer methods for callbacks with real logic
- › Use `partial` when the intent is clearer than a `lambda`
- › Move long tasks to threads or `after()` (Sheets 50–51)

## QUICK SUMMARY

- › `command=` takes a zero-argument callable
- › Use `lambda` or `partial` to pass data
- › Capture loop values with defaults
- › Keep callbacks short

## BINDING EVENTS TO HANDLERS

`widget.bind(sequence, handler)` calls `handler(event)` whenever the **event sequence** occurs on that widget. Sequences are strings in angle brackets: `<Modifier-Type-Detail>`, such as `<Button-1>` (left click), `<Control-s>`, `<KeyPress-Return>` or `<Double-Button-1>`. Common shorthand works too: `<Return>`, `<Escape>`, `<Key>` (any key). `<Configure>` fires on resize or move, and `<Enter>/<Leave>` track the mouse pointer entering or leaving a widget.

## NOTES

- › Handlers always receive one `event` argument
- › Letters are case-sensitive: `<Control-S>` needs Shift
- › `add="+"` adds a handler instead of replacing
- › Key events go to the widget with keyboard focus
- › macOS uses `<Command-...>` for Cmd shortcuts

## MOUSE, KEYBOARD AND RESIZE

```
import tkinter as tk

root = tk.Tk()
canvas = tk.Canvas(root, width=300, height=200, bg="white")
canvas.pack(fill="both", expand=True)
status = tk.Label(root, anchor="w"); status.pack(fill="x")

def on_click(e):
    canvas.create_oval(e.x - 4, e.y - 4, e.x + 4, e.y + 4, fill="red")

def on_drag(e):
    status.config(text=f"drag {e.x},{e.y}")

canvas.bind("<Button-1>", on_click)
canvas.bind("<B1-Motion>", on_drag)
canvas.bind("<Double-Button-1>", lambda e: canvas.delete("all"))
canvas.bind("<Enter>", lambda e: canvas.config(cursor="crosshair"))
canvas.bind("<Configure>",
            lambda e: status.config(text=f"size {e.width}x{e.height}"))
root.bind("<Control-s>", lambda e: print("save"))
root.bind("<Escape>", lambda e: root.destroy())
root.bind("<Key>", lambda e: print("key", e.keysym), add="+")
canvas.unbind("<B1-Motion>")      # remove a binding
root.mainloop()
```

## CODE EXPLAINED

- `<Button-1>` handler draws a dot at the click position
- `<B1-Motion>` = mouse moved while button 1 held
- `<Configure>` reports the new size on every resize
- Shortcuts bound on root work wherever focus is in that window
- `add="+"` keeps any existing `<Key>` handler

## MOUSE EVENTS

| SEQUENCE                             | WHEN                  |
|--------------------------------------|-----------------------|
| <code>&lt;Button-1&gt;</code>        | Left press            |
| <code>&lt;ButtonRelease-1&gt;</code> | Left release          |
| <code>&lt;Double-Button-1&gt;</code> | Double-click          |
| <code>&lt;B1-Motion&gt;</code>       | Drag with left        |
| <code>&lt;Button-3&gt;</code>        | Right click (Win/X11) |

## KEYBOARD EVENTS

| SEQUENCE                       | WHEN          |
|--------------------------------|---------------|
| <code>&lt;Key&gt;</code>       | Any key press |
| <code>&lt;Return&gt;</code>    | Enter key     |
| <code>&lt;Escape&gt;</code>    | Esc           |
| <code>&lt;Control-s&gt;</code> | Ctrl+S        |
| <code>&lt;F1&gt;</code>        | F1 key        |

## WINDOW EVENTS

| SEQUENCE                                                | WHEN             |
|---------------------------------------------------------|------------------|
| <code>&lt;Configure&gt;</code>                          | Resized / moved  |
| <code>&lt;Enter&gt;</code> / <code>&lt;Leave&gt;</code> | Pointer in / out |
| <code>&lt;FocusIn&gt;</code>                            | Gains focus      |
| <code>&lt;Map&gt;</code> / <code>&lt;Unmap&gt;</code>   | Shown / hidden   |
| <code>&lt;Destroy&gt;</code>                            | Being destroyed  |

## △ COMMON MISTAKES

- › Handler without an `event` parameter (TypeError on trigger)
- › Binding `<Control-S>` and wondering why Ctrl+S does nothing
- › Binding keys to a widget that never gets focus

## ✓ TIPS &amp; BEST PRACTICES

- › Bind app shortcuts on the root or with `bind_all`
- › Use `def handler(event=None)` to share with `command=`
- › Check `e.widget` when one handler serves many widgets

## QUICK SUMMARY

- › `bind("<Sequence>", handler)`
- › Handlers take one `event` argument
- › `<Modifier-Type-Detail>` syntax
- › `unbind` and `add="+"` manage handlers

## WHAT THE EVENT TELLS YOU

Every bound handler receives an **Event object** describing what happened. Which attributes are meaningful depends on the event type: mouse events fill `x/y` (relative to the widget) and `x_root/y_root` (relative to the screen); key events fill `keysym` (a name like "Return"), `char` (the typed character, possibly empty) and `keycode`; `<Configure>` fills `width/height`; `<MouseWheel>` fills `delta`. `event.widget` always names the widget that received the event.

## NOTES

- › Unused attributes hold `??` or `0`
- › `char` is `""` for keys like Shift or arrows
- › `keysym` is reliable across keyboard layouts
- › `state` is a bitmask of held modifiers
- › `delta` is  $\pm 120$  per notch on Windows, small values on macOS

## INSPECTING EVENTS

```
import tkinter as tk

root = tk.Tk()
out = tk.Label(root, width=48, anchor="w", font=("Consolas", 10))
out.pack(fill="x")
area = tk.Frame(root, width=320, height=160, bg="#eef")
area.pack(fill="both", expand=True)

def show(e):
    out.config(text=f"{e.type}: x={e.x} y={e.y} "
                  f"root=({e.x_root},{e.y_root}) num={e.num}")

def key(e):
    shift = bool(e.state & 0x0001)
    ctrl = bool(e.state & 0x0004)
    out.config(text=f"keysym={e.keysym!r} char={e.char!r} "
                  f"shift={shift} ctrl={ctrl}")

def wheel(e):
    step = -1 if e.delta > 0 else 1  # Windows/macOS
    out.config(text=f"wheel delta={e.delta} step={step}")
area.bind("<Button>", show)  # any mouse button
root.bind("<Key>", key)
area.bind("<MouseWheel>", wheel)
area.bind("<Button-4>", lambda e: out.config(text="X11 wheel up"))
area.bind("<Configure>", lambda e: print(e.widget, e.width, e.height))
root.mainloop()
```

## CODE EXPLAINED

- `e.type` names the event kind, e.g. `ButtonPress`
- `e.num` tells which mouse button was pressed
- Bit masks on `e.state` reveal Shift and Control
- `e.delta` sign gives wheel direction
- X11 sends wheel as `<Button-4>` / `<Button-5>` instead

## POSITION

| ATTRIBUTE                   | MEANING          |
|-----------------------------|------------------|
| <code>x, y</code>           | In widget pixels |
| <code>x_root, y_root</code> | On screen        |
| <code>width, height</code>  | Configure size   |
| <code>widget</code>         | Receiving widget |
| <code>time</code>           | Timestamp (ms)   |

## KEYBOARD

| ATTRIBUTE               | EXAMPLE             |
|-------------------------|---------------------|
| <code>keysym</code>     | "Return", "a", "F5" |
| <code>char</code>       | "a", "\r", ""       |
| <code>keycode</code>    | Hardware code       |
| <code>keysym_num</code> | Numeric keysym      |
| <code>state</code>      | Modifier mask       |

## STATE BITS

| MASK                | MODIFIER            |
|---------------------|---------------------|
| <code>0x0001</code> | Shift               |
| <code>0x0004</code> | Control             |
| <code>0x0008</code> | Alt / Mod1 (varies) |
| <code>0x0100</code> | Button 1 held       |
| <code>0x0400</code> | Button 3 held       |

## △ COMMON MISTAKES

- › Using `e.char` to detect arrows or function keys (it's empty)
- › Mixing up widget `x / y` and screen `x_root / y_root`
- › Assuming `delta` is  $\pm 120$  on every platform

## ✓ TIPS &amp; BEST PRACTICES

- › Print the whole event while learning: `print(e)`
- › Match on `keysym` for named keys
- › Normalize wheel input with the sign of `delta`

## QUICK SUMMARY

- › Handlers get an Event object
- › `x / y`, `x_root / y_root` for position
- › `keysym`, `char`, `state` for keys
- › `widget` names the source

## BIND TAGS AND CUSTOM EVENTS

Each widget has a list of **bindtags** that decides which bindings run for an event, in order: the widget itself, its **class** ("Entry"), its **toplevel** window, then "all". `bind()` targets the widget, `bind_class()` a whole class, and `bind_all()` the "all" tag. A handler that returns "break" stops the remaining tags, which is how you override default behavior. **Virtual events** like <<Save>> are named events you define with `event_add()` or fire with `event_generate()`.

## NOTES

- › Class bindings implement default widget behavior
- › Changing `bind_class` affects every widget of that class
- › Built-in virtual events: <<Copy>>, <<Paste>>, <<Modified>>
- › `event_generate` runs handlers immediately by default
- › `when="tail"` queues a generated event instead

## OVERRIDE, BROADCAST, SIGNAL

```
import tkinter as tk

root = tk.Tk()
entry = tk.Entry(root); entry.pack(padx=10, pady=10)
print(entry.bindtags())  # ('.!entry', 'Entry', '!', 'all')

def digits_only(e):
    if e.char and not e.char.isdigit() and e.keysym != "BackSpace":
        return "break"  # skip the class binding: no insert

entry.bind("<Key>", digits_only)

# Same shortcut for every widget in the app
root.bind_all("<Control-q>", lambda e: root.destroy())
# Virtual event mapped to two physical key combos
root.event_add("<<Save>>", "<Control-s>", "<F2>")
root.bind("<<Save>>", lambda e: print("saving..."))
# A custom signal any code can fire
root.bind("<<DataLoaded>>", lambda e: print("refresh UI"))
root.after(500, lambda: root.event_generate("<<DataLoaded>>"))
# Reorder tags: run toplevel bindings before the widget's own
tags = entry.bindtags()
entry.bindtags((tags[2], tags[0], tags[1], tags[3]))
root.mainloop()
```

## CODE EXPLAINED

- Tag order: widget, class, toplevel, all
- Returning "break" prevents the Entry class from inserting
- `bind_all` catches Ctrl+Q anywhere in the app
- `event_add` maps several key combos to <<Save>>
- `event_generate` fires a custom event on demand

## BINDING LEVELS

| METHOD                            | SCOPE                  |
|-----------------------------------|------------------------|
| <code>w.bind()</code>             | One widget             |
| <code>w.bind_class(c, ...)</code> | All widgets of class   |
| <code>w.bind_all()</code>         | Whole application      |
| <code>toplevel.bind()</code>      | Widgets in that window |
| <code>w.bindtags(tags)</code>     | Get/set order          |

## BUILT-IN VIRTUAL

| EVENT                | FIRES ON           |
|----------------------|--------------------|
| <<Copy>> <<Paste>>   | Clipboard keys     |
| <<Modified>>         | Text changed       |
| <<ListboxSelect>>    | Listbox selection  |
| <<ComboboxSelected>> | Combobox pick      |
| <<TreeviewSelect>>   | Treeview selection |

## VIRTUAL METHODS

| METHOD                          | DOES           |
|---------------------------------|----------------|
| <code>event_add(v, *seq)</code> | Map sequences  |
| <code>event_delete(v)</code>    | Remove mapping |
| <code>event_info(v)</code>      | List mappings  |
| <code>event_generate(ev)</code> | Fire event     |
| <code>when="tail"</code>        | Queue instead  |

## △ COMMON MISTAKES

- › Returning "break" from a `command=` callback (no effect)
- › Using `bind_class` and changing every Entry by accident
- › Firing `event_generate` from a worker thread

## ✓ TIPS &amp; BEST PRACTICES

- › Use "break" for input filters and custom keys
- › Name app events <<Noun>> and fire them on state changes
- › Prefer `bind_all` for global shortcuts only

## QUICK SUMMARY

- › Bindtags: widget → class → toplevel → all
- › "break" stops further handlers
- › `bind_class` / `bind_all` widen scope
- › Virtual events: <<Name>>

## KEYBOARD FOCUS AND NAVIGATION

Only one widget at a time has **keyboard focus**, and key events go to it. Users move focus with **Tab** and **Shift+Tab** in creation (stacking) order, skipping widgets whose `takefocus` is false. Set focus in code with `focus_set()`, and check it with `focus_get()`. `<FocusIn>` and `<FocusOut>` fire as focus moves, which suits field validation and highlighting. **Accelerators** shown in menus are just labels; you must also bind the keys yourself.

## NOTES

- ▷ `focus_set()` only takes effect when the window is active
- ▷ `focus_force()` steals focus from other apps; avoid it
- ▷ Labels and Frames don't take focus by default
- ▷ Tab order follows stacking order; `lift()` / `lower()` change it
- ▷ Use `tk_focusNext()` to find the next widget in order

## FORM FOCUS HANDLING

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
fields = []
for r, name in enumerate(("Name", "Email", "Phone")):
    ttk.Label(root, text=name).grid(row=r, column=0, sticky="w", padx=4)
    e = ttk.Entry(root, width=28)
    e.grid(row=r, column=1, pady=2, padx=4)
    fields.append(e)

ttk.Button(root, text="?", takefocus=False).grid(row=0, column=2) # no Tab
def next_field(event):
    event.widget.tk_focusNext().focus_set()
    return "break" # don't insert newline
def mark(event, on):
    event.widget.configure(style="Focus.TEntry" if on else "TEntry")
ttk.Style().configure("Focus.TEntry", fieldbackground="#ffffbd6")
for e in fields:
    e.bind("<Return>", next_field) # Enter acts like Tab
    e.bind("<FocusIn>", lambda ev: mark(ev, True))
    e.bind("<FocusOut>", lambda ev: mark(ev, False))
fields[0].focus_set() # start in Name
root.bind("<Control-l>", lambda e: print(root.focus_get()))
root.mainloop()
```

## CODE EXPLAINED

- Entries are created in order, so Tab follows rows
- `takefocus=False` removes the help button from the Tab cycle
- `tk_focusNext()` gives the next widget; "break" stops default
- `<FocusIn>` / `<FocusOut>` swap a highlighted style
- `focus_get()` returns the focused widget object

## FOCUS METHODS

| METHOD                      | DOES              |
|-----------------------------|-------------------|
| <code>focus_set()</code>    | Request focus     |
| <code>focus_get()</code>    | Focused widget    |
| <code>focus_force()</code>  | Force focus       |
| <code>tk_focusNext()</code> | Next in order     |
| <code>tk_focusPrev()</code> | Previous in order |

## FOCUS OPTIONS

| OPTION                          | EFFECT               |
|---------------------------------|----------------------|
| <code>takefocus=True</code>     | Always a tab stop    |
| <code>takefocus=False</code>    | Never a tab stop     |
| <code>highlightthickness</code> | Focus ring (classic) |
| <code>highlightcolor</code>     | Ring color           |

## ACCELERATOR PAIRS

| MENU LABEL   | BINDING     |
|--------------|-------------|
| Ctrl+S       | <Control-s> |
| Ctrl+Shift+S | <Control-S> |
| F5           | <F5>        |
| Cmd+S (mac)  | <Command-s> |
| Alt+X        | <Alt-x>     |

## △ COMMON MISTAKES

- ▷ Expecting `accelerator=` in menus to bind keys
- ▷ Calling `focus_set()` before the window is mapped
- ▷ Creating widgets out of visual order, scrambling Tab order

## ✓ TIPS &amp; BEST PRACTICES

- ▷ Set initial focus to the first field users need
- ▷ Reorder a Tab stop with `w.lift(other)` instead of re-creating it
- ▷ Keep keyboard-only use working for every form

## QUICK SUMMARY

- ▷ One focused widget receives keys
- ▷ Tab order = creation order
- ▷ `takefocus` controls tab stops
- ▷ Bind accelerator keys yourself

## BUILDING A MENU BAR

A menu bar is a `tk.Menu` attached to a window with `config(menu=menubar)`. Each top-level entry (File, Edit, Help) is another Menu added with `add_cascade()`, and its items are added with `add_command()`. Set `tearoff=0` on every menu, or Tk adds a dashed line that detaches the menu into its own window (an old X11 feature). `accelerator=` only **displays** a shortcut; bind the key separately. `underline=` marks the Alt-key mnemonic.

## NOTES

- There is no ttk menu; `tk.Menu` is native on Windows and macOS
- macOS puts the menu bar at the top of the screen
- A menu named `"apple"` becomes the macOS application menu
- `root.option_add("*tearOff", False)` disables tear-offs globally
- Menus are owned by the window; they can't be packed

## FILE / EDIT / HELP MENUS

```
import tkinter as tk
from tkinter import messagebox

root = tk.Tk()
root.option_add("*tearOff", False)
def new(e=None): print("new")
def save(e=None): print("save")

menubar = tk.Menu(root)
root.config(menu=menubar)

file_menu = tk.Menu(menubar)
menubar.add_cascade(label="File", menu=file_menu, underline=0)
file_menu.add_command(label="New", accelerator="Ctrl+N", command=new)
file_menu.add_command(label="Save", accelerator="Ctrl+S", command=save)
file_menu.add_separator()
file_menu.add_command(label="Exit", command=root.destroy)

help_menu = tk.Menu(menubar, name="help") # special Help menu name
menubar.add_cascade(label="Help", menu=help_menu, underline=0)
help_menu.add_command(label="About",
                      command=lambda: messagebox.showinfo("About", "Demo 1.0"))

root.bind("<Control-n>", new); root.bind("<Control-s>", save)
root.mainloop()
```

## CODE EXPLAINED

- `option_add("*tearOff", False)` must come before menus are made
- `config(menu=menubar)` installs the bar on the window
- Each cascade's `menu` is a child Menu of the bar
- `name="help"` gives the Help menu its platform placement
- `accelerator` text plus a real `bind()` for each shortcut

## MENU METHODS

| METHOD                         | ADDS           |
|--------------------------------|----------------|
| <code>add_cascade()</code>     | Submenu        |
| <code>add_command()</code>     | Clickable item |
| <code>add_separator()</code>   | Divider line   |
| <code>add_checkbutton()</code> | Toggle item    |
| <code>add_radiobutton()</code> | Choice item    |

## ITEM OPTIONS

| OPTION                   | PURPOSE           |
|--------------------------|-------------------|
| <code>label</code>       | Item text         |
| <code>command</code>     | Callback          |
| <code>accelerator</code> | Shortcut label    |
| <code>underline</code>   | Mnemonic index    |
| <code>state</code>       | normal / disabled |

## SPECIAL NAMES

| NAME=                 | EFFECT              |
|-----------------------|---------------------|
| <code>"apple"</code>  | macOS app menu      |
| <code>"help"</code>   | Help menu placement |
| <code>"window"</code> | macOS Window menu   |
| <code>"system"</code> | Windows system menu |

## △ COMMON MISTAKES

- Leaving tear-off lines on every menu
- Expecting `accelerator=` to bind the shortcut
- Calling `pack()` on a menu bar

## ✓ TIPS &amp; BEST PRACTICES

- Use the same function for the menu item and the key binding
- Group items with separators: New/Open, Save, Exit
- Test on macOS: the bar moves to the screen top

## QUICK SUMMARY

- `Menu + config(menu=...)`
- `add_cascade` for submenus, `add_command` for items
- `tearoff=0` everywhere
- Accelerators need separate bindings

## MENU ITEMS AND POPUP MENU

Menus can hold more than commands: `add_checkbutton()` toggles a variable, `add_radiobutton()` picks one value from a group, and nested `add_cascade()` builds submenus. Items are addressed by **index** or **label**; `entryconfigure()` changes them later, such as enabling Paste only when the clipboard has text. `postcommand=` runs just before a menu opens, which is the right time to refresh item states. A **context menu** is a Menu shown at the pointer with `tk_popup(x, y)`.

## NOTES

- › Right-click is `<Button-3>` on Windows/Linux, `<Button-2>` on macOS
- › Also bind `<Control-Button-1>` on macOS for one-button mice
- › `index("end")` gives the last item's index
- › Check and radio items share Tk variables like widgets
- › `delete(0, "end")` clears a menu for rebuilding

## VIEW OPTIONS AND RIGHT-CLICK MENU

```
import tkinter as tk

root = tk.Tk()
menubar = tk.Menu(root); root.config(menu=menubar)
text = tk.Text(root, width=40, height=8); text.pack()
wrap = tk.BooleanVar(value=True); theme = tk.StringVar(value="light")

view = tk.Menu(menubar, tearoff=0, postcommand=lambda: print("opening"))
menubar.add_cascade(label="View", menu=view)
view.add_checkbutton(label="Word wrap", variable=wrap,
    command=lambda: text.config(wrap="word" if wrap.get() else "none"))
themes = tk.Menu(view, tearoff=0)
view.add_cascade(label="Theme", menu=themes)
for t in ("light", "dark"):
    themes.add_radiobutton(label=t.title(), value=t, variable=theme)
popup = tk.Menu(root, tearoff=0)
for ev in ("Cut", "Copy", "Paste"):
    popup.add_command(label=ev, command=lambda ev=ev: text.event_generate(f"<<{ev}>>"))
def show_popup(e):
    state = "normal" if text.tag_ranges("sel") else "disabled"
    for label in ("Cut", "Copy"): popup.entryconfigure(label, state=state)
    popup.tk_popup(e.x_root, e.y_root)
aqua = root.tk.call("tk", "windowingsystem") == "aqua"
text.bind("<Button-2>" if aqua else "<Button-3>", show_popup)
```

## CODE EXPLAINED

- `add_checkbutton` toggles `wrap` and applies it
- A nested Menu becomes the Theme submenu
- Radio items share `theme`, so only one is ticked
- `entryconfigure(label, ...)` disables Cut/Copy without a selection
- `tk_popup` opens at screen coordinates from the event

## ITEM TYPES

| METHOD                       | BEHAVES LIKE |
|------------------------------|--------------|
| <code>add_command</code>     | Button       |
| <code>add_checkbutton</code> | Checkbutton  |
| <code>add_radiobutton</code> | Radiobutton  |
| <code>add_cascade</code>     | Submenu      |
| <code>add_separator</code>   | Divider      |

## EDITING ITEMS

| METHOD                              | DOES         |
|-------------------------------------|--------------|
| <code>entryconfigure(i, ...)</code> | Change item  |
| <code>entrycget(i, opt)</code>      | Read option  |
| <code>index(label)</code>           | Find index   |
| <code>delete(a, b)</code>           | Remove items |
| <code>invoke(i)</code>              | Run item     |

## POPUP CALLS

| CALL                        | PURPOSE            |
|-----------------------------|--------------------|
| <code>tk_popup(x, y)</code> | Show at screen pos |
| <code>post(x, y)</code>     | Show (low level)   |
| <code>unpost()</code>       | Hide               |
| <code>grab_release()</code> | Free pointer (X11) |

## △ COMMON MISTAKES

- › Binding only `<Button-3>`, so macOS right-click does nothing
- › Using widget `x / y` instead of `x_root / y_root` for popups
- › Changing items by numeric index after inserting new ones

## ✓ TIPS &amp; BEST PRACTICES

- › Refresh item states in `postcommand` or just before popping up
- › Address items by label so inserts don't break code
- › Reuse Cut/Copy/Paste through virtual events

## QUICK SUMMARY

- › Check, radio and cascade items
- › `entryconfigure` updates items
- › `postcommand` refreshes before opening
- › `tk_popup(x_root, y_root)` for context menus

## STANDARD MESSAGE BOXES

`tkinter.messagebox` shows native modal dialogs with one call. The **show** functions (`showinfo`, `showwarning`, `showerror`) only inform and return "ok". The **ask** functions return the user's answer: `askyesno()` and `askokcancel()` return `True/False`, `askyesnocancel()` adds `None` for Cancel, `askretrycancel()` returns a bool, and `askquestion()` returns the string "yes" or "no". Always pass `parent=` so the dialog is centered on, and owned by, the right window.

## NOTES

- › The call blocks until the user answers
- › `icon=` overrides the default (info, warning, error, question)
- › `default=` picks the button activated by Enter
- › `detail=` adds smaller secondary text (Tk 8.5+)
- › Appearance is native, so it differs by OS

## INFORM, CONFIRM, DECIDE

```
import tkinter as tk
from tkinter import messagebox as mb

root = tk.Tk()
dirty = True

def on_close():
    if dirty:
        answer = mb.askyesnocancel(
            "Unsaved changes", "Save changes before closing?",
            detail="Your edits will be lost if you don't save.",
            icon="warning", parent=root)
        if answer is None:           # Cancel: keep the window open
            return
        if answer:                   # Yes
            print("saving...")
        root.destroy()              # Yes, No, or nothing to save

def delete():
    if mb.askokcancel("Delete", "Delete 3 files?", icon="warning",
        default="cancel", parent=root):
        mb.showinfo("Done", "Files deleted.", parent=root)
tk.Button(root, text="Delete...", command=delete).pack(padx=30, pady=20)
root.protocol("WM_DELETE_WINDOW", on_close)
```

## CODE EXPLAINED

- `askyesnocancel` gives three outcomes: `True`, `False`, `None`
- Test `is None` first; `None` is also falsy
- `detail=` explains consequences under the main question
- `default="cancel"` makes Enter the safe choice
- `parent=root` keeps dialogs on top of the app

## FUNCTIONS

| FUNCTION                   | RETURNS                   |
|----------------------------|---------------------------|
| <code>showinfo()</code>    | "ok"                      |
| <code>showwarning()</code> | "ok"                      |
| <code>showerror()</code>   | "ok"                      |
| <code>askyesno()</code>    | <code>True / False</code> |
| <code>askokcancel()</code> | <code>True / False</code> |

## MORE

| FUNCTION                         | RETURNS                   |
|----------------------------------|---------------------------|
| <code>askretrycancel()</code>    | <code>True / False</code> |
| <code>askquestion()</code>       | "yes" / "no"              |
| <code>Message(...).show()</code> | Custom type               |

## OPTIONS

| OPTION               | VALUES                      |
|----------------------|-----------------------------|
| <code>parent</code>  | Owner window                |
| <code>icon</code>    | info/warning/error/question |
| <code>default</code> | ok/cancel/yes/no/retry      |
| <code>detail</code>  | Secondary text              |

## △ COMMON MISTAKES

- › Treating `askquestion()` like a bool ( "no" is truthy)
- › Checking `if not answer` and merging No with Cancel
- › Omitting `parent=` so dialogs appear behind Toplevels

## ✓ TIPS &amp; BEST PRACTICES

- › Make destructive confirmations default to Cancel
- › Write titles as short nouns, messages as questions
- › Use `showerror` for failures the user must act on

## QUICK SUMMARY

- › `show*` inform; `ask*` return answers
- › `askyesnocancel` → `True/False/None`
- › `parent=`, `icon=`, `default=`, `detail=`
- › Modal: blocks until answered

## OPEN AND SAVE FILE PICKERS

`tkinter.filedialog` wraps the native file pickers. `askopenfilename()` returns a **path string** (or `""` if cancelled), `askopenfilenames()` returns a tuple of paths, `asksaveasfilename()` returns the chosen save path, and `askdirectory()` returns a folder. The `askopenfile()/asksaveasfile()` variants return an **open file object** (or `None`). `filetypes` is a list of (label, pattern) pairs that fills the type drop-down.

## NOTES

- › Cancel returns `""` (or `()` / `None` for some variants)
- › Paths use forward slashes even on Windows
- › `defaultextension` is appended if the user omits one
- › `confirmoverwrite` (default `True`) asks before replacing
- › `initialfile` pre-fills the file name box

## OPEN, SAVE AS, CHOOSE FOLDER

```
import tkinter as tk
from tkinter import filedialog as fd
from pathlib import Path

root = tk.Tk()
TYPES = [("Text files", "*.txt"), ("Markdown", "*.md *.markdown"),
         ("All files", "*..*")]
text = tk.Text(root, width=60, height=15); text.pack()

def open_file():
    path = fd.askopenfilename(parent=root, title="Open",
                             filetypes=TYPES, initialdir=Path.home())

    if not path:
        # cancelled
        return
    text.delete("1.0", "end")
    text.insert("1.0", Path(path).read_text(encoding="utf-8"))

def save_as():
    path = fd.asksaveasfilename(parent=root, filetypes=TYPES,
                                defaultextension=".txt", initialfile="notes")

    if path:
        Path(path).write_text(text.get("1.0", "end-1c"), encoding="utf-8")
tk.Button(root, text="Open", command=open_file).pack(side="left")
tk.Button(root, text="Save As", command=save_as).pack(side="left")
tk.Button(root, text="Folder", command=lambda: print(
    fd.askdirectory(parent=root, mustexist=True))).pack(side="left")
```

## CODE EXPLAINED

- Patterns in one entry are space-separated
- `if not path` handles Cancel
- `initialdir` starts browsing in the home folder
- `defaultextension` adds `.txt` when missing
- `"end-1c"` avoids saving Text's extra newline

## FUNCTIONS

| FUNCTION                       | RETURNS        |
|--------------------------------|----------------|
| <code>askopenfilename</code>   | Path str       |
| <code>askopenfilenames</code>  | Tuple of paths |
| <code>asksaveasfilename</code> | Path str       |
| <code>askdirectory</code>      | Folder str     |
| <code>askopenfile</code>       | File object    |

## OPTIONS

| OPTION                        | PURPOSE          |
|-------------------------------|------------------|
| <code>filetypes</code>        | Type filter list |
| <code>initialdir</code>       | Start folder     |
| <code>initialfile</code>      | Default name     |
| <code>defaultextension</code> | Auto suffix      |
| <code>title</code>            | Dialog title     |

## FILETYPES PATTERNS

| ENTRY                                     | MATCHES          |
|-------------------------------------------|------------------|
| <code>("Images", "*.png *.jpg")</code>    | Several patterns |
| <code>("Python", "*.py")</code>           | One extension    |
| <code>("All", "*..*")</code>              | Everything       |
| <code>("Data", ("*.csv", "*.tsv"))</code> | Tuple form       |

## △ COMMON MISTAKES

- › Opening `""` after the user cancels
- › Using `askopenfile()` without closing the file object
- › Missing a `("All files", "*..*")` fallback entry

## ✓ TIPS &amp; BEST PRACTICES

- › Remember the last folder and pass it as `initialdir`
- › Prefer the filename functions plus `pathlib` for I/O
- › Always pass an encoding when reading text

## QUICK SUMMARY

- › `askopenfilename`, `asksaveasfilename`, `askdirectory`
- › Cancel → empty string
- › `filetypes` list of (label, pattern)
- › `defaultextension` for save dialogs

## QUICK INPUT AND COLOR DIALOGS

`tkinter.simplifiedialog` provides tiny modal prompts: `askstring()`, `askinteger()` and `askfloat()` show a field with OK/Cancel and return the typed value, or `None` if cancelled. The numeric versions validate input and support `minvalue`/`maxvalue`. `tkinter.colorchooser.askcolor()` opens the native color picker and returns `((r, g, b), "#rrggbb")`, or `(None, None)` on cancel. For anything richer, subclass `simplifiedialog.Dialog` and override `body()` and `apply()`.

## NOTES

- › Numeric dialogs re-prompt automatically on bad input
- › `initialvalue=` pre-fills the field
- › `show="*"` works on `askstring` for passwords
- › `Dialog` subclasses get OK/Cancel buttons for free
- › Tk has no built-in date picker; see `tkcalendar` (Sheet 60)

## PROMPTS AND A CUSTOM DIALOG

```
import tkinter as tk
from tkinter import simplifiedialog as sd, colorchooser, ttk

root = tk.Tk()
name = sd.askstring("Name", "Your name?", initialvalue="Ada", parent=root)
age = sd.askinteger("Age", "Age in years:", minvalue=0, maxvalue=130,
                    parent=root)
rgb, hexcolor = colorchooser.askcolor("#3366cc", title="Pick a color",
                                       parent=root)

if hexcolor:
    root.config(bg=hexcolor)

class LoginDialog(sd.Dialog):
    def body(self, master):
        ttk.Label(master, text="User").grid(row=0, column=0, sticky="w")
        ttk.Label(master, text="Password").grid(row=1, column=0, sticky="w")
        self.user = ttk.Entry(master); self.user.grid(row=0, column=1)
        self.pw = ttk.Entry(master, show="*"); self.pw.grid(row=1, column=1)
        return self.user                # widget with initial focus
    def validate(self):
        return bool(self.user.get())    # False keeps dialog open
    def apply(self):
        self.result = (self.user.get(), self.pw.get())
dlg = LoginDialog(root, title="Log in")
print(name, age, hexcolor, dlg.result)  # result is None on Cancel
```

## CODE EXPLAINED

- Each prompt returns `None` if the user cancels
- `askinteger` enforces the 0–130 range
- `askcolor` returns RGB and hex; hex is `None` on cancel
- `body()` builds fields and returns the focus widget
- `apply()` stores the answer in `self.result`

## SIMPLIFIEDIALOG

| FUNCTION                     | RETURNS              |
|------------------------------|----------------------|
| <code>askstring()</code>     | str or None          |
| <code>askinteger()</code>    | int or None          |
| <code>askfloat()</code>      | float or None        |
| <code>Dialog</code> subclass | <code>.result</code> |

## PROMPT OPTIONS

| OPTION                    | PURPOSE         |
|---------------------------|-----------------|
| <code>initialvalue</code> | Pre-filled text |
| <code>minvalue</code>     | Lower bound     |
| <code>maxvalue</code>     | Upper bound     |
| <code>show</code>         | Mask characters |
| <code>parent</code>       | Owner window    |

## DIALOG HOOKS

| METHOD                    | ROLE           |
|---------------------------|----------------|
| <code>body(master)</code> | Build fields   |
| <code>buttonbox()</code>  | Custom buttons |
| <code>validate()</code>   | OK allowed?    |
| <code>apply()</code>      | Store result   |

## △ COMMON MISTAKES

- › Using the result without checking for `None`
- › Reading `askcolor()[1]` as always present
- › Building fields in `__init__` instead of `body()`

## ✓ TIPS &amp; BEST PRACTICES

- › Use `simplifiedialog` for one value, a `Dialog` subclass for forms
- › Return the first `Entry` from `body()` for focus
- › Validate in `validate()` and explain errors with a `messagebox`

## QUICK SUMMARY

- › `askstring` / `askinteger` / `askfloat`
- › `askcolor` → (rgb, hex)
- › Cancel returns `None`
- › Subclass `Dialog` for custom forms

## WRITING YOUR OWN MODAL DIALOG

A **modal** dialog blocks the rest of the app until it closes. Build one from a `Toplevel` with four steps: `transient(parent)` to keep it above its parent, `grab_set()` to route all input to it, `wait_window()` to pause the caller until it's destroyed, and a result attribute the caller reads afterward. Bind `<Return>` to OK and `<Escape>` to Cancel, route the close button through `protocol()`, and center the dialog on its parent so it appears where the user is looking.

## NOTES

- › `wait_window()` keeps processing events (not frozen)
- › `grab_set()` may fail before the window is visible; call `wait_visibility()` first on X11
- › Release grabs automatically by destroying the dialog
- › Store the result before `destroy()`
- › A `simpldialog.Dialog` subclass does most of this for you

## REUSABLE MODAL DIALOG

```
import tkinter as tk
from tkinter import ttk

class RenameDialog(tk.Toplevel):
    def __init__(self, parent, old_name):
        super().__init__(parent)
        self.title("Rename"); self.result = None
        self.transient(parent)
        self.var = tk.StringVar(value=old_name)
        e = ttk.Entry(self, textvariable=self.var, width=30)
        e.pack(padx=12, pady=12); e.select_range(0, "end"); e.focus_set()
        ttk.Button(self, text="OK", command=self.ok).pack(side="left", padx=12)
        ttk.Button(self, text="Cancel", command=self.destroy).pack(side="right", padx=12)
        self.bind("<Return>", lambda e: self.ok())
        self.bind("<Escape>", lambda e: self.destroy())
        self.update_idletasks()                # center on parent
        x = parent.winfo_rootx() + (parent.winfo_width() - self.winfo_width()) // 2
        y = parent.winfo_rooty() + (parent.winfo_height() - self.winfo_height()) // 3
        self.geometry(f"+{x}+{y}")
        self.wait_visibility(); self.grab_set()
        self.wait_window()                     # block until closed

    def ok(self):
        self.result = self.var.get().strip() or None
        self.destroy()

# usage: name = RenameDialog(root, "report.txt").result
```

## CODE EXPLAINED

- `transient` + `grab_set` = classic modal behavior
- Entry text is pre-selected so typing replaces it
- Enter and Escape map to OK and Cancel
- Geometry is computed from the parent's position
- `wait_window()` returns after `destroy()`, then `.result` is read

## MODAL RECIPE

| STEP          | CALL                           |
|---------------|--------------------------------|
| Create        | <code>Toplevel(parent)</code>  |
| Stay on top   | <code>transient(parent)</code> |
| Capture input | <code>grab_set()</code>        |
| Block caller  | <code>wait_window()</code>     |
| Return value  | <code>self.result</code>       |

## GRAB METHODS

| METHOD                         | DOES                  |
|--------------------------------|-----------------------|
| <code>grab_set()</code>        | Local grab (this app) |
| <code>grab_set_global()</code> | Whole display (avoid) |
| <code>grab_release()</code>    | Release               |
| <code>grab_current()</code>    | Who holds the grab    |
| <code>grab_status()</code>     | local / global / None |

## WAIT METHODS

| METHOD                          | WAITS FOR   |
|---------------------------------|-------------|
| <code>wait_window(w)</code>     | w destroyed |
| <code>wait_visibility(w)</code> | w visible   |
| <code>wait_variable(v)</code>   | v written   |

## △ COMMON MISTAKES

- › Forgetting `grab_set()`, so users click the main window
- › Reading `.result` before `wait_window()` returns
- › Using `grab_set_global()`, which locks the whole desktop

## ✓ TIPS &amp; BEST PRACTICES

- › Return `None` for Cancel, a value for OK
- › Wrap the pattern in a base class for all your dialogs
- › Keep dialogs non-resizable unless content needs it

## QUICK SUMMARY

- › `Toplevel` + `transient` + `grab_set` + `wait_window`
- › Enter = OK, Escape = Cancel
- › Center on the parent window
- › Caller reads `dialog.result`

## THEMED WIDGETS AND THEMES

`tkinter.ttk` provides **themed** versions of most widgets plus several new ones (Combobox, Notebook, Progressbar, Treeview, Separator, Sizegrip). Their look comes from the active **theme** rather than per-widget color options, so the same code looks native on Windows (vista), macOS (aqua) and gets a clean cross-platform look with `clam.ttk.Style().theme_use()` reads or switches the theme for the whole app at once. Appearance changes go through **styles** (Sheet 34).

## NOTES

- › Importing `ttk` doesn't replace `tk` widgets; use `ttk.` explicitly
- › `from tkinter.ttk import *` after `from tkinter import *` shadows `tk` widgets
- › Linux defaults to `default`; `clam` usually looks better
- › Theme changes apply instantly to existing widgets
- › No `ttk` version of `Text`, `Canvas`, `Listbox`, `Menu` or `Toplevel`

## LISTING AND SWITCHING THEMES

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
style = ttk.Style(root)
print(style.theme_names())  # ('winnative', 'clam', 'alt', 'default', 'classic', 'vista')
print(style.theme_use())    # current theme, e.g. 'vista'

theme = tk.StringVar(value=style.theme_use())
box = ttk.Combobox(root, values=style.theme_names(),
                  textvariable=theme, state="readonly")
box.pack(padx=10, pady=10)
box.bind("<<ComboboxSelected>>", lambda e: style.theme_use(theme.get()))

ttk.Button(root, text="ttk.Button").pack(pady=4)
ttk.Checkbutton(root, text="ttk.Checkbutton").pack(pady=4)
ttk.Entry(root).pack(pady=4)
ttk.Progressbar(root, value=60, length=160).pack(pady=4)
tk.Button(root, text="classic tk.Button").pack(pady=4)  # unaffected

if root.tk.call("tk", "windowingsystem") == "x11":
    style.theme_use("clam")  # nicer default on Linux
root.mainloop()
```

## CODE EXPLAINED

- `theme_names()` lists themes available on this platform
- `theme_use()` with no argument returns the current theme
- Choosing a theme restyles every `ttk` widget immediately
- Classic `tk.Button` ignores `ttk` themes
- Switch Linux apps to `clam` for a modern flat look

## BUILT-IN THEMES

| THEME            | PLATFORM            |
|------------------|---------------------|
| vista / xpnative | Windows native      |
| winnative        | Windows classic     |
| aqua             | macOS native        |
| clam             | All; flat, modern   |
| alt / default    | All; basic          |
| classic          | All; old Motif look |

## TK → TTK

| CLASSIC        | THEMED                    |
|----------------|---------------------------|
| Button, Label  | ttk.Button, ttk.Label     |
| Entry, Frame   | ttk.Entry, ttk.Frame      |
| Checkbutton    | ttk.Checkbutton           |
| Scale, Spinbox | ttk.Scale, ttk.Spinbox    |
| OptionMenu     | ttk.Combobox / OptionMenu |
| PanedWindow    | ttk.Panedwindow           |

## TTK-ONLY WIDGETS

| WIDGET      | PURPOSE           |
|-------------|-------------------|
| Combobox    | Entry + drop-down |
| Notebook    | Tabs              |
| Progressbar | Progress          |
| Treeview    | Tree / table      |
| Separator   | Divider line      |
| Sizegrip    | Resize corner     |

## △ COMMON MISTAKES

- › Wildcard-importing `tkinter` and `ttk` in the wrong order
- › Setting `bg=` / `fg=` on `ttk` widgets
- › Hard-coding `vista` and crashing on macOS/Linux

## ✓ TIPS &amp; BEST PRACTICES

- › Use `ttk` for every widget it offers
- › Check `theme_names()` before calling `theme_use()`
- › Pick `clam` when you need consistent custom colors

## QUICK SUMMARY

- › `ttk` = themed, native-looking widgets
- › `Style().theme_use(name)` switches globally
- › Appearance via styles, not options
- › Six widgets exist only in `ttk`

## STYLING TTK WIDGETS

A **style** is a named bundle of appearance settings. Every ttk widget uses a default style named after its class (TButton, TLabel, TEntry, Treeview). `Style.configure(name, **opts)` sets options for a style, and `Style.map(name, **opts)` sets **state-dependent** options as lists of (state spec, value) pairs, such as a different background while active or pressed. Create a custom style by **prefixing** a class style ("Danger.TButton") and passing `style=` to the widget.

## NOTES

- › Changing `TButton` restyles every ttk Button
- › Prefixed styles inherit everything from the base style
- › Some themes (vista, aqua) ignore many color options; use `clam`
- › `lookup()` reads an effective option value
- › Use `"."` to configure the root style for all widgets

## CUSTOM BUTTON STYLES

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
style = ttk.Style(root)
style.theme_use("clam")                # honors color options

style.configure(".", font=("Segoe UI", 10))    # all widgets
style.configure("TButton", padding=(10, 4))
style.configure("Danger.TButton", foreground="white",
                background="#c62828", bordercolor="#8e0000")
style.map("Danger.TButton",
          background=[("pressed", "#8e0000"), ("active", "#e53935"),
                      ("disabled", "#bdbdbd")],
          foreground=[("disabled", "#eeeeee")])

style.configure("Title.TLabel", font=("Segoe UI", 16, "bold"))
style.configure("Hint.TLabel", foreground="gray40")

ttk.Label(root, text="Account", style="Title.TLabel").pack(anchor="w", padx=10)
ttk.Label(root, text="This can't be undone.", style="Hint.TLabel").pack(padx=10)
ttk.Button(root, text="Cancel").pack(side="left", padx=10, pady=10)
ttk.Button(root, text="Delete", style="Danger.TButton").pack(side="right", padx=10)
print(style.lookup("Danger.TButton", "background"))    # '#c62828'
root.mainloop()
```

## CODE EXPLAINED

- `clam` respects background/foreground; native themes may not
- `"."` sets defaults for every style
- `Danger.TButton` inherits TButton and overrides colors
- `map()` entries are checked in order; first matching state wins
- Widgets opt in with `style="Name.TClass"`

## STYLE METHODS

| METHOD                         | DOES                    |
|--------------------------------|-------------------------|
| <code>configure(s, **o)</code> | Set options             |
| <code>map(s, **o)</code>       | State-based options     |
| <code>lookup(s, opt)</code>    | Read effective value    |
| <code>layout(s)</code>         | Element tree (Sheet 35) |
| <code>theme_use(name)</code>   | Switch theme            |

## CLASS STYLE NAMES

| WIDGET                     | STYLE                        |
|----------------------------|------------------------------|
| <code>Button</code>        | <code>TButton</code>         |
| <code>Label / Entry</code> | <code>TLabel / TEntry</code> |
| <code>Frame</code>         | <code>TFrame</code>          |
| <code>Notebook</code>      | <code>TNotebook</code>       |
| <code>Treeview</code>      | <code>Treeview</code>        |

## STATE SPECS

| SPEC                   | MATCHES        |
|------------------------|----------------|
| <code>active</code>    | Mouse over     |
| <code>pressed</code>   | Being clicked  |
| <code>disabled</code>  | state disabled |
| <code>focus</code>     | Has focus      |
| <code>!disabled</code> | NOT disabled   |

## △ COMMON MISTAKES

- › Styling on `vista / aqua` and seeing no color change
- › Naming a style `Danger` without the `.TButton` suffix
- › Using `configure` for hover colors instead of `map`

## ✓ TIPS &amp; BEST PRACTICES

- › Define all styles in one function at startup
- › Name styles by role: `Primary.TButton`, `Muted.TLabel`
- › Put specific states ( `pressed` ) before general ones ( `active` )

## QUICK SUMMARY

- › Styles named `Prefix.TClass`
- › `configure` = static, `map` = per-state
- › Widgets choose via `style=`
- › `clam` for full color control

## LAYOUTS, ELEMENTS AND CUSTOM THEMES

Under the hood, each ttk style is drawn from **elements** (border, padding, label, indicator...) arranged in a **layout** tree. `Style.layout(name)` shows or replaces that tree, and `element_options(element)` lists what each element accepts, which tells you which `configure()` options actually work in the current theme. `element_create()` builds new elements (for example from images), and `theme_create()` with `theme_settings()` defines a whole theme based on an existing parent theme.

## NOTES

- › Layouts differ between themes; inspect, don't assume
- › Removing an element from a layout hides that part
- › Image elements enable fully custom-looking widgets
- › `theme_settings()` can change an existing theme too
- › Libraries like sv-ttk ship complete image-based themes

## INSPECT AND MODIFY A LAYOUT

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
style = ttk.Style(root); style.theme_use("clam")
print(style.layout("TButton"))
# [('Button.border', {'sticky': 'nswe', 'border': '1', 'children':
#   [('Button.focus', {... 'children': [('Button.padding', {...
#     'children': [('Button.label', {'sticky': 'nswe'})]}]}]}))]
print(style.element_options("Button.label")) # ('compound', 'space', 'text', ...)
# Notebook without the dotted focus ring around tab labels
style.layout("TNotebook.Tab", [{"Notebook.tab", {"sticky": "nswe", "children": [
  ("Notebook.padding", {"side": "top", "sticky": "nswe", "children": [
    ("Notebook.label", {"side": "top", "sticky": ""})]}]}]})
# A new theme derived from clam
style.theme_create("brand", parent="clam", settings={
    "TButton": {"configure": {"padding": 8, "background": "#00695c",
        "foreground": "white"},
    "map": {"background": ["active", "#00897b"]}},
    "TLabel": {"configure": {"foreground": "#004d40"}},
})
style.theme_use("brand")
ttk.Label(root, text="Branded").pack(padx=20, pady=6)
ttk.Button(root, text="Go").pack(pady=6)
root.mainloop()
```

## CODE EXPLAINED

- `layout()` returns a nested list of (element, options)
- `element_options` reveals supported options per element
- Replacing the Tab layout drops `Notebook.focus`
- `settings` uses `configure / map / layout` keys per style
- Derived themes inherit everything they don't override

## ELEMENT API

| METHOD                          | DOES              |
|---------------------------------|-------------------|
| <code>element_names()</code>    | Elements in theme |
| <code>element_options(e)</code> | Its options       |
| <code>element_create()</code>   | New element       |
| <code>layout(s, spec)</code>    | Set layout        |
| <code>layout(s)</code>          | Read layout       |

## THEME API

| METHOD                               | DOES         |
|--------------------------------------|--------------|
| <code>theme_create(n, parent)</code> | New theme    |
| <code>theme_settings(n, d)</code>    | Modify theme |
| <code>theme_use(n)</code>            | Activate     |
| <code>theme_names()</code>           | List themes  |

## LAYOUT KEYS

| KEY                   | MEANING             |
|-----------------------|---------------------|
| <code>side</code>     | Pack side in parent |
| <code>sticky</code>   | Stretch edges       |
| <code>expand</code>   | Take extra space    |
| <code>border</code>   | Border size         |
| <code>children</code> | Nested elements     |

## △ COMMON MISTAKES

- › Configuring options the theme's elements don't support
- › Copying a layout from one theme into another blindly
- › Creating the same theme twice ( `TclError` )

## ✓ TIPS &amp; BEST PRACTICES

- › Print `layout()` before editing it
- › Derive custom themes from `clam`
- › Reach for sv-ttk or ttkbootstrap before hand-building themes

## QUICK SUMMARY

- › Styles = layouts of elements
- › `layout()` and `element_options()` to inspect
- › `theme_create / theme_settings` for themes
- › Derive from `clam` for control

## TTK BASICS AND WIDGET STATE

Core ttk widgets (Button, Label, Entry, Checkbutton, Radiobutton, Frame, Scale, Scrollbar) work like their classic counterparts but share a common **state** system. Each widget has a set of state flags (disabled, focus, pressed, selected, readonly, invalid, alternate...). `state(["disabled"])` sets flags, `state(["!disabled"])` clears them, and `instate(["selected"])` tests them. Styles map their looks to these same flags.

## NOTES

- › `state()` with no args returns current flags
- › `configure(state="disabled")` still works on most ttk widgets
- › `invalid` is set by validation and can be styled
- › `padding` is a ttk option on many widgets
- › Classic-only options ( `bg` , `relief` ) raise `TclError`

## TOGGLING AND TESTING STATE

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
frm = ttk.Frame(root, padding=12); frm.pack()

agree = tk.BooleanVar()
name = ttk.Entry(frm, width=24)
check = ttk.Checkbutton(frm, text="I agree", variable=agree)
submit = ttk.Button(frm, text="Submit")
name.grid(row=0, column=0, pady=4)
check.grid(row=1, column=0, sticky="w")
submit.grid(row=2, column=0, pady=6)
def refresh(*_):
    ok = agree.get() and name.get().strip()
    submit.state(["!disabled"] if ok else ["disabled"])
    name.state(["!invalid"] if name.get().strip() else ["invalid"])
agree.trace_add("write", refresh)
name.bind("<KeyRelease>", refresh)
refresh()
ttk.Style().map("TEntry", fieldbackground=[("invalid", "#ffe0e0")])
print(submit.state())           # ('disabled',)
print(check.instate(["selected"])) # False
check.state(["alternate"])      # tri-state "mixed" look
root.mainloop()
```

## CODE EXPLAINED

- `state(["disabled"])` / `["!disabled"]` toggle a flag
- Submit is enabled only when both conditions hold
- `invalid` flag plus a style map tints the Entry
- `instate()` returns a bool for a flag test
- `alternate` shows a Checkbutton as partially checked

## STATE FLAGS

| FLAG                  | MEANING            |
|-----------------------|--------------------|
| <code>disabled</code> | Not interactive    |
| <code>readonly</code> | No editing         |
| <code>focus</code>    | Has keyboard focus |
| <code>selected</code> | Checked / on       |
| <code>invalid</code>  | Failed validation  |

## STATE METHODS

| CALL                            | DOES           |
|---------------------------------|----------------|
| <code>state()</code>            | Current flags  |
| <code>state(["f"])</code>       | Set flag       |
| <code>state(["!f"])</code>      | Clear flag     |
| <code>instate(["f"])</code>     | Test flag      |
| <code>instate(["f"], cb)</code> | Call cb if set |

## COMMON TTK OPTIONS

| OPTION                 | WIDGETS              |
|------------------------|----------------------|
| <code>style</code>     | All                  |
| <code>padding</code>   | Button, Label, Frame |
| <code>width</code>     | Button, Label, Entry |
| <code>cursor</code>    | All                  |
| <code>takefocus</code> | Interactive widgets  |

## △ COMMON MISTAKES

- › Passing a string instead of a list: `state("disabled")`
- › Mixing `configure(state=...)` and `state()` inconsistently
- › Expecting `instate` to return the flag list

## ✓ TIPS & BEST PRACTICES

- › Drive enabled/disabled from one `refresh()` function
- › Style the `invalid` state for validation feedback
- › Use `alternate` for "some selected" parent checkboxes

## QUICK SUMMARY

- › Shared state flags across ttk
- › `state([...])` sets/clears with `!`
- › `instate([...])` tests
- › Styles map looks to states

## DROP-DOWNS AND SPIN INPUTS

`ttk.Combobox` combines an `Entry` with a drop-down list from `values`. By default users can type anything; `state="readonly"` restricts them to the list, which suits fixed choices. Read the value with `get()` or a `textvariable`, the position with `current()`, and react with `<<ComboboxSelected>>`. `ttk.Spinbox` steps through a range or list with arrows, and `ttk.Scale` is a themed slider whose value is a float you round yourself.

## NOTES

- › `values` can be updated at any time with `configure()`
- › `current(i)` selects by index; `current()` returns it (-1 if none)
- › `<<ComboboxSelected>>` fires only on list picks, not typing
- › `postcommand` refreshes the list just before it opens
- › `ttk.Spinbox` fires `<<Increment>>` and `<<Decrement>>`

## COUNTRY / STATE PICKER

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
data = {"USA": ["California", "Texas", "Wisconsin"],
        "Canada": ["Ontario", "Quebec", "Alberta"]}

country = ttk.Combobox(root, values=list(data), state="readonly", width=18)
region = ttk.Combobox(root, state="readonly", width=18)
country.grid(row=0, column=0, padx=8, pady=6)
region.grid(row=0, column=1, padx=8)

def on_country(event):
    region.configure(values=data[country.get()])
    region.current(0)
country.bind("<<ComboboxSelected>>", on_country)
country.current(0); on_country(None)
qty = ttk.Spinbox(root, from_=1, to=20, width=5, wrap=True)
qty.set(1); qty.grid(row=1, column=0, sticky="w", padx=8)
zoom = tk.DoubleVar(value=100)
ttk.Scale(root, from_=25, to=400, variable=zoom,
           command=lambda v: zoom.set(round(float(v) / 25) * 25)
           ).grid(row=1, column=1, sticky="ew", padx=8)
ttk.Label(root, textvariable=zoom).grid(row=2, column=1)
root.mainloop()
```

## CODE EXPLAINED

- `readonly` limits choices to `values`
- Selecting a country reloads the region list
- `current(0)` selects the first entry in code
- `Spinbox.set()` sets the shown value
- The Scale callback snaps the float to steps of 25

## COMBOBOX

| MEMBER                                   | PURPOSE             |
|------------------------------------------|---------------------|
| <code>values</code>                      | Choice list         |
| <code>state</code>                       | normal / readonly   |
| <code>current(i)</code>                  | Select / get index  |
| <code>get()</code> / <code>set(v)</code> | Read / write text   |
| <code>postcommand</code>                 | Refresh before open |

## TTK.SPINBOX

| OPTION                  | PURPOSE        |
|-------------------------|----------------|
| <code>from_ / to</code> | Range          |
| <code>increment</code>  | Step           |
| <code>values</code>     | Fixed list     |
| <code>wrap</code>       | Loop at ends   |
| <code>command</code>    | On arrow click |

## TTK.SCALE

| OPTION                  | PURPOSE               |
|-------------------------|-----------------------|
| <code>from_ / to</code> | Range                 |
| <code>variable</code>   | Linked DoubleVar      |
| <code>orient</code>     | horizontal / vertical |
| <code>length</code>     | Pixel length          |
| <code>command</code>    | On change (str)       |

## △ COMMON MISTAKES

- › Binding `<<ComboboxSelected>>` and expecting typed input to fire it
- › Using `current()` result -1 as a valid index
- › Expecting `ttk.Scale` to support `resolution`

## ✓ TIPS &amp; BEST PRACTICES

- › Use readonly Comboboxes for enums and categories
- › Chain dependent Comboboxes with the selected event
- › Show a Scale's value in a Label for clarity

## QUICK SUMMARY

- › Combobox: `values`, `current()`, `readonly`
- › `<<ComboboxSelected>>` on list picks
- › `ttk.Spinbox`: arrows over range/list
- › `ttk.Scale`: float value, round yourself

## TABS AND SPLIT PANES

`ttk.Notebook` shows one child at a time behind a row of **tabs**. Each page is usually a `Frame` added with `add(child, text=...)`. `select()` switches tabs, `tab()` reads or changes tab options, and `<<NotebookTabChanged>>` fires when the tab changes. `enable_traversal()` adds `Ctrl+Tab` navigation. `ttk.Panedwindow` is the themed splitter: add panes with `add(child, weight=n)` and users drag the sash between them.

## NOTES

- › Tabs can be identified by index, child widget or `"current"`
- › `hide(tab)` hides a tab; `add()` the same child to show it again
- › `forget(tab)` removes it entirely
- › `state="disabled"` greys out a tab
- › `ttk.Panedwindow` uses `weight`, not `minsize` / `stretch`

## SETTINGS WINDOW WITH TABS

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk(); root.geometry("420x260")
nb = ttk.Notebook(root)
nb.pack(fill="both", expand=True, padx=6, pady=6)

general, advanced, about = (ttk.Frame(nb, padding=10) for _ in range(3))
nb.add(general, text="General", underline=0)
nb.add(advanced, text="Advanced", underline=0)
nb.add(about, text="About", state="disabled")
nb.enable_traversal()           # Ctrl+Tab, Alt+G, Alt+A

ttk.Checkbutton(general, text="Start at login").pack(anchor="w")
panes = ttk.Panedwindow(advanced, orient="horizontal")
panes.pack(fill="both", expand=True)
panes.add(ttk.Treeview(panes, show="tree"), weight=1)
panes.add(tk.Text(panes, width=20), weight=3)
def changed(event):
    i = nb.index("current")
    root.title(f"Settings - {nb.tab(i, 'text')}")
nb.bind("<<NotebookTabChanged>>", changed)
nb.select(advanced)             # open on Advanced
nb.tab(about, state="normal")   # enable later
root.mainloop()
```

## CODE EXPLAINED

- Each tab's page is a padded `Frame`
- `underline` plus `enable_traversal()` adds `Alt` shortcuts
- A disabled tab is visible but not selectable
- Pane weights 1:3 split extra width
- `index("current") + tab(i, "text")` read the active tab

## NOTEBOOK METHODS

| METHOD                     | DOES                 |
|----------------------------|----------------------|
| <code>add(w, **o)</code>   | Add tab              |
| <code>select(tab)</code>   | Switch / get current |
| <code>tab(tab, **o)</code> | Tab options          |
| <code>hide(tab)</code>     | Hide tab             |
| <code>forget(tab)</code>   | Remove tab           |

## TAB OPTIONS

| OPTION                                     | PURPOSE                |
|--------------------------------------------|------------------------|
| <code>text</code>                          | Label                  |
| <code>image</code> / <code>compound</code> | Icon                   |
| <code>state</code>                         | normal/disabled/hidden |
| <code>underline</code>                     | Mnemonic               |
| <code>sticky</code>                        | Page stretch           |

## TTK.PANEDWINDOW

| METHOD                        | DOES         |
|-------------------------------|--------------|
| <code>add(w, weight=n)</code> | Add pane     |
| <code>insert(pos, w)</code>   | Insert pane  |
| <code>forget(w)</code>        | Remove pane  |
| <code>sashpos(i, x)</code>    | Get/set sash |
| <code>panes()</code>          | List panes   |

## ⚠ COMMON MISTAKES

- › Packing pages into the Notebook instead of `add()`
- › Using `select()` return value as an index (it's a widget name)
- › Passing `minsize=` to `ttk.Panedwindow` panes

## ✓ TIPS &amp; BEST PRACTICES

- › Build each tab as its own `Frame` subclass
- › Load expensive tabs lazily on first `<<NotebookTabChanged>>`
- › Save `sashpos` in settings to restore layouts

## QUICK SUMMARY

- › Notebook: `add`, `select`, `tab`
- › `<<NotebookTabChanged>>` event
- › `enable_traversal()` for keyboard
- › Panedwindow: `add(w, weight=n)`

# Progressbar, Separator & Sizegrip

ttk.Progressbar · determinate · indeterminate · start() · step() ·  
ttk.Separator · ttk.Sizegrip

## PROGRESS, DIVIDERS AND RESIZE GRIPS

`ttk.Progressbar` shows progress in two modes. **Determinate** fills toward maximum as you set value (or call `step()`). **Indeterminate** bounces back and forth with `start(ms)` / `stop()` when the total is unknown. Update the bar from the main thread, usually inside `after()` callbacks; a loop that blocks the event loop freezes it. `ttk.Separator` draws a thin horizontal or vertical divider, and `ttk.Sizegrip` adds the resize handle in a window's bottom-right corner.

## NOTES

- › `maximum` defaults to 100
- › `step(n)` adds `n` and wraps at `maximum`
- › Bind the bar to a `DoubleVar` with `variable=`
- › Separators need `fill="x"` / `sticky="ew"` to stretch
- › macOS shows its own resize corner; `Sizegrip` is optional there

## DOWNLOAD SIMULATION

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk(); root.geometry("360x180")
progress = tk.DoubleVar()

ttk.Label(root, text="Downloading...").pack(anchor="w", padx=10, pady=(10, 0))
bar = ttk.Progressbar(root, mode="determinate", maximum=50,
                      variable=progress, length=320)
bar.pack(padx=10, pady=6)
spinner = ttk.Progressbar(root, mode="indeterminate", length=320)
spinner.pack(padx=10)
ttk.Separator(root, orient="horizontal").pack(fill="x", pady=10)
status = ttk.Label(root, text="0%"); status.pack(side="left", padx=10)
ttk.Sizegrip(root).pack(side="right", anchor="se")

def tick():
    if progress.get() < bar["maximum"]:
        progress.set(progress.get() + 1)
        status.config(text=f"{progress.get() / bar['maximum']:.0%}")
        root.after(80, tick)          # schedule next update
    else:
        spinner.stop(); status.config(text="Done")
spinner.start(15)                    # ms per animation step
root.after(200, tick)
root.mainloop()
```

## CODE EXPLAINED

- `maximum=50` means 50 units fill the bar
- `variable=progress` drives the bar from a `DoubleVar`
- The indeterminate bar animates on its own after `start()`
- `after(80, tick)` updates without blocking the loop
- `Sizegrip` packs into the bottom-right corner

## PROGRESSBAR

| MEMBER                                       | PURPOSE                     |
|----------------------------------------------|-----------------------------|
| <code>mode</code>                            | determinate / indeterminate |
| <code>maximum</code>                         | Full value                  |
| <code>value</code>                           | Current value               |
| <code>variable</code>                        | Linked var                  |
| <code>start(ms)</code> / <code>stop()</code> | Auto animate                |

## SEPARATOR

| OPTION                         | USE               |
|--------------------------------|-------------------|
| <code>orient=horizontal</code> | Row divider       |
| <code>orient=vertical</code>   | Column divider    |
| <code>pack(fill="x")</code>    | Stretch with pack |
| <code>grid(sticky="ns")</code> | Stretch with grid |

## MODE CHOICE

| SITUATION     | MODE                 |
|---------------|----------------------|
| Known total   | determinate          |
| Unknown total | indeterminate        |
| Many files    | determinate by count |
| Network wait  | indeterminate        |

## △ COMMON MISTAKES

- › Updating the bar in a `for` loop with `time.sleep` (frozen UI)
- › Forgetting `stop()` on an indeterminate bar
- › Setting `value` above `maximum`

## ✓ TIPS & BEST PRACTICES

- › Pair the bar with a text percentage for accessibility
- › Feed progress from threads through a queue (Sheet 51)
- › Use `length=` for a consistent bar width

## QUICK SUMMARY

- › Determinate: `value` / `maximum`
- › Indeterminate: `start()` / `stop()`
- › Update via `after()`, not loops
- › Separator divides, `Sizegrip` resizes

## TABLES AND TREES WITH TREEVIEW

`ttk.Treeview` displays **hierarchical** items, **tabular** rows with columns, or both. Declare data columns with `columns=(...)`, then set each header with `heading()` and width with `column()`. `show="headings"` hides the tree column for a plain table, and `show="tree"` shows only the tree. `insert(parent, index, values=...)` adds a row and returns its **item id**; use `""` as the parent for top-level items. `item()` reads or updates a row, and `delete()` removes rows.

## NOTES

- › Column `#0` is the tree column (labels via `text=`)
- › Item ids are strings; pass `iid=` to choose your own
- › `get_children()` lists items under a parent
- › Values are stored as strings; convert when reading
- › Add a Scrollbar with `yscrollcommand` like a Listbox

## EMPLOYEE TABLE

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
cols = ("name", "dept", "salary")
tree = ttk.Treeview(root, columns=cols, show="headings", height=8)
sb = ttk.Scrollbar(root, orient="vertical", command=tree.yview)
tree.config(yscrollcommand=sb.set)
tree.grid(row=0, column=0, sticky="nsew"); sb.grid(row=0, column=1, sticky="ns")
root.columnconfigure(0, weight=1); root.rowconfigure(0, weight=1)

for c, title, w, anchor in [("name", "Name", 160, "w"),
                           ("dept", "Department", 120, "w"),
                           ("salary", "Salary", 90, "e")]:
    tree.heading(c, text=title, anchor=anchor)
    tree.column(c, width=w, anchor=anchor, stretch=(c == "name"))
rows = [("Ada Lovelace", "R&D", 98000), ("Alan Turing", "R&D", 102000),
        ("Grace Hopper", "Ops", 95000)]
for r in rows:
    tree.insert("", "end", values=(r[0], r[1], f"{r[2]:,}"))
iid = tree.insert("", 0, iid="new", values=("New Hire", "Sales", "60,000"))
tree.item(iid, values=("Jo Doe", "Sales", "61,000")) # update row
print(tree.item(iid, "values")) # ('Jo Doe', 'Sales', '61,000')
print(len(tree.get_children())) # 4
tree.delete(*tree.get_children()[2:]) # remove rows 3+
root.mainloop()
```

## CODE EXPLAINED

- `show="headings"` hides the tree column for a flat table
- `heading()` sets titles; `column()` sets width and alignment
- `stretch` lets only the Name column absorb extra width
- `insert("", "end", values=...)` appends a top-level row
- `item(iid, values=...)` edits a row in place

## SETUP

| CALL                            | PURPOSE                |
|---------------------------------|------------------------|
| <code>columns=(...)</code>      | Column ids             |
| <code>show=</code>              | tree / headings / both |
| <code>heading(c, text=)</code>  | Header label           |
| <code>column(c, width=)</code>  | Width                  |
| <code>column(c, anchor=)</code> | Alignment              |

## ITEMS

| METHOD                         | DOES             |
|--------------------------------|------------------|
| <code>insert(p, i, ...)</code> | Add; returns iid |
| <code>item(iid, **o)</code>    | Read / update    |
| <code>set(iid, col, v)</code>  | One cell         |
| <code>delete(*iids)</code>     | Remove           |
| <code>get_children(p)</code>   | Child ids        |

## INSERT() OPTIONS

| OPTION              | PURPOSE           |
|---------------------|-------------------|
| <code>text</code>   | Tree column label |
| <code>values</code> | Column values     |
| <code>iid</code>    | Custom id         |
| <code>open</code>   | Expanded?         |
| <code>tags</code>   | Style/event tags  |

## △ COMMON MISTAKES

- › Forgetting `show="headings"` and getting an empty first column
- › Reusing an `iid` (raises `TclError`)
- › Sorting numeric columns as strings

## ✓ TIPS &amp; BEST PRACTICES

- › Use database primary keys as `iid` for easy lookup
- › Right-align numeric columns with `anchor="e"`
- › Clear with `delete(*tree.get_children())`

## QUICK SUMMARY

- › `columns`, `heading`, `column` define the table
- › `insert("", "end", values=...)` adds rows
- › Item ids identify rows
- › `show="headings"` for flat tables

# Treeview — Selection, Tags & Sorting

selection() · <<TreeviewSelect>> · tag\_configure() · parent/child items · sort on heading click · see() · move()

## WORKING WITH TREEVIEW DATA

Treeview selections are **item ids**: selection() returns the selected ids, and <<TreeviewSelect>> fires when it changes. focus() gives the item with keyboard focus. For hierarchies, pass a parent id to insert(), open or close nodes with item(iiid, open=True), and react to <<TreeviewOpen>> to **lazy-load** children. **Tags** style rows (striping, highlighting) and can receive events via tag\_bind(). Sorting isn't built in; reorder rows with move() from a heading's command.

## NOTES

- › selectmode: extended (default), browse, none
- › see(iiid) scrolls an item into view
- › identify\_row(y) finds the row under the mouse
- › parent(iiid) and next(iiid) navigate the tree
- › Tag colors need the clam-style themes on some platforms

## SORTABLE, STRIPED, HIERARCHICAL

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
tree = ttk.Treeview(root, columns=("size",)); tree.pack(fill="both", expand=True)
tree.heading("#0", text="Name")
tree.tag_configure("odd", background="#f3f3f8")
tree.tag_configure("big", foreground="#c62828")

docs = tree.insert("", "end", text="Documents", open=True)
for i, (name, kb) in enumerate([("cv.pdf", 120), ("video.mp4", 9800),
                               ("notes.txt", 4)]):
    tags = (("odd",) if i % 2 else ()) + (("big",) if kb > 1000 else ())
    tree.insert(docs, "end", text=name, values=(kb,), tags=tags)
def sort_by(col, reverse=False):
    for parent in ("",) + tree.get_children(""):
        kids = list(tree.get_children(parent))
        kids.sort(key=lambda k: float(tree.set(k, col) or 0), reverse=reverse)
        for idx, k in enumerate(kids):
            tree.move(k, parent, idx)
    tree.heading(col, command=lambda: sort_by(col, not reverse))
tree.heading("size", text="KB", command=lambda: sort_by("size"))
tree.bind("<<TreeviewSelect>>",
        lambda e: print([tree.item(i, "text") for i in tree.selection()]))
tree.bind("<Double-1>", lambda e: print("open", tree.identify_row(e.y)))
root.mainloop()
```

## CODE EXPLAINED

- #0 is the tree column; its header is set like any other
- Children are inserted under the docs parent id
- Tags combine: striping plus a red highlight for big files
- move() reorders rows; the heading toggles sort direction
- identify\_row(e.y) maps a click to an item id

## SELECTION

| MEMBER          | PURPOSE              |
|-----------------|----------------------|
| selection()     | Selected ids         |
| selection_set() | Replace selection    |
| selection_add() | Add to selection     |
| focus()         | Focused item         |
| selectmode      | extended/browse/none |

## TREE NAVIGATION

| METHOD           | RETURNS            |
|------------------|--------------------|
| parent(iiid)     | Parent id          |
| next() / prev()  | Sibling id         |
| index(iiid)      | Position           |
| move(iiid, p, i) | Reparent / reorder |
| see(iiid)        | Scroll into view   |

## EVENTS

| EVENT              | FIRES ON              |
|--------------------|-----------------------|
| <<TreeviewSelect>> | Selection change      |
| <<TreeviewOpen>>   | Node expanded         |
| <<TreeviewClose>>  | Node collapsed        |
| <Double-1>         | Double-click          |
| tag_bind()         | Events on tagged rows |

## △ COMMON MISTAKES

- › Treating selection() results as row values
- › Sorting with string comparison ("100" < "9")
- › Loading huge trees up front instead of lazily

## ✓ TIPS & BEST PRACTICES

- › Lazy-load children on <<TreeviewOpen>> with a dummy child
- › Re-apply stripe tags after sorting
- › Keep a dict mapping iid → your data object

## QUICK SUMMARY

- › selection() returns item ids
- › Parents make hierarchies; open= expands
- › Tags style and bind rows
- › Sort via move() in heading commands

## DRAWING ON A CANVAS

A Canvas is a drawing surface for lines, shapes, text, images and even embedded widgets. Each `create_*`() call adds an **item** and returns its integer **id**. Coordinates are pixels from the canvas's top-left, with **y growing downward**. Rectangles and ovals are defined by a **bounding box** (x1, y1, x2, y2), lines and polygons by a list of points. Unlike drawing in many libraries, items are **retained objects**: you can move, recolor or delete them later without redrawing everything.

## NOTES

- › Ovals are drawn inside their bounding box
- › `fill=""` means no fill (transparent interior)
- › `width` is the outline thickness
- › Later items draw on top of earlier ones
- › Use `highlightthickness=0` to remove the focus border

## BASIC SHAPES

```
import tkinter as tk

root = tk.Tk()
c = tk.Canvas(root, width=360, height=240, bg="white", highlightthickness=0)
c.pack()

c.create_line(10, 10, 350, 10, fill="gray", dash=(4, 2))
c.create_line(20, 200, 80, 140, 140, 180, 200, 120,
              fill="navy", width=3, smooth=True, arrow="last")
c.create_rectangle(20, 30, 120, 100, fill="#90caf9", outline="#1565c0", width=2)
c.create_oval(140, 30, 240, 100, fill="#ffcc80", outline="")
c.create_oval(260, 30, 330, 100, outline="green", width=4)           # circle
c.create_polygon(260, 220, 300, 140, 340, 220, fill="#a5d6a7",
                outline="black")
c.create_arc(140, 120, 240, 220, start=30, extent=300,
             style="pieslice", fill="gold")                          # Pac-Man

c.create_text(180, 230, text="Canvas demo", font=("Helvetica", 10, "bold"))
c.create_rectangle(0, 0, 360, 240, outline="red", width=1)
root.mainloop()
```

## CODE EXPLAINED

- `dash=(4, 2)` draws 4 px on, 2 px off
- Multi-point lines can be smoothed into curves
- Rectangles and ovals take two opposite corners
- `create_arc` uses `start / extent` in degrees
- `create_text` centers on the point by default

## CREATE\_\* METHODS

| METHOD                        | COORDS              |
|-------------------------------|---------------------|
| <code>create_line</code>      | x1,y1, x2,y2, ...   |
| <code>create_rectangle</code> | x1,y1, x2,y2        |
| <code>create_oval</code>      | Bounding box        |
| <code>create_polygon</code>   | x1,y1, ... (closed) |
| <code>create_arc</code>       | Bounding box        |

## SHAPE OPTIONS

| OPTION               | EFFECT                |
|----------------------|-----------------------|
| <code>fill</code>    | Interior / line color |
| <code>outline</code> | Border color          |
| <code>width</code>   | Line thickness        |
| <code>dash</code>    | Dash pattern          |
| <code>stipple</code> | Bitmap pattern        |

## LINE &amp; ARC OPTIONS

| OPTION                     | VALUES                    |
|----------------------------|---------------------------|
| <code>arrow</code>         | first / last / both       |
| <code>smooth</code>        | True for curves           |
| <code>capstyle</code>      | butt / round / projecting |
| <code>style (arc)</code>   | pieslice / chord / arc    |
| <code>start, extent</code> | Degrees                   |

## △ COMMON MISTAKES

- › Expecting y to increase upward like math plots
- › Passing width/height to `create_oval` instead of corners
- › Using `fill` on an arc with `style="arc"` (no interior)

## ✓ TIPS &amp; BEST PRACTICES

- › Wrap repeated shapes in helper functions
- › Store returned ids for items you'll change later
- › Use `outline=""` for flat, borderless shapes

## QUICK SUMMARY

- › `create_*` returns an item id
- › Pixel coords, y downward
- › Boxes for rect/oval/arc, points for lines
- › Items persist and can be changed

## CHANGING ITEMS WITH IDS AND TAGS

Every canvas item has a unique integer **id** and any number of string **tags**. Methods that take an item accept either form: an id affects one item, a tag affects **every item carrying it**, and the special tag "all" means everything. `itemconfigure()` changes options, `coords()` reads or replaces coordinates, `move()` shifts by an offset, and `delete()` removes items. `find_withtag()` and friends return matching ids, and `tag_raise()/tag_lower()` change stacking order.

## NOTES

- › Tags are added with `tags=` or `addtag_withtag()`
- › "current" is the item under the mouse pointer
- › `gettags(id)` lists an item's tags
- › `type(id)` returns "oval", "line", etc.
- › `moveto()` (Python 3.8+) moves to absolute coordinates

## GROUPING WITH TAGS

```
import tkinter as tk

root = tk.Tk()
c = tk.Canvas(root, width=360, height=200, bg="white"); c.pack()

for i in range(5):
    x = 20 + i * 68
    team = "red" if i % 2 else "blue"
    c.create_oval(x, 80, x + 50, 130, fill=team, tags=("piece", team))

label = c.create_text(180, 20, text="Click a key: r, b, d, s")
def recolor(team, color):
    c.itemconfigure(team, fill=color)
root.bind("r", lambda e: recolor("red", "salmon"))
root.bind("b", lambda e: c.move("blue", 0, 20))
root.bind("d", lambda e: c.delete("red"))
root.bind("s", lambda e: c.itemconfigure(label,
    text=f"{len(c.find_withtag('piece'))} pieces"))
first = c.find_withtag("piece")[0]
print(c.coords(first))
c.coords(first, 20, 150, 70, 190)
c.addtag_withtag("selected", first)
print(c.gettags(first))
c.tag_raise("selected")
root.mainloop()
```

## CODE EXPLAINED

- Each oval carries two tags: `piece` and its team
- `itemconfigure("red", ...)` changes all red items at once
- `move(tag, dx, dy)` shifts by an offset
- `find_withtag` returns a tuple of ids
- `coords(id, ...)` replaces an item's coordinates

## MODIFY ITEMS

| METHOD                             | DOES             |
|------------------------------------|------------------|
| <code>itemconfigure(t, **o)</code> | Change options   |
| <code>itemcget(t, opt)</code>      | Read option      |
| <code>coords(t, *xy)</code>        | Get / set coords |
| <code>move(t, dx, dy)</code>       | Shift            |
| <code>delete(t)</code>             | Remove           |

## FIND ITEMS

| METHOD                          | RETURNS            |
|---------------------------------|--------------------|
| <code>find_withtag(t)</code>    | Ids with tag       |
| <code>find_all()</code>         | Every id           |
| <code>find_closest(x, y)</code> | Nearest item       |
| <code>find_overlapping()</code> | Items in box       |
| <code>find_enclosed()</code>    | Items fully inside |

## TAG METHODS

| METHOD                            | DOES           |
|-----------------------------------|----------------|
| <code>addtag_withtag(n, t)</code> | Add tag n      |
| <code>dtag(t, n)</code>           | Remove tag n   |
| <code>gettags(id)</code>          | List tags      |
| <code>tag_raise(t)</code>         | Bring to front |
| <code>tag_lower(t)</code>         | Send to back   |

## △ COMMON MISTAKES

- › Using numeric strings as tags ("1" looks like an id)
- › Calling `coords()` with too few numbers for the item type
- › Forgetting "all" matches the background too

## ✓ TIPS &amp; BEST PRACTICES

- › Tag items by role and by group
- › Use `delete("all")` to clear before redrawing
- › Prefer tags over storing long lists of ids

## QUICK SUMMARY

- › Ids for one item, tags for groups
- › `itemconfigure`, `coords`, `move`, `delete`
- › `find_*` methods return ids
- › `tag_raise` / `tag_lower` set stacking

## TEXT, IMAGES AND WIDGETS ON A CANVAS

Besides shapes, a canvas can hold **text items** (`create_text`), **images** (`create_image` with a `PhotoImage`) and real **widgets** (`create_window`). For all three, `anchor` says which point of the item sits on the given coordinate: "center" by default, "nw" for top-left. `bbox(item)` returns the bounding box (`x1`, `y1`, `x2`, `y2`) of any item or tag, which is how you size a background behind text or check whether things overlap.

## NOTES

- Text items support `width=` for wrapping and `justify=`
- Keep a Python reference to images or they disappear
- Embedded widgets always draw above other canvas items
- `itemcget(id, "text")` reads a text item's string
- Canvas text can be edited with `dchars()` / `insert()`

## LABELLED CARD WITH IMAGE AND BUTTON

```
import tkinter as tk

root = tk.Tk()
c = tk.Canvas(root, width=320, height=200, bg="#263238",
              highlightthickness=0)
c.pack()

img = tk.PhotoImage(file="avatar.png").subsample(2)
c.image = img                      # keep a reference
c.create_image(20, 20, image=img, anchor="nw", tags="card")

title = c.create_text(110, 30, text="Ada Lovelace", anchor="nw",
                     fill="white", font=("Helvetica", 14, "bold"))
c.create_text(110, 60, anchor="nw", width=190, fill="#b0bec5",
             text="Wrote the first published algorithm for a machine.")

x1, y1, x2, y2 = c.bbox(title)      # box around the name
bg = c.create_rectangle(x1 - 4, y1 - 2, x2 + 4, y2 + 2, fill="#37474f",
                       outline="")
c.tag_lower(bg, title)              # put it behind the text

btn = tk.Button(c, text="Follow", command=lambda: print("followed"))
c.create_window(300, 180, window=btn, anchor="se")

print(c.itemcget(title, "text"))    # 'Ada Lovelace'
root.mainloop()
```

## CODE EXPLAINED

- `anchor="nw"` places the image's top-left at (20, 20)
- Storing `img` on the canvas prevents garbage collection
- `width=190` wraps the description text
- `bbox + tag_lower` creates a highlight behind text
- `create_window` embeds a real Button at the corner

## ITEM KINDS

| METHOD                     | KEY OPTIONS             |
|----------------------------|-------------------------|
| <code>create_text</code>   | text, font, fill, width |
| <code>create_image</code>  | image, anchor           |
| <code>create_window</code> | window, width, height   |
| <code>create_bitmap</code> | bitmap (built-ins)      |

## ANCHOR POINTS

| VALUE   | POINT ON ITEM       |
|---------|---------------------|
| center  | Middle (default)    |
| nw / ne | Top corners         |
| sw / se | Bottom corners      |
| n / s   | Top / bottom middle |
| w / e   | Left / right middle |

## MEASURING

| CALL                        | RETURNS           |
|-----------------------------|-------------------|
| <code>bbox(t)</code>        | (x1, y1, x2, y2)  |
| <code>bbox("all")</code>    | Box of everything |
| <code>coords(t)</code>      | Item coordinates  |
| <code>itemcget(t, o)</code> | Option value      |
| <code>type(t)</code>        | Item type         |

## COMMON MISTAKES

- Creating a `PhotoImage` in a function and losing it
- Expecting canvas items to draw over embedded widgets
- Using `x / y` of text as its top-left without `anchor="nw"`

## TIPS &amp; BEST PRACTICES

- Use `anchor="nw"` for layout-style positioning
- Measure text with `bbox` before placing neighbors
- Embed forms with `create_window` inside scrollable canvases

## QUICK SUMMARY

- `create_text`, `create_image`, `create_window`
- `anchor` picks the reference point
- `bbox()` measures items
- Keep image references alive

## INTERACTIVE CANVAS ITEMS

`tag_bind(tag_or_id, sequence, handler)` attaches events to canvas **items** rather than the whole widget, so each shape can react to clicks, hovers or drags. Inside a handler, the special tag `"current"` names the item under the pointer. Dragging is a three-event pattern: on **press**, remember the item and pointer position; on **motion**, `move()` the item by the difference; on **release**, finish. `find_closest()` and `find_overlapping()` help with hit-testing and snapping.

## NOTES

- › Item bindings fire only over painted areas, not empty interiors with `fill=""`
- › Widget-level bindings still run after item bindings
- › Use `canvasx()` / `canvasy()` when the canvas is scrolled
- › `<Enter>` / `<Leave>` on tags give hover effects
- › `find_overlapping` takes a rectangle, not a point

## DRAG-AND-DROP SHAPES

```
import tkinter as tk
c = tk.Canvas(tk.Tk(), width=400, height=260, bg="white"); c.pack()
for x, color in ((40, "tomato"), (160, "gold"), (280, "skyblue")):
    c.create_rectangle(x, 100, x + 80, 160, fill=color, tags="draggable")
c.create_rectangle(150, 200, 250, 250, dash=(3, 3), tags="target")
drag = {"item": None, "x": 0, "y": 0}
def press(e):
    drag["item"] = c.find_withtag("current")[0]
    drag["x"], drag["y"] = c.canvasx(e.x), c.canvasy(e.y)
    c.tag_raise(drag["item"])
def motion(e):
    x, y = c.canvasx(e.x), c.canvasy(e.y)
    c.move(drag["item"], x - drag["x"], y - drag["y"])
    drag["x"], drag["y"] = x, y
def release(e):
    hits = c.find_overlapping(*c.bbox("target"))
    if drag["item"] in hits:
        c.itemconfigure(drag["item"], outline="green", width=3)
        drag["item"] = None
c.tag_bind("draggable", "<ButtonPress-1>", press)
c.tag_bind("draggable", "<B1-Motion>", motion)
c.tag_bind("draggable", "<ButtonRelease-1>", release)
c.tag_bind("draggable", "<Enter>", lambda e: c.config(cursor="fleur"))
c.tag_bind("draggable", "<Leave>", lambda e: c.config(cursor=""))
c.mainloop()
```

## CODE EXPLAINED

- Only items tagged `draggable` respond to the mouse
- `"current"` gives the item that was clicked
- Motion moves by the delta since the last event
- `find_overlapping(*bbox)` checks for a drop on the target
- Cursor changes on hover signal draggability

## ITEM EVENTS

| CALL                             | EFFECT             |
|----------------------------------|--------------------|
| <code>tag_bind(t, ev, fn)</code> | Bind item events   |
| <code>tag_unbind(t, ev)</code>   | Remove binding     |
| <code>"current"</code> tag       | Item under pointer |
| <code>find_closest(x, y)</code>  | Nearest item       |
| <code>find_overlapping()</code>  | Items in rectangle |

## DRAG PATTERN

| EVENT                                    | ACTION                       |
|------------------------------------------|------------------------------|
| <code>&lt;ButtonPress-1&gt;</code>       | Record item + pos            |
| <code>&lt;B1-Motion&gt;</code>           | <code>move()</code> by delta |
| <code>&lt;ButtonRelease-1&gt;</code>     | Drop / snap                  |
| <code>&lt;Enter&gt;/&lt;Leave&gt;</code> | Cursor feedback              |

## COORDINATES

| VALUE                     | SPACE         |
|---------------------------|---------------|
| <code>e.x, e.y</code>     | Widget pixels |
| <code>canvasx(e.x)</code> | Canvas coords |
| <code>canvasy(e.y)</code> | Canvas coords |
| <code>e.x_root</code>     | Screen pixels |

## △ COMMON MISTAKES

- › Using `find_closest` for clicks (it always returns something)
- › Forgetting `canvasx` / `canvasy` on scrolled canvases
- › Binding drag events on the canvas, so the background drags too

## ✓ TIPS &amp; BEST PRACTICES

- › Store drag state in a dict or object, not globals
- › Raise the dragged item so it stays on top
- › Snap to a grid by rounding coordinates on release

## QUICK SUMMARY

- › `tag_bind` = events per item or tag
- › `"current"` = item under the mouse
- › Press / motion / release for dragging
- › `find_*` for hit-testing

## LARGE DRAWINGS AND MOVING PICTURES

A canvas can be bigger than its window. Set `scrollregion` to the drawing's extent (often `bbox("all")`) and connect scrollbars with `xview/yview`, exactly as with a `ListBox`. `scale(tag, x, y, sx, sy)` zooms items around a point (it scales coordinates, not line widths or fonts). **Animation** means updating item positions on a timer: a function moves things, then reschedules itself with `after(ms, func)`. Never animate with `while True + time.sleep`, which freezes the window.

## NOTES

- › About 16 ms per frame  $\approx$  60 fps; 33 ms  $\approx$  30 fps
- › `after_cancel(id)` stops a scheduled frame
- › `xview_moveto(0)` jumps to the left edge
- › Mouse wheel scrolling needs your own bindings
- › For heavy graphics, consider Pygame or OpenGL instead

## BOUNCING BALL ON A SCROLLABLE CANVAS

```
import tkinter as tk
root = tk.Tk()
W, H = 800, 600                                # world size
c = tk.Canvas(root, width=400, height=300, bg="black",
               scrollregion=(0, 0, W, H))
hs = tk.Scrollbar(root, orient="horizontal", command=c.xview)
vs = tk.Scrollbar(root, orient="vertical", command=c.yview)
c.configure(xscrollcommand=hs.set, yscrollcommand=vs.set)
c.grid(row=0, column=0); vs.grid(row=0, column=1, sticky="ns")
hs.grid(row=1, column=0, sticky="ew")
ball = c.create_oval(10, 10, 40, 40, fill="orange")
vel = [4, 3]
def frame():
    x1, y1, x2, y2 = c.coords(ball)
    if x1 + vel[0] < 0 or x2 + vel[0] > W: vel[0] = -vel[0]
    if y1 + vel[1] < 0 or y2 + vel[1] > H: vel[1] = -vel[1]
    c.move(ball, *vel)
    root.anim = root.after(16, frame)           # ~60 fps
def zoom(factor):
    c.scale("all", 0, 0, factor, factor)
    c.configure(scrollregion=c.bbox("all"))
root.bind("+", lambda e: zoom(1.25)); root.bind("-", lambda e: zoom(0.8))
root.bind("<space>", lambda e: root.after_cancel(root.anim))
frame()
root.mainloop()
```

## CODE EXPLAINED

- `scrollregion` defines the full 800×600 world
- Scrollbars wire to `xview / yview` both ways
- Each frame bounces off world edges, then moves
- `after(16, frame)` schedules the next frame
- `scale()` zooms; `scrollregion` is updated to match

## SCROLLING

| MEMBER                          | PURPOSE            |
|---------------------------------|--------------------|
| <code>scrollregion</code>       | (x1, y1, x2, y2)   |
| <code>xview / yview</code>      | Scroll commands    |
| <code>xview_moveto(f)</code>    | Jump to fraction   |
| <code>yview_scroll(n, u)</code> | Scroll units/pages |
| <code>canvasx(px)</code>        | Window → canvas x  |

## ZOOM &amp; TRANSFORM

| CALL                                | EFFECT         |
|-------------------------------------|----------------|
| <code>scale(t, x, y, sx, sy)</code> | Scale coords   |
| <code>move(t, dx, dy)</code>        | Translate      |
| <code>moveto(t, x, y)</code>        | Absolute move  |
| <code>bbox("all")</code>            | Current extent |

## ANIMATION LOOP

| STEP         | CODE                                        |
|--------------|---------------------------------------------|
| Update state | positions, velocity                         |
| Redraw       | <code>move()</code> / <code>coords()</code> |
| Schedule     | <code>after(ms, frame)</code>               |
| Stop         | <code>after_cancel(id)</code>               |
| Pace         | 16–33 ms                                    |

## ⚠ COMMON MISTAKES

- › Animating with `time.sleep` in a loop
- › Forgetting to update `scrollregion` after zooming
- › Starting several `after` loops by calling `frame()` twice

## ✓ TIPS &amp; BEST PRACTICES

- › Keep the `after` id so you can pause and resume
- › Move items instead of deleting and recreating them
- › Base movement on elapsed time for steady speed

## QUICK SUMMARY

- › `scrollregion` + scrollbars for big drawings
- › `scale()` zooms coordinates
- › Animate with `after()` loops
- › Never block with `sleep`

## COLORS AND BORDERS ON CLASSIC WIDGETS

Classic tk widgets accept colors as **names** ("red", "SteelBlue", around 750 X11 names) or **hex** strings "#rgb", "#rrggbb" (or 12-digit "#rrrrggggbbbb"). Platform-specific **system colors** such as "SystemButtonFace" (Windows) or "systemWindowBackgroundColor" (macOS) follow the OS theme. Borders come from relief and borderwidth, and the **focus ring** from highlightthickness/highlightcolor. ttk widgets ignore these options; style them instead (Sheet 34).

## NOTES

- › `wininfo_rgb(color)` returns 16-bit (r, g, b) components
- › `activebackground` applies on hover for buttons
- › `disabledforeground` colors text in disabled widgets
- › `selectbackground` colors selected text in Entry/Text
- › Avoid relying on color alone to convey meaning

## RELIEFS, COLORS AND HIGHLIGHTS

```
import tkinter as tk

root = tk.Tk()
root.configure(bg="#eceff1")

reliefs = ("flat", "raised", "sunken", "groove", "ridge", "solid")
for i, r in enumerate(reliefs):
    tk.Label(root, text=r, relief=r, borderwidth=3, width=8,
             bg="white").grid(row=0, column=i, padx=4, pady=8)

btn = tk.Button(root, text="Hover me", bg="#1976d2", fg="white",
                activebackground="#0d47a1", activeforeground="white",
                relief="flat", padx=12, pady=4, cursor="hand2")
btn.grid(row=1, column=0, columnspan=3, pady=6)
entry = tk.Entry(root, highlightthickness=2, highlightcolor="#ff9800",
                 highlightbackground="#cfd8dc", selectbackground="#ffe0b2",
                 selectforeground="black", insertbackground="#ff9800")
entry.grid(row=1, column=3, columnspan=3)
def lighten(color, f=0.3):
    r, g, b = (v // 257 for v in root.wininfo_rgb(color))
    r, g, b = (int(v + (255 - v) * f) for v in (r, g, b))
    return f"#{r:02x}{g:02x}{b:02x}"
print(lighten("SteelBlue"))          # '#7da7ca'
root.mainloop()
```

## CODE EXPLAINED

- Six reliefs show the classic border styles
- `active*` colors apply while the mouse is over the button
- `highlight*` options style the Entry's focus ring
- `insertbackground` sets the text cursor color
- `wininfo_rgb` converts any color spec to numbers

## COLOR FORMATS

| FORM         | EXAMPLE           |
|--------------|-------------------|
| Name         | "SteelBlue"       |
| #rgb         | "#f80"            |
| #rrggbb      | "#ff8800"         |
| System (Win) | "SystemHighlight" |
| System (mac) | "systemTextColor" |

## COLOR OPTIONS

| OPTION                          | APPLIES TO    |
|---------------------------------|---------------|
| <code>bg / fg</code>            | Normal state  |
| <code>activebackground</code>   | Hover / press |
| <code>disabledforeground</code> | Disabled text |
| <code>selectbackground</code>   | Selected text |
| <code>insertbackground</code>   | Text cursor   |

## BORDER OPTIONS

| OPTION                           | EFFECT            |
|----------------------------------|-------------------|
| <code>relief</code>              | Border style      |
| <code>borderwidth / bd</code>    | Border size       |
| <code>highlightthickness</code>  | Focus ring size   |
| <code>highlightcolor</code>      | Ring when focused |
| <code>highlightbackground</code> | Ring unfocused    |

## △ COMMON MISTAKES

- › Setting `bg` on a macOS `tk.Button` (native buttons ignore it)
- › Using colors on ttk widgets instead of styles
- › Choosing text/background pairs with poor contrast

## ✓ TIPS &amp; BEST PRACTICES

- › Keep a palette dict and reference colors by role
- › Set `highlightthickness=0` for flat, borderless designs
- › Use `cursor="hand2"` on clickable labels

## QUICK SUMMARY

- › Names, `#rgb`, `#rrggbb`, system colors
- › `relief` + `borderwidth` for borders
- › `highlight*` for focus rings
- › Classic widgets only; ttk uses styles

## WORKING WITH FONTS

Fonts can be given as a **tuple** ("Family", size, "bold italic"), a **string** "Helvetica 12 bold", or a `tkinter.font.Font` **object**. Font objects are live: change one with `configure()` and every widget using it updates. Positive sizes are **points**, negative sizes are **pixels**. Tk also defines **named fonts** like `TkDefaultFont`, `TkTextFont` and `TkFixedFont`; adjusting them with `nametofont()` restyles the whole app consistently, including ttk widgets.

## NOTES

- › `font.families()` lists installed font families
- › `measure(text)` gives pixel width; `metrics()` gives heights
- › Unknown families silently fall back to a default
- › Keep a reference to `Font` objects you create
- › Import as `tkfont` to avoid clashing with variables named `font`

## NAMED FONTS AND FONT OBJECTS

```
import tkinter as tk
import tkinter.font as tkfont
from tkinter import ttk

root = tk.Tk()

default = tkfont.nametofont("TkDefaultFont")      # app-wide base font
default.configure(family="Segoe UI", size=10)
tkfont.nametofont("TkFixedFont").configure(size=11)

heading = tkfont.Font(family="Georgia", size=16, weight="bold")
ttk.Label(root, text="Report", font=heading).pack(anchor="w", padx=10)
ttk.Label(root, text="Uses TkDefaultFont").pack(anchor="w", padx=10)
tk.Text(root, height=3, font="TkFixedFont").pack(padx=10, pady=4)

def bigger(): heading.configure(size=int(heading.cget("size")) + 2)
ttk.Button(root, text="A+", command=bigger).pack(pady=4)

print(heading.measure("Report"))      # pixel width of the text
print(heading.metrics("linespace"))   # line height in px
print(heading.actual())               # resolved family, size, weight...
print("Consolas" in tkfont.families())
mono = ("Courier New", 10)           # tuple form
small_italic = "Helvetica 9 italic"  # string form
root.mainloop()
```

## CODE EXPLAINED

- `nametofont("TkDefaultFont")` changes the base font everywhere
- A `Font` object updates all widgets using it on `configure()`
- Text widgets can use named fonts by name string
- `measure` and `metrics` help size layouts precisely
- `actual()` shows what the OS really chose

## FONT SPECS

| FORM           | EXAMPLE                       |
|----------------|-------------------------------|
| Tuple          | ("Arial", 12, "bold")         |
| String         | "Arial 12 bold"               |
| Spaces in name | "{Segoe UI} 10"               |
| Pixels         | ("Arial", -14)                |
| Font object    | <code>tkfont.Font(...)</code> |

## NAMED FONTS

| NAME                       | USED BY           |
|----------------------------|-------------------|
| <code>TkDefaultFont</code> | Most widgets      |
| <code>TkTextFont</code>    | Entry, Text       |
| <code>TkFixedFont</code>   | Monospace         |
| <code>TkHeadingFont</code> | Treeview headings |
| <code>TkMenuFont</code>    | Menus             |

## FONT METHODS

| METHOD                      | RETURNS                  |
|-----------------------------|--------------------------|
| <code>configure(**o)</code> | Change font              |
| <code>actual()</code>       | Resolved attributes      |
| <code>measure(text)</code>  | Width in px              |
| <code>metrics(opt)</code>   | ascent/descent/linespace |
| <code>copy()</code>         | Independent copy         |

## △ COMMON MISTAKES

- › Writing `("Segoe UI 10")` (a string in parentheses, not a tuple)
- › Creating `Font()` before `Tk()` exists
- › Hard-coding a font family that isn't installed elsewhere

## ✓ TIPS &amp; BEST PRACTICES

- › Change named fonts once at startup for a consistent look
- › Use `TkFixedFont` for code and tabular text
- › Scale fonts, not widgets, for accessibility settings

## QUICK SUMMARY

- › Tuple, string or `Font` object
- › Positive = points, negative = pixels
- › `nametofont` to restyle the whole app
- › `measure` / `metrics` for sizing

## SHOWING IMAGES

`tk.PhotoImage` loads **PNG** and **GIF** (and PPM/PGM) natively; Tk 9.0 adds SVG support. It can scale by whole factors with `zoom(n)` and `subsample(n)`, and set pixels with `put()`. For **JPEG**, smooth resizing or other formats, use **Pillow**: open with `PIL.Image`, process, then wrap with `PIL.ImageTk.PhotoImage`. Whatever you use, **keep a reference** to the image object. If it's only a local variable, Python frees it and the widget goes blank.

## NOTES

- › `pip install pillow` provides `PIL.Image` and `PIL.ImageTk`
- › `compound="left"` shows image and text together
- › `PhotoImage(width=, height=)` creates a blank canvas image
- › Animated GIF frames load with `format="gif -index n"`
- › Use `Image.LANCZOS` for high-quality downscaling

## PHOTOIMAGE AND PILLOW

```
import tkinter as tk
from tkinter import ttk
from PIL import Image, ImageTk, ImageOps

root = tk.Tk()

icon = tk.PhotoImage(file="save.png")           # native PNG
small = icon.subsample(2)                       # half size
ttk.Button(root, text="Save", image=small, compound="left").pack(pady=4)

pil = Image.open("photo.jpg")                   # JPEG via Pillow
pil = ImageOps.exif_transpose(pil)              # respect rotation
pil.thumbnail((300, 200), Image.LANCZOS)       # fit, keep ratio
photo = ImageTk.PhotoImage(pil)
label = ttk.Label(root, image=photo); label.pack(padx=10, pady=10)
label.image = photo                             # keep references!
root.images = [icon, small]

gray = ImageTk.PhotoImage(ImageOps.grayscale(pil))
label.bind("<Enter>", lambda e: label.configure(image=gray))
label.bind("<Leave>", lambda e: label.configure(image=photo)); label.gray = gray
dot = tk.PhotoImage(width=8, height=8)
dot.put("red", to=(0, 0, 8, 8))                 # solid red square
ttk.Label(root, image=dot, text=" Online", compound="left").pack()
root.dot = dot
root.mainloop()
```

## CODE EXPLAINED

- `subsample(2)` keeps every 2nd pixel: half size
- `exif_transpose` fixes sideways phone photos
- `thumbnail` resizes in place, preserving aspect ratio
- Attaching images to widgets keeps them alive
- `put(color, to=box)` fills pixels on a blank image

## PHOTOIMAGE

| MEMBER                         | PURPOSE                |
|--------------------------------|------------------------|
| <code>file= / data=</code>     | Load from file / bytes |
| <code>zoom(n)</code>           | Enlarge ×n             |
| <code>subsample(n)</code>      | Shrink ÷n              |
| <code>put(c, to=)</code>       | Set pixels             |
| <code>width(), height()</code> | Size                   |

## FORMAT SUPPORT

| FORMAT                    | HOW                       |
|---------------------------|---------------------------|
| <code>PNG, GIF</code>     | PhotoImage                |
| <code>PPM / PGM</code>    | PhotoImage                |
| <code>SVG</code>          | Tk 9.0 PhotoImage         |
| <code>JPEG, WebP</code>   | Pillow ImageTk            |
| <code>ICO (window)</code> | <code>iconbitmap()</code> |

## PILLOW OPS

| CALL                            | DOES           |
|---------------------------------|----------------|
| <code>Image.open(p)</code>      | Load           |
| <code>thumbnail(size)</code>    | Fit within box |
| <code>resize(size)</code>       | Exact size     |
| <code>rotate(deg)</code>        | Rotate         |
| <code>ImageTk.PhotoImage</code> | Tk-ready image |

## △ COMMON MISTAKES

- › Images vanishing because only a local variable held them
- › Loading JPEG with `tk.PhotoImage` (unsupported in Tk 8.6)
- › Creating images before `Tk()` exists

## ✓ TIPS &amp; BEST PRACTICES

- › Cache resized images instead of resizing on every redraw
- › Store icons in a dict on the app object
- › Use `compound` for toolbar buttons with labels

## QUICK SUMMARY

- › PhotoImage: PNG/GIF natively
- › Pillow for JPEG and resizing
- › `zoom / subsample` scale by integers
- › Always keep a reference

## SCHEDULING WORK ON THE EVENT LOOP

`after(ms, func, *args)` asks Tk to call `func` once, at least `ms` milliseconds later, from the event loop. It returns an `id` you can pass to `after_cancel()`. Repeating timers are made by having the function **reschedule itself**. `after_idle(func)` runs once the loop has no pending events. `update_idletasks()` processes pending redraws and geometry work immediately, which is safe; `update()` processes **all** events, including clicks, and can re-enter your code unexpectedly.

## NOTES

- › Timing is a minimum, not exact; long callbacks delay timers
- › `after(0, f)` runs `f` as soon as the loop is free
- › Cancel pending timers before destroying widgets they touch
- › `after` without a function sleeps but blocks; avoid it
- › Each `after` callback must finish quickly

## CLOCK, COUNTDOWN AND DEBOUNCE

```
import tkinter as tk, time

root = tk.Tk()
clock = tk.Label(root, font=("Consolas", 24)); clock.pack(padx=20)
def tick():
    clock.config(text=time.strftime("%H:%M:%S"))
    root.after(1000 - int(time.time() * 1000) % 1000, tick) # align to second
tick()
count = tk.IntVar(value=10)
tk.Label(root, textvariable=count).pack()
def countdown():
    if count.get() > 0:
        count.set(count.get() - 1)
        root.countdown_id = root.after(1000, countdown)
countdown()
tk.Button(root, text="Stop",
          command=lambda: root.after_cancel(root.countdown_id)).pack()
search = tk.Entry(root); search.pack(pady=6)
pending = None
def on_key(event):
    # debounce: run 300 ms after typing stops
    global pending
    if pending: root.after_cancel(pending)
    pending = root.after(300, lambda: print("search", search.get()))
search.bind("<KeyRelease>", on_key)
root.after_idle(lambda: print("UI ready"))
```

## CODE EXPLAINED

- The clock reschedules itself, aligned to whole seconds
- The countdown stores its id so Stop can cancel it
- Debounce cancels the previous timer on every keystroke
- Only the last pending search runs after typing pauses
- `after_idle` runs once startup events are processed

## TIMER METHODS

| METHOD                        | DOES                  |
|-------------------------------|-----------------------|
| <code>after(ms, f, *a)</code> | Run later; returns id |
| <code>after_idle(f)</code>    | Run when idle         |
| <code>after_cancel(id)</code> | Cancel pending        |
| <code>after_info()</code>     | Pending ids (3.13+)   |

## UPDATE METHODS

| METHOD                          | PROCESSES           |
|---------------------------------|---------------------|
| <code>update_idletasks()</code> | Redraws, geometry   |
| <code>update()</code>           | All events (risky)  |
| <code>mainloop()</code>         | Everything, forever |
| <code>wait_variable(v)</code>   | Until v changes     |

## PATTERNS

| PATTERN      | SHAPE                   |
|--------------|-------------------------|
| Repeat       | f reschedules f         |
| Countdown    | Stop at 0               |
| Debounce     | Cancel + reschedule     |
| Poll         | Check queue, reschedule |
| Chunked work | Do a slice, reschedule  |

## △ COMMON MISTAKES

- › `time.sleep()` in callbacks, freezing the window
- › Calling `update()` inside callbacks and re-entering handlers
- › Leaving timers running after their widget is destroyed

## ✓ TIPS &amp; BEST PRACTICES

- › Split long loops into chunks scheduled with `after(0, ...)`
- › Debounce expensive work triggered by typing or resizing
- › Keep timer ids on `self` for clean cancellation

## QUICK SUMMARY

- › `after(ms, f)` schedules; returns an id
- › Self-rescheduling = repeating timer
- › `after_cancel` stops it
- › Prefer `update_idletasks` over `update`

## KEEPING THE UI RESPONSIVE

Tk runs everything on **one thread**: while a callback works, the window can't redraw or respond. Move slow work (network, files, heavy math) to a **worker thread**, but remember that Tkinter is **not thread-safe**: workers must not touch widgets or Tk variables. Instead they put results on a queue. Queue, and the main thread **polls** the queue with `after()` and updates the UI. `concurrent.futures` works the same way with a future you check from an `after()` loop.

## NOTES

- › Mark workers `daemon=True` so they don't block exit
- › Pass data, not widgets, into worker functions
- › Disable the start button while work runs
- › Catch exceptions in the worker and queue them
- › CPU-bound work may need `multiprocessing` instead

## WORKER THREAD + QUEUE + AFTER()

```
import tkinter as tk, threading, queue, time
from tkinter import ttk

root = tk.Tk(); q = queue.Queue()
bar = ttk.Progressbar(root, length=260); bar.pack(padx=10, pady=8)
status = ttk.Label(root, text="Idle"); status.pack()
def worker(n):                                # runs off the main thread
    try:
        for i in range(1, n + 1):
            time.sleep(0.05)                  # slow work stand-in
            q.put(("progress", i * 100 / n))
        q.put(("done", f"Processed {n} items"))
    except Exception as exc:
        q.put(("error", str(exc)))
def poll():                                  # runs on the main thread
    while not q.empty():
        kind, value = q.get_nowait()
        if kind == "progress":
            bar["value"] = value
        else:
            status.config(text=value); start.state(["!disabled"]); return
    root.after(50, poll)
def begin():
    start.state(["disabled"]); status.config(text="Working...")
    threading.Thread(target=worker, args=(60,), daemon=True).start(); poll()
start = ttk.Button(root, text="Start", command=begin); start.pack(pady=8)
```

## CODE EXPLAINED

- The worker only writes to the queue, never to widgets
- Errors are sent through the queue too
- `poll()` drains all queued messages each tick
- Polling stops after the final message
- The button is disabled while work runs

## THREAD RULES

| DO                             | DON'T                         |
|--------------------------------|-------------------------------|
| Queue results                  | Touch widgets in worker       |
| Poll with <code>after()</code> | Block on <code>q.get()</code> |
| <code>daemon=True</code>       | Join in a callback            |
| Copy data in                   | Share mutable state           |

## TOOLS

| MODULE                          | USE                  |
|---------------------------------|----------------------|
| <code>threading</code>          | I/O-bound work       |
| <code>queue.Queue</code>        | Thread-safe channel  |
| <code>concurrent.futures</code> | Pools, futures       |
| <code>multiprocessing</code>    | CPU-bound work       |
| <code>asyncio</code>            | Separate loop thread |

## FUTURES PATTERN

| STEP       | CODE                              |
|------------|-----------------------------------|
| Submit     | <code>fut = pool.submit(f)</code> |
| Check      | <code>fut.done()</code>           |
| Result     | <code>fut.result()</code>         |
| Reschedule | <code>after(100, check)</code>    |

## △ COMMON MISTAKES

- › Calling `label.config()` from a worker thread
- › Using `q.get()` (blocking) on the main thread
- › Starting a new poll loop on every click

## ✓ TIPS &amp; BEST PRACTICES

- › Wrap the pattern in a small helper class
- › Send tagged tuples like `("progress", 40)`
- › Show progress or a spinner for anything over ~0.2 s

## QUICK SUMMARY

- › One UI thread; never block it
- › Workers → queue → `after()` poll
- › Never touch Tk from workers
- › Disable controls while busy

## VALIDATING ENTRY INPUT

Entry and Spinbox can check input **before** it's accepted. Set `validate=` to when validation runs ("key" for every keystroke, "focusout", "all"... ) and `validatecommand=` to a callback registered with `register()` plus **percent substitutions** that choose what Tk passes in, such as `%P` (the proposed new text). The callback returns `True` to allow the change or `False` to reject it. `invalidcommand=` runs when validation fails.

## NOTES

- › The callback must return a bool, or validation turns off
- › Changing the Entry's text inside the callback disables validation
- › `%P` includes text not yet inserted
- › Allow the empty string so users can clear the field
- › Validate the whole form again before saving

## NUMERIC AND LENGTH VALIDATION

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()

def is_number(proposed):
    if proposed in ("", "-", ".", "-."):
        return True
    try:
        float(proposed); return True
    except ValueError:
        return False

def max_len(proposed, limit):
    return len(proposed) <= int(limit)

def on_invalid(widget_name):
    root.nametowidget(widget_name).bell() # beep on rejection

num_cmd = (root.register(is_number), "%P")
len_cmd = (root.register(max_len), "%P", 5)
bad_cmd = (root.register(on_invalid), "%W")

ttk.Entry(root, validate="key", validatecommand=num_cmd,
           invalidcommand=bad_cmd).pack(padx=8, pady=4) # price
ttk.Entry(root, validate="key", validatecommand=len_cmd,
           width=8).pack(padx=8, pady=4) # ZIP code
```

## CODE EXPLAINED

- `register()` wraps a Python function as a Tcl command
- The tuple adds substitutions (`%P`) and fixed arguments (5)
- Partial values like `"-"` must be allowed while typing
- `%W` gives the widget's name for the invalid handler
- `nametowidget` turns that name back into the widget

## VALIDATE=

| VALUE                 | RUNS ON           |
|-----------------------|-------------------|
| <code>none</code>     | Never (default)   |
| <code>key</code>      | Each edit         |
| <code>focus</code>    | Focus in or out   |
| <code>focusout</code> | Leaving the field |
| <code>all</code>      | All of the above  |

## SUBSTITUTIONS

| CODE            | PASSES                |
|-----------------|-----------------------|
| <code>%P</code> | Text if allowed       |
| <code>%s</code> | Text before edit      |
| <code>%S</code> | Inserted/deleted text |
| <code>%d</code> | 1 insert, 0 delete    |
| <code>%W</code> | Widget name           |

## MORE CODES

| CODE            | PASSES           |
|-----------------|------------------|
| <code>%i</code> | Index of edit    |
| <code>%v</code> | validate setting |
| <code>%V</code> | Trigger type     |

## △ COMMON MISTAKES

- › Passing the plain function instead of the `register()` ed name
- › Rejecting `""`, so users can't delete the last character
- › Returning `None` (no explicit `return True`)

## ✓ TIPS &amp; BEST PRACTICES

- › Use `key` for format, `focusout` for completeness checks
- › Show errors next to fields, not just with beeps
- › Use ttk's `invalid` state to tint bad fields

## QUICK SUMMARY

- › `validate=` when, `validatecommand=` how
- › `register() + %P` for proposed text
- › Return `True` to accept
- › Allow partial input while typing

## SCROLLING A PANEL OF WIDGETS

Frames can't scroll, but a Canvas can, and a Canvas can hold a widget with `create_window()`. The standard recipe: put an **inner Frame** inside a Canvas, add widgets to the inner Frame, and whenever its size changes (<Configure>), set the canvas `scrollregion` to `bbox("all")`. Also stretch the inner Frame to the canvas width so rows fill horizontally. Mouse-wheel scrolling needs explicit bindings, which differ by platform.

## NOTES

- › Bind the wheel only while the pointer is over the panel
- › Windows: `delta ±120`; macOS: small deltas; X11: Button-4/5
- › Tk 9.0 unifies X11 wheel events as `<MouseWheel>`
- › Thousands of rows? Use a Treeview or a virtualized list
- › Wrap the recipe in a reusable class

## REUSABLE SCROLLABLEFRAME

```
import tkinter as tk
from tkinter import ttk

class ScrollableFrame(ttk.Frame):
    def __init__(self, parent, **kw):
        super().__init__(parent, **kw)
        self.canvas = tk.Canvas(self, highlightthickness=0)
        sb = ttk.Scrollbar(self, orient="vertical", command=self.canvas.yview)
        self.canvas.configure(yscrollcommand=sb.set)
        self.canvas.pack(side="left", fill="both", expand=True)
        sb.pack(side="right", fill="y")
        self.inner = ttk.Frame(self.canvas)
        win = self.canvas.create_window((0, 0), window=self.inner, anchor="nw")
        self.inner.bind("<Configure>", lambda e: self.canvas.configure(
            scrollregion=self.canvas.bbox("all")))
        self.canvas.bind("<Configure>",
            lambda e: self.canvas.itemconfigure(win, width=e.width))
        self.bind("<Enter>", lambda e: self.bind_all("<MouseWheel>", self._wheel))
        self.bind("<Leave>", lambda e: self.unbind_all("<MouseWheel>"))
    def _wheel(self, e):
        # Windows/macOS
        self.canvas.yview_scroll(-1 if e.delta > 0 else 1, "units")
root = tk.Tk(); root.geometry("300x250")
panel = ScrollableFrame(root); panel.pack(fill="both", expand=True)
for i in range(40):
    ttk.Checkbutton(panel.inner, text=f"Option {i + 1}").pack(anchor="w")
```

## CODE EXPLAINED

- The inner Frame lives in the canvas via `create_window`
- Inner `<Configure>` keeps `scrollregion` in sync
- Canvas `<Configure>` stretches the inner Frame's width
- Wheel is bound globally only while hovering
- Callers add widgets to `panel.inner`

## RECIPE STEPS

| STEP         | CODE                                                |
|--------------|-----------------------------------------------------|
| Canvas + bar | <code>yscrollcommand</code> wiring                  |
| Inner frame  | <code>create_window(..., nw)</code>                 |
| Track size   | inner <code>&lt;Configure&gt;</code>                |
| Match width  | <code>itemconfigure(width=)</code>                  |
| Wheel        | <code>bind_all</code> on <code>&lt;Enter&gt;</code> |

## WHEEL BY PLATFORM

| PLATFORM     | EVENT                                               |
|--------------|-----------------------------------------------------|
| Windows      | <code>&lt;MouseWheel&gt;</code> , <code>±120</code> |
| macOS        | <code>&lt;MouseWheel&gt;</code> , <code>±1–n</code> |
| X11 (Tk 8.6) | <code>&lt;Button-4/5&gt;</code>                     |
| Tk 9.0       | <code>&lt;MouseWheel&gt;</code> everywhere          |
| Horizontal   | <code>&lt;Shift-MouseWheel&gt;</code>               |

## SCROLL CALLS

| CALL                                  | DOES           |
|---------------------------------------|----------------|
| <code>yview_scroll(n, "units")</code> | By lines       |
| <code>yview_scroll(n, "pages")</code> | By pages       |
| <code>yview_moveto(0)</code>          | Jump to top    |
| <code>bbox("all")</code>              | Content extent |

## △ COMMON MISTAKES

- › Forgetting to update `scrollregion` as content grows
- › Binding the wheel with `bind_all` permanently
- › Using `pack(fill="x")` in the inner frame without matching width

## ✓ TIPS &amp; BEST PRACTICES

- › Expose `inner` as the parent for child widgets
- › Call `yview_moveto(0)` after rebuilding content
- › Add X11 Button-4/5 bindings for Linux users on Tk 8.6

## QUICK SUMMARY

- › Canvas + inner Frame + `create_window`
- › `scrollregion = bbox("all")` on resize
- › Stretch inner width to canvas width
- › Wheel bindings per platform

## STRUCTURING LARGER APPS

As apps grow, split them into **pages** (Frame subclasses), a **controller** (usually the `tk.Tk` subclass) that owns shared state and navigation, and a **model** layer with no Tk imports. A common navigation trick stacks all pages in the same grid cell and brings one forward with `tkraise()`. Pages talk to the controller, not to each other, and the model can be unit-tested without opening a window. This mirrors MVC without needing a framework.

## NOTES

- › Pass the controller into each page's constructor
- › Keep file, network and math code in the model
- › Use virtual events ( `<<Saved>>` ) to notify pages
- › Build pages lazily if they're expensive
- › One module per page keeps diffs small

## CONTROLLER + PAGES + TKRAISE()

```
import tkinter as tk
from tkinter import ttk
class Model:                                # no Tk imports needed
    user = None
    def login(self, name): self.user = name.strip() or None; return self.user
class LoginPage(ttk.Frame):
    def __init__(self, parent, app):
        super().__init__(parent, padding=20); name = tk.StringVar()
        ttk.Entry(self, textvariable=name).pack(pady=6)
        ttk.Button(self, text="Log in", command=lambda: app.login(name.get())).pack()
class HomePage(ttk.Frame):
    def __init__(self, parent, app):
        super().__init__(parent, padding=20)
        self.msg = ttk.Label(self); self.msg.pack(pady=6)
        ttk.Button(self, text="Log out", command=lambda: app.show("LoginPage")).pack()
    def on_show(self, app): self.msg.config(text=f"Welcome, {app.model.user}")
class App(tk.Tk):
    def __init__(self):
        super().__init__(); self.model = Model()
        self.pages = {P.__name__: P(self, self) for P in (LoginPage, HomePage)}
        for p in self.pages.values(): p.grid(row=0, column=0, sticky="nsew")
        self.show("LoginPage")
    def show(self, name):
        page = self.pages[name]
        if hasattr(page, "on_show"): page.on_show(self)
        page.tkraise()
    def login(self, name):
        if self.model.login(name): self.show("HomePage")
```

## CODE EXPLAINED

- `Model` holds state and rules, testable without a GUI
- Pages receive the controller ( `app` ) to request actions
- All pages share one grid cell; `tkraise()` picks the visible one
- `on_show` hooks refresh a page when it appears
- Navigation lives only in the controller

## ROLES

| PART             | OWNS                     |
|------------------|--------------------------|
| Model            | Data, rules, I/O         |
| Controller (App) | Navigation, shared state |
| Pages (Frames)   | Widgets for one screen   |
| Dialogs          | Short-lived input        |

## NAVIGATION OPTIONS

| APPROACH                     | FITS                |
|------------------------------|---------------------|
| <code>tkraise()</code> stack | Wizard / few pages  |
| Notebook                     | User picks freely   |
| Destroy + rebuild            | Rare, heavy pages   |
| Toplevels                    | Independent windows |

## PROJECT LAYOUT

| FILE                  | CONTAINS                  |
|-----------------------|---------------------------|
| <code>app.py</code>   | App + <code>main()</code> |
| <code>model.py</code> | Data classes, logic       |
| <code>pages/</code>   | One page per module       |
| <code>tests/</code>   | Model unit tests          |

## △ COMMON MISTAKES

- › Pages reaching into each other's widgets
- › Database or HTTP calls inside button callbacks
- › Building every page with global variables

## ✓ TIPS &amp; BEST PRACTICES

- › Unit-test the model with `pytest`; no window needed
- › Give pages an `on_show` hook for refreshes
- › Prefer composition: small Frame components in pages

## QUICK SUMMARY

- › Model / controller / pages
- › Stacked frames + `tkraise()`
- › Pages talk only to the controller
- › Logic stays testable without Tk

## DPI SCALING AND PLATFORM DIFFERENCES

Tkinter apps run on Windows, macOS and Linux, but each platform differs. On **Windows**, apps are blurry on high-DPI screens unless the process declares DPI awareness through ctypes **before** creating Tk(). Tk's `tk scaling` sets pixels per point, so point-sized fonts scale while pixel sizes don't. `tk windowingsystem` (win32, aqua, x11) lets you branch on mouse buttons, shortcuts, menus and theme choices.

## NOTES

- › Specify fonts in points (positive sizes) so they scale
- › macOS swaps mouse buttons 2 and 3 compared to others
- › Use `<Command-...>` for shortcuts on macOS
- › Wayland desktops run Tk through XWayland
- › Test on each target OS before release

## CROSS-PLATFORM SETUP

```
import sys, tkinter as tk

if sys.platform == "win32":
    import ctypes
    try:
        ctypes.windll.shcore.SetProcessDpiAwareness(1) # system DPI aware
    except (AttributeError, OSError):
        ctypes.windll.user32.SetProcessDPIAware()      # Vista/7 fallback

root = tk.Tk()
ws = root.tk.call("tk", "windowingsystem") # 'win32', 'aqua', 'x11'
print(ws, root.tk.call("tk", "scaling"))    # pixels per point

dpi = root.winfo_fpixels("1i")              # pixels per inch
print(f"{dpi:.0f} DPI")
if ws == "x11":
    root.tk.call("tk", "scaling", dpi / 72)  # match real DPI

MOD = "Command" if ws == "aqua" else "Control"
RIGHT = "<Button-2>" if ws == "aqua" else "<Button-3>"
root.bind(f"<{MOD}-s>", lambda e: print("save"))
root.bind(RIGHT, lambda e: print("context menu"))

def px(n):
    return int(n * dpi / 96) # scale hard-coded pixels

tk.Frame(root, width=px(200), height=px(100)).pack()
root.mainloop()
```

## CODE EXPLAINED

- DPI awareness must be set before the first window
- `windowingsystem` drives platform branches
- `winfo_fpixels("1i")` measures the real DPI
- Shortcuts and right-click use platform constants
- `px()` scales fixed pixel sizes from a 96-DPI baseline

## WINDOWINGSYSTEM

| VALUE | PLATFORM                    |
|-------|-----------------------------|
| win32 | Windows                     |
| aqua  | macOS                       |
| x11   | Linux / BSD (X or XWayland) |

## PLATFORM DIFFERENCES

| TOPIC        | NOTES                           |
|--------------|---------------------------------|
| Right-click  | Button-3; Button-2 on mac       |
| Shortcut key | Control; Command on mac         |
| Menu bar     | In window; top of screen on mac |
| Native theme | vista / aqua / none             |
| Wheel        | <MouseWheel>; Button-4/5 on X11 |

## SCALING TOOLS

| CALL                                | PURPOSE             |
|-------------------------------------|---------------------|
| <code>tk scaling</code>             | Pixels per point    |
| <code>winfo_fpixels("1i")</code>    | Actual DPI          |
| <code>SetProcessDpiAwareness</code> | Sharp on Windows    |
| Point font sizes                    | Scale automatically |

## COMMON MISTAKES

- › Setting DPI awareness after `Tk()` (no effect)
- › Hard-coding `<Button-3>` for context menus
- › Mixing pixel and point sizes so layouts break at 150%

## TIPS & BEST PRACTICES

- › Centralize platform constants in one module
- › Prefer layout managers over fixed pixel sizes
- › Use `clam` on Linux for a consistent look

## QUICK SUMMARY

- › Declare DPI awareness first on Windows
- › Branch on `tk windowingsystem`
- › Points scale, pixels don't
- › Mind mouse buttons and modifier keys

## TESTING AND DEBUGGING TKINTER APPS

GUI code is easiest to test when logic lives outside it (Sheet 54). For the UI itself, tests can create a real `Tk()` root, call `update_idletasks()` or `update()` to process events, and drive widgets with `invoke()` or `event_generate()`. Exceptions inside callbacks don't crash the app; Tk passes them to `report_callback_exception`, which prints a traceback. Override it to log errors or show a dialog. On headless CI, run tests under **Xvfb**.

## NOTES

- › Create one root per test and `destroy()` it in teardown
- › `event_generate` needs the widget mapped and focused for keys
- › `wininfo_children()` helps find widgets in tests
- › `root.tk.call(...)` lets you inspect raw Tcl state
- › `pytest-xvfb` starts a virtual display automatically

## UNITTEST WITH A REAL ROOT

```
import unittest, tkinter as tk
from tkinter import ttk

class Counter(ttk.Frame):
    def __init__(self, parent):
        super().__init__(parent)
        self.value = tk.IntVar(value=0)
        self.button = ttk.Button(self, text="+1", command=lambda:
                                self.value.set(self.value.get() + 1))
        self.button.pack()

class CounterTest(unittest.TestCase):
    def setUp(self):
        self.root = tk.Tk(); self.root.withdraw()  # no visible window
        self.w = Counter(self.root); self.w.pack()

    def tearDown(self):
        self.root.destroy()

    def test_click_increments(self):
        self.w.button.invoke()
        self.assertEqual(self.w.value.get(), 1)

    def test_errors_are_reported(self):
        seen = []
        self.root.report_callback_exception = lambda *exc: seen.append(exc[1])
        self.root.after(0, lambda: 1 / 0); self.root.update()
        self.assertIsInstance(seen[0], ZeroDivisionError)
```

## CODE EXPLAINED

- `withdraw()` keeps test windows off-screen
- `invoke()` simulates a button click
- `update()` runs the scheduled `after(0, ...)` callback
- `report_callback_exception` receives (type, value, traceback)
- Each test gets a fresh root, destroyed in `tearDown`

## DRIVING WIDGETS

| CALL                          | SIMULATES            |
|-------------------------------|----------------------|
| <code>invoke()</code>         | Button click         |
| <code>event_generate()</code> | Key / mouse event    |
| <code>insert("end", s)</code> | Typing text          |
| <code>focus_force()</code>    | Focus for key events |
| <code>update()</code>         | Process events       |

## DEBUGGING TOOLS

| TOOL                                   | SHOWS             |
|----------------------------------------|-------------------|
| <code>wininfo_children()</code>        | Widget tree       |
| <code>w.configure()</code>             | All option values |
| <code>print(event)</code>              | Event details     |
| <code>report_callback_exception</code> | Callback errors   |
| <code>tk.call()</code>                 | Tcl internals     |

## CI SETUP

| NEED           | SOLUTION        |
|----------------|-----------------|
| Linux display  | xvfb-run pytest |
| pytest plugin  | pytest-xvfb     |
| GitHub Actions | xvfb on ubuntu  |
| Skip headless  | TclError guard  |

## △ COMMON MISTAKES

- › Running tests without a display on Linux CI
- › Sharing one root across tests and leaking state
- › Asserting before `update()` processed pending events

## ✓ TIPS &amp; BEST PRACTICES

- › Test models directly; test the GUI lightly
- › Override `report_callback_exception` to log in production
- › Name widgets ( `name="save"` ) to find them with `nametowidget`

## QUICK SUMMARY

- › Real root + `update()` in tests
- › `invoke()` and `event_generate()` drive UI
- › `report_callback_exception` for errors
- › Xvfb for headless CI

## SHIPPING A TKINTER APP

End users usually don't have Python, so bundle the interpreter, Tcl/Tk and your code into an executable. **PyInstaller** is the most common tool: `--windowed` hides the console window, `--onefile` produces a single file (slower to start), and `--add-data` includes images and other resources. Inside the bundle, locate resources relative to `sys._MEIPASS` or the script file. **Nuitka** compiles to C for speed, and **cx\_Freeze** or **Briefcase** suit installers and app stores.

## NOTES

- › Build on each target OS; there's no cross-compiling
- › `--add-data` uses `src:dest`; Windows needed ; before PyInstaller 6
- › Antivirus tools sometimes flag `--onefile` builds
- › Rename a script to `.pyw` to run without a console on Windows
- › Sign and notarize macOS apps for distribution

## BUNDLING WITH PYINSTALLER

```
# Install and build
pip install pyinstaller
pyinstaller --windowed --onefile --name Inventory \
    --icon assets/app.ico --add-data "assets:assets" app.py
# Output: dist/Inventory(.exe) | build/ = scratch | Inventory.spec

# One-folder build (faster startup, easier debugging)
pyinstaller --windowed --name Inventory --add-data "assets:assets" app.py

# Rebuild from the generated spec after editing it
pyinstaller Inventory.spec

# Resource helper inside app.py (works frozen or not):
# import sys
# from pathlib import Path
# BASE = Path(getattr(sys, "_MEIPASS", Path(__file__).parent))
# icon = tk.PhotoImage(file=BASE / "assets" / "save.png")

# Alternatives
python -m nuitka --standalone --enable-plugin=tk-inter \
    --windows-console-mode=disable app.py
cxfreeze build # cx_Freeze with pyproject config
briefcase create && briefcase build # BeeWare installers
```

## CODE EXPLAINED

- `--windowed` = no console window behind the GUI
- `--add-data "src:dest"` copies resources into the bundle
- The spec file records options for repeatable builds
- `sys._MEIPASS` is the unpack folder in frozen apps
- Nuitka needs the `tk-inter` plugin for Tkinter

## PYINSTALLER FLAGS

| FLAG                    | EFFECT            |
|-------------------------|-------------------|
| <code>--windowed</code> | No console        |
| <code>--onefile</code>  | Single executable |
| <code>--name</code>     | Output name       |
| <code>--icon</code>     | App icon          |
| <code>--add-data</code> | Bundle resources  |

## TOOLS COMPARED

| TOOL        | STRENGTH          |
|-------------|-------------------|
| PyInstaller | Popular, simple   |
| Nuitka      | Compiled, faster  |
| cx_Freeze   | MSI / installers  |
| Briefcase   | Native installers |
| py2app      | macOS .app        |

## CHECKLIST

| ITEM               | WHY                |
|--------------------|--------------------|
| Relative resources | Paths work frozen  |
| Test clean machine | Missing files show |
| Version info       | Windows properties |
| Code signing       | Fewer warnings     |
| One-folder first   | Easier debugging   |

## △ COMMON MISTAKES

- › Loading files by relative path from the current directory
- › Shipping a console window with a GUI app
- › Only testing the build on the developer's machine

## ✓ TIPS &amp; BEST PRACTICES

- › Keep all assets in one folder and add it once
- › Commit the `.spec` file for reproducible builds
- › Debug with a console build before switching to `--windowed`

## QUICK SUMMARY

- › PyInstaller `--windowed --onefile`
- › `--add-data` for assets
- › Resolve paths via `sys._MEIPASS`
- › Build on every target OS

## MODERN LOOKS WITH THEME PACKAGES

Two popular packages give ttk apps a modern look with almost no code changes. **sv-ttk** (Sun Valley) applies a Windows 11-style light or dark theme with one call, plus extra styles like `Accent.TButton` and `Switch.TCheckbutton`. **ttkbootstrap** brings more than 20 Bootstrap-inspired themes, a `bootstyle=` keyword for color roles (success, danger–outline...) and extra widgets such as `Meter`, `DateEntry`, `Floodgauge` and `Tableview`. Both are on PyPI: `pip install sv-ttk ttkbootstrap`.

## NOTES

- › Both work with regular ttk widgets and layouts
- › Pick one theme package per app; don't mix them
- › ttkbootstrap's `Window` replaces `tk.Tk()`
- › ttkbootstrap can also be used as `import ttkbootstrap as ttk`
- › Classic `tk` widgets aren't themed by either

## SV-TTK AND TTKBOOTSTRAP

```
# Two separate examples: pick ONE theme package per app
# --- sv-ttk: one call on a normal Tk app -----
import tkinter as tk
from tkinter import ttk
import sv_ttk

root = tk.Tk()
ttk.Button(root, text="Save", style="Accent.TButton").pack(pady=6)
ttk.Checkbutton(root, text="Dark mode", style="Switch.TCheckbutton",
                 command=sv_ttk.toggle_theme).pack(pady=6)
sv_ttk.set_theme("dark")           # or "light"; get_theme()

# --- ttkbootstrap: its own Window and bootstyle keyword -----
import ttkbootstrap as tb
from ttkbootstrap.constants import SUCCESS, DANGER
app = tb.Window(themename="darkly", title="Dashboard")
tb.Button(app, text="Deploy", bootstyle=SUCCESS).pack(side="left", padx=8)
tb.Button(app, text="Delete", bootstyle=(DANGER, "outline")).pack(side="left")
tb.Meter(app, amountused=72, subtext="CPU", bootstyle="info",
          interactive=True).pack(pady=10)
tb.DateEntry(app, dateformat="%Y-%m-%d").pack()
tb.Progressbar(app, value=40, bootstyle="striped").pack(fill="x", padx=8)
app.style.theme_use("flatly")      # switch themes at runtime
print(app.style.theme_names())     # all ttkbootstrap themes
app.mainloop()
```

## CODE EXPLAINED

- sv-ttk restyles every ttk widget on the root
- `Accent.TButton` and `Switch.TCheckbutton` are sv-ttk styles
- `tb.Window` creates the root with a theme
- `bootstyle` sets the color role and variant
- `Meter` and `DateEntry` are ttkbootstrap-only widgets

## SV-TTK API

| CALL                             | DOES               |
|----------------------------------|--------------------|
| <code>set_theme("dark")</code>   | Apply theme        |
| <code>toggle_theme()</code>      | Light ↔ dark       |
| <code>get_theme()</code>         | Current theme      |
| <code>Accent.TButton</code>      | Highlighted button |
| <code>Switch.TCheckbutton</code> | Toggle switch      |

## BOOTSTYLE VALUES

| VALUE                            | LOOK             |
|----------------------------------|------------------|
| <code>primary / secondary</code> | Main colors      |
| <code>success / info</code>      | Green / blue     |
| <code>warning / danger</code>    | Orange / red     |
| <code>"danger-outline"</code>    | Outlined variant |
| <code>"success-striped"</code>   | Striped bar      |

## TTKBOOTSTRAP EXTRAS

| WIDGET                         | PURPOSE           |
|--------------------------------|-------------------|
| <code>Meter</code>             | Radial gauge      |
| <code>DateEntry</code>         | Date picker field |
| <code>Floodgauge</code>        | Filled progress   |
| <code>Tableview</code>         | Sortable table    |
| <code>ToastNotification</code> | Popup toast       |

## △ COMMON MISTAKES

- › Calling `sv_ttk.set_theme()` before creating `Tk()`
- › Creating both `tk.Tk()` and `tb.Window()`
- › Expecting classic `tk.Button` to pick up the theme

## ✓ TIPS &amp; BEST PRACTICES

- › Use sv-ttk for a native Windows 11 look
- › Use ttkbootstrap for dashboards and colorful UIs
- › Respect the OS dark mode setting with a toggle

## QUICK SUMMARY

- › sv-ttk: `set_theme("dark")`
- › ttkbootstrap: `Window(themename=...)`
- › `bootstyle=` for color roles
- › Extra widgets: `Meter`, `DateEntry`, `Tableview`

## CUSTOMTKINTER WIDGETS

**CustomTkinter** (pip install customtkinter) is a widget library built on Tkinter that draws its own rounded, modern widgets with automatic **light/dark mode** and **HiDPI scaling**. Its widgets are prefixed Ctk (CtkButton, CtkEntry, CtkSwitch...) and use their own options such as corner\_radius, fg\_color and hover\_color. Layout still uses pack, grid and place, and standard Tk variables and command= callbacks work as usual.

## NOTES

- › Use `ctk.Ctk()` as the root instead of `tk.Tk()`
- › Colors can be a pair: `("light_color", "dark_color")`
- › `CTkImage` supports separate light/dark images and scaling
- › Mixing ttk widgets in looks inconsistent
- › Use `CTkFont` for fonts that scale with the UI

## SETTINGS PANEL IN CUSTOMTKINTER

```
import customtkinter as ctk

ctk.set_appearance_mode("system")          # "light", "dark", "system"
ctk.set_default_color_theme("blue")        # "green", "dark-blue", or a .json

app = ctk.Ctk()
app.title("Settings"); app.geometry("360x300")
app.grid_columnconfigure(0, weight=1)

ctk.CtkLabel(app, text="Profile", font=ctk.CtkFont(size=18, weight="bold"))
    .grid(row=0, column=0, padx=20, pady=(20, 6), sticky="w")
name = ctk.CtkEntry(app, placeholder_text="Display name")
name.grid(row=1, column=0, padx=20, pady=6, sticky="ew")
dark = ctk.StringVar(value="off")
ctk.CtkSwitch(app, text="Dark mode", variable=dark, onvalue="on",
    offvalue="off", command=lambda: ctk.set_appearance_mode(
        "dark" if dark.get() == "on" else "light"))
    .grid(row=2, column=0, padx=20, pady=6, sticky="w")
size = ctk.CtkSegmentedButton(app, values=["S", "M", "L"])
size.set("M"); size.grid(row=3, column=0, padx=20, pady=6)
ctk.CtkButton(app, text="Save", corner_radius=8,
    fg_color=("#2e7d32", "#43a047"), hover_color="#1b5e20",
    command=lambda: print(name.get(), size.get()))
    .grid(row=4, column=0, padx=20, pady=16, sticky="ew")
app.mainloop()
```

## CODE EXPLAINED

- Appearance and color theme are set globally first
- `CTkEntry` supports placeholder text
- `CTkSwitch` toggles the appearance mode live
- `CTkSegmentedButton` is a modern radio group
- `fg_color` pair = (light-mode, dark-mode) colors

## CORE WIDGETS

| CTK CLASS                       | LIKE            |
|---------------------------------|-----------------|
| <code>CtkButton</code>          | Button          |
| <code>CtkEntry</code>           | Entry           |
| <code>CtkTextbox</code>         | Text            |
| <code>CtkOptionMenu</code>      | OptionMenu      |
| <code>CtkScrollableFrame</code> | Scrolling Frame |

## STYLE OPTIONS

| OPTION                     | EFFECT          |
|----------------------------|-----------------|
| <code>corner_radius</code> | Rounded corners |
| <code>fg_color</code>      | Main color      |
| <code>hover_color</code>   | Hover color     |
| <code>border_width</code>  | Outline width   |
| <code>text_color</code>    | Text color      |

## GLOBAL SETTINGS

| CALL                                   | EFFECT                |
|----------------------------------------|-----------------------|
| <code>set_appearance_mode()</code>     | Light / dark / system |
| <code>set_default_color_theme()</code> | Accent theme          |
| <code>set_widget_scaling(f)</code>     | Widget size           |
| <code>set_window_scaling(f)</code>     | Window size           |

## △ COMMON MISTAKES

- › Using `bg=` / `fg=` instead of `fg_color` / `text_color`
- › Creating `tk.Tk()` and placing Ctk widgets in it
- › Setting the color theme after widgets exist

## ✓ TIPS &amp; BEST PRACTICES

- › Default to `"system"` appearance to follow the OS
- › Use `CTkTabview` and `CtkScrollableFrame` for layout
- › Keep logic separate so you can swap toolkits later

## QUICK SUMMARY

- › Modern drawn widgets prefixed `CTk`
- › Automatic light/dark mode
- › `fg_color`, `corner_radius`, `hover_color`
- › Same layout managers and callbacks

## CHARTS AND POPULAR ADD-ONS

**Matplotlib** plots embed in Tkinter through `FigureCanvasTkAgg`, which turns a `Figure` into a Tk widget, plus an optional `NavigationToolbar2Tk` for zoom and pan. Create the figure with `matplotlib.figure.Figure` rather than `pyplot`, so no extra window or global state is created. Other widely used add-ons fill gaps in Tk: **tkcalendar** (date pickers), **tkinterdnd2** (drag files in from the OS) and **Pillow** (image formats, Sheet 49).

## NOTES

- › Call `canvas.draw()` (or `draw_idle()`) after changing plots
- › `pack_toolbar=False` lets you grid the toolbar yourself
- › `mpl_connect` handles clicks and hovers on the plot
- › `tkinterdnd2` needs its own root: `TkinterDnD.Tk()`
- › `get_date()` from `tkcalendar` returns a `datetime.date`

## LIVE PLOT, DATE PICKER, FILE DROP

```
import tkinter as tk
from matplotlib.figure import Figure
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg, NavigationToolbar2Tk
from tkcalendar import DateEntry
from tkinterdnd2 import TkinterDnD, DND_FILES

root = TkinterDnD.Tk()                                # Tk root with drag-and-drop
fig = Figure(figsize=(5, 3), dpi=100)
ax = fig.add_subplot()
line, = ax.plot([1, 2, 3, 4], [3, 1, 4, 2], marker="o")
canvas = FigureCanvasTkAgg(fig, master=root)
canvas.get_tk_widget().pack(fill="both", expand=True)
NavigationToolbar2Tk(canvas, root).update()

def add_point():
    xs, ys = list(line.get_xdata()), list(line.get_ydata())
    line.set_data(xs + [xs[-1] + 1], ys + [ys[-1] + 1])
    ax.relim(); ax.autoscale_view(); canvas.draw_idle()
tk.Button(root, text="Add point", command=add_point).pack()
when = DateEntry(root, date_pattern="yyyy-mm-dd"); when.pack(pady=4)
when.bind("<<DateEntrySelected>>", lambda e: print(when.get_date()))
drop = tk.Label(root, text="Drop files here", relief="groove", height=3)
drop.pack(fill="x", padx=8, pady=8)
drop.drop_target_register(DND_FILES)
drop.dnd_bind("<<Drop>>", lambda e: print(root.tk.splitlist(e.data)))
root.mainloop()
```

## CODE EXPLAINED

- `Figure` + `FigureCanvasTkAgg` = plot as a Tk widget
- The toolbar adds zoom, pan and save buttons
- `relim` / `autoscale_view` refit axes after new data
- `DateEntry` is a drop-down calendar field
- `splitlist` splits dropped paths safely (spaces in braces)

## MATPLOTLIB EMBED

| CALL                              | DOES            |
|-----------------------------------|-----------------|
| <code>Figure(figsize, dpi)</code> | Plot container  |
| <code>FigureCanvasTkAgg</code>    | Figure → widget |
| <code>get_tk_widget()</code>      | Widget to pack  |
| <code>draw_idle()</code>          | Redraw soon     |
| <code>mpl_connect(ev, f)</code>   | Plot events     |

## ADD-ON PACKAGES

| PACKAGE                  | PROVIDES                         |
|--------------------------|----------------------------------|
| <code>tkcalendar</code>  | Calendar, <code>DateEntry</code> |
| <code>tkinterdnd2</code> | OS drag-and-drop                 |
| <code>Pillow</code>      | Image formats                    |
| <code>pystray</code>     | System tray icon                 |
| <code>tktooltip</code>   | Hover tooltips                   |

## DRAG &amp; DROP

| CALL                                          | PURPOSE          |
|-----------------------------------------------|------------------|
| <code>TkinterDnD.Tk()</code>                  | DnD-capable root |
| <code>drop_target_register</code>             | Accept drops     |
| <code>dnd_bind("&lt;&lt;Drop&gt;&gt;")</code> | Handle drop      |
| <code>e.data</code>                           | Dropped paths    |

## △ COMMON MISTAKES

- › Using `plt.figure()` and getting a second window
- › Changing data without calling `draw()` / `draw_idle()`
- › Splitting dropped paths on spaces

## ✓ TIPS &amp; BEST PRACTICES

- › Reuse one `Figure` and update data instead of recreating
- › Use `draw_idle` for frequent updates
- › Check each add-on's license before shipping

## QUICK SUMMARY

- › `FigureCanvasTkAgg` embeds Matplotlib
- › Use `Figure`, not `pyplot`
- › `tkcalendar` for dates, `tkinterdnd2` for drops
- › `Pillow` for images

## WIDGETS AT A GLANCE

This sheet collects the widget set on one page: every common widget, whether it has a **ttk** version, the options you'll set most often, and the three geometry managers. Prefer the **ttk** widget whenever one exists; it looks native and is styled through `ttk.Style`. Classic tk widgets remain the right choice for **Text**, **Canvas**, **Listbox** and **Menu**, which have no ttk equivalent. Sheet numbers in the tables point to the detailed pages.

## NOTES

- › Every widget's first argument is its parent
- › Create, then place: `w = W(parent); w.grid(...)`
- › `configure()` changes options; `cget()` reads them
- › Constants: `"end"`, `"both"`, `"left"` as strings
- › Detailed pages: widgets 07–15, ttk 33–41

## WIDGET CREATION CHEAT CODES

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()

ttk.Label(root, text="Hi", image=img, compound="left")  # img = PhotoImage
ttk.Button(root, text="OK", command=fn, style="Accent.TButton")
ttk.Entry(root, textvariable=sv, show="*", width=20)
ttk.Checkbutton(root, text="On", variable=bv)
ttk.Radiobutton(root, text="A", value="a", variable=sv)
ttk.Combobox(root, values=["a", "b"], state="readonly")
ttk.Spinbox(root, from_=0, to=10, increment=1)
ttk.Scale(root, from_=0, to=100, orient="horizontal", variable=dv)
ttk.Progressbar(root, mode="determinate", maximum=100, value=40)
ttk.Treeview(root, columns=("a", "b"), show="headings")
ttk.Notebook(root); ttk.Separator(root); ttk.Sizegrip(root)
ttk.Frame(root, padding=8); ttk.LabelFrame(root, text="Group")
ttk.Panedwindow(root, orient="horizontal")
ttk.Scrollbar(root, orient="vertical", command=widget.yview)

tk.Text(root, wrap="word", undo=True, height=10)
tk.Canvas(root, width=300, height=200, bg="white")
tk.Listbox(root, selectmode="extended", height=6)
tk.Menu(root, tearoff=0); tk.Toplevel(root)
tk.PhotoImage(file="icon.png")
```

## CODE EXPLAINED

- One line per widget with its most-used options
- `sv`, `bv`, `dv` stand for String/Boolean/Double vars
- `fn` is any zero-argument callback
- ttk widgets first, then classic-only widgets
- Placeholders ( `img`, `widget` ) must exist in real code

## CLASSIC-ONLY

| WIDGET   | SHEET |
|----------|-------|
| Text     | 10–11 |
| Canvas   | 42–46 |
| Listbox  | 13    |
| Menu     | 27–28 |
| Toplevel | 05    |

## GEOMETRY MANAGERS

| MANAGER      | KEY OPTIONS         |
|--------------|---------------------|
| pack         | side, fill, expand  |
| grid         | row, column, sticky |
| grid weights | columnconfigure     |
| place        | relx, rely, anchor  |
| All          | padx, pady          |

## UNIVERSAL OPTIONS

| OPTION              | MEANING           |
|---------------------|-------------------|
| text / textvariable | Displayed text    |
| command             | Click callback    |
| state               | normal / disabled |
| width               | Chars or px       |
| style (ttk)         | Named style       |

## △ COMMON MISTAKES

- › Chaining `.grid()` onto the constructor and keeping `None`
- › Using classic widgets where a ttk one exists
- › Mixing pack and grid in one parent

## ✓ TIPS &amp; BEST PRACTICES

- › Keep this sheet next to the detailed pages
- › Start every app with `import tkinter as tk + ttk`
- › Reach for Treeview before building tables by hand

## QUICK SUMMARY

- › ttk first; tk for Text, Canvas, Listbox, Menu
- › pack / grid / place
- › Variables link data to widgets
- › Options via `configure()`

## EVENTS, METHODS AND HELPERS

The second quick reference covers what happens **after** widgets exist: binding events, reading the event object, scheduling with `after()`, querying geometry with `winfo_*`, standard dialogs and control variables. These calls make up most of the glue code in a Tkinter app. Keep callbacks short, move slow work off the main thread (Sheet 51), and remember that Tk is single-threaded: only the main thread may touch widgets.

## NOTES

- › Handlers from `bind()` take one `event` argument
- › `command=` callbacks take none
- › `after()` returns an id for `after_cancel()`
- › Dialogs return `None` / `""` when cancelled
- › Detailed pages: events 21–26, dialogs 29–32, timers 50

## GLUE CODE CHEAT CODES

```
w.bind("<Button-1>", lambda e: print(e.x, e.y))    # widget binding
root.bind_all("<Control-s>", save)                # app-wide shortcut
w.event_generate("<<Refresh>>")                  # fire virtual event

var = tk.StringVar(value="x"); var.trace_add("write", lambda *a: ...)
job = root.after(500, tick); root.after_cancel(job)

w.winfo_width(); w.winfo_height()               # size (after layout)
w.winfo_rootx(); w.winfo_rooty()               # screen position
w.winfo_children(); w.winfo_toplevel(); w.winfo_exists()
root.update_idletasks()                        # finish layout now

from tkinter import messagebox, filedialog, simplifiedialog
messagebox.askyesno("Quit?", "Really quit?", parent=root) # True/False
filedialog.askopenfilename(filetypes=[("Text", "*.txt")]) # "" on cancel
simplifiedialog.askinteger("Age", "Age?", minvalue=0)     # None on cancel

root.clipboard_clear(); root.clipboard_append("copied")
text = root.clipboard_get()
root.protocol("WM_DELETE_WINDOW", on_close)
w.focus_set(); w.lift(); w.destroy()
```

## CODE EXPLAINED

- Bindings: widget, app-wide and virtual events
- Variables and timers are the main state tools
- `winfo_*` queries need layout done first
- Standard dialogs return values or cancel markers
- Clipboard, close handling and focus helpers

## EVENT SEQUENCES

| SEQUENCE          | WHEN         |
|-------------------|--------------|
| <Button-1>        | Left click   |
| <Double-Button-1> | Double click |
| <B1-Motion>       | Drag         |
| <Key> / <Return>  | Keys         |
| <Configure>       | Resize       |

## EVENT ATTRIBUTES

| ATTRIBUTE      | HOLDS           |
|----------------|-----------------|
| widget         | Source widget   |
| x, y           | Widget coords   |
| x_root, y_root | Screen coords   |
| keysym / char  | Key name / text |
| delta          | Wheel amount    |

## CONTROL VARIABLES

| CLASS      | TYPICAL USE            |
|------------|------------------------|
| StringVar  | Entry, Label, Combobox |
| IntVar     | Spinbox, Radiobutton   |
| DoubleVar  | Scale, Progressbar     |
| BooleanVar | Checkbutton            |
| trace_add  | React to changes       |

## ⚠ COMMON MISTAKES

- › Touching widgets from worker threads
- › Blocking the loop with `sleep` or long loops
- › Reading `winfo_*` before the window is drawn

## ✓ TIPS &amp; BEST PRACTICES

- › Bind shortcuts once on the root
- › Use virtual events to decouple parts of the app
- › Wrap dialogs in helpers that pass `parent=`

## QUICK SUMMARY

- › `bind` + event attributes
- › `after` for timing
- › `winfo_*` for geometry
- › Dialogs, clipboard, protocol