KUBERNETES

CHEAT SHEETS

A Complete Reference for Running Apps on Kubernetes

Architecture · kubectl · Manifests & Labels · Pods · Deployments · StatefulSets · Jobs · Probes · Services · Gateway API · Network Policies · ConfigMaps & Secrets · Storage · Scheduling · Autoscaling · RBAC · Pod Security · Debugging · Helm & Kustomize

25 REFERENCE SHEETS

CONTENTS

INTRODUCTION & SETUP

01 Introduction & Architecture
02 Local Clusters & Installing kubectl
03 kubeconfig, Contexts & Namespaces

KUBECTL ESSENTIALS

04 Inspecting Resources & Output Formats
05 Imperative vs Declarative
06 Manifests, Labels & Selectors

WORKLOADS

07 Pods
08 Deployments & Rollouts
09 StatefulSets & DaemonSets
10 Jobs & CronJobs
11 Health Probes & Pod Lifecycle

NETWORKING

12 Services & DNS
13 Ingress & Gateway API
14 Network Policies

CONFIGURATION & STORAGE

15 ConfigMaps & Secrets
16 Volumes & Persistent Storage

RESOURCES, SCHEDULING & SCALING

17 Requests, Limits & Quotas
18 Scheduling & Node Placement
19 Autoscaling & Disruption Budgets

SECURITY

20 RBAC & ServiceAccounts
21 Pod Security

OPERATIONS & TOOLING

22 Debugging & Troubleshooting
23 Helm & Kustomize

QUICK REFERENCE

24 Quick Reference — kubectl Commands
25 Quick Reference — Manifests & Troubleshooting

Kubernetes Reference

Table of Contents

25 reference sheets · syntax · examples · notes

Sheet 1
Introduction & Architecture
control plane · kube-apiserver · etcd · scheduler · kubelet · kube-proxy · reconcile loop

Sheet 2
Local Clusters & Installing kubectl
kind · minikube · k3d / k3s · kubectl install · version skew · EKS / GKE / AKS

Sheet 3
kubeconfig, Contexts & Namespaces
~/.kube/config · KUBECONFIG · use-context · set-context --namespace · kubectx / kubens

Sheet 4
Inspecting Resources & Output Formats
get · describe · -o wide / yaml / json · jsonpath · custom-columns · explain · api-resources

Sheet 5
Imperative vs Declarative
create · run · expose · apply -f · diff · --dry-run=client -o yaml · edit / patch · --server-side

Sheet 6
Manifests, Labels & Selectors
apiVersion / kind / metadata / spec · --- · labels · selectors · annotations · app.kubernetes.io/*

Sheet 7
Pods
containers · command / args · env · initContainers · sidecars · phases · restartPolicy · imagePullPolicy

Sheet 8
Deployments & Rollouts
ReplicaSet · replicas · RollingUpdate · maxSurge / maxUnavailable · Recreate · rollout undo · scale

Sheet 9
StatefulSets & DaemonSets
stable pod names · headless Service · volumeClaimTemplates · podManagementPolicy · DaemonSet · partition

Sheet 10
Jobs & CronJobs
completions · parallelism · backoffLimit · activeDeadlineSeconds · ttlSecondsAfterFinished · schedule · concurrencyPolicy

Sheet 11
Health Probes & Pod Lifecycle
livenessProbe · readinessProbe · startupProbe · httpGet / tcpSocket / exec / grpc · preStop · terminationGracePeriodSeconds

Sheet 12
Services & DNS
ClusterIP · NodePort · LoadBalancer · ExternalName · port vs targetPort · EndpointSlices · CoreDNS

Sheet 13
Ingress & Gateway API
Ingress rules · ingressClassName · TLS · GatewayClass · Gateway · HTTPRoute · path / header matching

Sheet 14
Network Policies
default deny · podSelector · namespaceSelector · ingress / egress · ipBlock · ports · CNI

Sheet 15
ConfigMaps & Secrets
create --from-literal / --from-file / --from-env-file · valueFrom · envFrom · volume mounts · base64 · immutable

Sheet 16
Volumes & Persistent Storage
emptyDir · hostPath · PersistentVolume · PersistentVolumeClaim · StorageClass · RWO / RWX / RWOP · CSI

Sheet 17
Requests, Limits & Quotas
requests vs limits · millicores / Mi · QoS classes · OOMKilled · CPU throttling · LimitRange · ResourceQuota

Sheet 18
Scheduling & Node Placement
nodeSelector · node affinity · pod anti-affinity · taints & tolerations · topologySpreadConstraints · drain

Sheet 19
Autoscaling & Disruption Budgets
HorizontalPodAutoscaler · kubectl autoscale · metrics-server · VPA · Cluster Autoscaler · Karpenter · PodDisruptionBudget

Sheet 20
RBAC & ServiceAccounts
Role / ClusterRole · RoleBinding / ClusterRoleBinding · verbs · ServiceAccount · create token · auth can-i

Sheet 21
Pod Security
securityContext · runAsNonRoot · readOnlyRootFilesystem · drop ALL · allowPrivilegeEscalation · seccomp · Pod Security Admission

Sheet 22
Debugging & Troubleshooting
logs -f / --previous · exec -it · kubectl debug · port-forward · events · top · CrashLoopBackOff / Pending

Sheet 23
Helm & Kustomize
helm repo add · upgrade --install · values.yaml / -f / --set · helm template / rollback · kustomization.yaml · overlays · apply -k

Sheet 24
Quick Reference — kubectl Commands
contexts & namespaces · get / describe · apply / delete · rollouts & scaling · logs / exec · nodes · auth can-i

Sheet 25
Quick Reference — Manifests & Troubleshooting
apiVersion / kind · short names · manifest skeletons

Sheet 01

Introduction & Architecture

control plane · kube-apiserver · etcd · scheduler · kubelet · kube-proxy · reconcile loop

WHAT KUBERNETES IS

Kubernetes (K8s) is an open-source **container orchestrator**: it places containers on a pool of machines, restarts them when they fail, scales them and gives them stable networking. You **declare the desired state** in YAML; **controllers** keep nudging the actual state toward it, forever. That loop (*observe → diff → act*) explains everything else in this set.

GOOD TO KNOW

- Started at Google, v1.0 in 2015, now a CNCF project; ~3 releases a year
- Nodes run `containerd` or CRI-O, not Docker Engine; Docker-built images still work
- `kubectl` only writes objects to the API; controllers do the work
- Everything is an **object** in the API: Pods, Services, even Nodes

WATCH THE RECONCILE LOOP

```
kubectl create deployment hello --image=nginx:1.27
kubectl scale deployment hello --replicas=3   # desired: 3 pods
kubectl get pods                    # 3 x hello-6d8f9c7b5-…  Running
kubectl delete pod hello-6d8f9c7b5-x7k2p      # "crash" one
kubectl get pods                    # still 3: a new one replaced it
kubectl expose deployment hello --port=80     # stable Service IP
kubectl get nodes -o wide           # machines in the cluster
kubectl get pods -n kube-system     # coredns, kube-proxy, etcd…
kubectl get --raw='/readyz?verbose' # control-plane health
kubectl delete deployment,svc hello # clean up
```

CODE EXPLAINED

- → `create deployment` — stores an object; controllers create the Pods
- → `delete pod` — actual (2) ≠ desired (3), so a replacement appears
- → `expose` — a Service gives pods one stable IP + DNS name
- → `kube-system` — namespace for cluster components
- → `/readyz` — replaces deprecated `get componentstatuses`
- → `get nodes -o wide` — node IPs, OS, kernel, runtime version

CONTROL PLANE

COMPONENT	JOB
`kube-apiserver`	Front door; every read and write goes through it
`etcd`	Key-value store holding all cluster state
`kube-scheduler`	Picks a node for each new Pod
`controller-manager`	Runs built-in controllers (Deployment, Job, Node…)
`cloud-controller`	Cloud load balancers, routes, node lifecycle
`etcd quorum`	3 or 5 members; losing a majority stops writes

EVERY WORKER NODE

COMPONENT	JOB
`kubelet`	Starts the node's Pods, reports their status
`containerd / CRI-O`	Container runtime that runs the containers
`kube-proxy`	Programs Service routing (iptables / IPVS / nftables)
`CNI plugin`	Pod networking: Calico, Cilium, Flannel
`CoreDNS`	Cluster DNS add-on, runs as pods
`Pod`	Smallest unit: 1+ containers sharing IP + volumes

⚠ COMMON MISTAKES

- Bare Pods for apps — nothing recreates them if the node dies; use a Deployment
- Assuming `apply` succeeded = app running; controllers act afterward
- Fixing things on nodes by hand — controllers overwrite drift
- Expecting `docker ps` on nodes — use `crictl ps`

✓ TIPS & BEST PRACTICES

- Read the Events in `kubectl describe` first; they explain most failures
- Change the spec and let controllers converge; don't script steps
- Learn on a throwaway local cluster (Sheet 02)
- `kubectl api-resources` lists every kind the cluster knows

QUICK SUMMARY

- `apiserver` — the only door; state lives in `etcd`
- `scheduler` — placement; `controllers` — reconcile
- `kubelet` — runs pods on each node
- `Pod` — smallest unit, usually owned by a controller

Local Clusters & Installing kubectl

GETTING A CLUSTER

You need the **`kubectl`** CLI and a **cluster** to point it at. For learning and CI, run a disposable cluster inside Docker with **kind**, **minikube** or **k3d**; each starts in about a minute. In production most teams use a **managed** control plane (EKS, GKE, AKS) and only run workloads and nodes.

NOTES

- Local tools add a context to `~/.kube/config` automatically
- Locally built images are invisible to the cluster until loaded or pushed
- Docker Desktop has a one-click single-node cluster
- kind names contexts `kind-<name>`; minikube's is `minikube`

INSTALL & CREATE

```
brew install kubectl                          # macOS
winget install -e --id Kubernetes.kubectl     # Windows
sudo snap install kubectl --classic           # Linux (or dl.k8s.io binary)
kubectl version --client                      # Client Version: v1.3x.x
kind create cluster --name dev                # 1 node in Docker
kind create cluster --name dev --config kind.yaml   # multi-node
kind load docker-image myapp:dev --name dev         # copy image in
minikube start --driver=docker --cpus=4 --memory=8g
minikube addons enable metrics-server         # built-in add-ons
k3d cluster create dev --agents 2             # k3s + 2 workers
kind delete cluster --name dev                # gone in seconds
```

CODE EXPLAINED

- → `version` — without `--client` also shows the server
- → `kind.yaml` — `nodes:` list with `role: control-plane` / `worker`
- → `kind load` — skip the registry for dev images
- → `--agents` — k3d's name for worker nodes
- → `minikube addons list` — ingress, dashboard, registry…
- → `delete cluster` — also removes its kubeconfig context

LOCAL OPTIONS

TOOL	BEST FOR
`kind`	CI, multi-node tests, upstream K8s
`minikube`	Learning; easy add-ons
`k3d`	Fast k3s with built-in LB
`Docker Desktop`	Zero setup on Mac/Windows
`k3s`	Edge, Pi, small Linux VMs

MANAGED: FETCH CREDENTIALS

SERVICE	COMMAND
EKS	`aws eks update-kubeconfig --name c1`
GKE	`gcloud container clusters get-credentials c1`
AKS	`az aks get-credentials -g rg -n c1`
Create	`eksctl · gcloud … create-auto · az aks create`

VERSION SKEW

PAIR	ALLOWED
`kubectl`	±1 minor of API
`kubelet`	≤ 3 minors older
`upgrades`	1 minor at a time

⚠ COMMON MISTAKES

- `ErrImagePull` on a local image — `kind load` it or push it
- `:latest` dev tag forces `Always` pull, ignoring the loaded image
- kubectl 2+ minors from the server — odd errors, missing flags
- Leaving local clusters running — they keep eating CPU and RAM

✓ TIPS & BEST PRACTICES

- Pin the node image (`--image kindest/node:v1.3x.y`) to match prod
- Recreate a broken local cluster instead of repairing it
- Manage kubectl versions with `mise` or `asdf`
- Autopilot (GKE) and Fargate (EKS) hide nodes entirely

QUICK SUMMARY

- `kubectl` — brew / winget / snap
- `kind · k3d · minikube` — local clusters
- `get-credentials` — managed clusters
- `skew` — kubectl within one minor of the API

kubeconfig, Contexts & Namespaces

WHERE KUBECTL POINTS

kubeconfig (`~/.kube/config`) holds **clusters** (API URL + CA), **users** (credentials) and **contexts** (cluster + user + default namespace). The `current-context` decides where every command goes. **Namespaces** split one cluster into named areas; names only need to be unique within one.

NOTES

- Without `-n`, commands use the context's namespace, else `default`
- Nodes, PVs and Namespaces are **cluster-scoped**
- kubeconfig holds credentials: `chmod 600`
- `KUBECONFIG` can list several files; kubectl merges them

CONTEXTS & NAMESPACES

```
kubectl config get-contexts            # * marks the current one
kubectl config current-context         # kind-dev
kubectl config use-context prod-east   # switch cluster + user
kubectl config set-context --current --namespace=shop
kubectl config view --minify           # active context only
kubectl config delete-context old-lab
export KUBECONFIG=~/.kube/config:~/.kube/eks.yaml   # merge
kubectl config view --flatten > ~/.kube/merged      # one file
kubectl --context prod-east -n shop get pods        # one-off
kubectl create namespace shop
kubectl delete namespace shop          # deletes EVERYTHING in it
```

CODE EXPLAINED

- → `use-context` — rewrites the file; affects every terminal
- → `--current --namespace` — default ns for this context
- → `KUBECONFIG` — `:` separator (`;` on Windows)
- → `--flatten` — inlines certs so the file stands alone
- → `--context` — safest choice in scripts
- → `delete namespace` — waits for every object inside to finalize
- → `view` — redacts secrets; add `--raw` to show them

KUBECONFIG KEYS

KEY	HOLDS
`clusters`	`server` URL + CA data
`users`	Token, cert or `exec` plugin
`contexts`	cluster + user + namespace
`current-context`	Active context name
`preferences`	Rarely used; ignore
`exec plugins`	aws, gke-gcloud-auth-plugin, kubelogin

BUILT-IN NAMESPACES

NAMESPACE	PURPOSE
`default`	Used when none given
`kube-system`	Cluster components
`kube-public`	Readable by everyone
`kube-node-lease`	Node heartbeats
`your-app`	One per app/team/env
`cluster-scoped`	Node, PV, Namespace, ClusterRole

KUBECTX / KUBENS

COMMAND	DOES
`kubectx`	List contexts
`kubectx prod`	Switch context
`kubectx -`	Previous context
`kubens shop`	Set namespace
`kubens -`	Previous namespace
`kubectx -d old`	Delete a context

⚠ COMMON MISTAKES

- Deleting in the wrong cluster — check `current-context` first
- `delete namespace` as cleanup — removes PVCs and all
- Treating namespaces as network isolation — they aren't (Sheet 14)
- Committing kubeconfig to Git — it often holds long-lived tokens

✓ TIPS & BEST PRACTICES

- Show context + namespace in your prompt (kube-ps1, starship)
- Name contexts by environment: `dev`, `prod-east`
- Pass `--context` explicitly in CI scripts
- One namespace per app or team per environment

QUICK SUMMARY

- `get-contexts / use-context` — list / switch
- `set-context --current --namespace`
- `-n` one ns · `-A` all namespaces
- `KUBECONFIG=a:b` — merge several files

Inspecting Resources & Output Formats

READING THE CLUSTER

`kubectl get` lists objects as a table; `-o` switches format, from extra columns to the full live YAML. `kubectl describe` gives a readable summary plus recent **Events**, where most errors show up. `explain` and `api-resources` document the API straight from your cluster.

NOTES

- `get pod web-0` and `get pod/web-0` both work
- List several kinds at once: `get deploy,svc,pods`
- `get all` skips ConfigMaps, Secrets, Ingress, PVCs
- Live YAML includes `status` and server-set fields

INSPECT

```
kubectl get pods -A                      # all namespaces
kubectl get pods -o wide                 # + IP and NODE
kubectl get deploy web -o yaml           # full live object
kubectl get pods -l app=web --show-labels
kubectl get pods --field-selector status.phase!=Running
kubectl get pods --sort-by=.metadata.creationTimestamp
kubectl get pods -w                      # watch changes
kubectl get pod web-0 -o jsonpath='{.status.podIP}'   # 10.244.1.7
kubectl get pods -o custom-columns=NAME:.metadata.name,NODE:.spec.nodeName
kubectl describe pod web-0               # details + Events
kubectl explain deploy.spec.strategy     # field docs
kubectl api-resources --namespaced=false
```

CODE EXPLAINED

- `--field-selector` — server-side filter on a few fields
- `-w` — stream updates until Ctrl-C
- `jsonpath` — use single quotes in the shell
- `explain` — types and docs for any field path
- `api-resources` — every kind and its short name

-O FORMATS

FLAG	GIVES
`-o wide`	Extra columns
`-o yaml|json`	Full object
`-o name`	`kind/name` lines
`-o jsonpath=`	Picked fields
`-o custom-columns=`	Your own table
`-o go-template=`	Go template

SHORT NAMES

SHORT	KIND
`po · deploy · rs`	Pod · Deployment · ReplicaSet
`sts · ds · cj`	StatefulSet · DaemonSet · CronJob
`svc · ing · cm`	Service · Ingress · ConfigMap
`pv · pvc · sa`	PV · PVC · ServiceAccount
`no · ns · hpa`	Node · Namespace · HPA
`sc · ep · secret`	StorageClass · Endpoints · Secret

HANDY FLAGS

FLAG	DOES
`-l k=v`	Label filter
`-L env`	Label as column
`--no-headers`	Drop header
`-v=6`	Show API calls
`{range}`	jsonpath loop
`--show-kind`	Prefix rows with kind

⚠ COMMON MISTAKES

- Trusting `get all` — config, storage and CRDs are missing
- Double-quoted jsonpath in bash — `$` and braces get mangled
- Committing `-o yaml` output — status and uid make noisy diffs
- Skipping the Events at the bottom of `describe` — they name the problem

✓ TIPS & BEST PRACTICES

- `get events --sort-by=.lastTimestamp` for a timeline
- `-o name | xargs` for bulk actions
- `alias k=kubectl` + shell completion
- krew plugin `kubectl neat` strips server fields from YAML

QUICK SUMMARY

- `get` — table; `-o` for more
- `describe` — summary + Events
- `explain` — the API documents itself
- `jsonpath / custom-columns` — script-friendly output

Sheet 05

Imperative vs Declarative

create · run · expose · apply -f · diff · --dry-run=client -o yaml · edit / patch · --server-side

TWO WAYS TO CHANGE A CLUSTER

Imperative commands (`run`, `create`, `scale`, `set`) say *do this now*: quick, but unrecorded. **Declarative** management keeps manifests in Git and runs `kubectl apply`, which creates or updates objects to match the files. Best of both: generate YAML with `--dry-run=client -o yaml`, then `apply` it.

NOTES

- `apply` is idempotent; a second run changes nothing
- `create -f` fails if the object exists
- `edit`, `patch`, `scale` drift from Git
- Server-side apply records a **field manager** per field
- `replace --force` deletes and recreates (immutable fields)

IMPERATIVE → DECLARATIVE

```
kubectl run tmp --image=busybox:1.36 --rm -it --restart=Never -- sh
kubectl create deployment web --image=nginx:1.27 --replicas=2
kubectl expose deployment web --port=80 --target-port=8080
kubectl set image deployment/web nginx=nginx:1.28
kubectl create deploy web --image=nginx:1.27 --dry-run=client -o yaml > web.yaml
kubectl apply -f web.yaml               # create or update
kubectl apply -f k8s/ -R                # whole folder
kubectl diff -f web.yaml                # preview changes
kubectl apply -f web.yaml --server-side --field-manager=ci
kubectl edit deployment web             # live object in $EDITOR
kubectl patch deployment web -p '{"spec":{"replicas":3}}'
kubectl delete -f web.yaml              # remove what it defines
```

CODE EXPLAINED

- → `--rm -it --restart=Never` — interactive, deleted on exit
- → `--dry-run=client -o yaml` — prints YAML, creates nothing
- → `diff` — exits 1 when there are changes; a CI gate
- → `--server-side` — API server merges and tracks field owners
- → `patch -p` — strategic merge by default
- → `edit` — saved on exit; invalid YAML reopens the editor
- → `delete -f` — deletes only objects named in the file

THREE APPROACHES

STYLE	USE FOR
`create deploy web …`	Experiments
`create -f x.yaml`	Rare; fails if exists
`apply -f dir/`	Everything real
`replace --force -f`	Immutable changes

PATCH --TYPE

TYPE	LISTS ARE…
`strategic`	Merged by key (default)
`merge`	Replaced whole
`json`	Edited by RFC 6902 ops
`--subresource=scale`	Patch only scale/status

DRY RUN

FLAG	MEANING
`=client`	Render locally
`=server`	Validate + admission
`--validate=strict`	Reject unknown fields
`diff -f`	Compare file to live

⚠ COMMON MISTAKES

- Hotfixing with `edit` — the next `apply` reverts it
- `create -f` in CI — reruns fail with `AlreadyExists`
- Expecting `apply` to delete objects removed from Git
- Hand-writing YAML from memory — generate it to avoid typos

✓ TIPS & BEST PRACTICES

- Run `kubectl diff` before applying to shared clusters
- `--dry-run=server` catches policy rejections early
- Copy any live hotfix back into Git right away
- Name the `--field-manager` per tool in CI

QUICK SUMMARY

- `create / run / expose` — imperative
- `apply -f` — declarative, idempotent
- `--dry-run=client -o yaml` — make YAML
- `diff` — preview; `edit / patch` — live drift

Sheet 06

Manifests, Labels & Selectors

apiVersion / kind / metadata / spec · --- · labels · selectors · annotations · app.kubernetes.io/*

ANATOMY OF A MANIFEST

Every object has `apiVersion`, `kind`, `metadata` and `spec` (what you want); Kubernetes adds `status` (what it has). **Labels** are key/value tags that **selectors** match: that's how a Service finds its Pods and a Deployment knows which Pods it owns. **Annotations** hold non-identifying data for tools.

NOTES

- Core kinds use `v1`; others `group/version`
- Label values ≤ 63 chars: letters, digits, `- _ .`
- Annotations can hold any string, up to 256 KB total
- Keys may carry a DNS prefix: `app.kubernetes.io/name`

A LABELED MANIFEST

```yaml
apiVersion: apps/v1              # group/version
kind: Deployment
metadata:
  name: web                      # unique per kind + namespace
  namespace: shop
  labels:                        # identifying, selectable
    app.kubernetes.io/name: web
    tier: frontend
  annotations:                   # free-form, for tools
    team: storefront@acme.io
spec:
  selector:                      # which pods it owns
    matchLabels: { app.kubernetes.io/name: web }
    matchExpressions:
      - { key: tier, operator: In, values: [frontend, edge] }
  template: { ... }              # pod template (Sheet 08)
---                              # next object, same file
```

CODE EXPLAINED

- → `apiVersion` — look it up in `api-resources`
- → `matchLabels` — every pair must match
- → `operator` — In, NotIn, Exists, DoesNotExist
- → `---` — separates documents in one file
- → `labels` on metadata — lets `get -l` find the Deployment
- → `{ ... }` — YAML flow style, same as indented maps

-L SELECTORS

EXPRESSION	MATCHES
`app=web`	Equals
`app!=web`	Not equal / missing
`'env in (a,b)'`	Any listed value
`tier`	Key exists
`'!tier'`	Key missing
`'env notin (dev)'`	None of the values

LABEL COMMANDS

KUBECTL …	DOES
`label po web env=prod`	Add
`… env=dev --overwrite`	Change
`label po web env-`	Remove
`annotate deploy web k=v`	Annotate
`get po -L env`	Show as column
`label po -l app=web x=1`	Bulk by selector

RECOMMENDED

APP.KUBERNETES.IO/	EXAMPLE
`name`	mysql
`instance`	mysql-orders
`version`	8.4.1
`part-of`	storefront
`managed-by`	Helm
`component`	database

⚠ COMMON MISTAKES

- Selector ≠ template labels — the API rejects the Deployment
- Editing a Deployment selector — it's immutable; recreate instead
- Two Deployments with overlapping selectors fight over Pods
- Putting URLs or long text in labels — values are limited to 63 chars

✓ TIPS & BEST PRACTICES

- Use the `app.kubernetes.io/*` labels; tools understand them
- Keep selectors small and stable
- Data goes in annotations, not labels
- `get pods -L app.kubernetes.io/version` shows versions at a glance

QUICK SUMMARY

- `apiVersion · kind · metadata · spec`
- `labels` — select; `annotations` — describe
- `-l` — filter; `label k-` — remove
- `matchLabels / matchExpressions` — how controllers find pods

Pods

THE SMALLEST UNIT

A **Pod** is one or more containers on one node sharing an IP (talk over `localhost`) and volumes. **Init containers** run to completion, in order, before the app. A **sidecar** is an init container with `restartPolicy: Always`: it starts first and runs beside the app. Pods are disposable; controllers create them from a template.

NOTES

- Recreated Pods get a new IP; use a Service
- `command` = ENTRYPOINT, `args` = CMD
- Native sidecars are stable since 1.33
- Most Pod spec fields are immutable; recreate instead of editing

POD SPEC

```yaml
apiVersion: v1
kind: Pod
metadata: { name: api, labels: { app: api } }
spec:
  restartPolicy: Always            # Always | OnFailure | Never
  initContainers:
    - name: wait-db                # must exit 0 first
      image: busybox:1.36
      command: ["sh", "-c", "until nc -z db 5432; do sleep 2; done"]
    - name: logs                   # sidecar: runs alongside
      image: fluent/fluent-bit:3.1
      restartPolicy: Always
  containers:
    - name: api
      image: ghcr.io/acme/api:1.4.2
      command: ["/app/server"]     # overrides ENTRYPOINT
      args: ["--port=8080"]        # overrides CMD
      ports: [{ containerPort: 8080, name: http }]
```

CODE EXPLAINED

- → `restartPolicy` — Deployments require `Always`
- → `initContainers` — setup, waits, migrations
- → `restartPolicy: Always` on init — native sidecar
- → `name: http` — reference by name in Services/probes
- → `until nc -z` — blocks the app until the DB port answers
- → `image` — pin a tag or `@sha256:` digest

POD PHASES

PHASE	MEANS
Pending	Not scheduled or still pulling
Running	On a node, a container is up
Succeeded	All exited 0, no restart
Failed	All stopped, one failed
Unknown	Node stopped reporting

STATUS REASONS

REASON	CAUSE
ImagePullBackOff	Bad tag or no auth
CrashLoopBackOff	Keeps exiting
OOMKilled	Over memory limit
Completed	Exited 0
ContainerCreating	Pulling, mounting volumes

IMAGEPULLPOLICY

VALUE	PULLS
IfNotPresent	If missing (pinned tags)
Always	Every start (`:latest`)
Never	Local only

⚠ COMMON MISTAKES

- Bare Pod for an app — not rescheduled when its node dies
- `:latest` tags — nodes may run different builds
- Setting `command` skips the image's entrypoint script
- Two containers binding one port — they share a network namespace

✓ TIPS & BEST PRACTICES

- One main process per container; helpers as sidecars
- `kubectl run api --image=… --dry-run=client -o yaml`
- Name ports and reference them by name
- `env` from ConfigMaps/Secrets: Sheet 15

QUICK SUMMARY

- `Pod` — containers sharing IP + volumes
- `initContainers` — run first, in order
- `command / args` — ENTRYPOINT / CMD
- `restartPolicy: Always` init container — native sidecar

Deployments & Rollouts

STATELESS APPS, UPDATED SAFELY

A **Deployment** owns **ReplicaSets**, which keep N identical Pods running. Changing the pod `template` creates a new ReplicaSet and **rolls** pods over gradually; the old one is kept at 0 replicas so you can **undo**. Changing only `replicas` scales without a rollout.

NOTES

- Pod names: `web-<template-hash>-<id>`
- Rollouts advance only as new pods turn **Ready**
- Stuck after `progressDeadlineSeconds` (600) = failed, not rolled back
- Need stable names or per-pod disks? Use a StatefulSet (Sheet 09)

DEPLOYMENT

```yaml
apiVersion: apps/v1
kind: Deployment
metadata: { name: web }
spec:
  replicas: 3
  revisionHistoryLimit: 5        # old ReplicaSets kept for undo
  selector:
    matchLabels: { app: web }    # = template labels; immutable
  strategy:
    type: RollingUpdate          # or Recreate
    rollingUpdate:
      maxSurge: 25%              # extra pods during update
      maxUnavailable: 0          # never below 3 ready
  template:
    metadata: { labels: { app: web } }
    spec:
      containers: [{ name: web, image: nginx:1.27 }]
```

CODE EXPLAINED

- → `replicas` — leave out if an HPA scales it
- → `revisionHistoryLimit` — default 10
- → `maxUnavailable: 0` — zero downtime, needs spare room
- → `template` — any change triggers a rollout
- → `selector` — must match template labels exactly
- → `maxSurge: 25%` — of 3 replicas rounds up to 1 extra pod

ROLLOUT COMMANDS (KUBECTL ROLLOUT …)

COMMAND	DOES
`status deploy/web`	Wait; non-zero exit on failure
`history deploy/web`	List revisions
`undo deploy/web`	Previous revision
`undo deploy/web --to-revision=2`	Specific revision
`restart deploy/web`	New pods, same spec
`pause / resume deploy/web`	Batch edits into one rollout

STRATEGIES

TYPE	BEHAVIOR
`RollingUpdate`	Gradual; versions overlap
`Recreate`	All down, then up

SCALE & UPDATE

KUBECTL …	DOES
`scale deploy/web --replicas=5`	Scale
`set image deploy/web web=nginx:1.28`	Roll out

⚠ COMMON MISTAKES

- Editing a ConfigMap and expecting a restart — `rollout restart`
- No readiness probe — rollout "succeeds" before pods work
- `maxUnavailable: 0` on a full cluster — surge pods stay Pending
- Treating `rollout undo` as a fix — Git still has the bad version

✓ TIPS & BEST PRACTICES

- Gate CI on `rollout status --timeout=5m`
- `Recreate` when two versions can't coexist
- After `undo`, fix the manifest in Git too
- Pair with a PodDisruptionBudget for node drains (Sheet 19)

QUICK SUMMARY

- `Deployment → ReplicaSet → Pods`
- `maxSurge / maxUnavailable` — speed vs capacity
- `rollout status / undo / restart`
- `template` change — rollout; `replicas` — scale only

StatefulSets & DaemonSets

IDENTITY AND PER-NODE WORKLOADS

A **StatefulSet** gives each pod a **stable name** (`db-0`, `db-1`), a stable DNS entry via a **headless Service**, and its **own PVC** that follows it across reschedules. Pods start in order and stop in reverse. A **DaemonSet** runs exactly **one pod per node** (or per matching node): log shippers, metrics agents, CNI and storage drivers.

NOTES

- StatefulSets don't make an app clustered; the app must handle its own replication
- PVCs from `volumeClaimTemplates` survive scale-down and deletion by default
- DaemonSets ignore `replicas`; new nodes get a pod automatically

STATEFULSET

```yaml
apiVersion: apps/v1
kind: StatefulSet
metadata: { name: db }
spec:
  serviceName: db                  # headless Service (clusterIP: None)
  replicas: 3                      # db-0, db-1, db-2, created in order
  podManagementPolicy: OrderedReady    # or Parallel
  updateStrategy: { rollingUpdate: { partition: 0 } }
  selector: { matchLabels: { app: db } }
  template: { ... }                # container mounts volume "data"
  volumeClaimTemplates:            # one PVC per pod: data-db-0 …
    - metadata: { name: data }
      spec:
        accessModes: [ReadWriteOnce]
        resources: { requests: { storage: 10Gi } }
```

DAEMONSET

```yaml
apiVersion: apps/v1
kind: DaemonSet
metadata: { name: node-exporter, namespace: monitoring }
spec:
  selector: { matchLabels: { app: node-exporter } }
  template: { ... }                # + nodeSelector / tolerations
```

CODE EXPLAINED

- → `serviceName` — gives pods DNS like `db-0.db.shop.svc.cluster.local`
- → `OrderedReady` — db-1 waits for db-0 to be Ready; `Parallel` doesn't
- → `partition: 2` — only pods with ordinal ≥ 2 update (canary)
- → `volumeClaimTemplates` — PVC named `<tmpl>-<pod>`
- → `maxUnavailable` — DaemonSet pods replaced per step
- → `nodeSelector` — limit a DaemonSet to some nodes

WHICH CONTROLLER?

FEATURE	DEPLOYMENT	STATEFULSET	DAEMONSET
Pod names	Random	`name-0…N`	Random, 1/node
Storage	Shared or none	PVC per pod	Usually hostPath
Scaling	`replicas`	`replicas`, ordered	Follows nodes
Use for	Web/API	DBs, Kafka, ZooKeeper	Agents, drivers

COMMANDS

KUBECTL …	DOES
`scale sts db --replicas=5`	Adds db-3, db-4
`rollout status sts/db`	Wait for update
`rollout restart ds/node-exporter`	Bounce all
`delete sts db --cascade=orphan`	Keep pods

⚠ COMMON MISTAKES

- Forgetting the headless Service — stable pod DNS names don't resolve
- Expecting PVCs to vanish on scale-down — they stay (and keep billing)
- Scaling a database StatefulSet and assuming data replicates by itself

✓ TIPS & BEST PRACTICES

- Use an operator (CloudNativePG, Strimzi) for serious databases
- Set `persistentVolumeClaimRetentionPolicy` to control PVC cleanup
- `Parallel` speeds up apps that don't need ordering

QUICK SUMMARY

- `StatefulSet` — stable names, ordered, PVC per pod
- `serviceName` — headless Service for pod DNS
- `partition` — staged rollouts
- `DaemonSet` — one pod per node

Jobs & CronJobs

RUN TO COMPLETION

A **Job** runs pods until a set number **succeed**, retrying failures up to `backoffLimit`. Use it for migrations, batch processing and one-off tasks. A **CronJob** creates a Job on a **cron schedule**, with rules for overlapping runs and how much history to keep.

NOTES

- Job pods need `restartPolicy: Never` or `OnFailure`
- Missed CronJob runs beyond `startingDeadlineSeconds` are skipped
- `timeZone` takes IANA names; otherwise the controller's zone is used

JOB

```yaml
apiVersion: batch/v1
kind: Job
metadata: { name: migrate }
spec:
  completions: 1                # successes needed
  backoffLimit: 4               # retries before Failed
  activeDeadlineSeconds: 600    # hard time limit for the Job
  ttlSecondsAfterFinished: 3600 # auto-delete 1h after finishing
  template:
    spec:
      restartPolicy: Never
      containers: [{ name: m, image: acme/api:1.4.2, command: ["./migrate"] }]
```

CRONJOB

```yaml
apiVersion: batch/v1
kind: CronJob
metadata: { name: nightly-report }
spec:
  schedule: "30 2 * * *"        # 02:30 every day
  timeZone: America/Chicago
  concurrencyPolicy: Forbid     # skip if last run still going
  jobTemplate: { spec: { template: { ... } } }
```

CODE EXPLAINED

- → `completions: 5, parallelism: 2` — 5 successes, 2 at a time
- → `backoffLimit` — default 6
- → `activeDeadlineSeconds` — beats `backoffLimit`; kills running pods
- → `ttlSecondsAfterFinished` — keeps the namespace tidy
- → `Never` — new pod per retry; `OnFailure` restarts in place
- → `jobTemplate` — a full Job spec

CRON FIELDS

FIELD	RANGE
`minute`	0–59
`hour`	0–23
`day of month`	1–31
`month`	1–12
`day of week`	0–6 (Sun = 0)

CONCURRENCYPOLICY

VALUE	IF STILL RUNNING
`Allow`	Start another (default)
`Forbid`	Skip this run
`Replace`	Kill old, start new
`suspend: true`	Pause the schedule

COMMANDS

KUBECTL …	DOES
`create job now --from=cronjob/x`	Run now
`logs job/migrate`	Logs of a job pod
`wait --for=condition=complete job/m`	Block in CI
`get jobs -w`	Watch progress

⚠ COMMON MISTAKES

- `restartPolicy: Always` in a Job — rejected by the API
- Non-idempotent job code — retries run it twice (double charges, dup emails)

✓ TIPS & BEST PRACTICES

- Test a CronJob instantly with `create job --from=cronjob/…`
- Use `Forbid` for jobs that must not overlap
- `completionMode: Indexed` gives each pod a `JOB_COMPLETION_INDEX`

QUICK SUMMARY

- `Job` — run until N successes
- `backoffLimit / activeDeadlineSeconds` — limits
- `CronJob` — Job on a schedule
- `concurrencyPolicy` — overlap rules

Health Probes & Pod Lifecycle

livenessProbe · readinessProbe · startupProbe · httpGet / tcpSocket / exec / grpc · preStop · terminationGracePeriodSeconds

TELLING KUBERNETES WHAT HEALTHY MEANS

The kubelet runs **probes** against each container. A failing **readiness** probe removes the pod from Service endpoints (no traffic) without restarting it. A failing **liveness** probe restarts the container. A **startup** probe holds off the other two until a slow app has booted. On shutdown, pods get `SIGTERM`, a grace period, then `SIGKILL`.

NOTES

- No probes: the pod is Ready as soon as the process starts
- Liveness should check the process only, never databases or other services
- Readiness can (carefully) check dependencies the pod truly needs
- Probe traffic comes from the kubelet on the node, not from the Service

PROBES & SHUTDOWN

```yaml
spec:
  terminationGracePeriodSeconds: 30  # SIGTERM → wait → SIGKILL
  containers:
    - name: api
      image: ghcr.io/acme/api:1.4.2
      ports: [{ name: http, containerPort: 8080 }]
      startupProbe:                  # protects slow starters
        httpGet: { path: /healthz, port: http }
        periodSeconds: 5
        failureThreshold: 30         # up to 150s to boot
      livenessProbe:                 # fail → restart container
        httpGet: { path: /healthz, port: http }
        periodSeconds: 10
        timeoutSeconds: 2
      readinessProbe:                # fail → no Service traffic
        httpGet: { path: /ready, port: http }
        periodSeconds: 5
      lifecycle:
        preStop: { exec: { command: ["sleep", "5"] } }   # let LBs drain
```

CODE EXPLAINED

- → `startupProbe` — liveness/readiness start only after it passes
- → `failureThreshold × periodSeconds` — time before giving up
- → `port: http` — named container port
- → `timeoutSeconds` — default is just 1s
- → `preStop` — runs before SIGTERM; counts against the grace period
- → `sleep 5` — endpoints update before the app stops accepting

PROBE HANDLERS

HANDLER	PASSES WHEN
`httpGet`	Status 200–399
`tcpSocket`	Port accepts a connection
`exec`	Command exits 0
`grpc`	gRPC health check SERVING

FIELDS & DEFAULTS

FIELD	DEFAULT
`initialDelaySeconds`	0
`periodSeconds`	10
`timeoutSeconds`	1
`failureThreshold`	3
`successThreshold`	1

SHUTDOWN ORDER

STEP	WHAT HAPPENS
1	Pod marked Terminating, leaves endpoints
2	`preStop` hook runs
3	`SIGTERM` to PID 1
4	`SIGKILL` after grace period

⚠ COMMON MISTAKES

- Liveness probe that checks the database — a DB blip restarts every pod
- Same endpoint and timing for liveness and readiness — restarts when you only wanted to shed load
- Liveness with no startup probe on a slow app — restart loop before it ever boots

✓ TIPS & BEST PRACTICES

- Liveness: cheap "is the process alive"; readiness: "can I serve now"
- Raise `timeoutSeconds` to 2–5s for real-world endpoints
- Use exec-form ENTRYPOINT so your app is PID 1 and gets SIGTERM

QUICK SUMMARY

- `readiness` — gates traffic
- `liveness` — restarts the container
- `startup` — delays the others for slow boots
- `preStop + grace period` — clean shutdown

Services & DNS

A STABLE ADDRESS FOR CHANGING PODS

Pods come and go with new IPs; a **Service** gives a set of pods (chosen by **label selector**) one stable virtual IP and DNS name and load-balances across the **Ready** ones. kube-proxy (or the CNI) programs the routing on every node. **CoreDNS** answers `<svc>.<ns>.svc.cluster.local`.

NOTES

- Selector matches nothing → Service exists but has no endpoints
- Pods in the same namespace can just use the short name: `http://web`
- EndpointSlices list the backing pod IPs; the old Endpoints API is deprecated

SERVICE

```yaml
apiVersion: v1
kind: Service
metadata: { name: web, namespace: shop }
spec:
  type: ClusterIP                # default; see types table
  selector: { app: web }         # pods that get traffic
  ports:
    - name: http
      port: 80                   # what clients connect to
      targetPort: http           # container port (number or name)
```

CODE EXPLAINED

- → `selector` — must match pod labels, not Deployment labels
- → `port` vs `targetPort` — Service side vs container side
- → `nodePort` — set only for NodePort/LoadBalancer (30000–32767)
- → `endpointslices` — empty means selector or readiness problem

CHECK IT

```bash
kubectl get svc,endpointslices -n shop -l app=web
kubectl port-forward svc/web 8080:80 -n shop     # http://localhost:8080
```

SERVICE TYPES

TYPE	REACHABLE FROM
`ClusterIP`	Inside the cluster only
`NodePort`	Every node's IP on a high port
`LoadBalancer`	Cloud LB → NodePort → pods
`ExternalName`	DNS CNAME to an outside host
`clusterIP: None`	Headless: DNS returns pod IPs

DNS NAMES

NAME	RESOLVES TO
`web`	Same-namespace Service
`web.shop`	Service in namespace shop
`web.shop.svc.cluster.local`	Fully qualified
`db-0.db.shop.svc…`	One StatefulSet pod

USEFUL FIELDS

FIELD	EFFECT
`externalTrafficPolicy: Local`	Keep client IP
`sessionAffinity: ClientIP`	Sticky by IP
`internalTrafficPolicy: Local`	Node-local only
`loadBalancerSourceRanges`	IP allowlist

⚠ COMMON MISTAKES

- Selector copied from the Deployment's metadata labels instead of pod template labels
- `targetPort` not matching the container's listening port — connection refused
- One LoadBalancer Service per app — costly; share an Ingress/Gateway

✓ TIPS & BEST PRACTICES

- Name ports and use `targetPort: http` so port changes live in one place
- `kubectl get endpointslices` first when a Service "doesn't work"
- `port-forward` for local testing; no Service type change needed

QUICK SUMMARY

- `Service` — stable IP + DNS over Ready pods
- `ClusterIP / NodePort / LoadBalancer` — widening reach
- `port → targetPort` — client side → container side
- `svc.ns.svc.cluster.local` — CoreDNS name

Ingress & Gateway API

HTTP ROUTING INTO THE CLUSTER

Ingress routes HTTP(S) by host and path to Services, through an **ingress controller** you install. It's stable but frozen. **Gateway API** is its successor: roles are split into `GatewayClass` (provider), `Gateway` (listeners, ports, TLS; owned by ops) and `HTTPRoute` (owned by app teams), with header matching, traffic weights and more built in.

NOTES

- Both need a controller: Envoy Gateway, Istio, Cilium, Traefik, cloud LBs…
- Community `ingress-nginx` is retired; plan a migration
- Gateway API CRDs may need installing

INGRESS

```yaml
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata: { name: shop }
spec:
  ingressClassName: traefik          # which controller handles it
  tls: [{ hosts: [shop.acme.io], secretName: shop-tls }]
  rules:
    - host: shop.acme.io
      http:
        paths:
          - path: /api
            pathType: Prefix
            backend: { service: { name: api, port: { number: 80 } } }
```

GATEWAY API: HTTPROUTE

```yaml
apiVersion: gateway.networking.k8s.io/v1
kind: HTTPRoute
metadata: { name: shop }
spec:
  parentRefs: [{ name: public-gw }]  # attach to a Gateway
  rules:
    - matches: [{ path: { type: PathPrefix, value: /api } }]
      backendRefs:
        - { name: api, port: 80, weight: 90 }
        - { name: api-v2, port: 80, weight: 10 }   # 10% canary
```

CODE EXPLAINED

- → `ingressClassName` — picks the controller; list with `get ingressclass`
- → `tls.secretName` — a `kubernetes.io/tls` Secret
- → `pathType: Prefix` — `/api` matches `/api/x`, not `/apix`
- → `parentRefs` — the Gateway must allow routes from this namespace
- → `weight` — split traffic without a service mesh

GATEWAY API OBJECTS

KIND	OWNED BY · HOLDS
`GatewayClass`	Provider · which controller
`Gateway`	Platform team · listeners, ports, TLS
`HTTPRoute`	App team · hosts, paths, backends
`ReferenceGrant`	Allows cross-namespace refs

INGRESS PATHTYPE

VALUE	MATCHES
`Exact`	Only that path
`Prefix`	Path segments
`ImplementationSpecific`	Controller-defined

⚠ COMMON MISTAKES

- No controller installed — Ingress objects are accepted and do nothing
- Missing `ingressClassName` with no default class — ignored
- Controller-specific annotations don't port between controllers

✓ TIPS & BEST PRACTICES

- New setups: start with Gateway API
- `kubectl describe httproute shop` → status shows Accepted / ResolvedRefs
- Automate TLS with cert-manager

QUICK SUMMARY

- `Ingress` — host/path → Service, frozen API
- `Gateway` — listeners, owned by ops
- `HTTPRoute` — routing rules, owned by apps
- controller required for both

Network Policies

A FIREWALL FOR PODS

By default every pod can reach every other pod in the cluster. A **NetworkPolicy** selects pods and lists the traffic **allowed** in (`ingress`) or out (`egress`). Once any policy selects a pod for a direction, everything not explicitly allowed in that direction is denied. Policies only add allows, so their order doesn't matter.

NOTES

- Enforced by the **CNI plugin**; without support, policies are silently ignored
- Selects by labels, namespaces and CIDRs, at L3/L4 (no HTTP paths)
- Replies to allowed connections are allowed automatically
- Deny egress → remember to allow DNS (port 53 to kube-system)

DEFAULT DENY + ALLOW

```yaml
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata: { name: default-deny, namespace: shop }
spec:
  podSelector: {}                  # every pod in the namespace
  policyTypes: [Ingress, Egress]   # nothing in or out by default
---
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata: { name: api-from-web, namespace: shop }
spec:
  podSelector: { matchLabels: { app: api } }    # applies to api pods
  ingress:
    - from:
        - podSelector: { matchLabels: { app: web } }       # this ns
        - namespaceSelector: { matchLabels: { team: ops } } # OR these
      ports: [{ protocol: TCP, port: 8080 }]
```

CODE EXPLAINED

- → `podSelector: {}` — empty selector = all pods
- → `policyTypes` — directions isolated; defaults from the rules present
- → `from:` list items — OR'ed together
- → `podSelector` alone — same namespace as the policy
- → `ports` — applies to every `from` above it

AND VS OR

SHAPE	MEANING
`-podSel / -nsSel`	Two items: OR
`-nsSel + podSel`	One item: AND
`-ipBlock: {cidr}`	IP ranges (+ except)

COMMON POLICIES

POLICY	RULE
`Deny all ingress`	Select all, no rules
`Allow DNS`	Egress 53 to kube-system
`Allow ingress ctrl`	Select its namespace
`Same ns only`	`from: [podSelector: {}]`

CNI SUPPORT

CNI	POLICIES
`Calico`	✔
`Cilium`	✔ (+L7 own CRD)
`Antrea`	✔
`Flannel alone`	✖

⚠ COMMON MISTAKES

- Applying policies on a CNI that doesn't enforce them — false sense of security
- Default-deny egress without a DNS rule — every lookup times out
- One extra `-` turns AND into OR and opens access
- Using `namespaceSelector` on a label the namespace lacks

✓ TIPS & BEST PRACTICES

- Select namespaces by the built-in `kubernetes.io/metadata.name` label
- Start with default-deny per namespace, then add allows
- Test with `kubectl exec … -- nc -zv api 8080`
- Hubble (Cilium) or Calico flow logs show dropped traffic

QUICK SUMMARY

- `NetworkPolicy` — allow-list per pod selector
- `podSelector: {}` + no rules — default deny
- list items OR, keys in one item AND
- CNI must support it

ConfigMaps & Secrets

CONFIGURATION OUTSIDE THE IMAGE

A **ConfigMap** holds non-secret key/value config; a **Secret** holds sensitive values and is handled a bit more carefully (RBAC, tmpfs mounts, optional encryption at rest). Pods consume both as **environment variables** or as **files** in a mounted volume. Same image, different config per environment.

NOTES

- Secret values are **base64-encoded, not encrypted**
- Env vars are read once at start; mounted files update (≈1 min), except `subPath`
- Size limit: 1 MiB per ConfigMap or Secret
- `immutable: true` blocks edits and lightens API server load

CREATE

```
kubectl create cm app-cfg --from-literal=LOG_LEVEL=info --from-file=app.yaml
kubectl create cm env-cfg --from-env-file=.env
kubectl create secret generic db --from-literal=pw='s3cr3t!'
kubectl create secret tls shop-tls --cert=tls.crt --key=tls.key
kubectl get secret db -o jsonpath='{.data.pw}' | base64 -d     # s3cr3t!
```

CONSUME

```
spec:
  containers:
    - name: api
      envFrom: [{ configMapRef: { name: env-cfg } }]   # every key → env
      env:
        - name: DB_PASSWORD
          valueFrom: { secretKeyRef: { name: db, key: pw } }
      volumeMounts: [{ name: cfg, mountPath: /etc/app, readOnly: true }]
  volumes:
    - name: cfg
      configMap: { name: app-cfg }     # each key becomes a file
```

CODE EXPLAINED

- → `--from-file` — key = filename, value = contents
- → `--from-env-file` — one key per `KEY=value` line
- → `secret tls` — keys `tls.crt` and `tls.key`
- → `envFrom` — bulk import; `prefix:` avoids clashes
- → `secretKeyRef` — one key into one env var
- → `/etc/app/app.yaml` — file from the ConfigMap key

CONSUMING

METHOD	LIVE UPDATE?
`env valueFrom`	✖ restart
`envFrom`	✖ restart
`volume mount`	✔ ~1 min
`volume + subPath`	✖

SECRET TYPES

TYPE:	FOR
`Opaque`	Anything (default)
`kubernetes.io/tls`	Cert + key
`kubernetes.io/dockerconfigjson`	Registry auth
`kubernetes.io/basic-auth`	User + password

KEEPING SECRETS SAFE

TOOL	DOES
`EncryptionConfiguration`	Encrypt in etcd
`RBAC on secrets`	Limit get/list
`External Secrets`	Sync from Vault/AWS/GCP
`Sealed Secrets / SOPS`	Encrypted in Git

⚠ COMMON MISTAKES

- Committing Secret YAML to Git — base64 is readable by anyone
- Expecting env vars to change after editing a ConfigMap — restart the pods
- `subPath` mounts never update
- Giving `list secrets` broadly — it returns every value in the namespace

✓ TIPS & BEST PRACTICES

- Add a config hash annotation to the pod template so changes roll out
- Use `stringData:` in YAML to write plain text; the API encodes it
- Registry auth: `create secret docker-registry` + `imagePullSecrets`
- Prefer an external secret manager for production

QUICK SUMMARY

- `ConfigMap` — plain config
- `Secret` — sensitive, base64 only
- `env / envFrom` — read at start
- `volume` — files, updated live

Volumes & Persistent Storage

DATA THAT OUTLIVES CONTAINERS

A **volume** is a directory mounted into containers. `emptyDir` lives as long as the pod. For data that must survive the pod, a **PersistentVolumeClaim** (PVC) requests storage; a **StorageClass** tells a **CSI driver** to provision a matching **PersistentVolume** (PV) on demand, such as an EBS, Persistent Disk or Azure Disk volume.

NOTES

- PVCs are namespaced; PVs and StorageClasses are cluster-scoped
- One class can be the default (annotation `is-default-class`)
- Block disks are usually `ReadWriteOnce`: one node at a time
- Shared RWX needs a file system: EFS, Filestore, Azure Files, NFS

PVC + POD

```yaml
apiVersion: v1
kind: PersistentVolumeClaim
metadata: { name: pg-data }
spec:
  accessModes: [ReadWriteOnce]        # one node at a time
  storageClassName: fast-ssd          # omit → default class
  resources: { requests: { storage: 20Gi } }
---
# inside a Pod / pod template spec:
volumes:
  - { name: data, persistentVolumeClaim: { claimName: pg-data } }
  - { name: scratch, emptyDir: { sizeLimit: 1Gi } }   # dies with pod
containers:
  - name: db
    image: postgres:17
    volumeMounts:
      - { name: data, mountPath: /var/lib/postgresql/data }
      - { name: scratch, mountPath: /tmp }
```

CODE EXPLAINED

- → `accessModes` — must be supported by the driver
- → `storageClassName: ""` — bind only to a pre-made PV
- → `requests.storage` — grow later if the class allows expansion
- → `claimName` — PVC must be in the pod's namespace
- → `emptyDir.medium: Memory` — tmpfs, counts toward memory

VOLUME TYPES

TYPE	LIFETIME / USE
`emptyDir`	Pod lifetime; scratch, caches
`persistentVolumeClaim`	Independent; databases
`configMap / secret`	Config files (Sheet 15)
`hostPath`	Node's disk; agents only

ACCESS MODES

MODE	MEANING
`RWO`	Read-write, one node
`RWOP`	Read-write, one pod
`ROX`	Read-only, many nodes
`RWX`	Read-write, many nodes

STORAGECLASS FIELDS

FIELD	VALUES
`provisioner`	`ebs.csi.aws.com`…
`reclaimPolicy`	Delete | Retain
`volumeBindingMode`	WaitForFirstConsumer
`allowVolumeExpansion`	true

⚠ COMMON MISTAKES

- PVC stuck `Pending` — no default class, or the class can't satisfy the access mode
- `reclaimPolicy: Delete` on precious data — deleting the PVC deletes the disk
- Two pods on different nodes sharing an RWO volume — second one won't start

✓ TIPS & BEST PRACTICES

- Use `WaitForFirstConsumer` so disks are created in the pod's zone
- Resize: edit `spec.resources.requests.storage` on the PVC
- Back up volumes with VolumeSnapshots or Velero

QUICK SUMMARY

- `emptyDir` — scratch, pod lifetime
- `PVC` — request; `PV` — actual disk
- `StorageClass` — dynamic provisioning via CSI
- `RWO / RWX / RWOP` — who can mount

Requests, Limits & Quotas

SIZING CONTAINERS

Requests are what the scheduler reserves: a pod only lands on a node with that much unrequested CPU and memory. **Limits** are hard caps enforced at runtime: going over the CPU limit gets the container **throttled**; going over the memory limit gets it **OOMKilled**. **LimitRange** sets per-container defaults in a namespace; **ResourceQuota** caps the namespace's totals.

NOTES

- Requests drive scheduling and autoscaling; set them on every container
- Many teams set a memory limit but no CPU limit, to avoid throttling
- With a quota on CPU/memory, pods without requests are rejected

RESOURCES & QUOTA

```yaml
containers:
  - name: api
    image: ghcr.io/acme/api:1.4.2
    resources:
      requests: { cpu: 250m, memory: 256Mi }   # reserved for scheduling
      limits:   { memory: 512Mi }              # hard cap (no CPU limit)
---
apiVersion: v1
kind: ResourceQuota                  # totals for the whole namespace
metadata: { name: shop-quota, namespace: shop }
spec:
  hard:
    requests.cpu: "8"
    requests.memory: 16Gi
    limits.memory: 32Gi
    pods: "50"
    persistentvolumeclaims: "10"
```

CODE EXPLAINED

- → `250m` — 250 millicores = a quarter of one CPU
- → `256Mi` — mebibytes (2^{20}); `M` is 10^6
- → Limit only → request defaults to the limit
- → `hard` — new pods that would exceed it are rejected
- → `kubectl describe quota -n shop` — used vs hard

QOS CLASSES

CLASS	WHEN	EVICTED
`Guaranteed`	requests = limits, all containers	Last
`Burstable`	Some requests/limits set	Middle
`BestEffort`	Nothing set	First

GOING OVER

RESOURCE	RESULT
`CPU limit`	Throttled (slow, not killed)
`Memory limit`	OOMKilled, exit 137
`Node memory`	Eviction by QoS + usage
`Ephemeral disk`	Evicted

LIMITRANGE FIELDS

FIELD	SETS
`defaultRequest`	Request if missing
`default`	Limit if missing
`min / max`	Allowed range
`maxLimitRequestRatio`	Limit ÷ request cap

⚠ COMMON MISTAKES

- No requests — scheduler overpacks nodes and the HPA can't compute utilization
- Memory limit below real peak usage — random OOMKilled restarts
- Tight CPU limits on latency-sensitive apps — throttling spikes p99

✓ TIPS & BEST PRACTICES

- Measure with `kubectl top pods` before picking numbers
- Set memory request = limit for predictable memory
- Add LimitRange defaults so forgotten specs still get sane values

QUICK SUMMARY

- `requests` — reserved, used to schedule
- `limits` — CPU throttles, memory kills
- `LimitRange / ResourceQuota` — defaults / totals

Scheduling & Node Placement

CONTROLLING WHERE PODS LAND

The scheduler filters nodes that fit a pod's requests, then scores them. You steer it with **nodeSelector** and **node affinity** (pod wants certain nodes), **pod affinity / anti-affinity** (near or away from other pods), **topology spread** (even out across zones or nodes) and **taints**, which repel pods unless they carry a matching **toleration**.

NOTES

- `required…` rules are hard; `preferred…` rules are weighted hints
- `…IgnoredDuringExecution`: running pods aren't evicted if labels change
- A toleration allows a tainted node; it doesn't attract pods there

PLACEMENT RULES

```
spec:
  nodeSelector: { kubernetes.io/arch: arm64 }   # simple must-match
  affinity:
    podAntiAffinity:                    # keep replicas apart
      preferredDuringSchedulingIgnoredDuringExecution:
        - weight: 100
          podAffinityTerm:
            labelSelector: { matchLabels: { app: web } }
            topologyKey: kubernetes.io/hostname
  topologySpreadConstraints:            # even across zones
    - maxSkew: 1
      topologyKey: topology.kubernetes.io/zone
      whenUnsatisfiable: ScheduleAnyway
      labelSelector: { matchLabels: { app: web } }
  tolerations:                          # may use GPU nodes
    - { key: gpu, operator: Exists, effect: NoSchedule }
```

CODE EXPLAINED

- → `nodeSelector` — node must have every label
- → `topologyKey: hostname` — "apart" means different nodes
- → `maxSkew: 1` — zone pod counts differ by at most 1
- → `ScheduleAnyway` — soft; `DoNotSchedule` — hard
- → `operator: Exists` — any value of the key

NODE COMMANDS (KUBECTL …)

COMMAND	DOES
`cordon worker-1`	No new pods
`drain worker-1 --ignore-daemonsets --delete-emptydir-data`	Evict for maintenance
`uncordon worker-1`	Schedulable again
`taint nodes worker-1 gpu=true:NoSchedule`	Add taint
`taint nodes worker-1 gpu-`	Remove taint
`label nodes worker-1 disktype=ssd`	Add label

TAINT EFFECTS

EFFECT	PODS WITHOUT TOLERATION
`NoSchedule`	Not scheduled
`PreferNoSchedule`	Avoided if possible
`NoExecute`	Evicted too

WELL-KNOWN LABELS

LABEL	EXAMPLE
`kubernetes.io/hostname`	worker-1
`topology.kubernetes.io/zone`	us-east-1a
`node.kubernetes.io/instance-type`	m7g.large

⚠ COMMON MISTAKES

- Hard anti-affinity with more replicas than nodes — extra pods stay Pending
- Expecting a toleration to pin pods to tainted nodes — add affinity too
- `drain` without a PDB — every replica may be evicted at once

✓ TIPS & BEST PRACTICES

- Prefer topology spread over pod anti-affinity for spreading
- Dedicated nodes = taint + toleration + node affinity together
- `describe pod` Events show which filter failed

QUICK SUMMARY

- `nodeSelector / nodeAffinity` — pick nodes
- `taints + tolerations` — keep pods off
- `cordon / drain / uncordon` — maintenance

Autoscaling & Disruption Budgets

SCALING PODS AND NODES

The **HorizontalPodAutoscaler** (HPA) changes a workload's `replicas` to hold a target metric, usually CPU utilization *relative to requests*. The **VerticalPodAutoscaler** adjusts the requests themselves. When pods don't fit, **Cluster Autoscaler** or **Karpenter** adds nodes. A **PodDisruptionBudget** limits how many pods voluntary disruptions (drains, upgrades, scale-down) may take at once.

NOTES

- Resource metrics need **metrics-server** installed
- Remove `replicas` from Git manifests the HPA manages
- PDBs don't protect against node crashes (involuntary)

HPA + PDB

```yaml
apiVersion: autoscaling/v2
kind: HorizontalPodAutoscaler
metadata: { name: web }
spec:
  scaleTargetRef: { apiVersion: apps/v1, kind: Deployment, name: web }
  minReplicas: 2
  maxReplicas: 20
  metrics:
    - type: Resource
      resource:
        name: cpu
        target: { type: Utilization, averageUtilization: 70 }
---
apiVersion: policy/v1
kind: PodDisruptionBudget
metadata: { name: web }
spec:
  minAvailable: 2                    # or maxUnavailable: 1
  selector: { matchLabels: { app: web } }
```

CODE EXPLAINED

- → `scaleTargetRef` — Deployment, StatefulSet, or any `/scale`
- → `averageUtilization: 70` — 70% of the CPU *request*
- → `behavior:` — tune scale-up/down speed (default 5 min down window)
- → `minAvailable` — drains wait while fewer would remain
- → `selector` — same pods as the Deployment
- → `maxReplicas` — a cost ceiling; set it deliberately

AUTOSCALERS

TOOL	SCALES
HPA	Pod count from metrics
VPA	Pod requests (add-on)
KEDA	Pods from events/queues, to zero
Cluster Autoscaler	Node groups for Pending pods
Karpenter	Right-sized nodes on demand

COMMANDS (KUBECTL …)

COMMAND	DOES
`autoscale deploy web --max=10 --cpu-percent=70`	Create HPA
`get hpa -w`	Watch targets vs current
`describe hpa web`	Scaling events
`top pods`	Live CPU/memory
`get pdb`	Allowed disruptions
`get hpa web -o yaml`	Current metrics, conditions

⚠ COMMON MISTAKES

- HPA on pods with no CPU requests — target shows `<unknown>`
- HPA and VPA both acting on CPU — they fight; use one per resource
- PDB `minAvailable` = replicas — drains block forever
- Expecting instant scale-up — new nodes can take minutes to join

✓ TIPS & BEST PRACTICES

- Set `minReplicas` ≥ 2 for anything user-facing
- Scale on custom metrics (RPS, queue depth) via adapters or KEDA
- Run VPA in `Off` mode to get request recommendations
- Pair HPA with Cluster Autoscaler or Karpenter so new pods have room

QUICK SUMMARY

- `HPA` — replicas from metrics
- `Cluster Autoscaler` / `Karpenter` — nodes
- `PDB` — cap voluntary disruptions
- `VPA` — right-size requests

RBAC & ServiceAccounts

WHO CAN DO WHAT

RBAC answers *can subject X do verb Y on resource Z*. A **Role** (namespaced) or **ClusterRole** lists allowed verbs on resources; a **RoleBinding** or **ClusterRoleBinding** grants it to users, groups or **ServiceAccounts**. ServiceAccounts are identities for pods and automation; humans usually come from your cloud IAM or OIDC.

NOTES

- RBAC is additive: no deny rules, only allows
- Every namespace has a `default` ServiceAccount with no extra rights
- Pod tokens are short-lived and auto-rotated (projected volume)

SERVICEACCOUNT, ROLE, BINDING

```yaml
apiVersion: v1
kind: ServiceAccount
metadata: { name: ci-deployer, namespace: shop }
---
apiVersion: rbac.authorization.k8s.io/v1
kind: Role                          # ClusterRole = cluster-wide
metadata: { name: deployer, namespace: shop }
rules:
  - apiGroups: ["apps"]             # "" = core group (pods, services)
    resources: ["deployments"]
    verbs: ["get", "list", "watch", "patch", "update"]
---
apiVersion: rbac.authorization.k8s.io/v1
kind: RoleBinding
metadata: { name: ci-deployer, namespace: shop }
subjects: [{ kind: ServiceAccount, name: ci-deployer, namespace: shop }]
roleRef: { kind: Role, name: deployer, apiGroup: rbac.authorization.k8s.io }
```

CODE EXPLAINED

- → `apiGroups` — from `kubectl api-resources` APIVERSION
- → `resources` — plural names; subresources like `pods/log`
- → `verbs` — see table; `*` means all
- → `roleRef` — immutable; delete and recreate to change
- → Pod uses it via `serviceAccountName: ci-deployer`

SCOPE COMBINATIONS

ROLE + BINDING	GRANTS
`Role + RoleBinding`	One namespace
`ClusterRole + RoleBinding`	Reused rules, one ns
`ClusterRole + CRB`	Whole cluster

COMMANDS (KUBECTL …)

COMMAND	DOES
`auth can-i delete pods -n shop`	yes / no
`auth can-i --list -n shop`	Everything you can do
`… --as=system:serviceaccount:shop:ci-deployer`	Check as the SA
`create token ci-deployer --duration=1h`	Short-lived token
`create rolebinding v --clusterrole=view --user=amy -n shop`	Quick grant

BUILT-IN CLUSTERROLES

ROLE	ALLOWS
`cluster-admin`	Everything
`admin`	All in a ns, incl. RBAC
`edit`	Read/write, no RBAC
`view`	Read-only, no Secrets

⚠ COMMON MISTAKES

- Binding `cluster-admin` to CI — one leaked token owns the cluster
- Granting `list secrets` — returns every secret's contents
- Pods auto-mounting tokens they never use — set `automountServiceAccountToken: false`

✓ TIPS & BEST PRACTICES

- Test with `auth can-i … --as=` before handing out access
- Start from `view` / `edit` and add narrow Roles
- Use cloud workload identity (IRSA, GKE WI) instead of static keys

QUICK SUMMARY

- `Role / ClusterRole` — what is allowed
- `RoleBinding / ClusterRoleBinding` — to whom
- `auth can-i` — verify

Pod Security

securityContext · runAsNonRoot · readOnlyRootFilesystem · drop ALL · allowPrivilegeEscalation · seccomp · Pod Security Admission

LOCKING DOWN CONTAINERS

A container's **securityContext** controls the Linux user, capabilities, privilege escalation, seccomp profile and file-system writes. **Pod Security Admission** (built in) checks pods against the **Pod Security Standards**: `privileged`, `baseline` or `restricted`, chosen per namespace with labels. It replaced PodSecurityPolicy, removed in 1.25.

NOTES

- Pod-level `securityContext` sets defaults; container-level wins
- `runAsNonRoot` fails pods whose image runs as UID 0
- Need custom rules? Use Kyverno or OPA Gatekeeper

RESTRICTED NAMESPACE + HARDENED POD

```yaml
apiVersion: v1
kind: Namespace
metadata:
  name: shop
  labels:
    pod-security.kubernetes.io/enforce: restricted   # reject violators
    pod-security.kubernetes.io/warn: restricted      # warn on apply
---
spec:                                  # pod spec
  securityContext:
    runAsNonRoot: true
    runAsUser: 10001
    fsGroup: 10001                     # group owning mounted volumes
    seccompProfile: { type: RuntimeDefault }
  containers:
    - name: api
      securityContext:
        allowPrivilegeEscalation: false
        readOnlyRootFilesystem: true
        capabilities: { drop: [ALL] }
```

CODE EXPLAINED

- → `enforce` — rejected at the API; `warn` — shown to kubectl
- → `runAsUser: 10001` — avoid UIDs that exist on the host
- → `RuntimeDefault` — the runtime's default syscall filter
- → `readOnlyRootFilesystem` — mount an `emptyDir` for `/tmp`
- → `drop: [ALL]` — add back only e.g. `NET_BIND_SERVICE`

POD SECURITY STANDARDS

LEVEL	ALLOWS
`privileged`	Anything (system add-ons)
`baseline`	Blocks known escalations
`restricted`	Hardened best practice

NAMESPACE LABEL MODES

POD-SECURITY…/	EFFECT
`enforce`	Reject pod
`audit`	Audit log entry
`warn`	kubectl warning
`enforce-version`	Pin rules, e.g. v1.3x

RESTRICTED BLOCKS

FIELD	RULE
`privileged / host*`	Not allowed
`hostPath volumes`	Not allowed
`runAsNonRoot`	Must be true
`capabilities`	Drop ALL

⚠ COMMON MISTAKES

- Enforcing `restricted` on `kube-system` — breaks CNI and CSI pods
- `readOnlyRootFilesystem` without a writable `/tmp` — app crashes
- Images built to run as root — `runAsNonRoot` blocks them
- Assuming PSA blocks everything bad — it only checks pod fields

✓ TIPS & BEST PRACTICES

- Roll out with `warn` + `audit` first, then `enforce`
- `kubectl label --dry-run=server ns shop pod-security…=restricted` lists violators
- Set `USER 10001` in your Dockerfile
- `kubectl debug` profiles help keep debug pods compliant

QUICK SUMMARY

- `securityContext` — user, caps, seccomp
- `privileged / baseline / restricted`
- `pod-security.kubernetes.io/enforce`

Debugging & Troubleshooting

A DEBUGGING ROUTINE

Work outside in: `get` shows **what** is wrong (status, restarts), `describe` and **events** show **why** the cluster couldn't do it, `logs` show why the app failed, and `exec`/`debug` let you look inside. Most problems are a typo in an image name, a missing ConfigMap key, too little memory, or a selector that matches nothing.

NOTES

- Events expire after about an hour; check them early
- `kubectl debug` adds a tool container to a running pod
- Distroless images have no shell; use `debug`, not `exec`
- `kubectl get pod x -o yaml` → `status.containerStatuses` has the exact reason

DEBUG TOOLKIT

```
kubectl get pods -o wide                          # STATUS, RESTARTS, NODE
kubectl describe pod api-7d9f-x2k                 # Events: the why
kubectl get events -n shop --sort-by=.lastTimestamp
kubectl logs api-7d9f-x2k -c api --tail=100 -f    # follow one container
kubectl logs api-7d9f-x2k --previous              # before the last crash
kubectl logs deploy/api --all-containers --since=15m
kubectl exec -it api-7d9f-x2k -- sh               # shell inside
kubectl debug -it api-7d9f-x2k --image=busybox:1.36 --target=api
kubectl debug node/worker-1 -it --image=ubuntu    # host fs at /host
kubectl port-forward pod/api-7d9f-x2k 8080:8080   # reach it locally
kubectl top pods --containers                     # needs metrics-server
kubectl run net --rm -it --image=nicolaka/netshoot -- bash
```

CODE EXPLAINED

- → `--previous` — the crashed container's last output
- → `deploy/api` — logs from one pod of the Deployment
- → `--target=api` — share the app container's process namespace
- → `debug node/` — privileged pod on that node
- → `netshoot` — dig, curl, tcpdump, nc in one image
- → `--since=15m` — or `--since-time`, `--timestamps`
- → `port-forward` — bypasses Services and Ingress to isolate the app

SYMPTOM → CAUSE → CHECK

STATUS	LIKELY CAUSE	CHECK
`Pending`	No room, PVC unbound, taints	`describe pod` Events
`ImagePullBackOff`	Wrong tag, private registry	Image name, `imagePullSecrets`
`CrashLoopBackOff`	App exits on start	`logs --previous`
`OOMKilled`	Over memory limit	Raise limit, check leaks
`CreateContainerConfigError`	Missing ConfigMap/Secret key	`describe pod`
`Running, no traffic`	Not Ready, bad selector	`get endpointslices`

EXIT CODES

CODE	MEANING
`0`	Clean exit
`1`	App error
`126 / 127`	Not executable / not found
`137`	SIGKILL (OOM, grace over)
`143`	SIGTERM
`139`	Segfault (SIGSEGV)

⚠ COMMON MISTAKES

- Reading current logs of a crash-looping pod — use `--previous`
- Restarting pods before reading Events — the evidence disappears
- `exec` into distroless images — no shell; use `debug`
- Blaming Kubernetes for app config errors — read the app's own logs first

✓ TIPS & BEST PRACTICES

- Install `stern` to tail logs across many pods
- `k9s` gives a live terminal UI over all of this
- Check endpoints before blaming the network
- `kubectl get pods --field-selector status.phase=Failed -A` finds casualties

QUICK SUMMARY

- `get → describe → logs → exec/debug`
- `logs --previous` — why it crashed
- `debug` — tools without rebuilding the image
- `events` — cluster's side; `logs` — app's side

Helm & Kustomize

PACKAGING AND VARIANTS

Helm is a package manager: a **chart** is a set of templated manifests plus `values.yaml`; installing it creates a versioned **release** you can upgrade and roll back. **Kustomize** is template-free and built into kubectl: plain YAML **bases** plus per-environment **overlays** that patch them. Many teams use Helm for third-party apps and Kustomize for their own.

NOTES

- Charts come from HTTP repos or OCI registries (`oci://`)
- Release state is stored as Secrets in the release namespace
- `kubectl kustomize` renders without applying
- No server component since Helm 3; Helm 4 keeps the same workflow

HELM

```
helm repo add prom https://prometheus-community.github.io/helm-charts
helm show values prom/kube-prometheus-stack > values.yaml
helm upgrade --install mon prom/kube-prometheus-stack \
  -n monitoring --create-namespace -f values.yaml --set grafana.enabled=true
helm list -A ; helm history mon -n monitoring
helm rollback mon 1 -n monitoring
helm template mon prom/kube-prometheus-stack -f values.yaml   # render only
```

KUSTOMIZE: OVERLAYS/PROD/KUSTOMIZATION.YAML

```
resources: [../../base]            # base: deployment.yaml, service.yaml
namespace: shop-prod
images: [{ name: ghcr.io/acme/api, newTag: "1.4.2" }]
replicas: [{ name: api, count: 5 }]
patches: [{ path: memory-patch.yaml }]
configMapGenerator: [{ name: api-cfg, literals: [LOG_LEVEL=warn] }]
# kubectl apply -k overlays/prod
```

CODE EXPLAINED

- → `upgrade --install` — idempotent install-or-upgrade
- → `-f` then `--set` — later values win
- → `template` — render YAML locally; diff or review it
- → `images` / `replicas` — common edits without patches
- → `configMapGenerator` — adds a hash suffix, so pods roll on change
- → `helm show values` — start your values file from the defaults
- → `resources: [../../base]` — overlays reference a shared base

HELM VS KUSTOMIZE

	HELM	KUSTOMIZE
Style	Go templates + values	Patches on plain YAML
Install	Separate CLI	`kubectl -k`
Rollback	`helm rollback`	Via Git
Best for	Third-party apps	Your own apps

CHART LAYOUT

PATH	HOLDS
`Chart.yaml`	Name, version
`values.yaml`	Defaults
`templates/`	Manifests
`charts/`	Dependencies
`values.schema.json`	Optional validation

WHERE NEXT

TOPIC	TOOLS
GitOps	Argo CD, Flux
Operators	CRDs + controllers
Policy	Kyverno, Gatekeeper
Mesh	Istio, Linkerd
Packaging	Helmfile, Timoni

⚠ COMMON MISTAKES

- `helm install` in CI — fails on rerun; use `upgrade --install`
- Long `--set` chains — unreviewable; keep values files in Git
- Mixing `helm` and `kubectl edit` on the same release
- Editing rendered chart output by hand — next upgrade overwrites it

✓ TIPS & BEST PRACTICES

- Pin chart versions with `--version`
- `helm diff` plugin previews upgrades
- Kustomize can inflate Helm charts via `helmCharts:`
- `--rollback-on-failure` (Helm 4) / `--atomic` (Helm 3) auto-reverts

QUICK SUMMARY

- `helm upgrade --install` — releases
- `kustomization.yaml` — base + overlays
- `kubectl apply -k` — apply an overlay
- `helm rollback` — previous release revision

Sheet 24

Quick Reference — kubectl Commands

contexts & namespaces · get / describe · apply / delete · rollouts & scaling · logs / exec · nodes · auth can-i

CONTEXTS & NAMESPACES

COMMAND	DOES	#
`config get-contexts`	List contexts	03
`config use-context prod`	Switch cluster	03
`config set-context --current --namespace=shop`	Default ns	03
`create ns shop`	New namespace	03
`get pods -n shop · -A`	One ns · all	03
`config view --minify`	Active config	03

GET & INSPECT

COMMAND	DOES	#
`get pods -o wide`	IP + node	04
`get deploy web -o yaml`	Live object	04
`get pods -l app=web -w`	Filter + watch	04
`describe pod web-0`	Details + Events	04
`explain deploy.spec`	Field docs	04
`api-resources`	All kinds	04

CREATE, APPLY & DELETE

COMMAND	DOES	#
`apply -f file.yaml · -f dir/ -R`	Create or update	05
`diff -f file.yaml`	Preview changes	05
`create deploy web --image=… --dry-run=client -o yaml`	Generate YAML	05
`delete -f file.yaml`	Remove objects	05
`apply -k overlays/prod`	Kustomize	23
`edit deploy web`	Live edit (drift)	05

ROLLOUTS & SCALING

COMMAND	DOES	#
`set image deploy/web web=nginx:1.28`	New version	08
`rollout status deploy/web`	Wait for it	08
`rollout undo deploy/web`	Roll back	08
`rollout restart deploy/web`	Bounce pods	08
`scale deploy/web --replicas=5`	Scale	08
`rollout history deploy/web`	Revisions	08

LOGS, EXEC & DEBUG

COMMAND	DOES	#
`logs pod -f · --previous`	Stream · last crash	22
`exec -it pod -- sh`	Shell inside	22
`debug -it pod --image=busybox --target=app`	Ephemeral tools	22
`port-forward svc/web 8080:80`	Local access	12
`get events --sort-by=.lastTimestamp`	Timeline	22
`top pods --containers`	Per-container usage	22

NODES, SCALING & ACCESS

COMMAND	DOES	#
`cordon · drain --ignore-daemonsets · uncordon`	Maintenance	18
`taint nodes n1 gpu=true:NoSchedule`	Repel pods	18
`top pods · top nodes`	Usage	17
`autoscale deploy web --max=10 --cpu-percent=70`	HPA	19
`auth can-i create deploy --as=…`	Check RBAC	20
`get nodes -o wide`	Node IPs, versions	01

CONFIG, SECRETS & STORAGE

COMMAND	DOES	#
`create cm app --from-literal=K=v --from-file=f`	ConfigMap	15
`create secret generic db --from-literal=pw=…`	Secret	15
`get secret db -o jsonpath='{.data.pw}' | base64 -d`	Read a value	15
`get pv,pvc -A`	Storage status	16
`create secret tls t --cert=c --key=k`	TLS Secret	15

HELM

COMMAND	DOES	#
`helm repo add name URL`	Add chart repo	23
`helm upgrade --install rel chart -f values.yaml`	Install/upgrade	23
`helm list -A · history rel`	Releases	23
`helm rollback rel 1`	Roll back	23
`helm template rel chart`	Render only	23

⚠ COMMON MISTAKES

- Running against the wrong context — check before you delete
- `delete ns` deletes everything inside
- `kubectl edit` changes are lost on the next apply

✓ TIPS & BEST PRACTICES

- `alias k=kubectl` + completion
- `-o name | xargs` for bulk work
- `kubectl explain` beats searching docs for field names

QUICK SUMMARY

- All commands are `kubectl …`
- `#` = sheet with details
- Sheet 25 covers YAML and status codes

Quick Reference — Manifests & Troubleshooting

apiVersion / kind · short names · manifest skeletons · probe & resource snippets · status → cause → fix

APIVERSION / KIND

KIND	APIVERSION	SHORT
Pod · Service · ConfigMap · Secret	v1	po · svc · cm
PersistentVolumeClaim · ServiceAccount	v1	pvc · sa
Deployment · StatefulSet · DaemonSet	apps/v1	deploy · sts · ds
Job · CronJob	batch/v1	— · cj
Ingress · NetworkPolicy	networking.k8s.io/v1	ing · netpol
HorizontalPodAutoscaler	autoscaling/v2	hpa
PodDisruptionBudget	policy/v1	pdb
Role · RoleBinding (Cluster…)	rbac.authorization.k8s.io/v1	—
HTTPRoute · Gateway	gateway.networking.k8s.io/v1	—

SKELETONS & SNIPPETS

NEED	YAML
Any object	`apiVersion · kind · metadata: {name, labels} · spec`
Deployment	`spec: {replicas, selector: {matchLabels}, template: {metadata: {labels}, spec: {containers}}}`
Service	`spec: {selector: {app: web}, ports: [{port: 80, targetPort: http}]}`
Resources	`resources: {requests: {cpu: 100m, memory: 128Mi}, limits: {memory: 256Mi}}`
Readiness	`readinessProbe: {httpGet: {path: /ready, port: http}, periodSeconds: 5}`
Env from Secret	`valueFrom: {secretKeyRef: {name: db, key: pw}}`
Hardening	`securityContext: {runAsNonRoot: true, allowPrivilegeEscalation: false}`

STATUS → LIKELY CAUSE → FIX

STATUS	LIKELY CAUSE	FIX
Pending	No capacity, taint, unbound PVC	`describe pod`; add nodes, toleration, StorageClass
ContainerCreating (stuck)	Volume mount or CNI problem	Events; check PVC and CNI pods
ImagePullBackOff	Bad name/tag, no registry auth	Fix image; add `imagePullSecrets`
CrashLoopBackOff	App exits at start	`logs --previous`; check command, config
OOMKilled	Memory limit too low	Raise limit; profile memory
Evicted	Node out of memory or disk	Set requests; clean disk; `delete pod`
CreateContainerConfigError	Missing ConfigMap/Secret or key	Create it; check key names
Service, no endpoints	Selector mismatch or pods not Ready	`get endpointslices`; fix labels/probe

DEFAULTS WORTH KNOWING

SETTING	DEFAULT
terminationGracePeriodSeconds	30
revisionHistoryLimit	10
progressDeadlineSeconds	600
Job backoffLimit	6
probe period / timeout / failures	10s / 1s / 3
NodePort range	30000–32767

SELECTORS & LABELS

SYNTAX	MEANS
`-l app=web,tier!=db`	AND of conditions
`-l 'env in (prod,stage)'`	Set match
`label po x env=prod --overwrite`	Set label
`label po x env-`	Remove label
`-L env`	Label as column
`--field-selector spec.nodeName=n1`	Field filter

⚠ COMMON MISTAKES

- Selector ≠ pod labels → no endpoints
- `:latest` → unpredictable pulls

✓ TIPS & BEST PRACTICES

- `kubectl explain <kind>.spec` for any field
- Generate skeletons with `--dry-run=client -o yaml`

QUICK SUMMARY

- Events explain most failures
- Details: Sheets 07, 12, 17, 22