

# Principles of Programming Languages

## Lecture 4: Abstract syntax and semantics of expressions

Andrei Arusoaie<sup>1</sup>

<sup>1</sup>Department of Computer Science

October 19, 2020

# Outline

Alphabet. Lexical analysis. Parsing.

Parse Trees

Abstract syntax trees

# Sentences in a programming language

*Which phrases are correct?*

- ▶ `int x; x = x + 2`
- ▶ `int x; x = x + 2;`
- ▶ `if (a > 0) then x = 1; else x = -1;`
- ▶ `(a > 0) ? x = 1 : x = -1;`

# Sentences in a programming language

*Which phrases are correct?*

- ▶ `int x; x = x + 2`
- ▶ `int x; x = x + 2;`
- ▶ `if (a > 0) then x = 1; else x = -1;`
- ▶ `(a > 0) ? x = 1 : x = -1;`

# Sentences in a programming language

*Which phrases are correct?*

- ▶ `int x; x = x + 2`
- ▶ `int x; x = x + 2;`
- ▶ `if (a > 0) then x = 1; else x = -1;`
- ▶ `(a > 0) ? x = 1 : x = -1;`

# Overview: alphabet, lexical analysis, syntax.

- ▶ ***Alphabet*** : set of (allowed) symbols
- ▶ *Lexical analysis*: identify the sequence of symbols constituting the *words* (or *tokens*)
  - ▶ *Lexical rules*
- ▶ *Syntax*: describes which sequences of words constitute “legal” phrases
  - ▶ *Grammars*

# Overview: alphabet, lexical analysis, syntax.

- ▶ *Alphabet* : set of (allowed) symbols
- ▶ *Lexical analysis*: identify the sequence of symbols constituting the *words* (or *tokens*)
  - ▶ *Lexical rules*
- ▶ *Syntax*: describes which sequences of words constitute “legal” phrases
  - ▶ *Grammars*

# Overview: alphabet, lexical analysis, syntax.

- ▶ *Alphabet* : set of (allowed) symbols
- ▶ *Lexical analysis*: identify the sequence of symbols constituting the *words* (or *tokens*)
  - ▶ *Lexical rules*
- ▶ *Syntax*: describes which sequences of words constitute “legal” phrases
  - ▶ *Grammars*



# Alphabet

The Alphabet of C from the Standard has 96 symbols:

- ▶ a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, z
- ▶ A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
- ▶ 0, 1, 2, 3, 4, 5, 6, 7, 8, 9
- ▶ ! " # % & ' ( ) \* + , - . /
- ▶ : ; < = > ? [ \ ] ^ \_ { | } ~
- ▶ *Separators*: space, horizontal and vertical tab, form feed, newline

# Lexical analysis

*Problem:* Given a sequence of characters, find the pieces with assigned meaning from that sequence: words or *tokens*

*Example:*

- ▶ Input: `if (a > 0) then x = 1; else x = -1;`
- ▶ Output: `if, (, a, >, 0,), then, x, =, 1,;, else, x, =, -1,;`
- ▶ *Tokens = pieces with assigned/identified meaning*

*Lexical analyzer (lexer) = a program that implements an algorithm that solves the problem above*

# Lexical analysis

*Problem:* Given a sequence of characters, find the pieces with assigned meaning from that sequence: words or *tokens*

*Example:*

- ▶ Input: `if (a > 0) then x = 1; else x = -1;`
- ▶ Output: `if, (, a, >, 0,) , then, x, =, 1,, ;, else, x, =, -1,, ;`
- ▶ *Tokens = pieces with assigned/identified meaning*

*Lexical analyzer (lexer) = a program that implements an algorithm that solves the problem above*

# Lexical analysis

*Problem:* Given a sequence of characters, find the pieces with assigned meaning from that sequence: words or *tokens*

*Example:*

- ▶ Input: `if (a > 0) then x = 1; else x = -1;`
- ▶ Output: `if, (, a, >, 0,) , then, x, =, 1,;, else, x, =, -1,;`
- ▶ *Tokens = pieces with assigned/identified meaning*

*Lexical analyzer (lexer)* = a program that implements an algorithm that solves the problem above

# Lexical analysis

*Problem:* Given a sequence of characters, find the pieces with assigned meaning from that sequence: words or *tokens*

*Example:*

- ▶ Input: `if (a > 0) then x = 1; else x = -1;`
- ▶ Output: `if, (, a, >, 0,) , then, x, =, 1, ;, else, x, =, -1, ;`
- ▶ *Tokens = pieces with assigned/identified meaning*

*Lexical analyzer* (lexer) = a program that implements an algorithm that solves the problem above

# Example I - Lexical rules

- ▶ **Integers: 6, 0, -2, +3**
- ▶ The *alphabet*  $A = \{+, -\} \cup \mathbb{N}$
- ▶ *Lexical rules*: used to describe atomic language constructions: numbers, identifiers, ...
- ▶ *Lexical rules* are expressed using *regular grammars* (see LFAC course)
- ▶ **Regular expressions**, a.k.a **regex**
  - ▶ Regex for integers: `[\+-]? \d+`

# Example I - Lexical rules

- ▶ Integers: 6, 0, -2, +3
- ▶ The *alphabet*  $A = \{+, -\} \cup \mathbb{N}$
- ▶ *Lexical rules*: used to describe atomic language constructions: numbers, identifiers, ...
- ▶ *Lexical rules* are expressed using *regular grammars* (see LFAC course)
- ▶ **Regular expressions**, a.k.a **regex**
  - ▶ Regex for integers: `[\+-]? \d+`

# Example I - Lexical rules

- ▶ Integers: 6, 0, -2, +3
- ▶ The *alphabet*  $A = \{+, -\} \cup \mathbb{N}$
- ▶ *Lexical rules*: used to describe atomic language constructions: numbers, identifiers, ...
- ▶ *Lexical rules* are expressed using *regular grammars* (see LFAC course)
- ▶ **Regular expressions**, a.k.a **regex**
  - ▶ Regex for integers: `[\+-]? \d+`



# Example I - Lexical rules

- ▶ Integers: 6, 0, -2, +3
- ▶ The *alphabet*  $A = \{+, -\} \cup \mathbb{N}$
- ▶ *Lexical rules*: used to describe atomic language constructions: numbers, identifiers, ...
- ▶ *Lexical rules* are expressed using *regular grammars* (see LFAC course)
- ▶ Regular expressions, a.k.a *regex*
  - ▶ Regex for integers: `[\+-]?\d+`

# Example I - Lexical rules

- ▶ Integers: 6, 0, -2, +3
- ▶ The *alphabet*  $A = \{+, -\} \cup \mathbb{N}$
- ▶ *Lexical rules*: used to describe atomic language constructions: numbers, identifiers, ...
- ▶ *Lexical rules* are expressed using *regular grammars* (see LFAC course)
- ▶ **Regular expressions**, a.k.a **regex**
  - ▶ Regex for integers: `[\+-]?\d+`

# Parsing

Problem: how to combine the tokens in (valid) sentences?

- ▶ Answer: we define the *grammar* of the language
- ▶ Noam Chomsky: *generative grammar*
- ▶ Grammars allow us to transform a program given as an sequence of characters into a *syntax tree*
- ▶ Parser = program which attempts to do this transformation
- ▶ Only valid programs can be parsed!

# Parsing

Problem: how to combine the tokens in (valid) sentences?

- ▶ Answer: we define the *grammar* of the language
- ▶ Noam Chomsky: *generative grammar*
- ▶ Grammars allow us to transform a program given as an sequence of characters into a *syntax tree*
- ▶ Parser = program which attempts to do this transformation
- ▶ Only valid programs can be parsed!

# Parsing

Problem: how to combine the tokens in (valid) sentences?

- ▶ Answer: we define the *grammar* of the language
- ▶ Noam Chomsky: *generative grammar*
- ▶ Grammars allow us to transform a program given as an sequence of characters into a *syntax tree*
- ▶ Parser = program which attempts to do this transformation
- ▶ Only valid programs can be parsed!

# Parsing

Problem: how to combine the tokens in (valid) sentences?

- ▶ Answer: we define the *grammar* of the language
- ▶ Noam Chomsky: *generative grammar*
- ▶ Grammars allow us to transform a program given as an sequence of characters into a *syntax tree*
- ▶ Parser = program which attempts to do this transformation
- ▶ Only valid programs can be parsed!

# Parsing

Problem: how to combine the tokens in (valid) sentences?

- ▶ Answer: we define the *grammar* of the language
- ▶ Noam Chomsky: *generative grammar*
- ▶ Grammars allow us to transform a program given as an sequence of characters into a *syntax tree*
- ▶ Parser = program which attempts to do this transformation
- ▶ Only valid programs can be parsed!

## Example II - Grammar

- ▶ Language of palindromic strings using symbols  $a$  and  $b$
- ▶ The *alphabet*  $A = \{a, b\}$
- ▶ Can we describe palindromes using regex?



## Example II - Grammar

- ▶ Language of palindromic strings using symbols  $a$  and  $b$
- ▶ The *alphabet*  $A = \{a, b\}$
- ▶ Can we describe palindromes using regex?

## Example II - Grammar

- ▶ Language of palindromic strings using symbols  $a$  and  $b$
- ▶ The *alphabet*  $A = \{a, b\}$
- ▶ Can we describe palindromes using regex?

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
    - ▶ Base:  $a$  and  $b$  are palindromic strings
    - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$



## Example II - Grammar

- ▶ How do we “formally” describe palindromic strings?
  - ▶ Note that there is a simple recursion of a palindromic string
  - ▶ Base:  $a$  and  $b$  are palindromic strings
  - ▶ Recursion: if  $s$  is a palindromic string then so are  $asa$  and  $bsb$
- ▶ Examples: “aba”, “aabaa”, “bab”, etc
- ▶ *Problem?* yes: “aa”, “abba”.
- ▶ Fix: add the empty string to base, hereafter denoted by  $\epsilon$

# Example II - Grammar

- ▶ **Base case:**

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ **Recursion:**

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ **Context-free grammar** (you study this in your compiler course!)

# Example II - Grammar

- ▶ **Base case:**

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ **Recursion:**

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ **Context-free grammar** (you study this in your compiler course!)

# Example II - Grammar

- ▶ **Base case:**

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ **Recursion:**

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ **Context-free grammar** (you study this in your compiler course!)

# Example II - Grammar

- ▶ Base case:

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ Recursion:

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ Context-free grammar (you study this in your compiler course!)

# Example II - Grammar

- ▶ Base case:

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ Recursion:

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ Context-free grammar (you study this in your compiler course!)

# Example II - Grammar

- ▶ Base case:

- ▶  $P \rightarrow \epsilon$

- ▶  $P \rightarrow a$

- ▶  $P \rightarrow b$

- ▶ Recursion:

- ▶  $P \rightarrow aPa$

- ▶  $P \rightarrow bPb$

- ▶ Context-free grammar (you study this in your compiler course!)

# Example II - Grammar

- ▶ Base case:
  - ▶  $P \rightarrow \epsilon$
  - ▶  $P \rightarrow a$
  - ▶  $P \rightarrow b$
- ▶ Recursion:
  - ▶  $P \rightarrow aPa$
  - ▶  $P \rightarrow bPb$
- ▶ Context-free grammar (you study this in your compiler course!)



# Example II - Grammar

- ▶ Base case:
  - ▶  $P \rightarrow \epsilon$
  - ▶  $P \rightarrow a$
  - ▶  $P \rightarrow b$
- ▶ Recursion:
  - ▶  $P \rightarrow aPa$
  - ▶  $P \rightarrow bPb$
- ▶ **Context-free grammar** (you study this in your compiler course!)

# Backus-Naur Form (BNF)

- ▶ *Meta-language* introduced by Backus and Naur to define ALGOL60
- ▶ Vocabulary:
  - ▶ **Terminals** : simple language strings; typically: *tokens* or symbols
  - ▶ **Non-terminals**: complex language constructions

# Backus-Naur Form (BNF)

- ▶ *Meta-language* introduced by Backus and Naur to define ALGOL60
- ▶ Vocabulary:
  - ▶ **Terminals** : simple language strings; typically: *tokens* or symbols
  - ▶ **Non-terminals**: complex language constructions

# Backus-Naur Form (BNF)

- ▶ *Meta-language* introduced by Backus and Naur to define ALGOL60
- ▶ Vocabulary:
  - ▶ **Terminals** : simple language strings; typically: *tokens* or symbols
  - ▶ **Non-terminals**: complex language constructions

# BNF - example I

## ► Palindromic strings:

$P ::= \epsilon \quad (1)$

$\quad | a \quad (2)$

$\quad | b \quad (3)$

$\quad | a P a \quad (4)$

$\quad | b P b \quad (5)$

# Derivations

- ▶ How to obtain a *derivation*: read the production as rewrite rules and find a finite sequence of rewrite steps
- ▶ Example: derivation for  $abba$   
 $P \rightarrow^4 aPa \rightarrow^5 abPba \rightarrow^1 abba$

# Parse trees

► Derivation:  $P \rightarrow^4 aPa \rightarrow^5 abPba \rightarrow^1 abba$


► Parse tree:

► contains nodes labeled with terminals, nonterminals, and  $\epsilon$



# Parse trees

- ▶ Derivation:  $P \rightarrow^4 aPa \rightarrow^5 abPba \rightarrow^1 abba$
- ▶ Parse tree:
  - ▶ contains nodes labeled with terminals, nonterminals, and  $\epsilon$







# BNF - example II

► Simple expressions language:

```
Int   ::=  [\+-]?[0-9]+
Exp   ::=  Int
        |  Exp "+" Exp
        |  Exp "*" Exp
        |  Exp "/" Exp
        |  "(" Exp ")"
```



# Multiple parses available

Possible parse trees for  $2 + 4 + 6$ :



# Multiple parses available

Possible parse trees for  $2 + 4 + 6$ :



# Ambiguities

Possible parse trees for  $2 + 4 + 6$ :





## ► Solutions?

- Use the parentheses defined in the syntax: ' ( ' and ' ) '
- Encode some kind of associativity: **left** or **right**

# Ambiguities

Possible parse trees for  $2 + 4 + 6$ :




## ► Solutions?

- Use the parentheses defined in the syntax: ' ( ' and ' ) '
- Encode some kind of associativity: **left** or **right**

# Ambiguities

Possible parse trees for  $2 + 4 + 6$ :




## ► Solutions?

- Use the parentheses defined in the syntax: ‘(’ and ‘)’
- Encode some kind of associativity: **left** or **right**

# Priorities



Possible parse trees for  $4 / 2 + 6$ :



► What parse tree is correct in this case?

# Priorities

Possible parse trees for  $4 / 2 + 6$ :





► What parse tree is correct in this case?





# Priorities

Possible parse trees for  $4 / 2 + 6$ :



- What parse tree is correct in this case?

# Priorities



Solutions:

- ▶ establish priorities between various constructs
- ▶ filtering vs. modify the grammar

# Abstract Syntax Trees

- ▶ Grammars define *concrete syntax*
- ▶ Arithmetic expressions:
  - ▶  $1 + 2$  – infix notation
  - ▶  $(+ 1 2)$  – prefix notation
  - ▶  $(1 2 +)$  – postfix notation
- ▶ Each variant has a particular grammar production:
  - ▶  $E \rightarrow E + E$  // infix
  - ▶  $E \rightarrow + E E$  // prefix
  - ▶  $E \rightarrow E E +$  // postfix

# Abstract Syntax Trees

- ▶ Grammars define *concrete syntax*
- ▶ Arithmetic expressions:
  - ▶  $1 + 2$  – infix notation
  - ▶  $(+ 1 2)$  – prefix notation
  - ▶  $(1 2 +)$  – postfix notation
- ▶ Each variant has a particular grammar production:
  - ▶  $E \rightarrow E + E$  // infix
  - ▶  $E \rightarrow + E E$  // prefix
  - ▶  $E \rightarrow E E +$  // postfix

# Abstract Syntax Trees

- ▶ Grammars define *concrete syntax*
- ▶ Arithmetic expressions:
  - ▶  $1 + 2$  – infix notation
  - ▶  $(+ 1 2)$  – prefix notation
  - ▶  $(1 2 +)$  – postfix notation
- ▶ Each variant has a particular grammar production:
  - ▶  $E \rightarrow E + E$  // infix
  - ▶  $E \rightarrow + E E$  // prefix
  - ▶  $E \rightarrow E E +$  // postfix

# Abstract syntax trees

## ► Variants:

- $1 + 2$  – infix notation
- $(+ 1 2)$  – prefix notation
- $(1 2 +)$  – postfix notation

## ► Parse trees:

infix



prefix




postfix




# Abstract syntax trees

- ▶ Variants:
  - ▶  $1 + 2$  – infix notation
  - ▶  $(+ 1 2)$  – prefix notation
  - ▶  $(1 2 +)$  – postfix notation
- ▶ Parse trees:


infix



prefix




postfix




# Abstract syntax trees

## ► Parse trees:


infix



prefix



postfix



## ► *abstract* representation of all the above trees:







# Abstract syntax trees

## ► Parse trees:


infix




prefix



postfix



## ► *abstract* representation of all the above trees:




# Abstract Syntax Trees

- ▶ Grammars define *concrete syntax*
- ▶ An AST is a *tree* representation of the structure of a program where the syntactical details are ignored
- ▶ For instance, addition has the same abstract tree even if in some languages the syntax is different (e.g., C vs. Haskell)
- ▶ Compilers use ASTs as the main data structure

# Example: arithmetic expressions

AST for  $2 + (4 + 6)$ :



```
Inductive Exp :=  
| number : nat -> Exp  
| plus : Exp -> Exp -> Exp.
```

```
Coercion number : nat >-> Exp.
```

```
Check (plus 2 (plus 4 6)).  
plus 2 (plus 4 6)  
      : Exp
```

# Abstract Syntax in Coq

The BNF grammar of arithmetic expressions:

►  $E ::= \text{nat} \mid E + E \mid E * E$

The corresponding Coq encoding is:

```
Inductive Exp : Type :=  
  | num : nat -> Exp  
  | plus : Exp -> Exp -> Exp  
  | mul : Exp -> Exp -> Exp.
```

# Abstract Syntax in Coq

The BNF grammar of arithmetic expressions:

►  $E ::= \text{nat} \mid E + E \mid E * E$

The corresponding Coq encoding is:

```
Inductive Exp : Type :=  
  | num : nat -> Exp  
  | plus : Exp -> Exp -> Exp  
  | mul : Exp -> Exp -> Exp.
```

# Coercion

Complicated:

```
Check (plus (num1) (num2)) .
```

Less complicated:

```
Check (plus 1 2) .
```

# Coercion

Complicated:

```
Check (plus (num1) (num2)) .
```

Less complicated:

```
Check (plus 1 2) .
```

# Notations

```
Inductive AExp :=  
| avar : string -> AExp  
| anum : nat -> AExp  
| aplus : AExp -> AExp -> AExp  
| amul : AExp -> AExp -> AExp.
```

```
Coercion anum : nat >-> AExp.
```

```
Coercion avar : string >-> AExp.
```

```
Notation "A +' B" := (aplus A B)  
      (at level 50, left associativity).
```

```
Notation "A *' B" := (amul A B)  
      (at level 40, left associativity).
```



## Demo

- ▶ Arithmetic expressions
- ▶ Boolean expressions
- ▶ Statements

# Bibliography

- ▶ Sections 2.1-2.4 from *Programming Languages: Principles and Paradigms*, Maurizio Gabbrielli, Simone Martini; 2010.  
Link: [http://websrv.dthu.edu.vn/attachments/newsevents/content2415/Programming\\_Languages\\_-\\_Principles\\_and\\_Paradigms\\_thereds1106.pdf](http://websrv.dthu.edu.vn/attachments/newsevents/content2415/Programming_Languages_-_Principles_and_Paradigms_thereds1106.pdf)