

3

Displaying Data from Multiple Tables

Objectives

At the end of this lesson, you should be able to:

- **Write SELECT statements to access data from more than one table using equality and nonequality joins**
- **View data that generally does not meet a join condition by using outer joins**
- **Join a table to itself**

Obtaining Data from Multiple Tables

EMP

EMPNO	ENAME	...	DEPTNO
-----	-----	...	-----
7839	KING	...	10
7698	BLAKE	...	30
...			
7934	MILLER	...	10

DEPT

DEPTNO	DNAME	LOC
-----	-----	-----
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON



EMPNO	DEPTNO	LOC
-----	-----	-----
7839	10	NEW YORK
7698	30	CHICAGO
7782	10	NEW YORK
7566	20	DALLAS
7654	30	CHICAGO
7499	30	CHICAGO
...		
14 rows selected.		

What Is a Join?

Use a join to query data from more than one table.

```
SELECT    table.column, table.column  
FROM      table1, table2  
WHERE     table1.column1 = table2.column2;
```

- Write the join condition in the WHERE clause.
- Prefix the column name with the table name when the same column name appears in more than one table.

Cartesian Product

- **A Cartesian product is formed when:**
 - **A join condition is omitted**
 - **A join condition is invalid**
 - **All rows in the first table are joined to all rows in the second table**
- **To avoid a Cartesian product, always include a valid join condition in a WHERE clause.**

Generating a Cartesian Product

EMP (14 rows)

EMPNO	ENAME	...	DEPTNO
-----	-----	...	-----
7839	KING	...	10
7698	BLAKE	...	30
...			
7934	MILLER	...	10

DEPT (4 rows)

DEPTNO	DNAME	LOC
-----	-----	-----
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON




“Cartesian
product:
14*4=56 rows” →


ENAME	DNAME
-----	-----
KING	ACCOUNTING
BLAKE	ACCOUNTING
...	
KING	RESEARCH
BLAKE	RESEARCH
...	
56 rows selected.	

Types of Joins


Equijoin




Non-equijoin



Outer join



Self join



What Is an Equijoin?

EMP

EMPNO	ENAME	DEPTNO
-----	-----	-----
7839	KING	10
7698	BLAKE	30
7782	CLARK	10
7566	JONES	20
7654	MARTIN	30
7499	ALLEN	30
7844	TURNER	30
7900	JAMES	30
7521	WARD	30
7902	FORD	20
7369	SMITH	20
...		
14 rows selected.		

DEPT

DEPTNO	DNAME	LOC
-----	-----	-----
10	ACCOUNTING	NEW YORK
30	SALES	CHICAGO
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
30	SALES	CHICAGO
30	SALES	CHICAGO
30	SALES	CHICAGO
30	SALES	CHICAGO
20	RESEARCH	DALLAS
20	RESEARCH	DALLAS
...		
14 rows selected.		

Foreign key Primary key

Retrieving Records with Equijoins

```
SQL> SELECT  emp.empno, emp.ename, emp.deptno,  
2           dept.deptno, dept.loc  
3 FROM      emp, dept  
4 WHERE     emp.deptno=dept.deptno;
```

EMPNO	ENAME	DEPTNO	DEPTNO	LOC
7839	KING	10	10	NEW YORK
7698	BLAKE	30	30	CHICAGO
7782	CLARK	10	10	NEW YORK
7566	JONES	20	20	DALLAS

...

14 rows selected.

Qualifying Ambiguous Column Names

- Use table prefixes to qualify column names that are in multiple tables.
- Improve performance by using table prefixes.
- Distinguish columns that have identical names but reside in different tables by using column aliases.

Additional Search Conditions Using the AND Operator

EMP

EMPNO	ENAME	DEPTNO
-----	-----	-----
7839	KING	10
7698	BLAKE	30
7782	CLARK	10
7566	JONES	20
7654	MARTIN	30
7499	ALLEN	30
7844	TURNER	30
7900	JAMES	30
7521	WARD	30
7902	FORD	20
7369	SMITH	20
...		
14 rows selected.		

DEPT

DEPTNO	DNAME	LOC
-----	-----	-----
10	ACCOUNTING	NEW YORK
30	SALES	CHICAGO
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
30	SALES	CHICAGO
30	SALES	CHICAGO
30	SALES	CHICAGO
20	RESEARCH	DALLAS
20	RESEARCH	DALLAS
...		
14 rows selected.		

Using Table Aliases

Simplify queries by using table aliases.

```
SQL> SELECT emp.empno, emp.ename, emp.deptno,  
2          dept.deptno, dept.loc  
3 FROM     emp, dept  
4 WHERE    emp.deptno=dept.deptno;
```

```
SQL> SELECT e.empno, e.ename, e.deptno,  
2          d.deptno, d.loc  
3 FROM     emp e, dept d  
4 WHERE    e.deptno=d.deptno;
```

Joining More Than Two Tables

CUSTOMER

NAME	CUSTID
-----	-----
JOCKSPORTS	100
TKB SPORT SHOP	101
VOLLYRITE	102
JUST TENNIS	103
K+T SPORTS	105
SHAPE UP	106
WOMENS SPORTS	107
...	...
9 rows selected.	

ORD

CUSTID	ORDID
-----	-----
101	610
102	611
104	612
106	601
102	602
106	
106	
...	...
21 rows selected.	

ITEM

ORDID	ITEMID
-----	-----
610	3
611	1
612	1
601	1
602	1
...	
64 rows selected.	

Non-Equi Joins

EMP

EMPNO	ENAME	SAL
7839	KING	5000
7698	BLAKE	2850
7782	CLARK	2450
7566	JONES	2975
7654	MARTIN	1250
7499	ALLEN	1600
7844	TURNER	1500
7900	JAMES	950
...		
14 rows selected.		

SALGRADE

GRADE	LOSAL	HISAL
1	700	1200
2	1201	1400
3	1401	2000
4	2001	3000
5	3001	9999

“salary in the EMP table is between low salary and high salary in the SALGRADE table”

Retrieving Records with Non-Equi Joins

```
SQL>  SELECT    e.ename, e.sal, s.grade
      2  FROM      emp e, salgrade s
      3  WHERE     e.sal
      4  BETWEEN   s.losal AND s.hisal;
```

ENAME	SAL	GRADE
JAMES	950	1
SMITH	800	1
ADAMS	1100	1
...		

14 rows selected.

Outer Joins

EMP

ENAME	DEPTNO
-----	-----
KING	10
BLAKE	30
CLARK	10
JONES	20
...	

DEPT

DEPTNO	DNAME
-----	-----
10	ACCOUNTING
30	SALES
10	ACCOUNTING
20	RESEARCH
...	
40	OPERATIONS



**No employee in the
OPERATIONS department**

Outer Joins

- You use an outer join to see rows that do not usually meet the join condition.
- Outer join operator is the plus sign (+).

```
SELECT table.column, table.column  
FROM   table1, table2  
WHERE  table1.column (+) = table2.column;
```

```
SELECT table.column, table.column  
FROM   table1, table2  
WHERE  table1.column = table2.column (+);
```

Using Outer Joins

```
SQL> SELECT    e.ename, d.deptno, d.dname
  2  FROM      emp e, dept d
  3  WHERE     e.deptno(+) = d.deptno
  4  ORDER BY  e.deptno;
```

ENAME	DEPTNO	DNAME
-----	-----	-----
KING	10	ACCOUNTING
CLARK	10	ACCOUNTING
...		
	40	OPERATIONS

15 rows selected.

Self Joins

EMP(WORKER)

EMPNO	ENAME	MGR
-----	-----	-----
7839	KING	
7698	BLAKE	7839
7782	CLARK	7839
7566	JONES	7839
7654	MARTIN	7698
7499	ALLEN	7698

EMP(MANAGER)

EMPNO	ENAME
-----	-----
7839	KING
7839	KING
7839	KING
7698	BLAKE
7698	BLAKE



**“MGR in the WORKER table is equal to EMPNO in the
MANAGER table”**

Joining a Table to Itself




```
SQL> SELECT worker.ename || ' works for ' || manager.ename  
2   FROM   emp worker, emp manager  
3   WHERE  worker.mgr = manager.empno;
```

```
WORKER.ENAME || 'WORKSFOR' || MANAG  
-----  
BLAKE works for KING  
CLARK works for KING  
JONES works for KING  
MARTIN works for BLAKE  
...  
13 rows selected.
```

Summary

```
SELECT    table.column, table.column  
FROM      table1, table2  
WHERE     table1.column1 = table2.column2;
```

Equijoin Non-equijoin Outer join Self join



Practice Overview

- **Joining tables using an equijoin**
- **Performing outer and self joins**
- **Adding additional conditions**