

# Lab 10

[valid 2020-2021]

## Networking

Create an application where clients connect to a server in order to form a *social network*. The application will contain two parts (create a project for each one):

- The **server** is responsible with the management of the clients and the implementation of the services.
- The **client** will communicate with the server, sending it *commands* containing the name of the service and the required parameters. The commands are:
  - register *name*: adds a new person to the social network;
  - login *name*: establishes a connection between the server and the client;
  - friend *name<sub>1</sub> name<sub>2</sub> ... name<sub>k</sub>*: adds friendship relations between the person that sends the command and other persons;
  - send *message*: sends a message to all friends.
  - read: reads the messages from the server.

The main specifications of the application are:

---

### Compulsory (1p)

- Create the project for the server application.
- Implement the class responsible with the creation of a *ServerSocket* running at a specified port. The server will receive requests (commands) from clients and it will execute them.
- Create a class that will be responsible with communicating with a client *Socket*. The communication will be on a separate thread. If the server receives the command *stop* it will stop and will return to the client the response "Server stopped", otherwise it returns: "Server received the request ...".
- Create the project for the client application.
- A client will read commands from the keyboard and it will send them to the server. The client stops when it reads from the keyboard the string "exit".

---

### Optional (2p)

- Create an object-oriented model for your application and implement the commands.  
The command *stop* should "gracefully" stop the server - it will not accept new games but it will finish those in progress. When there are no more games, it will shutdown.
  - Implement a timeout for a connection (a number of minutes). If the server does not receive any command from a logged in client in the specified period of time, it will terminate the connection.
  - Create an HTML embeddable representation of the social network using [JFreeChart](#), [JGraphT](#) and [Apache Batik](#), or other technology.
  - Upload the HTML representation directly from the application to a Web server. You may use [JCraft](#) for connecting to a server using SFTP and transferring a file (or a similar solution).
- 

### Bonus (2p)

- Implement an algorithm to determine the [structural cohesion](#) of the network.
- Rewrite the application so it can act both as a server or a client, depending on circumstances.  
Suppose that the clients (agents) are inside an intranet and their IP addresses are known (or within a known limited range).  
Implement a [leader election](#) algorithm such that, if the server (the coordinator agent) fails, one of the other agents "elects" itself as the coordinator of the network and the communication can still continue.

### Resources

- [Custom Networking](#)
- [Remote Method Invocation \(RMI\)](#)
- [Java Networking](#)

### Objectives

- Understand terms and concepts related to networking: protocol, IP, port, URL, socket, and datagram.
- Get familiar with the client-server programming model.

- Write programs that communicate with other programs on the network, using TCP or UDP.
- Get acquainted with RMI technology.