Q1. What is the output of the following code snippet?

```
#include<stdio.h>
int main()
{
int a=30;
do{
printf(”%d ”, a);
a++;
} while(- -a <= 30);
return 0;
}
```

Q2. What is the output of the following code snippet?

```
#include < stdio.h >
void main() {
Int i;
if(! i)
printf(”hello”);
else
printf(”world”);
}
```

Q3. What is the output of the following code snippet?

```
#include <stdio.h>
void main() {
char val=1;
if(val- - ==0)
printf(”TRUE”);
else
printf(”FALSE”);
}
```

Q4. What is the output of the following code snippet?

```
#include <stdio.h>
int main() {
int a=1;
switch(a) {
printf(”Hello”);
}
printf(”world”);
return 0;
}
```

Q5. What will be the output of the following code snippet?

```
#include <stdio.h>
int main()
{
for(; ;);
for(; ;);
for(; ;);
printf(”Hello”);
return 0;
}
```

Q6. Write a C program to take a number as input and check if it is a perfect number or not. A perfect number is equal to the sum of all its factors except itself. For example, 6 is a perfect number as 6 = 1 + 2 + 3.
Assume the input to be a non-zero positive integer. Your program should output “Perfect” if the number is perfect; otherwise, output “Not Perfect”.
Sample Input 0
28
Sample Output 0

Perfect
as (28 = 1 + 2 + 4 + 7 + 14)
Sample Input 1
21
Sample Output 1
Not Perfect
as ((21/ = 1 + 3 + 7))

Q7. Write a C program that takes a positive integer n and prints a triangle like this:
(given example for n = 5)

```
5 4 3 2 1
4 3 2 1
3 2 1
2 1
1
```