Q1 Write a program that dynamically allocates memory for a 2D array using an array of pointers. Allow the user to input the number of rows and columns, fill the array with values, print it, and free the memory after use.
Example
Enter number of rows and columns: 2 3
Enter element [0][0]: 1
Enter element [0][1]: 2
Enter element [0][2]: 3
Enter element [1][0]: 4
Enter element [1][1]: 5
Enter element [1][2]: 6
Output:2D Array:
1 2 3
4 5 6

Q2.Create a function that takes an array of strings (array of char*), concatenates them into a single dynamically allocated string, and returns it.
Example input
Concatenating words: {"Hello", " ", "World", "!"}
Output: Concatenated String: Hello World!

Q3. Write a program that takes a number of words as input and dynamically allocates an array of char* pointers. Each pointer should point to a string of varying length, with each string dynamically allocated.

Input
Enter number of words: 3
Enter word 1: Hello
Enter word 2: World
Enter word 3: Dynamic
Output:
Words entered:
Hello
World
Dynamic

Q4 Write a program that compares two strings lexicographically (like strcmp function). Use dynamic memory allocation to store the input strings and compare them.(
Lexicographic order refers to the order in which words are arranged in a dictionary. It is based on the alphabetical order of the characters in the word. In lexicographic comparison, strings are compared character by character, using the character's ASCII (or Unicode) value.)
Input:

Enter first string: Apple

Enter second string: Banana

Output:

"Apple" is lexicographically smaller than "Banana"

Q5. You are given a string s and an integer array indices of the same length. The string s will be shuffled such that the character at the ith position moves to indices[i] in the shuffled string.
Input: s = "codeleet", indices = [4,5,6,7,0,2,1,3]
Output: "leetcode"
Explanation: As shown, "codeleet" becomes "leetcode" after shuffling