

Package ‘GTAPViz’

March 8, 2025

Title Automating GTAP Data Processing and Visualization

Version 0.0.0.9000

Author Pattawee Puangchit <ppuangch@purdue.edu>

Description GTAPViz is an extension package of HARplus, designed to provide seamless data visualization for GTAP model results from `.HAR` and `.SL4` files. This package focuses on user-friendly visualization tools, enabling GTAP users to analyze and compare simulation results efficiently without requiring deep coding knowledge. With built-in functions for pivoting, mapping, unit assignments, and graphical representation, GTAPViz enhances economic model interpretation by generating structured, publication-ready plots. It is ideal for GTAP researchers, policymakers, and analysts looking for intuitive data exploration and visual insights from GEMPACK outputs.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

BugReports <https://github.com/bodysbobb/GTAPViz/issues>

URL <https://bodysbobb.github.io/GTAPViz/>

Imports HARplus,

ggplot2,
dplyr,
tidyr,
openxlsx,
colorspace,
grDevices,
rlang,
scales,
utils,
methods,
stringdist,
stats

Remotes github::Bodysbobb/HARplus

Suggests knitr,
rmarkdown,
devtools

VignetteBuilder knitr

Depends R (>= 3.5)

Contents

add_mapping_info	2
auto_gtap_data	3
comparison_plot	6
convert_units	8
detail_plot	9
get_export_config	12
get_plot_config	13
get_plot_style_config	14
gtap_macros_data	17
rename_GTAP_bilateral	18
rename_value	19
report_table	20
sort_plot_data	21
stack_plot	22
Index	25

add_mapping_info	<i>Add Mapping Information to GTAP Data</i>
------------------	---

Description

Adds descriptions and unit information to GTAP data based on a specified mapping mode. Supports external mappings or default GTAPv7 mappings, allowing users to enrich datasets with standardized metadata.

Usage

```
add_mapping_info(  
  data_list,  
  external_map = NULL,  
  mapping = "GTAPv7",  
  description_info = TRUE,  
  unit_info = TRUE  
)
```

Arguments

data_list	A data structure containing GTAP variables.
external_map	Optional data frame with mapping information (must include "Variable", "Description", and "Unit" columns).
mapping	Character. Mapping mode: "GTAPv7" (default): Uses standard GTAPv7 definitions. "Yes": Uses only the supplied descriptions and units from external_map. "No": Does not add any descriptions or units. "Mix": Prioritizes external_map, but falls back to GTAPv7 for missing values.
description_info	Logical. If TRUE, adds description information to the data.
unit_info	Logical. If TRUE, adds unit information to the data.

Value

A data structure with added mapping information, preserving the original structure.

Author(s)

Pattawee Puangchit

See Also

[convert_units](#), [rename_value](#)

Examples

```
## Not run:
# Add mapping using GTAPv7 defaults
gtap_data <- add_mapping_info(gtap_data, mapping = "GTAPv7")

# Use an external mapping file
gtap_data <- add_mapping_info(gtap_data, external_map = my_mapping, mapping = "Mix")

## End(Not run)
```

auto_gtap_data

Process GTAP Data Automation with Flexible Output Options

Description

Processes GTAP data from SL4 and HAR files with options for exporting and preparing plot-ready data.

Usage

```
auto_gtap_data(
  experiment,
  mapping_info = "GTAPv7",
  project_path = NULL,
  input_path = NULL,
  output_path = NULL,
  output_formats = NULL,
  plot_data = FALSE,
  region_select = NULL,
  sector_select = NULL,
  subtotal_level = FALSE,
  sl4_output_name = "sl4.plot.data",
  har_output_name = "har.plot.data",
  macro_output_name = "GTAPMacro",
  process_sl4_vars = NULL,
  process_har_vars = NULL,
  sl4_mapping_info = NULL,
  har_mapping_info = NULL,
  sl4_extract_method = "group_data_by_dims",
```

```

    har_extract_method = "get_data_by_var",
    sl4_priority = NULL,
    har_priority = NULL,
    sl4_suffix = "",
    har_suffix = "-WEL"
)

```

Arguments

experiment	Character vector. Case names to process.
mapping_info	Character. Mapping mode: "GTAPv7" (default), "Yes", "No", or "Mix".
project_path	Character. Path to the project folder with "in" and "out" subfolders.
input_path	Character. Path to the input folder. Overrides project_path/in if specified.
output_path	Character. Path to the output folder. Overrides project_path/out if specified.
output_formats	Character vector or list. Exports data in these formats (valid: "csv", "stata", "rds", "txt").
plot_data	Logical. If TRUE, prepares data for plotting and assigns to variables.
region_select	Optional character vector. Specifies regions to filter the data.
sector_select	Optional character vector. Specifies sectors to filter the data.
subtotal_level	Logical. If TRUE, includes subtotal data. Default is FALSE.
sl4_output_name	Character. Variable name for SL4 plotting data if generating plot data. Default is "sl4.plot.data".
har_output_name	Character. Variable name for HAR plotting data if generating plot data. Default is "har.plot.data".
macro_output_name	Character. Variable name for GTAP macro data if generating plot data. Default is "GTAPMacro".
process_sl4_vars	Data frame, NULL, or FALSE. Variables to extract from SL4 files. Set to NULL to extract all variables, or FALSE to skip SL4 processing.
process_har_vars	Data frame, NULL, or FALSE. Variables to extract from HAR files. Set to NULL to extract all variables, or FALSE to skip HAR processing.
sl4_mapping_info	Data frame or NULL. Mapping information for SL4 variables (with "Variable", "Description", and "Unit" columns).
har_mapping_info	Data frame or NULL. Mapping information for HAR variables (with "Variable", "Description", and "Unit" columns).
sl4_extract_method	Character. SL4 extraction method. Options: "get_data_by_dims", "get_data_by_var", or "group_data_by_dims".
har_extract_method	Character. HAR extraction method. Options: "get_data_by_dims", "get_data_by_var", or "group_data_by_dims".
sl4_priority	Optional list. Priority rules for SL4 data grouping.

har_priority	Optional list. Priority rules for HAR data grouping.
sl4_suffix	Character. Custom suffix for SL4 files (e.g., "" or "-custom").
har_suffix	Character. Custom suffix for HAR files (e.g., "-WEL").

Details

This function automates the workflow for processing GTAP model outputs, with flexible output options and optional filtering for region- and sector-specific data.

The key parameters `process_sl4_vars` and `process_har_vars` accept three different input types:

- **Data frame:** Contains variable mappings with required "Variable" column. When provided, only specified variables will be extracted.
- **NULL:** Extracts all available variables from the respective file type.
- **FALSE:** Completely skips processing of that file type, allowing the function to focus only on the other file type.

The `mapping_info` parameter controls how descriptions and units are assigned:

- **GTAPv7:** Uses standard GTAPv7 definitions (default).
- **Yes:** Uses only the supplied descriptions and units from `sl4_mapping_info` / `har_mapping_info`.
- **No:** Does not add any descriptions or units.
- **Mix:** Prioritizes supplied descriptions and units, falling back to GTAPv7 for any missing values.

Value

Returns the processed data invisibly, which will not be printed to the console.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [gtap_macros_data](#)

Examples

```
## Not run:
# Extract data with region and experiment filters
auto_gtap_data(
  process_sl4_vars = NULL,
  process_har_vars = NULL,
  sl4_mapping_info = sl4_mapping_info,
  har_mapping_info = har_mapping_info,
  region_select = selected_regions,
  sector_select = NULL,
  subtotal_level = FALSE,
  experiment = experiment,
  mapping_info = "GTAPv7",
  project_path = project_folder,
  plot_data = TRUE,
  output_formats = list(
```

```

    "csv" = "No",
    "stata" = "No",
    "rds" = "No",
    "txt" = "No"))

## End(Not run)

```

comparison_plot

Create Comparative Bar Charts from HAR and SLA Data

Description

Generates comparative bar charts using GTAP data, allowing multiple visualization options such as panel facets, split grouping, and customizable styles.

Usage

```

comparison_plot(
  data,
  filter_var = NULL,
  x_axis_from,
  split_by = NULL,
  panel_var = "Experiment",
  variable_col = "Variable",
  unit_col = "Unit",
  desc_col = "Description",
  invert_pane = FALSE,
  separate_figure = FALSE,
  var_name_by_description = FALSE,
  add_var_info = FALSE,
  output_path = NULL,
  export_picture = TRUE,
  export_as_pdf = FALSE,
  export_config = NULL,
  plot_style_config = NULL
)

```

Arguments

data	A data frame or a list of data frames containing GTAP results.
filter_var	Vector or data frame. If a vector, filters the values in x_axis_from. If a data frame, filters value_col based on matching variable_col values.
x_axis_from	Character. Column name for x-axis categories (e.g., "REG", "Sector").
split_by	Character or vector. Column name(s) for data splitting (e.g., "COMM", "REG", "ACTS"). Set to NULL for no splitting, suitable for macro-level analysis.
panel_var	Character. Column for panel facets (default: "Experiment").
variable_col	Character. Column containing variable identifiers (default: "Variable").
unit_col	Character. Column containing unit information (default: "Unit").
desc_col	Character. Column containing variable descriptions (default: "Description").

invert_pane	Logical. If TRUE, creates horizontal bars instead of vertical ones (default: FALSE).
separate_figure	Logical. If TRUE, generates separate figures per panel value (default: FALSE).
var_name_by_description	Logical. If TRUE, uses descriptions instead of variable codes in titles (default: FALSE).
add_var_info	Logical. If TRUE, adds the variable code in parentheses after the description (default: FALSE).
output_path	Character. Directory path for saving output files. If NULL, plots are only returned in R.
export_picture	Logical. If TRUE, exports plots as image files (default: TRUE).
export_as_pdf	Logical or "merged". If TRUE, exports separate PDFs; if "merged", creates a multi-page PDF; if FALSE, skips PDF (default: FALSE).
export_config	List. Export settings, including: • width: Output file width (in inches). • height: Output file height (in inches). • Additional settings—see ?get_export_config.
plot_style_config	List. Custom plot styles—see ?get_plot_style_config.

Value

A ggplot2 object for a single plot or a list of ggplot2 objects for multiple plots.

Author(s)

Pattawee Puangchit

See Also

[get_plot_style_config](#), [get_export_config](#), [detail_plot](#), [stack_plot](#)

Examples

```
## Not run:
# Basic usage with data frame
p1 <- comparison_plot(
  data = gtap_results,
  x_axis_from = "REG",
  panel_var = "Experiment"
)

# Split by commodity with custom styling and export options
p2 <- comparison_plot(
  data = gtap_results,
  x_axis_from = "REG",
  split_by = "COMM",
  panel_var = "Experiment",
  var_name_by_description = TRUE,
  output_path = "results/plots",
  export_as_pdf = TRUE,
```

```

export_config = list(
  file_name = "commodity_impacts",
  width = 12,
  height = 8
),
plot_style_config = list(
  color_tone = "economic",
  title_size = 16,
  show_grid_major_y = TRUE
)
)

## End(Not run)

```

convert_units	<i>Convert Units in GTAP Data</i>
---------------	-----------------------------------

Description

Converts values in a dataset to different units based on predefined transformations or custom scaling. Supports manual and automatic conversions for economic and trade-related metrics.

Usage

```

convert_units(
  data,
  change_unit_from = NULL,
  change_unit_to = NULL,
  adjustment = NULL,
  value_col = "Value",
  unit_col = "Unit",
  variable_select = NULL,
  variable_col = "Variable",
  scale_auto = NULL
)

```

Arguments

data	A data structure (list, data frame, or nested combination).
change_unit_from	Character vector. Units to be converted (case-insensitive).
change_unit_to	Character vector. Target units corresponding to change_unit_from.
adjustment	Character or numeric vector. Specifies conversion operations (e.g., "/1000" to convert million to billion).
value_col	Character. Column name containing values to adjust (default: "Value").
unit_col	Character. Column name containing unit information (default: "Unit").
variable_select	Optional character vector. If provided, only these variables are converted.
variable_col	Character. Column name containing variable identifiers (default: "Variable").
scale_auto	Optional character vector of predefined conversion rules:

- "mil2bil": Converts million USD to billion USD (divides by 1000).
- "bil2mil": Converts billion USD to million USD (multiplies by 1000).
- "pct2frac": Converts percent to fraction (divides by 100).
- "frac2pct": Converts fraction to percent (multiplies by 100).

Details

If both `change_unit_from` and `scale_auto` are provided, the function prompts the user to choose between manual and automatic conversion.

Value

A data structure with values converted to the specified units.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [rename_value](#), [sort_plot_data](#)

Examples

```
## Not run:
# Convert million USD to billion USD
gtap_data <- convert_units(gtap_data,
  change_unit_from = "million USD",
  change_unit_to = "billion USD",
  adjustment = "/1000"
)

# Automatic conversion from percent to fraction
gtap_data <- convert_units(gtap_data, scale_auto = "pct2frac")

## End(Not run)
```

Description

Generates detailed bar charts to visualize the distribution of impacts across multiple dimensions. The function supports top impact filtering, color coding, and flexible visualization settings.

Usage

```

detail_plot(
  data,
  filter_var = NULL,
  x_axis_from,
  split_by = NULL,
  panel_var = "Experiment",
  variable_col = "Variable",
  unit_col = "Unit",
  desc_col = "Description",
  var_name_by_description = FALSE,
  add_var_info = FALSE,
  output_path = NULL,
  export_picture = TRUE,
  export_as_pdf = FALSE,
  export_config = NULL,
  top_impact = NULL,
  separate_figure = FALSE,
  invert_pane = FALSE,
  plot_style_config = NULL
)

```

Arguments

<code>data</code>	A data frame or a list of data frames containing GTAP results.
<code>filter_var</code>	Vector or data frame. If a vector, filters the values in <code>x_axis_from</code> . If a data frame, filters <code>value_col</code> based on matching <code>variable_col</code> values.
<code>x_axis_from</code>	Character. Column name for x-axis categories (e.g., "REG", "Sector").
<code>split_by</code>	Character or vector. Column name(s) for data splitting (e.g., "COMM", "REG", "ACTS"). Set to NULL for no splitting, suitable for macro-level analysis.
<code>panel_var</code>	Character. Column for panel facets (default: "Experiment").
<code>variable_col</code>	Character. Column containing variable identifiers (default: "Variable").
<code>unit_col</code>	Character. Column containing unit information (default: "Unit").
<code>desc_col</code>	Character. Column containing variable descriptions (default: "Description").
<code>var_name_by_description</code>	Logical. If TRUE, uses descriptions instead of variable codes in titles (default: FALSE).
<code>add_var_info</code>	Logical. If TRUE, adds the variable code in parentheses after the description (default: FALSE).
<code>output_path</code>	Character. Directory path for saving output files. If NULL, plots are only returned in R.
<code>export_picture</code>	Logical. If TRUE, exports plots as image files (default: TRUE).
<code>export_as_pdf</code>	Logical or "merged". If TRUE, exports separate PDFs; if "merged", creates a multi-page PDF; if FALSE, skips PDF (default: FALSE).
<code>export_config</code>	List. Export settings, including: • width: Output file width (in inches). • height: Output file height (in inches). • Additional settings—see <code>?get_export_config</code>.

top_impact	Numeric or NULL. If specified, shows only the top N impactful values; NULL shows all values.
separate_figure	Logical. If TRUE, generates separate figures per panel value (default: FALSE).
invert_pane	Logical. If TRUE, creates horizontal bars instead of vertical ones (default: FALSE).
plot_style_config	List. Custom plot styles—see <code>?get_plot_style_config</code> .

Value

A ggplot2 object for a single plot or a list of ggplot2 objects for multiple plots.

Author(s)

Pattawee Puangchit

See Also

[get_plot_style_config](#), [get_export_config](#), [comparison_plot](#), [stack_plot](#)

Examples

```
## Not run:
# Basic usage showing all impacts with export options
p1 <- detail_plot(
  data = gtap_results,
  x_axis_from = "REG",
  variable_col = "Variable",
  top_impact = NULL,
  output_path = "results/detail_plots",
  export_config = list(
    file_name = "regional_impacts",
    width = 14,
    height = 10
  )
)

# Show only top 10 impacts (balanced between positive and negative)
p2 <- detail_plot(
  data = gtap_results,
  x_axis_from = "Sector",
  split_by = "Region",
  panel_var = "Experiment",
  variable_col = "Variable",
  top_impact = 10,
  invert_pane = TRUE,
  export_as_pdf = TRUE
)

## End(Not run)
```

get_export_config	<i>Get Export Configuration Options</i>
-------------------	---

Description

Returns documentation and default values for export configuration options used in plotting functions.

Usage

```
get_export_config(as_dataframe = TRUE)
```

Arguments

`as_dataframe` Logical. Whether to return settings as a dataframe. Default is FALSE.

Details

Export Configuration Parameters:

- `file_name`: Character. Base name for exported files. Default: "gtap_plots"
- `width`: Numeric or NULL. Plot width in inches. Default: NULL (automatically calculated)
- `height`: Numeric or NULL. Plot height in inches. Default: NULL (automatically calculated)
- `dpi`: Numeric. Resolution for PNG export. Default: 300
- `bg`: Character. Background color. Default: "white"
- `limitsize`: Logical. Whether to limit size. Default: FALSE

Value

If `as_dataframe` is TRUE, returns a dataframe with export configuration settings. Otherwise, returns a list with configuration settings.

Author(s)

Pattawee Puangchit

See Also

[comparison_plot](#), [detail_plot](#), [stack_plot](#)

Examples

```
# Get export configuration as list
export_info <- get_export_config()

# Get as a formatted dataframe
export_df <- get_export_config(as_dataframe = TRUE)
```

`get_plot_config`*Get Plot and Export Configurations*

Description

Returns a list containing plot style configuration and export configuration. The function supports retrieving a single plot style or all available styles.

Usage

```
get_plot_config(plot_style = "default", config = NULL, export_config = NULL)
```

Arguments

<code>plot_style</code>	Character. The plot style to retrieve: "comparison", "detail", "stack", or "all". Default is "all", which returns configurations for all styles.
<code>config</code>	List. Optional custom style configuration to override defaults.
<code>export_config</code>	List. Optional custom export configuration to override defaults.

Value

A list with two components:

- `plot_style_config`: Plot style configuration(s). If `plot_style="all"`, contains a nested list with configurations for all styles.
- `export_config`: Export configuration as a data frame.

Author(s)

Pattawee Puangchit

See Also

[comparison_plot](#), [detail_plot](#), [stack_plot](#)

Examples

```
# Get all plot configurations with default settings
all_configs <- get_plot_config()

# Get only comparison plot configuration
comp_config <- get_plot_config("comparison")
```

get_plot_style_config *Get Plot Style Configuration*

Description

Returns configuration settings for plot styles, with options to view as a structured dataframe or to look up specific parameters. Also provides parameter validation for custom configurations.

Usage

```
get_plot_style_config(
  plot_type = "default",
  parameter_name = NULL,
  show_docs = FALSE,
  validate_custom = NULL,
  as_dataframe = TRUE
)
```

Arguments

plot_type	Character. Type of plot: "comparison" (default), "detail", or "stack".
parameter_name	Character or NULL. Name of specific parameter to return information about.
show_docs	Logical. Whether to include documentation in the output.
validate_custom	List or NULL. Custom configuration settings to validate.
as_dataframe	Logical. Whether to return settings as a dataframe.

Details

This function applies default styling for different types of plots and allows users to customize the appearance. The parameters are grouped as follows:

Title Settings:

- `show_title`: Logical. Show or hide the plot title. Default: TRUE
- `title_face`: Character. Font face ("bold", "plain", "italic"). Default: "bold"
- `title_size`: Numeric. Font size of title. Default: 20
- `title_hjust`: Numeric. Horizontal alignment (0 = left, 1 = right). Default: 0.5
- `add_unit_to_title`: Logical. Append unit to title if applicable. Default: TRUE
- `title_margin`: ggplot2 `margin()` object. Default: `ggplot2::margin(10, 0, 10, 0)`
- `title_format`: List or NULL. Formatting options for the title, with elements:
 - `type`: Character. One of "prefix", "suffix", "full", or "dynamic".
 - `text`: Character. Text to add, or column names used for dynamic titles.
 - `sep`: Character. Separator used for dynamic titles. Default: " - ".

X-Axis Settings:

- `show_x_axis_title`: Logical. Show or hide x-axis title. Default: FALSE
- `x_axis_title_face`: Character. Font face for x-axis title. Default: "bold"
- `x_axis_title_size`: Numeric. Font size of x-axis title. Default: 16

- `x_axis_title_margin`: ggplot2 `margin()`. Default: `ggplot2::margin(t = 20)`
- `show_x_axis_labels`: Logical. Show or hide x-axis labels. Default: `TRUE`
- `x_axis_text_face`: Character. Font face for x-axis labels. Default: `"bold"`
- `x_axis_text_size`: Numeric. Font size of x-axis labels. Default: `14`
- `x_axis_text_angle`: Numeric. Angle of x-axis labels. Default: `45`
- `x_axis_text_hjust`: Numeric. Horizontal justification of x-axis labels. Default: `1`
- `x_axis_description`: Character. Optional description for the x-axis. Default: `""`

Y-Axis Settings:

- `show_y_axis_title`: Logical. Show or hide y-axis title. Default: `TRUE`
- `y_axis_title_face`: Character. Font face for y-axis title. Default: `"bold"`
- `y_axis_title_size`: Numeric. Font size of y-axis title. Default: `16`
- `y_axis_title_margin`: ggplot2 `margin()`. Default: `ggplot2::margin(r = 20)`
- `show_y_axis_labels`: Logical. Show or hide y-axis labels. Default: `TRUE`
- `y_axis_text_face`: Character. Font face for y-axis labels. Default: `"plain"`
- `y_axis_text_size`: Numeric. Font size of y-axis labels. Default: `14`
- `y_axis_text_angle`: Numeric. Angle of y-axis labels. Default: `0`
- `y_axis_text_hjust`: Numeric. Horizontal justification of y-axis labels. Default: `0`
- `y_axis_description`: Character. Optional description for the y-axis. Default: `""`
- `show_axis_titles_on_all_facets`: Logical. Show axis titles on all facets. Default: `TRUE`

Value Label Settings:

- `show_value_labels`: Logical. Show or hide value labels. Default: `TRUE`
- `value_label_face`: Character. Font face for value labels. Default: `"plain"`
- `value_label_size`: Numeric. Font size of value labels. Default: `5`
- `value_label_position`: Character. Position of value labels (`"above"`, `"outside"`, `"top"`). Default: `"above"`
- `value_label_decimal_places`: Numeric. Number of decimal places in value labels. Default: `2`

Legend Settings:

- `show_legend`: Logical. Show or hide legend. Default: `FALSE`
- `show_legend_title`: Logical. Show or hide legend title. Default: `FALSE`
- `legend_position`: Character. Legend position (`"none"`, `"bottom"`, `"right"`). Default: `"none"`
- `legend_title_face`: Character. Font face for legend title. Default: `"bold"`
- `legend_text_face`: Character. Font face for legend text. Default: `"plain"`
- `legend_text_size`: Numeric. Font size for legend text. Default: `14`

Panel Strip Settings:

- `strip_face`: Character. Font face for panel strip. Default: `"bold"`
- `strip_text_size`: Numeric. Font size for panel strip. Default: `16`
- `strip_background`: Character. Background color of strip. Default: `"lightgrey"`
- `strip_text_margin`: ggplot2 `margin()`. Default: `ggplot2::margin(10, 0, 10, 0)`

Panel Layout:

- `panel_spacing`: Numeric. Spacing between panels. Default: `2`
- `panel_rows`: Numeric or `NULL`. Number of rows in panel layout. Default: `NULL`

- `panel_cols`: Numeric or NULL. Number of columns in panel layout. Default: NULL
- `theme`: ggplot2 theme object or NULL. Custom ggplot theme. Default: NULL

Color Settings:

- `color_tone`: Character or NULL. Base color theme. Default: NULL
- `positive_color`: Character. Color for positive values. Default: "#2E8B57"
- `negative_color`: Character. Color for negative values. Default: "#CD5C5C"
- `background_color`: Character. Background color of plot. Default: "white"
- `grid_color`: Character. Color of grid lines. Default: "grey90"
- `show_grid_major_x`: Logical. Show major grid lines on x-axis. Default: FALSE
- `show_grid_major_y`: Logical. Show major grid lines on y-axis. Default: TRUE
- `show_grid_minor_x`: Logical. Show minor grid lines on x-axis. Default: FALSE
- `show_grid_minor_y`: Logical. Show minor grid lines on y-axis. Default: FALSE

Zero Line Settings:

- `show_zero_line`: Logical. Show or hide zero line. Default: TRUE
- `zero_line_type`: Character. Line type ("solid", "dashed", "dotted"). Default: "dashed"
- `zero_line_color`: Character. Color of zero line. Default: "black"
- `zero_line_size`: Numeric. Line thickness of zero line. Default: 0.5
- `zero_line_position`: Numeric. Position of the zero line. Default: 0

Bar Chart Settings:

- `bar_width`: Numeric. Width of bars. Default: 0.9
- `bar_spacing`: Numeric. Spacing between bars. Default: 0.9

Scale Settings:

- `scale_limit`: Numeric vector of length 2. Manual limits for value axis. Example: `c(-10, 10)`
- `scale_increment`: Numeric. Step size for axis tick marks. Example: 2

Scale Expansion Settings:

- `expansion_y_mult`: Numeric vector. Y-axis expansion. Default: `c(0.05, 0.1)`
- `expansion_x_mult`: Numeric vector. X-axis expansion. Default: `c(0.05, 0.05)`

All Font Adjustment:

- `all_font_size`: Numeric. Master control for all font sizes. Default: 1

Value

If `parameter_name` is specified, returns a list with the value and documentation for that parameter. If `validate_custom` is specified, returns the validated configuration list. If `as_dataframe` is TRUE, returns a dataframe with configuration settings. Otherwise, returns a list with all configuration settings.

Author(s)

Pattawee Puangchit

See Also

[comparison_plot](#), [detail_plot](#), [stack_plot](#)

Examples

```
# Get default configuration
config <- get_plot_style_config("comparison")

# Get information about a specific parameter
param_info <- get_plot_style_config("detail", "bar_width")

# Get as structured dataframe
config_df <- get_plot_style_config("stack", as_dataframe = TRUE)

# Validate custom configuration
custom_config <- list(title_size = 24, bar_width = 0.7)
validated <- get_plot_style_config("comparison", validate_custom = custom_config)
```

gtap_macros_data

*Extract and Aggregate Scalar Macroeconomic Variables***Description**

Extracts scalar macroeconomic variables from multiple SL4 datasets and aggregates them into a structured data frame.

Usage

```
gtap_macros_data(
  input_dir = NULL,
  experiment_names = NULL,
  output_dir = NULL,
  output_formats = NULL,
  subtotal_level = FALSE,
  select_var = NULL
)
```

Arguments

input_dir	Character. Directory containing SL4 files.
experiment_names	Character vector. List of experiment names corresponding to SL4 files.
output_dir	Character (optional). Directory to save exported data.
output_formats	Character vector (optional). List of output formats (e.g., "csv", "xlsx").
subtotal_level	Logical. Whether to include subtotal levels in the processed data.
select_var	Character vector (optional). List of specific variable names to filter from the final result. If NULL, all variables are returned.

Value

A sorted dataframe containing processed GTAP macro data.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [auto_gtap_data](#)

Examples

```
## Not run:
# Method 1: Extract all variables
input_dir <- paste0(input.folder)
experiment <- c("EXP1", "EXP2") # File name (.sl4)
Macros <- gtap_macros_data(input_dir, experiment_names = experiment,
  subtotal_level = FALSE)

# Method 2: Filter specific variables
Macros <- gtap_macros_data(input_dir, experiment_names = experiment,
  select_var = c("qgdp", "pop", "gdpexp"))

## End(Not run)
```

rename_GTAP_bilateral *Rename GTAP Bilateral Trade Columns*

Description

Renames bilateral trade columns in GTAP data to standardized names, ensuring consistency in regional trade flows.

Usage

```
rename_GTAP_bilateral(data)
```

Arguments

`data` Data structure containing GTAP bilateral trade data.

Value

The same data structure with renamed bilateral trade columns.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [convert_units](#), [sort_plot_data](#)

Examples

```
## Not run:
# Rename bilateral trade columns in a GTAP dataset
gtap_data <- rename_GTAP_bilateral(gtap_data)

## End(Not run)
```

rename_value	<i>Rename Values in a Column</i>
--------------	----------------------------------

Description

Replaces specific values in a column based on a provided mapping file. Supports renaming across nested data structures and preserves factor levels.

Usage

```
rename_value(data, column_name = NULL, mapping.file)
```

Arguments

data	Data structure (data frame, list, or nested combination).
column_name	Character. Column to modify. If NULL, the function extracts it from mapping.file.
mapping.file	Data frame with "OldName" and "NewName" columns for renaming.

Value

The same data structure with specified values replaced.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [convert_units](#), [sort_plot_data](#)

Examples

```
## Not run:
# Rename variables in a dataset
rename_map <- data.frame(OldName = c("old_var1", "old_var2"), NewName = c("new_var1", "new_var2"))
gtap_data <- rename_value(gtap_data, column_name = "Variable", mapping.file = rename_map)

## End(Not run)
```

report_table	<i>Generate a Structured Report Table</i>
--------------	---

Description

Transforms multiple datasets into wide-format tables based on defined pivot columns, hierarchical grouping, and renaming rules. Supports optional subtotal filtering and exporting to Excel.

Usage

```
report_table(
  data_list,
  pivot_col,
  total_column = FALSE,
  export_table = FALSE,
  separate_file = FALSE,
  output_path = NULL,
  sheet_names = NULL,
  include_units = FALSE,
  component_exclude = NULL,
  group_by = NULL,
  rename_cols = NULL,
  var_name_by_description = TRUE,
  add_var_info = FALSE,
  decimal = 2,
  unit_select = NULL,
  separate_sheet_by = NULL,
  subtotal_level = FALSE,
  repeat_label = FALSE,
  workbook_name = "detail_results",
  add_group_line = FALSE
)
```

Arguments

data_list	A named list of data frames to process.
pivot_col	A named list specifying the column to pivot into a wide format for each dataset. Each dataset can have only one pivot column. Example: <code>pivot_col = list(A = "COLUMN", E1 = "PRICES")</code>
total_column	Logical. If TRUE, adds a "Total" column summing numeric values.
export_table	Logical. If TRUE, saves the output as an Excel file.
separate_file	Logical. If TRUE, saves each dataset as a separate Excel file.
output_path	Character. Directory for saving Excel files when <code>export_table = TRUE</code> .
sheet_names	Optional named list for custom sheet names.
include_units	Logical. If TRUE, includes "Unit" as a grouping column if applicable.
component_exclude	Optional character vector specifying pivoted values to exclude.

group_by	A named list defining hierarchical grouping for each dataset. The order of columns in each list determines the priority. Example: <code>group_by = list(A = list("Experiment", "REG"), E1 = list("Experiment", "REG", "COMM"))</code>
rename_cols	A named list for renaming columns across all datasets. Example: <code>rename_cols = list("REG" = "Region", "COMM" = "Commodities", "Experiment" = "Scenario")</code>
decimal	Numeric. Number of decimal places for rounding values.
separate_sheet_by	Optional column name to split sheets in Excel. If defined, each unique value in the specified column gets its own sheet. Example: <code>separate_sheet_by = "Scenario"</code> .
subtotal_level	Logical. If TRUE, includes all subtotal values; otherwise, keeps only TOTAL rows.
repeat_label	Logical. If TRUE, repeats the first group column in exports for clarity.
workbook_name	Character. Name of the Excel workbook (without extension).
add_group_line	Logical. If TRUE, adds a thin line after each group in the exported table.

Value

A named list of transformed data frames. If `export_table = TRUE`, tables are saved as Excel files.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [convert_units](#), [rename_value](#)

Examples

```
## Not run:
# Create a detailed report table with wide-format pivoting
report_data <- report_table(
  data_list = my_data,
  pivot_col = list("Variable" = "Value"),
  export_table = TRUE,
  output_path = "results/"
)

## End(Not run)
```

sort_plot_data

Sort GTAP Plot Data

Description

Sorts data for plotting using flexible options for column ordering and value-based sorting. Works with data frames, lists of data frames, or nested data structures.

Usage

```
sort_plot_data(
  data,
  cols = NULL,
  sort_by_value_desc = NULL,
  convert_to_factor = TRUE
)
```

Arguments

data A data frame or list structure containing data to be sorted.

cols Named list. Specifies columns to sort by and their ordering. Each element should be a character vector of values in desired order. For example, `list(Region = c("USA", "EU", "Japan", "China", "India", "Brazil", "Russia", "Mexico", "South Africa", "Australia", "Canada", "Other"), Experiment = c("Base", "Shock1", "Shock2"))`.

sort_by_value_desc Logical or NULL. Controls sorting by the "Value" column: - NULL (default): Don't sort by value, only use column-based sorting. - TRUE: After column-based sorting, sort by value in descending order. - FALSE: After column-based sorting, sort by value in ascending order.

convert_to_factor Logical. Whether to convert sorted columns to factors with custom ordering. Default is TRUE, which preserves ordering in GTAP plotting functions.

Value

A data structure with the same form as the input, with all contained data frames sorted.

Author(s)

Pattawee Puangchit

See Also

[add_mapping_info](#), [convert_units](#), [rename_GTAP_bilateral](#)

stack_plot

Create Stacked Bar Charts for Decomposition Analysis

Description

Generates stacked bar charts to visualize value compositions across multiple dimensions. The function supports stacked and unstacked presentations for decomposition analysis.

Usage

```
stack_plot(
  data,
  filter_var = NULL,
  x_axis_from,
  stack_value_from,
  split_by = NULL,
```

```

    panel_var = "Experiment",
    variable_col = "Variable",
    unit_col = "Unit",
    desc_col = "Description",
    invert_pane = FALSE,
    separate_figure = FALSE,
    unstack_plot = FALSE,
    output_path = NULL,
    export_picture = TRUE,
    export_as_pdf = FALSE,
    export_config = NULL,
    var_name_by_description = FALSE,
    add_var_info = FALSE,
    show_total = TRUE,
    top_impact = NULL,
    plot_style_config = NULL
  )

```

Arguments

<code>data</code>	A data frame or a list of data frames containing GTAP results.
<code>filter_var</code>	Vector or data frame. If a vector, filters the values in <code>x_axis_from</code> . If a data frame, filters <code>value_col</code> based on matching <code>variable_col</code> values.
<code>x_axis_from</code>	Character. Column name for x-axis categories (e.g., "REG", "Sector").
<code>stack_value_from</code>	Character. Column containing stack component categories (e.g., "COMM" for commodities).
<code>split_by</code>	Character or vector. Column name(s) for data splitting (e.g., "COMM", "REG", "ACTS"). Set to NULL for no splitting, suitable for macro-level analysis.
<code>panel_var</code>	Character. Column for panel facets (default: "Experiment").
<code>variable_col</code>	Character. Column containing variable identifiers (default: "Variable").
<code>unit_col</code>	Character. Column containing unit information (default: "Unit").
<code>desc_col</code>	Character. Column containing variable descriptions (default: "Description").
<code>invert_pane</code>	Logical. If TRUE, creates horizontal bars instead of vertical ones (default: FALSE).
<code>separate_figure</code>	Logical. If TRUE, generates separate figures per panel value (default: FALSE).
<code>unstack_plot</code>	Logical. If TRUE, creates separate bar plots for each <code>x_axis_from</code> value instead of stacked bars (default: FALSE).
<code>output_path</code>	Character. Directory path for saving output files. If NULL, plots are only returned in R.
<code>export_picture</code>	Logical. If TRUE, exports plots as image files (default: TRUE).
<code>export_as_pdf</code>	Logical or "merged". If TRUE, exports separate PDFs; if "merged", creates a multi-page PDF; if FALSE, skips PDF (default: FALSE).
<code>export_config</code>	List. Export settings, including: • width: Output file width (in inches). • height: Output file height (in inches). • Additional settings—see <code>?get_export_config</code>.

var_name_by_description	Logical. If TRUE, uses descriptions instead of variable codes in titles (default: FALSE).
add_var_info	Logical. If TRUE, adds the variable code in parentheses after the description (default: FALSE).
show_total	Logical. If TRUE, displays total values above stacked bars (default: TRUE).
top_impact	Numeric or NULL. If specified, shows only the top N impactful values; NULL shows all values.
plot_style_config	List. Custom plot styles—see <code>?get_plot_style_config</code> .

Value

A ggplot2 object for a single plot or a list of ggplot2 objects for multiple plots.

Author(s)

Pattawee Puangchit

See Also

[get_plot_style_config](#), [get_export_config](#), [comparison_plot](#), [detail_plot](#)

Examples

```
## Not run:
# Basic stacked bar chart by commodity with export options
p1 <- stack_plot(
  data = gtap_results,
  x_axis_from = "REG",
  stack_value_from = "COMM",
  output_path = "results/stacked",
  export_config = list(
    file_name = "commodity_stacks",
    width = 12,
    height = 9
  )
)

# Welfare Decomposition with PDF export
p2 <- stack_plot(
  data = headerA,
  x_axis_from = "Region",
  stack_value_from = "COLUMN",
  split_by = FALSE,
  unstack_plot = TRUE,
  show_total = TRUE,
  export_as_pdf = TRUE,
  export_config = list(
    file_name = "welfare_decomposition"
  )
)

## End(Not run)
```


Index

add_mapping_info, [2](#), [5](#), [9](#), [18](#), [19](#), [21](#), [22](#)
auto_gtap_data, [3](#), [18](#)

comparison_plot, [6](#), [11–13](#), [16](#), [24](#)
convert_units, [3](#), [8](#), [18](#), [19](#), [21](#), [22](#)

detail_plot, [7](#), [9](#), [12](#), [13](#), [16](#), [24](#)

get_export_config, [7](#), [11](#), [12](#), [24](#)
get_plot_config, [13](#)
get_plot_style_config, [7](#), [11](#), [14](#), [24](#)
gtap_macros_data, [5](#), [17](#)

rename_GTAP_bilateral, [18](#), [22](#)
rename_value, [3](#), [9](#), [19](#), [21](#)
report_table, [20](#)

sort_plot_data, [9](#), [18](#), [19](#), [21](#)
stack_plot, [7](#), [11–13](#), [16](#), [22](#)