

DESIGN SYSTEMS AN OVERVIEW

=====

What is a design system?

A design system is a collection of reusable components, guided by clear standards, that can be assembled together to build any number of applications. It bridges the gap between design and engineering by providing a single source of truth for visual and interaction patterns.

Core layers of a design system

1. Design tokens

The smallest units of the design language: color, spacing, typography, motion duration, and radius values expressed as named variables. Tokens make the system themeable and consistent across surfaces.

2. Component library

Reusable UI elements built on top of tokens: buttons, inputs, cards, modals, navigation. Each component ships with documented variants, states (default, hover, focus, disabled, error), and accessibility requirements.

3. Pattern library

Combinations of components that solve common UX problems: form layouts, data tables, onboarding flows, empty states, error pages.

4. Documentation and guidelines

Usage rules, accessibility notes, copywriting guidelines, and implementation examples that help teams use the system correctly.

Benefits of a design system

Consistency: users experience a coherent visual and interaction language across all products.

Speed: teams build new features faster by composing existing components rather than rebuilding patterns from scratch.

Quality: shared components are tested, accessible, and reviewed once, then reused everywhere.

Collaboration: designers and engineers share vocabulary, reducing miscommunication and back-and-forth.

Scalability: a system grows with the product and the team without accumulating inconsistency debt.

Design tokens in depth

Tokens are typically organized in three tiers:

Global tokens: raw values. Example: `--color-blue-500: #3B82F6`

Semantic tokens: role-based aliases. Example: `--color-action: var(--color-blue-500)`

Component tokens: component-specific. Example: `--button-bg: var(--color-action)`

This structure allows a complete theme change (e.g. dark mode, brand switch) by overriding only the semantic and global layers.

Typography in a design system

A typography scale defines:

- Font families (display, body, mono)
- Size scale (typically 8 10 steps, often based on a modular scale)
- Line height per size
- Letter spacing per size
- Font weight usage rules

Good typography systems distinguish between editorial type (display, hero) and UI type (labels, captions, body).

Motion in a design system

Motion guidelines specify:

- Easing curves per use case (enter, exit, in-place)
- Duration ranges (micro: 100ms, standard: 200ms, narrative: 400ms+)
- Which properties to animate (prefer transform and opacity)
- Reduced-motion fallback rules

Accessibility requirements

Every component in a design system must document:

- Keyboard interaction pattern (Tab, Enter, Space, Escape, Arrow keys)
- Required ARIA roles and attributes
- Minimum contrast ratio (WCAG AA: 4.5:1 for normal text)
- Focus indicator style
- Screen reader announcement behavior

Design system governance

A successful system needs clear ownership:

- A core team (or designated maintainers) reviews contributions
- A versioning strategy (semantic versioning is common)
- A deprecation policy for removing old patterns
- A feedback channel for product teams using the system

Common pitfalls

- Too abstract: tokens so generic they require guesswork to use
- Too prescriptive: components so rigid they cannot cover real use cases
- Unmaintained docs: guidelines diverge from implementation over time
- No adoption strategy: teams build around the system instead of with it

Summary

A design system is not a project with a finish line it is a product for product teams. The best systems are maintained, documented, and evolve together with the products they serve.