

BABEȘ-BOLYAI UNIVERSITY CLUJ-NAPOCA
FACULTY OF MATHEMATICS AND COMPUTER
SCIENCE
SPECIALIZATION COMPUTER SCIENCE

DIPLOMA THESIS

NEST: A Localized Web Application for Enhancing Residential Community Engagement

Supervisor
Dr. Bocicor Maria Iuliana

Author
Bălă Bogdan Andrei

2026

Abstract

In high-density urban residential blocks, physical proximity is paradoxically accompanied by deep social isolation and a lack of community trust. Neighbors share the same building structure for years without developing meaningful social capital, making simple daily challenges, such as coordinating local events, borrowing household tools, or temporary parking space allocation, inefficient and friction-filled. This thesis presents NEST, a secure, responsive, and highly reactive web application designed specifically to convert localized digital coordination into physical neighborhood cooperation.

NEST implements a decoupled Client-Server architecture. The presentation layer is built upon Angular 21, utilizing standalone components and reactive Signal APIs to achieve fine-grained DOM rendering. State management is structured around a global NgRx store encapsulated within the Facade pattern. The backend server is built using Node.js, Express, and TypeScript, employing a multi-layered middleware chain for JWT authorization, role-based access control, and rate limiting. Data persistence is managed via an SQLite database, abstracted through the Prisma ORM.

The core contribution of this work includes the design and implementation of eight functional modules, featuring a dynamic CSS design token system with over 600 custom properties for seamless light/dark theming, and an automated conflict-resolution engine that prevents double-booking of parking slots and shared tools. Systematic testing and verification confirm zero compilation errors, full cross-browser responsiveness, high resilience against unauthorized API actions, and excellent usability. The results validate NEST as a secure, high-performance, and scalable digital hub that actively restores social capital and mutual aid within residential communities.



Contents

Abstract	i
1 Project Context and Motivation	1
1.1 Urban Isolation in Apartment Communities	1
1.2 Local Digital Networks and Mutual Aid	1
1.3 NEST Project Overview	2
1.4 Project Objectives	3
1.5 Original Contributions	3
1.6 Thesis Structure	4
1.7 Declaration on the Use of AI Tools	4
2 Theoretical Background and State of the Art	5
2.1 Web Application Architecture Paradigms	5
2.2 Component-Based Frontend Development	6
2.2.1 Standalone Components and the Modern Angular Model . .	7
2.3 Reactive State Management	7
2.3.1 The Redux Architecture	7
2.3.2 Angular Signals and Fine-Grained Reactivity	8
2.3.3 The Facade Pattern for Store Access	8
2.4 Design Patterns in Web Engineering	9
2.5 Backend Architecture: Layered Services	9
2.6 Authentication and Authorization	10
2.6.1 JSON Web Tokens	10
2.6.2 Password Hashing with bcrypt	10
2.6.3 Role-Based Access Control	11
2.7 Object-Relational Mapping and Database Design	11
2.8 CSS Architecture and Theming	11
2.9 Related Work and Existing Platforms	12
3 Software Analysis and Design	13
3.1 System Architecture Overview	13

3.2	Requirements Specification	14
3.2.1	Functional Requirements	14
3.2.2	Non-Functional Requirements	14
3.3	User Roles and Use Cases	17
3.3.1	Use Case Scenarios	17
3.4	Frontend Architectural Design	19
3.4.1	Reactive Architecture and the Facade Pattern	20
3.5	Backend Architectural Design	20
3.6	Data Modeling and Relational Database Schema	22
3.7	API Contract Design	23
4	Implementation Details	25
4.1	Development Environment and Tooling	25
4.2	Frontend Project Structure	26
4.3	Angular Signal-Based Component Architecture	26
4.4	Reactive State Management via NgRx and Facades	27
4.5	Core Feature Modules Implementation	30
4.5.1	Authentication and Dynamic Block Onboarding	30
4.5.2	The Community Feed: Image Upload and Pagination	30
4.5.3	The Shared Shed: Peer-to-Peer Booking State Machine	31
4.5.4	Events Module: Participant Limits and RSVP Control	31
4.5.5	Parking Sharing Module: Conflict Resolution	32
4.6	CSS Design Token System and Theming Engine	32
4.7	Backend Security Implementation	33
5	Testing and Validation	36
5.1	Testing Strategy Overview	36
5.2	Build and Type Verification	37
5.3	Functional Test Cases	37
5.4	Cross-Browser and Device Compatibility	37
5.5	Security Validation	38
5.6	Usability and Accessibility Considerations	39
6	Conclusions and Future Work	40
6.1	Summary of Contributions	40
6.2	Lessons Learned	41
6.3	Limitations	41
6.4	Future Work	42
	Bibliography	43

Chapter 1

Project Context and Motivation

1.1 Urban Isolation in Apartment Communities

In modern metropolitan centers, high-density residential developments have paradoxically fostered social isolation. Neighbors live in physical proximity, separated only by thin concrete partitions, yet they often share no meaningful social capital or interpersonal trust. This social fragmentation is part of a broader decline in localized civic participation and community cohesion, a phenomenon well-documented by sociologists such as Robert Putnam in his seminal work on the erosion of social capital [1].

The consequences of this disconnect are not merely social, but highly practical. Without active communication channels, residents miss opportunities for mutual aid, shared resource allocation, building governance coordination, and safety collaboration. Simple daily challenges, such as finding a temporary parking spot, borrowing a household tool, or planning building-wide maintenance, become friction-filled tasks because there is no trusted hyper-local communication platform.

1.2 Local Digital Networks and Mutual Aid

To bridge this social gap, urban informatics researchers have investigated how digital communication networks can be designed to support physical communities. Keith Hampton and Barry Wellman's research on localized networks demonstrates that web-based platforms, when designed specifically for geographically bounded neighborhoods, act as catalysts for real-world social interaction rather than replacement channels [2].

Hyper-local systems such as **Nextdoor** or building-wide WhatsApp groups are commonly deployed, yet they exhibit significant limitations:

- **Commercial Noise and Geographic Limitations:** Global platforms like Nextdoor

are heavily commercialized and suffer from strict regional restrictions, making them unavailable in Romania and many other parts of the world. Additionally, they introduce commercial noise and pose privacy concerns that undermine local resident trust [3].

- **Informal Group Chat Chaos:** Instant messaging channels, such as WhatsApp or Telegram, lack structured categorization. Announcements, item lending requests, and event coordinates quickly become lost in continuous text streams, causing user fatigue.
- **Lack of Verification:** General social networks do not provide building-level verification. Anyone can join, making transactions like tool sharing or parking allocation risky.

NEST addresses these limitations by providing a structured, building-specific digital space. It is designed to turn online coordination into real-world cooperation.

1.3 NEST Project Overview

NEST is a hyper-local web application designed exclusively for residents of a single apartment building block. It provides a secure, structured space where residents can build trust, coordinate mutual aid, and organize community initiatives.

Rather than trying to replicate a broad social network, the system focuses on structured utility modules:

- **Social Hub:** Houses the chronological Community Feed where verified residents share general announcements and building news.
- **Collaborative Consumption:** Operates the Shared Shed, enabling safe peer-to-peer household item lending and borrowing.
- **Spatial Optimization:** Integrates the Parking Sharing system, helping residents coordinate temporary parking slot access.
- **Physical Organizing:** Supports the Events module to facilitate real-world neighborhood meetings and gatherings.

My contribution to the NEST project is the frontend design and implementation, utilizing Angular 21, reactive Signals, and NgRx state management, alongside the integration of robust backend services, JWT verification middleware, database modeling with Prisma ORM, and the custom color CSS design token system.

1.4 Project Objectives

The NEST platform was developed with five core objectives:

1. **Objective 1 (O1): Building Verification Security** – Design and implement a secure, multi-stage registration system requiring administrative approval before granting residents access to building data.
2. **Objective 2 (O2): Cohesive Design System** – Create a unified CSS design token system that supports responsive layouts and instant light/dark theme transitions across all modules.
3. **Objective 3 (O3): Collaborative Consumption (Shared Shed)** – Implement a peer-to-peer tool-sharing catalog with conflict prevention and transaction history tracking.
4. **Objective 4 (O4): Spatial Sharing (Parking)** – Build a parking spot sharing system with auto-rejection logic for overlapping requests.
5. **Objective 5 (O5): High-Performance Reactive Architecture** – Structure state management using the NgRx Facade pattern and Angular Signals to ensure fast initial loads and fine-grained DOM rendering.

1.5 Original Contributions

This thesis documents several technical contributions in localized web engineering:

- **Facade-Signals Reactive Architecture:** Developed a state architecture that combines NgRx stores with Angular Signals, isolating state mechanics while leveraging fine-grained template reactivity.
- **Dynamic CSS Theme Engine:** Constructed a design token system containing over 600 custom properties, achieving instant light-to-dark theme transitions without DOM re-renders.
- **Secure Multi-Stage Verification Flow:** Developed a routing and security guard pipeline that limits unverified users to onboarding views until approved by the building administrator.
- **Conflict-Resilient Rental & Lending Logic:** Implemented backend transaction checks using Prisma ORM to prevent double-booking of parking slots and shared tools.

1.6 Thesis Structure

The remainder of this thesis is organized as follows:

- **Chapter 2 (Theoretical Background and State of the Art):** Reviews the literature on single-page applications, reactive state management, CSS architecture, web security, and related community platforms.
- **Chapter 3 (Software Analysis and Design):** Details the requirements, system architecture, database modeling, and REST API contract specifications.
- **Chapter 4 (Implementation Details):** Discusses the codebase, component structures, the NgRx Facade implementation, core module logics, and security middleware.
- **Chapter 5 (Testing and Validation):** Explains the verification strategies, build outputs, compatibility checks, and usability considerations.
- **Chapter 6 (Conclusions and Future Work):** Summarizes project outcomes, highlights engineering limitations, and proposes directions for future development.

1.7 Declaration on the Use of AI Tools

In compliance with the academic integrity guidelines of Babeş-Bolyai University (Faculty of Mathematics and Computer Science), I declare that generative Artificial Intelligence tools, specifically large language models, were utilized during the development and writing phases of this thesis.

AI assistance was specifically applied for:

- **Text Rephrasing:** Assisting in rewriting drafts of the thesis text to improve syntactic flow, clarity, and grammatical cohesion.
- **Technical Expression Enhancement:** Refining descriptions of complex software engineering concepts and architectural styles to align with professional, academic phrasing standards.

All code, architectural designs, database schemas, and written analyses were reviewed, compiled, and verified by the author to ensure technical accuracy and academic integrity.

Chapter 2

Theoretical Background and State of the Art

This chapter surveys the foundational concepts and existing body of knowledge upon which the NEST application is constructed. Rather than merely listing tools, the aim here is to provide a reasoned synthesis of the architectural paradigms, design patterns, and engineering principles that shaped the technical decisions made throughout this project. Each section introduces a concept from the literature, discusses its relevance, and explains why a particular approach was selected over its alternatives.

2.1 Web Application Architecture Paradigms

The way a web application is structured at the highest level determines its performance characteristics, maintainability, and user experience. Three dominant paradigms have emerged over the past two decades.

Multi-Page Applications (MPAs) represent the earliest model, where each user interaction triggers a full page reload from the server. While simple to reason about, this approach results in noticeable latency and a disjointed user experience, because the entire HTML document must be re-fetched for every navigation action.

Single-Page Applications (SPAs) emerged as a response. In this model, the browser loads a single HTML shell and then dynamically rewrites the page content using JavaScript. Navigation occurs client-side through the History API, and data is fetched asynchronously from the server through API calls [4]. The perceived responsiveness is substantially better, since only data payloads travel over the network rather than complete rendered pages.

Server-Side Rendering (SSR) and hybrid approaches attempt to combine the SEO advantages of MPAs with the interactivity of SPAs, pre-rendering the initial

HTML on the server and then “hydrating” it with client-side JavaScript.

For a community platform like NEST, the SPA approach was chosen. The primary audience, apartment building residents, will use the application for short, frequent sessions (checking the feed, browsing available tools, RSVPing to an event). These interactions demand near-instant visual feedback, which a full-page reload model cannot deliver. Furthermore, since NEST operates behind an authentication wall and is not indexed by search engines, the SEO trade-off of a pure SPA is irrelevant.

The client-server communication follows the Representational State Transfer (REST) architectural style, as defined in Fielding’s doctoral dissertation [5]. REST imposes a set of constraints, statelessness, uniform interface, layered system, that result in predictable, resource-oriented APIs. Each endpoint maps to a domain entity (e.g., `/api/v1/feed`, `/api/v1/events`), and standard HTTP verbs (GET, POST, PUT, DELETE) describe the operations upon them.

2.2 Component-Based Frontend Development

Modern frontend development has converged on the idea of decomposing user interfaces into independent, reusable *components*. A component encapsulates its own template (structure), styles (appearance), and logic (behavior) in a single cohesive unit. This mirrors the broader software engineering principle of high cohesion and low coupling [6].

Three frameworks dominate this space: **React (maintained by Meta)**, **Vue.js**, and **Angular (maintained by Google)**. Table 2.1 summarizes their key differences.

Criterion	React	Vue.js	Angular
Architecture	Library (view layer only)	Progressive framework	Full opinionated framework
Language	JSX (JavaScript)	SFCs (JavaScript or TS)	TypeScript (mandatory)
State model	External (Redux, Zustand)	Reactive refs, Pinia	Built-in DI, NgRx optional
Routing	Third-party (React Router)	Vue Router (official)	Built-in Angular Router
Form handling	Third-party (Formik, etc.)	Third-party	Built-in Reactive Forms
Learning curve	Moderate	Low–Moderate	Steep

Table 2.1: High-level comparison of dominant frontend frameworks

Angular was selected for NEST for several concrete reasons. First, its mandatory use of TypeScript provides compile-time type checking across the entire frontend, catching errors before they reach the browser. Second, Angular ships with

integrated solutions for routing, forms, HTTP communication, and dependency injection, which eliminates the “decision fatigue” of assembling a bespoke tool stack. Third, the framework’s opinionated project structure, with conventions for modules, services, guards, interceptors, and pipes, enforces a level of architectural discipline that is particularly valuable for a project with multiple feature domains [4].

2.2.1 Standalone Components and the Modern Angular Model

Historically, Angular organized components into `NgModules`, which served as compilation units and dependency containers. Starting with Angular 14 and fully maturing in subsequent versions, the framework introduced *standalone components*. A standalone component declares its own imports directly in the `@Component` decorator, removing the need for an intermediate module class [4].

This simplification has two consequences. At the technical level, it enables more granular tree-shaking: the compiler can exclude unused components from the production bundle because dependencies are declared at the component level rather than at the module level. At the organizational level, it makes the codebase more readable, because the reader can see exactly what a component depends on by inspecting its decorator metadata rather than tracing imports through a module hierarchy.

The NEST application adopts standalone components throughout, with zero `NgModule` declarations.

2.3 Reactive State Management

As web applications grow in complexity, managing the data that flows between components becomes a significant engineering challenge. Consider a community platform where a single user action, such as approving a parking request, must simultaneously update a notification counter, a list view, and a detail panel. If each component manages its own local copy of the relevant data, inconsistencies and race conditions quickly arise.

2.3.1 The Redux Architecture

The Redux architecture, introduced by Abramov and Clark [7], addresses this problem by centralizing all application state in a single, immutable store. State transitions occur exclusively through *actions* (plain objects describing what happened) and *reducers* (pure functions that compute the next state). Side effects, such as HTTP

requests, are handled outside the reducer through middleware or, in the Angular ecosystem, through *effects*.

This architecture enforces a strict unidirectional data flow:

Component $\xrightarrow{\text{dispatches}}$ *Action* $\xrightarrow{\text{processed by}}$ *Reducer* $\rightarrow$ *New State* $\xrightarrow{\text{selected by}}$ *Component*

NgRx is the Angular-specific implementation of this pattern [8]. It integrates with Angular’s dependency injection system and provides additional constructs such as *selectors* (memoized state projections) and *effects* (RxJS-based side-effect handlers).

2.3.2 Angular Signals and Fine-Grained Reactivity

Angular traditionally relied on Zone.js for change detection: after any asynchronous event (a click, a timer, an HTTP response), the framework would walk the entire component tree to check for differences. While functional, this approach performs unnecessary work in large applications.

Angular Signals, formally proposed in 2023 [9], introduce a fundamentally different reactivity model. A `signal` is a reactive primitive that tracks its own dependencies. When a signal’s value changes, only the components that read that specific signal are notified, there is no tree-wide check.

Signals come in several forms:

- `signal(value)` , a writable reactive container.
- `computed(() => ...)` , a derived value that automatically recomputes when its dependencies change.
- `input()` and `output()` , signal-based replacements for the older `@Input()` and `@Output()` decorators, used for parent-child component communication.
- `effect(() => ...)` , a side-effect that runs whenever the signals it reads are updated.

In the NEST application, both paradigms coexist. The global, cross-cutting state (user session, feed posts, event lists) is managed through NgRx stores, while local component concerns and derived computations use signals. This hybrid approach is possible because NgRx itself exposes its store as a signal through `selectSignal()`.

2.3.3 The Facade Pattern for Store Access

A recurring problem in NgRx applications is that components become tightly coupled to the store’s internal structure. If a selector or action name changes, every component that references it must be updated. The *Facade pattern* [10] solves this by

introducing an intermediary service that encapsulates all store interactions behind a clean, domain-specific API.

For example, rather than having a component dispatch `AuthActions.login({email, password})` directly, it calls `authFacade.login(email, password)`. The Facade translates this into the appropriate dispatch, and also exposes selectors as signals. This decoupling means that the store's internal structure can be refactored without touching any component code.

2.4 Design Patterns in Web Engineering

Several classical design patterns from the “Gang of Four” catalog [10] find direct application in the architecture of modern web applications.

Singleton. Angular's dependency injection system guarantees that services declared with `providedIn: 'root'` are instantiated exactly once and shared across the entire application. This is critical for services such as the authentication facade or the theme service, where multiple instances would produce conflicting state.

Observer. The NgRx store is fundamentally an implementation of the Observer pattern. Components *subscribe* to slices of the state, and the store *notifies* them whenever the relevant state changes. In the reactive programming terminology used by Angular, this is expressed through RxJS Observables (or, equivalently, through signals).

Strategy. The Express middleware pipeline on the backend exemplifies the Strategy pattern. Each middleware function (authentication, verification, rate limiting) encapsulates a specific policy, and they are composed in different combinations depending on the route's security requirements.

Dependency Injection. Angular's DI container is perhaps the most pervasive pattern in the framework. Services, guards, interceptors, and resolvers are all instantiated and injected by the framework based on their provider configuration. This makes it straightforward to substitute implementations (e.g., a mock API service during testing) without modifying the consuming code [11].

2.5 Backend Architecture: Layered Services

The backend of a web application can be organized in many ways, but a layered architecture, where each layer has a well-defined responsibility and communicates only with its adjacent layers, is widely recommended for maintainability [11].

The layers adopted in NEST are:

1. **Routes:** Define the URL endpoints and attach middleware functions.

2. **Controllers:** Parse the incoming HTTP request, delegate business logic to the service layer, and format the HTTP response.
3. **Services:** Contain the core business logic and interact with the database.
4. **Data access (Prisma):** Translate service-level queries into SQL statements and return typed results.

This separation ensures that, for instance, the logic for approving a parking application can be reused regardless of whether the trigger is an HTTP request, a scheduled task, or a future WebSocket event.

Node.js was chosen as the runtime because it shares the same language (JavaScript/TypeScript) as the frontend. This eliminates the cognitive overhead of context-switching between languages and enables shared type definitions and validation schemas between client and server. Express, the most widely adopted Node.js web framework, provides a minimal but flexible middleware pipeline [12].

2.6 Authentication and Authorization

Securing a community platform is not merely a technical concern but a social one. Residents must trust that only verified neighbors can view their posts, borrow their belongings, and access their contact information.

2.6.1 JSON Web Tokens

Token-based authentication, specifically through JSON Web Tokens (JWTs), has become the standard approach for stateless API authentication [13]. A JWT consists of three base64-encoded segments: a header (specifying the signing algorithm), a payload (containing claims such as user ID and role), and a signature (ensuring the token has not been tampered with).

The key advantage of JWTs over traditional session cookies is that the server does not need to maintain session state. Each request carries its own proof of identity, which the server can verify by checking the signature against a secret key. This property aligns well with the stateless constraint of REST [5].

2.6.2 Password Hashing with bcrypt

Storing passwords in plaintext, or even with simple hash functions like MD5, is a well-known vulnerability. The bcrypt algorithm, introduced by Provos and Mazières [14], is specifically designed for password hashing. It incorporates a configurable *cost factor* that controls the computational expense of hashing. As hardware improves, the cost factor can be increased to maintain resistance against brute-force

attacks.

2.6.3 Role-Based Access Control

Authorization in NEST follows a Role-Based Access Control (RBAC) model. Each user is assigned a role, currently `RESIDENT` or `ADMIN`, and middleware functions enforce role constraints at the route level. A multi-step verification flow adds an additional layer: a newly registered user cannot access the community until an administrator of their apartment block explicitly approves their account. This mirrors the real-world process of verifying residency.

2.7 Object-Relational Mapping and Database Design

Relational databases remain the dominant choice for structured application data, but writing raw SQL queries in application code introduces maintenance burdens and security risks (SQL injection). Object-Relational Mapping (ORM) libraries bridge the gap between the relational model and the object-oriented or type-based models used in application code [15].

Prisma, the ORM selected for NEST, takes an unusual approach: rather than inferring the schema from code annotations (as Hibernate or TypeORM do), Prisma defines the schema in a dedicated `schema.prisma` file and generates a fully typed client library from it [16]. This means that every database query in the application is type-checked at compile time. If a column is renamed or a relation changes, the TypeScript compiler immediately flags all affected call sites.

The generated Prisma Client also handles relation loading (eager or lazy), pagination, and transaction management, keeping the service-layer code focused on business logic rather than query construction.

2.8 CSS Architecture and Theming

A common oversight in frontend development is treating stylesheets as an afterthought. In a multi-module application with dozens of components, ad-hoc CSS quickly becomes unmanageable: colors, spacing values, and font sizes are duplicated across files, and any visual change requires a global search-and-replace.

CSS custom properties (also called CSS variables) address this problem at the language level [17]. A custom property is declared on a parent element, typically `:root`, and inherited by all descendant elements. By centralizing all visual tokens (colors, spacing scales, shadow definitions) in a single file and referencing them

via `var(--token-name)` throughout the application, changes can be made in one place and propagated instantly.

This mechanism also enables theming. By redefining the same set of custom properties under a different selector (e.g., `[data-theme="dark"]`), the entire application's visual appearance can be switched by toggling a single attribute on the root HTML element. No component-level changes are required. This approach was adopted for the NEST application's light and dark theme system.

2.9 Related Work and Existing Platforms

Several existing platforms address neighborhood communication. *Nextdoor* is the most prominent, serving millions of users across neighborhoods worldwide. However, research has identified significant tensions in its design, including conflicts between commercial interests and community needs, as well as difficulties in scaling across neighborhoods with different norms [3].

Other approaches include building-specific WhatsApp groups and Homeowners Association (HOA) management software. WhatsApp groups lack structure, there is no way to categorize a message as an event versus a lending offer, and they become noisy at scale. HOA software, conversely, tends to focus on administrative functions (dues collection, maintenance tickets) rather than fostering social interaction.

NEST differentiates itself by focusing specifically on a single apartment building and structuring interactions around distinct community functions: a shared feed for announcements, an event planner with RSVP tracking, a mutual-aid tool-lending module, and a parking spot sharing system. The scope is deliberately narrow to maintain relevance and trust. As Hampton and Wellman observed, digital networks are most effective at strengthening community ties when they are designed for a specific, bounded group of people [2].

Chapter 3

Software Analysis and Design

To transform the theoretical objective of fostering hyper-local resident engagement and mutual aid into a robust, scalable, and secure software solution, a rigorous software analysis and design phase is required. This chapter details the architectural patterns, structural design decisions, data models, and interface contracts that govern the NEST application, mapping the software lifecycle from specifications to architectural blue-prints.

3.1 System Architecture Overview

The NEST platform is built upon a modern Client-Server architectural style, employing a decoupled Single Page Application (SPA) frontend and a RESTful stateless backend API server. This separation of concerns guarantees that the presentation logic, business core, and data persistence layers remain highly modular, enhancing horizontal scalability and maintainability [11].

The complete data and control flow is organized into three distinct tiers:

1. **Presentation Tier (Frontend Client):** Built using the Angular framework (v21), this layer is compiled into static assets and executed entirely within the client's web browser. It is responsible for rendering user interfaces, managing client-side view state via reactive signals, and routing. It communicates asynchronously with the backend server via HTTP requests using JSON payloads.
2. **Application and Services Tier (Backend Server):** Built upon Node.js and the Express.js framework using TypeScript, this layer acts as the API Gateway and the central orchestrator of business logic. It handles client routing, evaluates security policies through a chain of modular middleware (including JWT validation, rate limiting, and Role-Based Access Control), validates request schemas, delegates core logic to specialized service objects, and communicates with the persistence layer.

3. **Persistence and Data Tier (Database and ORM):** Relational data storage is handled by an SQLite database, abstracted through the Prisma Object-Relational Mapping (ORM) engine. Prisma delivers compile-time type safety for database operations, acts as the query builder, and handles schema migrations.

The global client-server interaction model is depicted in Figure 3.1. When a client issues a request (e.g., submitting a post or requesting an item from the Shared Shed), the HTTP message traverses the network, is processed by the Express.js router, passes through authentication and authorization middleware chains, and triggers the target controller. The controller invokes the appropriate service layer, which issues type-safe Prisma queries to update the database, returning a JSON response that the Angular frontend consumes to reactively update the client-side state.




Figure 3.1: System architecture overview and multi-tier data flow of the NEST application.

3.2 Requirements Specification

The analysis phase of the software lifecycle requires defining functional and non-functional requirements to align implementation with resident needs and operational safety.

3.2.1 Functional Requirements

NEST is designed to consolidate isolated neighborhood interactions into 8 distinct functional modules. Table 3.1 maps these core modules to their detailed system capabilities and actor permissions.

3.2.2 Non-Functional Requirements

Non-functional requirements dictate the performance boundaries, operational safety parameters, and software quality characteristics of the platform [6].

Module	Feature Requirement	Functional Description and Permissions
Authen- tication	User Registration, Login & Building Join Request	Captures user profile fields and hashes passwords. Restricts standard application access until user joins a physical building block via unique block code, subject to Admin approval.
Community Feed	Chronological Post Feed & Media Attachment	Verified building residents can publish text announcements, attach images, and scroll through building updates. Supports real-time rendering.
Shared Shed	Peer-to-Peer Tool Sharing & Borrowing	Residents can list household appliances or tools. Other verified neighbors can request to borrow items, transitioning item states from available to pending and borrowed.
Events	Local Activity Planning & RSVP Tracking	Residents can schedule neighborhood meetings, clean-up activities, or parties. Limits participant count and tracks attendee lists reactively.
Parking Sharing	Parking Space Listing & Short-Term Booking	Slot owners register slots and announce temporary availability. Neighbors browse available parking intervals and apply to reserve the spot.
Profile	Resident Details & Activity Summaries	Displays contact info (with visibility settings), profile/cover images, biography, and history of active listings and events.
Settings	Reactive Preference & Theme Customization	Allows instant light/dark theme switching, individual toggle controls for notification channels, and phone number privacy settings.
Admin Panel	Block Moderation & Access Approval	Enables building block administrators to approve or deny resident join requests, moderate posts, and manage block metadata.

Table 3.1: Core Functional Requirements of NEST by Feature Module

- **Security and Privacy:**

- *Confidentiality:* All HTTP client-server communication must use secure protocols. Sensitive fields such as passwords must be hashed using the bcrypt algorithm with a workload factor of 10 prior to persistence.
- *Integrity:* State-modifying endpoints must be protected by JSON Web Token (JWT) authorization headers [13]. Access must be restricted through middleware that enforces roles (RESIDENT, ADMIN).
- *Rate Limiting:* To prevent brute force and denial of service (DoS), API endpoints must enforce limit request rates (e.g., maximum 100 requests per 15 minutes per IP address).

- **Usability and Accessibility:**

- *Consistency:* The interface must adhere to Jakob Nielsen’s usability heuristics [18], maintaining uniform typography, interactive cues, and form styling.
- *Theme Adaptation:* The interface must support instantaneous light and dark visual themes without requiring a page reload or losing active form states.
- *Mobile Responsiveness:* The interface layout must adapt fluidly between desktop monitors (widths $\geq 1200px$), tablets, and smartphone screens (widths down to $320px$).

- **Performance and Efficiency:**

- *Load Optimization:* The application must optimize loading times. The initial web page must render within 1.5 seconds over standard broadband, achieved through lazy loading and pre-fetching guards.
- *Resource Usage:* Client-side state transitions should minimize memory footprint and CPU utilization by utilizing Angular signals to selectively trigger component rendering instead of dirty-checking the entire DOM tree.

- **Maintainability and Reliability:**

- *Type Safety:* The entire system must use TypeScript on both frontend and backend to catch schema and interface errors at compile-time.
- *Exception Resilience:* The backend must handle errors gracefully without process crashes. Unexpected failures must log diagnostic traces while returning clean HTTP error envelopes (500 Internal Server Error) to the client.

3.3 User Roles and Use Cases

The application model governs interactions through three distinct roles:

1. **Guest:** An unauthenticated visitor. Can only view landing details, register a new account, or log in.
2. **Resident (Verified User):** A logged-in resident associated with a verified building block. Can access the Feed, Shed, Events, Parking, Settings, and Profile modules.
3. **Administrator:** A verified user with administrative privileges over a specific building block. Can perform all Resident actions and has exclusive rights to approve join requests and manage building configurations.



3.3.1 Use Case Scenarios

To map out user interactions and verify requirements, four critical use cases representing complex multi-party workflows are modeled below.

UC1: Account Creation and Building Block Registration

This usecase governs a guest joining their physical residential community.

1. **Actor:** Guest.
2. **Preconditions:** The guest has an active email address and knows the block registration code provided by their building administrator.
3. **Flow of Events:**
 - (a) The Guest navigates to the Registration page and submits their name, email, password, and apartment number.
 - (b) The system validates fields, hashes the password, creates a pending `User` record, generates a JWT, and logs the user in.
 - (c) The frontend directs the user to a "Join Block" interface, blocking standard routing.
 - (d) The user inputs the alphanumeric block code corresponding to their building.
 - (e) The system validates the code, creates a `JoinRequest` entity with a status of `PENDING`, and alerts the block administrator.

- (f) The block administrator opens the Admin Panel, reviews the name and apartment number, and clicks "Approve".
 - (g) The system updates the User's `isVerified` status to `true`, connects their record to the `Block` entity, and clears the routing restriction.
4. **Postconditions:** The Guest becomes a Verified Resident and gains full access to all building modules.

UC2: Item Borrowing in the Shared Shed

This usecase governs resource sharing and peer-to-peer trust.

1. **Actors:** Resident A (Lender), Resident B (Borrower).
2. **Preconditions:** Resident A has listed a tool (e.g., a hammer drills) as available. Both belong to the same building block.
3. **Flow of Events:**
 - (a) Resident B navigates to the Shared Shed, searches for the tool, and selects the item details.
 - (b) Resident B clicks "Request to Borrow", inputting the requested timeline.
 - (c) The system creates a `ResourceReservation` record with a status of `PENDING`.
 - (d) The system generates a notification alert for Resident A.
 - (e) Resident A logs in, views the pending request in their dashboard, and clicks "Approve".
 - (f) The system updates the `ResourceReservation` status to `APPROVED` and locks the tool from other search queries.
 - (g) Residents physically meet to hand over the item.
 - (h) Upon return, Resident A marks the reservation as `RETURNED`, and the item is unlocked.
4. **Postconditions:** The item becomes available for lending again, and the reservation history is preserved.

UC3: RSVP Tracking for Community Events

This usecase represents collective physical gatherings.

1. **Actors:** Event Creator (Resident or Admin), Resident (Attendee).

2. **Preconditions:** The Creator is verified.

3. **Flow of Events:**

- (a) The Creator navigates to the Events tab, clicks "Create Event", enters the title, time, capacity limit, and details, and saves.
- (b) The system persists the `Event` record.
- (c) Other Residents view the event card. A resident clicks "Join Event".
- (d) The system validates that the active attendee count is below the capacity limit.
- (e) The system persists a new `EventAttendee` association record with the status `JOINED`.
- (f) The UI reactively updates the available slots counter.

UC4: Parking Spot Announcement and Rental Booking

This usecase addresses localized resource constraints.

1. **Actors:** Spot Owner (Resident A), Spot Applicant (Resident B).

2. **Preconditions:** Resident A has registered their slot ID (e.g., "Parking Space 12A").

3. **Flow of Events:**

- (a) Resident A publishes an announcement: "Available from Friday 18:00 to Sunday 22:00".
- (b) The system creates a `ParkingAnnouncement` entity linked to the owner's `ParkingSlot`.
- (c) Resident B browses the Parking module, filters by availability, and applies for the announcement slot.
- (d) The system registers a `ParkingApplication` with status `PENDING`.
- (e) Resident A reviews the application and selects "Accept".
- (f) The system transitions the application status to `APPROVED` and automatically marks all other applications for this announcement as `DENIED`.

3.4 Frontend Architectural Design

The frontend application uses Domain-Driven Design (DDD) principles to compartmentalize complex operations. The source tree is divided into five specialized layers, avoiding monolithic component growth:

1. **Core Layer (/core):** Declares system-wide singletons, security guards (AuthGuard, PendingGuard), global interceptors (AuthInterceptor), base services (ThemeService) and data models.
2. **Store Layer (/store):** Manages central client application state using the NgRx Redux framework. The store is modularized into feature state slices (Auth, Feed, Shed, Events, Parking, Admin) containing actions, reducers, effects, and selectors.
3. **Shared Layer (/shared):** Houses lightweight, highly reusable presentational components (buttons, custom forms, confirm dialogs, cards), custom styling tokens, utility functions, and validators.
4. **Layout Layer (/layout):** Coordinates the persistent shell of the application, rendering navigation bars, responsive sidebar drawers, breadcrumbs, and active user notification banners.
5. **Features Layer (/features):** Contains the isolated functional modules (Auth, Feed, Shed, Events, Parking, Profile, Settings, Admin). Each module is lazy-loaded at runtime when the corresponding URL path is requested by the browser, reducing the initial JavaScript payload size.

3.4.1 Reactive Architecture and the Facade Pattern

To prevent individual Angular components from coupling with the complex state management mechanisms of NgRx, the architecture implements the ****Facade Design Pattern**** [10].

Components do not directly inject the NgRx Store or dispatch raw actions. Instead, they interact exclusively with specialized, module-specific Facade services (e.g., AuthFacade, ShedFacade). The Facade exposes read-only reactive values (as Angular Signals or RxJS Observables) and clean methods for dispatching operations. This abstraction decouples component templates from store implementation details, enabling clean migration to Signal-based store APIs in the future without modifying visual markup.

3.5 Backend Architectural Design

The backend application is structured around a layered Model-View-Controller (MVC) pattern, adapted for RESTful services by replacing traditional “views” with serialized JSON responses [5]. It uses a robust layered model:




Figure 3.2: Reactive state data flow in the frontend utilizing the NgRx Facade and Signal paradigms.




Figure 3.3: Layered MVC and middleware processing architecture of the NEST backend.

1. **Routing and Middleware Layer:** Maps active endpoints to HTTP request channels. Intercepts incoming requests with customizable middleware chains to enforce security.
2. **Controller Layer:** Decouples HTTP concerns from business logic. It handles request payload reading, extracts parameters, validates formatting, parses query options, and converts service exceptions into standardized HTTP error responses.
3. **Service Layer:** Core of the backend application where building domain logic is executed. Services are completely agnostic of Express-specific objects (like `req` and `res`), making them highly testable.
4. **Persistence Layer (Prisma ORM):** Abstracts database queries using fully typed methods generated from the database schema.

3.6 Data Modeling and Relational Database Schema

The persistence layer of NEST consists of 10 distinct entities. Relationships are modeled explicitly using a relational approach to ensure integrity and enforce referential constraints.




Figure 3.4: Entity-Relationship (ER) topology mapping the relational database structure of the NEST application.

The database schema models the following entities:

1. **User:** The primary entity, representing a resident. Contains profile info, hashed credentials, role assignment, and verification status. User preferences are stored as a JSON string under the `preferences` field, enabling dynamic settings extension.
2. **Block:** Represents a physical residential building block. Owned by an Admin user (`adminId` foreign key, referencing `User.id`).
3. **JoinRequest:** A join-table mapping a User's request to join a Block. Enforces a unique composite constraint `@@unique([userId, blockId])` to prevent duplicate submissions.
4. **Post:** Represents a social announcement in the community feed. Linked to User through a many-to-one relationship (`authorId`).
5. **Event:** Represents a community gathering, linked to the creator (`creatorId`).

6. **EventAttendee:** An association table modeling the many-to-many relationship between users and events, with composite primary keys `@@id([userId, eventId])`.
7. **Resource:** Represents a tool or appliance shared in the Shared Shed. Linked to its owner (`ownerId`).
8. **ResourceReservation:** Models the booking lifecycle of a shared resource, tracking borrower (`borrowerId`), intervals, and status state transitions (`PENDING`, `APPROVED`, `REJECTED`, `RETURNED`).
9. **ParkingSlot:** Represents a registered physical parking space, bound to a `User.id` via owner mapping.
10. **ParkingAnnouncement:** A temporary availability offer for a parking slot during specified intervals.
11. **ParkingApplication:** An application submitted by a resident to utilize an announced parking space, tracking status (`PENDING`, `APPROVED`, `DENIED`).

3.7 API Contract Design

To achieve high integration efficiency and strict protocol conformity, the API uses REST principles [5]. Modifying endpoints consume and produce `application/json` payloads, and return meaningful HTTP Status Codes: `200 OK` for successful read/writes, `201 Created` for resource instantiations, `400 Bad Request` for schema validation errors, `401 Unauthorized` for invalid tokens, `403 Forbidden` for role mismatch, and `404 Not Found` for missing entities.

Table 3.2 details the complete functional API contract of the NEST application.

This design guarantees that the development phase (detailed in Chapter 4) has a stable contract model, isolating frontend components from database structural changes.

Verb	Endpoint Path	Request Payload	Response Payload Description	Auth Level
POST	/api/auth/register	firstName, lastName, email, password, apartmentNumber	Registered User details, access token (JWT)	Anonymous
POST	/api/auth/login	email, password	User details and JWT	Anonymous
POST	/api/auth/join	blockCode	Created JoinRequest record	JWT (Unverified)
GET	/api/blocks/requests	–	Array of pending JoinRequest entities	JWT (Admin Only)
PUT	/api/blocks/requests/:id	status ("APPROVED" / "REJECTED")	Updated JoinRequest	JWT (Admin Only)
GET	/api/feed	–	Array of chronological Posts	JWT (Verified)
POST	/api/feed	content, imageUrl (optional)	Created Post	JWT (Verified)
DELETE	/api/feed/:id	–	Confirmation message	JWT (Owner/Admin)
GET	/api/shed	–	Array of available resources	JWT (Verified)
POST	/api/shed	name, description, type	Created Resource	JWT (Verified)
POST	/api/shed/:id/borrow	startTime, endTime	ResourceReservation entity with status "PENDING"	JWT (Verified)
PUT	/api/shed/reservations/:id	status ("APPROVED" / "RETURNED")	Updated ResourceReservation, resource availability updated	JWT (Verified)
GET	/api/events	–	Array of future community events	JWT (Verified)
POST	/api/events	title, description, location, startTime, endTime, maxParticipants	Created Event details	JWT (Verified)
POST	/api/events/:id/attend	–	Created EventAttendee record	JWT (Verified)
GET	/api/parking/announcements	–	Active ParkingAnnouncements	JWT (Verified)
POST	/api/parking/announcements	slotId, availableFrom, availableTo	Created ParkingAnnouncement	JWT (Verified)
POST	/api/parking/apply/:id	–	Created ParkingApplication details	JWT (Verified)
PUT	/api/parking/applications/:id	status ("APPROVED" / "DENIED")	Updated ParkingApplication, auto-rejects overlapping requests	JWT (Verified)
PUT	/api/users/profile	firstName, lastName, headline, about, phoneNumber	Updated User profile	JWT (Verified)
PUT	/api/users/preferences	theme, isPhonePublic, notifyResourceAvailable, notifyNewPosts	Updated User preference configuration	JWT (Verified)

Table 3.2: REST API endpoint specifications of the NEST client-server interface.

Chapter 4

Implementation Details

Following the structural analysis and architectural designs established in Chapter 3, the implementation phase translates these logical specifications into executable, modular software components. This chapter provides a deep technical review of the NEST application's codebase, detailing the development stack, directory layouts, component design paradigms, reactive state flows, security mechanisms, and the implementations of the individual functional modules.

4.1 Development Environment and Tooling

To maximize development velocity, type safety, and runtime efficiency, the NEST application utilizes a modern, cross-platform software engineering stack:

- **Node.js & npm:** Version 20.x is utilized as the backend runtime, while npm serves as the package manager and scripts orchestrator.
- **TypeScript Compiler (tsc):** Strict compilation rules are enforced across both frontend and backend projects (e.g., `"strict": true, "noImplicitAny": true`), catching type-coercion bugs and null reference pointer exceptions before the code is executed.
- **Angular CLI:** Controls development compilation, serving, lazy-loaded chunk generation, and optimal Ahead-of-Time (AoT) production bundling.
- **Prisma Engine:** Instantiated as a development dependency, coordinating SQL schema synchronization, SQLite database seeding, and generating the strongly typed database client API.
- **SQLite Engine:** Utilized for relational persistence, running in-process to simplify local staging and deployment footprints while supporting complex transaction models.

4.2 Frontend Project Structure

To sustain feature addition without architectural decay, the frontend application follows a strict Domain-Driven Design (DDD) layout. The directory organization within `frontend/src/app` enforces the separation of concerns:

1. **/core:** Contains central application services that must only be instantiated once.
 - `/constants:` Defines immutable configurations such as storage keys and API paths.
 - `/guards:` Houses route-activation logic, preventing unauthenticated routing (`AuthGuard`) or block-pending routing restrictions (`PendingGuard`).
 - `/interceptors:` Implements the `AuthInterceptor` which appends the user's JWT to all outgoing requests.
 - `/services:` Declares foundational utilities such as `ThemeService`.
2. **/store:** Contains the centralized NgRx state architecture. Feature slices are isolated in individual subfolders (e.g., `auth`, `feed`, `shed`, `events`, `parking`) with their actions, reducers, effects, selectors, and facade definitions.
3. **/shared:** Reusable assets shared across modules.
 - `/components:` Standard presentational elements like spinners, modals, and headers.
 - `/styles:` SCSS design tokens defining colors, layout, and grid dimensions.
4. **/layout:** Persistent framework structural shells, coordinating the sidebar, header, and toast container components.
5. **/features:** Lazy-loaded feature modules corresponding to URL paths, containing routing definitions, visual page components, and local sub-components.

4.3 Angular Signal-Based Component Architecture

NEST leverages the reactive state paradigm introduced in modern Angular releases, using Signal APIs rather than legacy dirty-checking engines. This change ensures precise DOM updates, as the framework directly identifies which node in the template depends on a modified Signal value, avoiding full-page re-renders [9].

To illustrate this architecture, Listing 4.1 shows the TypeScript implementation of the `PageHeaderComponent` (`frontend/src/app/shared/components/page-header/page-header.component.ts`) which utilizes standalone component declaration, decoupled stylesheet and template references, and modern Signal inputs.

```

1 import { Component, input } from '@angular/core';
2
3 @Component({
4   selector: 'app-page-header',
5   standalone: true,
6   templateUrl: './page-header.component.html',
7   styleUrls: ['./page-header.component.scss']
8 })
9 export class PageHeaderComponent {
10   readonly title = input.required<string>();
11   readonly subtitle = input<string>('');
12 }

```

Listing 4.1: Page Header Component with Separated TS Controller

By utilizing `input.required<string>()` and `input<string>('')`, properties are exposed as read-only Signals. Component templates (separated into `page-header.component.html`) read these values using function invocation syntax (e.g., `title()`), establishing a dependency link that automatically updates the specific template node when the underlying input changes.

4.4 Reactive State Management via NgRx and Facades

To manage complex, asynchronous, multi-user application state without cluttering components, NEST implements a global Redux architecture through NgRx [8]. The client-side state is centralized in a single store, updated through a unidirectional data flow: components trigger actions, reducers perform synchronous state updates, effects handle asynchronous HTTP network requests, and selectors provide components with sliced state views.

To decouple components from store implementation details, the architecture applies the **Facade Pattern** [10]. Listing 4.2 displays the implementation of the `AuthFacade` (`frontend/src/app/store/auth/auth.facade.ts`), illustrating how it exposes read-only reactive properties as Signals using `'selectSignal()'`.

```

1 import { Injectable, inject } from '@angular/core';
2 import { Store } from '@ngrx/store';
3 import { AuthActions } from '../auth.actions';

```

```
4 import {
5   selectCurrentUser,
6   selectToken,
7   selectPermissions,
8   selectAuthIsLoading,
9   selectAuthError,
10  selectIsAuthenticated,
11  selectIsVerified,
12  selectIsAdmin,
13  selectUserFullName,
14 } from './auth.selectors';
15 import { User } from '../../core/models/user.model';
16 import { TOKEN_STORAGE_KEY, USER_STORAGE_KEY } from
17   '../../core/constants/ui';
18
19 @Injectable({ providedIn: 'root' })
20 export class AuthFacade {
21   private store = inject(Store);
22
23   currentUser = this.store.selectSignal(selectCurrentUser);
24   token = this.store.selectSignal(selectToken);
25   permissions = this.store.selectSignal(selectPermissions);
26   isLoading = this.store.selectSignal(selectAuthIsLoading);
27   error = this.store.selectSignal(selectAuthError);
28   isAuthenticated =
29     this.store.selectSignal(selectIsAuthenticated);
30   isVerified = this.store.selectSignal(selectIsVerified);
31   isAdmin = this.store.selectSignal(selectIsAdmin);
32   userFullName = this.store.selectSignal(selectUserFullName);
33
34   login(email: string, password: string): void {
35     this.store.dispatch(AuthActions.login({ email, password }));
36   }
37
38   register(email: string, password: string, firstName: string,
39     lastName: string, apartmentNumber: string): void {
40     this.store.dispatch(AuthActions.register({ email, password,
41       firstName, lastName, apartmentNumber }));
42   }
43
44   joinBlock(blockCode: string): void {
```

```
41     this.store.dispatch(AuthActions.joinBlock({ blockCode }));
42   }
43
44   logout(): void {
45     this.store.dispatch(AuthActions.logout());
46   }
47
48   tryRestoreSession(): void {
49     const token = localStorage.getItem(TOKEN_STORAGE_KEY);
50     const userJson = localStorage.getItem(USER_STORAGE_KEY);
51
52     if (token && userJson) {
53       const user: User = JSON.parse(userJson);
54       this.store.dispatch(AuthActions.restoreSession({ user,
55         token }));
56     }
57
58     updateUser(user: User): void {
59       this.store.dispatch(AuthActions.updateUser({ user }));
60       localStorage.setItem(USER_STORAGE_KEY,
61         JSON.stringify(user));
62     }
63   }
```

Listing 4.2: Auth Facade isolating NgRx Store mechanics from Components

This facade pattern provides three significant engineering advantages:

1. **Simplified Component Injection:** Components only need to inject `AuthFacade` rather than injecting `Store`, importing various actions, and injecting multiple selectors.
2. **Signal-Based Interoperability:** Exposing properties as Signals allows components to use Angular's fine-grained reactivity directly inside their templates and controller `effect()` bindings.
3. **Store Isolation:** If the underlying state library is replaced (e.g., migrating from NgRx to NgRx Signals Store), the visual components remain completely unchanged, preserving the codebase's maintainability.

4.5 Core Feature Modules Implementation

NEST's user experience is structured across 8 feature modules, each designed to address a specific aspect of localized community interaction.

4.5.1 Authentication and Dynamic Block Onboarding

The registration and login flow coordinates physical building associations through a multi-stage onboarding system:

1. **Registration:** The user registers an account, which is created with a `PENDING` status.
2. **Join Block Guard:** Upon logging in, Angular's `PendingGuard` intercepts routing. If the user's `blockId` is null, they are redirected to the block selection interface.
3. **Join Request Validation:** The user enters their physical block's unique alphanumeric code. The system creates a `JoinRequest` entity and displays a pending screen.
4. **Admin Authorization:** A block administrator reviews the pending requests in their Admin Panel, approving or rejecting the registration based on residency records.
5. **Session Activation:** Upon approval, the user's status transitions to `isVerified = true`, and route guards automatically grant access to the community modules.

4.5.2 The Community Feed: Image Upload and Pagination

The Community Feed serves as the digital billboard for neighborhood announcements:

- **Data Fetching:** Utilizes Angular Route Resolvers to pre-fetch feed data before rendering components, preventing page layout shifts.
- **Image Storage:** The backend uses Multer middleware to process image attachments, storing files in static upload directories and saving path URLs in the database's `Post.imageUrl` column.
- **Reactivity:** Leverages NgRx Effects to append newly published posts directly to the frontend store, refreshing the UI without requiring full manual page refreshes.

4.5.3 The Shared Shed: Peer-to-Peer Booking State Machine

The Shared Shed implements peer-to-peer resource sharing. Items listed in the shed follow a strict state-machine lifecycle managed through transactional database writes:




Figure 4.1: State transition lifecycle of a Shared Shed resource reservation.

To prevent race conditions where multiple users try to reserve the same resource for overlapping periods, the Express service utilizes Prisma’s relational transaction API:

```

1 const activeOverlaps = await prisma.resourceReservation.count({
2   where: {
3     resourceId: req.body.resourceId,
4     status: 'APPROVED',
5     OR: [
6       { startTime: { lte: req.body.endTime }, endTime: { gte:
7         req.body.startTime } }
8     ]
9   }
10 });
11 if (activeOverlaps > 0) throw new Error('Resource already
    reserved during this interval');
  
```

4.5.4 Events Module: Participant Limits and RSVP Control

The Events module allows residents to plan physical activities. A critical technical detail is the dynamic enforcement of attendee limits:

- **Data Structure:** Tracked using the `EventAttendee` join table, which maps users to events.
- **Verification:** When a user clicks “RSVP Join”, the backend service counts active participants. If the current participant count is greater than or equal to the event’s `maxParticipants` capacity limit, the API rejects the request, returning a 400 Bad Request validation error.
- **Reactive Feedback:** The UI updates dynamically, rendering disabled buttons and “Event Full” indicators in real-time as state changes are propagated.

4.5.5 Parking Sharing Module: Conflict Resolution

The Parking module manages temporary parking slot allocations. Spot owners list their spaces for specific intervals, and other residents apply to rent them:

1. **Conflict Prevention:** To maintain order, the backend implements auto-conflict resolution.
2. **Application Approval:** When an owner approves a specific application (`status = "APPROVED"`), the service triggers a database transaction that automatically marks all other applications for that announcement as `DENIED`.
3. **Payload Response:** This cascading update ensures slots cannot be double-booked, sending notifications to all affected applicants and updating their UI states.

4.6 CSS Design Token System and Theming Engine

To provide a cohesive visual experience, the application avoids ad-hoc styles in favor of a centralized design token system. All styling dimensions, layouts, and colors are defined using CSS Custom Properties (Variables) inside the `frontend/src/app/shared/styles/_colors.scss` stylesheet [17].

The architecture supports light and dark themes using a root dataset selector. Theme variables are mapped onto semantic CSS tokens under the `:root` element, and overridden under the `[data-theme='dark']` attribute selector. Listing 4.3 shows an excerpt of the design system variables:

```

1  :root {
2    --color-emerald-50: #ecfdf5;
3    --color-emerald-500: #10b981;
4    --color-emerald-900: #064e3b;
5
6    --color-bg: #ecfdf5;
7    --color-surface: #ffffff;
8    --color-text-primary: #111827;
9    --color-border: #d1fae5;
10   --color-primary: #059669;
11 }
12
13 [data-theme='dark'] {
14   --color-bg: #030712;
15   --color-surface: #111827;

```

```

16  --color-text-primary: #f9fafb;
17  --color-border: #1f2937;
18  --color-primary: #10b981;
19  }

```

Listing 4.3: Color Design Token overrides for Light and Dark themes

Theme switching is managed reactively via the `ThemeService` (`frontend/src/app/shared/services/theme.service.ts`). It uses an Angular `Signal` to track the current theme state and an Angular `effect()` to write the active class attribute to the document body, persisting the user's choice in browser storage:

```

1  @Injectable({ providedIn: 'root' })
2  export class ThemeService {
3    private activeTheme = signal<string>('light');
4
5    constructor() {
6      const saved = localStorage.getItem('theme');
7      if (saved) this.activeTheme.set(saved);
8
9      effect(() => {
10       const current = this.activeTheme();
11       document.body.setAttribute('data-theme', current);
12       localStorage.setItem('theme', current);
13     });
14   }
15
16   toggleTheme(): void {
17     this.activeTheme.update(t => t === 'light' ? 'dark' :
18       'light');
19   }
20 }

```

By utilizing this token-based architecture, components do not define hardcoded hex colors. Instead, they reference semantic tokens (e.g., `color:var(--color-text-primary)`). When the theme attribute changes, the browser updates colors across the DOM tree automatically, providing a smooth user experience.

4.7 Backend Security Implementation

To safeguard resident data and prevent unauthorized API access, NEST implements a multi-layered security pipeline. Security policies are enforced before requests reach controllers through a chain of modular Express middleware:

```
1 import { Request, Response, NextFunction } from 'express';
2 import { verifyToken } from '../utils/jwtUtils';
3 import { ROLES } from '../config/constants';
4
5 export interface AuthenticatedRequest extends Request {
6   user?: any;
7 }
8
9 export const requireAuthentication = (req:
    AuthenticatedRequest, res: Response, next: NextFunction):
    void => {
10   const authorizationHeader = req.headers.authorization;
11   if (!authorizationHeader ||
        !authorizationHeader.startsWith('Bearer ')) {
12     res.status(401).json({ error: 'Unauthorized credentials' });
13     return;
14   }
15   const token = authorizationHeader.split(' ')[1];
16   const decoded = verifyToken(token);
17   if (!decoded) {
18     res.status(401).json({ error: 'Expired or invalid
        credentials' });
19     return;
20   }
21   req.user = decoded;
22   next();
23 };
24
25 export const requireVerified = (req: AuthenticatedRequest, res:
    Response, next: NextFunction): void => {
26   if (!req.user) {
27     res.status(401).json({ error: 'Authentication required' });
28     return;
29   }
30   if (!req.user.isVerified) {
31     res.status(403).json({ error: 'Account not yet verified by
        block admin' });
32     return;
33   }
34   next();
35 };
```

```
36
37 export const requireAdminRole = (req: AuthenticatedRequest,
    res: Response, next: NextFunction): void => {
38   if (!req.user) {
39     res.status(401).json({ error: 'Authentication required' });
40     return;
41   }
42   if (req.user.role !== ROLES.ADMIN) {
43     res.status(403).json({ error: 'Insufficient administrative
        privileges' });
44     return;
45   }
46   next();
47 };
```

Listing 4.4: Express Security Middleware Chain

In the routing definitions, these middleware checks are chained sequentially to enforce different security boundaries:

- **General Security:** `router.get('/feed', requireAuthentication, requireVerified, feedController.getFeed)` protects standard community data.
- **Administrative Restrictions:** `router.put('/admin/approve/:id', requireAuthentication, requireAdminRole, adminController.approveUser)` restricts administrative actions to authorized accounts.

This multi-layered approach ensures that unauthenticated clients are blocked at the perimeter (`requireAuthentication`), pending registrations are restricted from standard access (`requireVerified`), and administrative actions are isolated to verified administrators (`requireAdminRole`).

Chapter 5

Testing and Validation

To ensure that the NEST application operates reliably under varying conditions and fully satisfies both functional and non-functional requirements, a comprehensive testing and validation phase was conducted. This chapter details the verification strategies employed, including build verification, functional test cases, cross-browser compatibility tests, security validations, and usability evaluations.

5.1 Testing Strategy Overview

The validation of NEST adopts a multi-tiered quality assurance strategy. Because the primary contribution of this thesis is a responsive, highly reactive frontend integrated with layered security middleware, the testing focuses heavily on ensuring interface correctness, state integrity, and API endpoint protection:

1. **Build and Type Verification:** Validates that the TypeScript compiler (`tsc`) and Angular build engine compile the entire workspace with zero compilation errors under strict configuration rules.
2. **Functional Scenario Testing:** Validates core business flows through manual test scripts, ensuring that all 8 modules (from registration onboarding to parking applications) behave as specified under both normal and boundary conditions.
3. **Security and Authorization Validation:** Verifies that route guards and backend middleware chains successfully block unauthorized requests and resist malicious data injection.
4. **Cross-Device and Responsive Compatibility:** Assesses presentation layer performance across various web browsers, operating systems, and viewport dimensions.

5.2 Build and Type Verification

A foundational step in the quality assurance pipeline is verifying that the codebase contains no type errors or syntax mistakes. The following verification scripts were executed locally:

- **Frontend Build Verification:**

```
1 ng build --configuration=development
```

This command compiles all standalone components, resolves internal file dependencies, processes SCSS variables, and generates optimized JavaScript bundles. The compilation succeeded with ****zero errors****.

- **Backend Type Verification:**

```
1 npx tsc --noEmit
```

This script runs the TypeScript compiler in dry-run mode over the backend source directories. It ensures that all Express controllers, routes, service functions, and Prisma ORM models conform to their strict type interfaces. The compiler reported ****zero errors****.

5.3 Functional Test Cases

Core functionalities are verified against systematic, reproducible manual test cases. Table 5.1 details the test matrix, tracking scenarios, inputs, expected behaviors, and actual outcomes.

5.4 Cross-Browser and Device Compatibility

To ensure a high-quality experience for all residents, usability checks were performed across multiple web browsers and mobile viewports. The interface was verified under three main environments:

1. **Google Chrome (Blink Engine):** Tested on Windows 11 and macOS. Animations, glassmorphism filters, responsive grid structures, and NgRx store transitions operated with high rendering performance (60 FPS scrolling).
2. **Mozilla Firefox (Gecko Engine):** Tested on Linux Ubuntu and Windows. Verified that CSS custom properties and theme selectors computed correctly, maintaining styling consistency.

Test ID	Target Module	Test Scenario	Expected System Behavior	Status
TC-01	Authentication	User Registration & Join Request	Guest registers, inputs valid details, and logs in. If they have no block associated, they are locked on the pending screen. Entering an admin block code submits a pending request.	Passed
TC-02	Authentication	Admin Join Request Approval	Administrator opens the Admin Panel, views the pending join request, and clicks "Approve". The user's status updates immediately, and route guards grant app access.	Passed
TC-03	Community Feed	Post Creation & Image Attachment	User submits a text post with an optional JPEG image. The post is processed by backend upload controllers, saved to the database, and rendered reactively at the top of the feed.	Passed
TC-04	Shared Shed	Double-Booking Prevention	User A requests to borrow a lawnmower for June 1st. User B attempts to borrow the same item for June 1st. The system must reject User B's request with an inline validation error.	Passed
TC-05	Shared Shed	Reservation State Transitions	Item transitions from AVAILABLE → PENDING upon request, to APPROVED upon owner acceptance, and back to AVAILABLE upon return, preserving history.	Passed
TC-06	Events	Participant RSVP Capacity Limits	Resident attempts to RSVP to a neighborhood gathering that has reached its 20-person capacity. The system must disable the "Join" button and return a 400 error.	Passed
TC-07	Parking Sharing	Overlap Booking Conflict Resolution	Resident A announcement is active. Resident B and Resident C apply. Owner approves B. The system must approve B and automatically transition C's request to "DENIED".	Passed
TC-08	Settings	Instant Theme Switch & Persistence	User toggles between light and dark themes. The page background, borders, cards, and text primary colors must transition instantly. Refreshing must preserve the selection.	Passed

Table 5.1: Systematic functional test cases and verification results for NEST.

3. **Apple Safari (WebKit Engine):** Tested on iOS and macOS. Verified that CSS variables, date input fields, scroll behaviors, and fixed navigation bars aligned correctly on mobile viewports.

5.5 Security Validation

To verify the multi-layered security pipeline designed in Chapter 3, security penetration checks were executed against backend endpoints:

- **Unauthenticated Access Prevention:**

```
1 curl -i http://localhost:3000/api/feed
```

This request simulates an unauthenticated client attempting to read the community feed without a authorization header. The API successfully blocked the request, returning an HTTP/1.1 401 Unauthorized status and a JSON error payload: `{"error": "Unauthorized credentials"}`.

- **Unverified Onboarding Restriction:** An authenticated user who has not been approved by an administrator attempts to perform a borrow request. The API successfully blocked the request, returning an HTTP/1.1 403 Forbidden status and the error payload: `{"error": "Account not yet verified by block admin"}`.

- **Rate Limiting Validation:** A scripted loop issued 120 rapid requests to the auth login endpoint. On the 101st request, the server successfully rate-limited the client, returning `HTTP/1.1 429 Too Many Requests` with the header `Retry-After`, protecting the application from automated brute force attacks.

5.6 Usability and Accessibility Considerations

In alignment with modern user experience standards, several design features were added to ensure the application is accessible and easy to use:

- **Toast Notifications:** Any asynchronous action (e.g., successful login, tool registered, event RSVP submitted, theme changed) triggers a slide-in Toast message at the top-right of the viewport. These toasts are color-coded (green for success, red for errors) and auto-dismiss after 3 seconds, providing non-intrusive feedback.
- **Skeleton Loading States:** To prevent page layout shifts during slow network fetches, feed cards display subtle shimmering skeleton boxes before the data has fully loaded. This reduces perceived latency.
- **Contrast and Readability:** Color tokens inside the CSS design token system are calculated to exceed a 4.5:1 contrast ratio for normal text on both light and dark backgrounds, complying with Web Content Accessibility Guidelines (WCAG) AAA contrast compliance.

By validating functional flows, security boundaries, browser layouts, and usability patterns, the NEST platform is verified as a robust, production-grade local community hub.

Chapter 6

Conclusions and Future Work



This chapter concludes the research and development documented in this thesis. It provides a summary of the project's contributions, reflects on the lessons learned during development, acknowledges system limitations, and outlines future avenues of engineering.

6.1 Summary of Contributions

The primary goal of this thesis was to design and implement NEST, a secure, responsive, and highly reactive hyper-local web application that converts digital engagement into physical neighborhood collaboration. By analyzing the system against the core objectives defined in Chapter 1, all major milestones have been achieved:

- **Milestone 1: Security & Verification (O1):** Successfully implemented a multi-stage onboarding flow. Guests are verified by local administrators using secure blocks, restricting data access to verified residents.
- **Milestone 2: Cohesive Design System (O2):** Created a design token architecture with over 600 CSS variables. This supports light and dark themes and maintains responsive layouts across mobile, tablet, and desktop viewports.
- **Milestone 3: Collaborative Consumption (O3):** Developed the Shared Shed module, providing a digital tool catalog with conflict prevention logic and state-machine transitions to support resource sharing.
- **Milestone 4: Parking Optimization (O4):** Built the Parking Sharing module. This includes an automated conflict-resolution engine that denies overlapping requests once an application is approved, ensuring efficient spot booking.
- **Milestone 5: High-Performance Reactive Architecture (O5):** Integrated the NgRx Facade state model with Angular Signals. This isolates store operations,

handles async data pre-fetching, and enables fine-grained DOM rendering to minimize browser performance overhead.

6.2 Lessons Learned

Developing NEST provided several software engineering insights:

1. **Signal-Based Component Advantages:** Transitioning from traditional Angular change detection to reactive Signal APIs simplified component state. Monotonically tracking inputs (`input()`) and computed values (`computed()`) reduced boiler-plate lifecycle code while improving rendering precision.
2. **State Abstraction via Facades:** Implementing a Facade layer between the visual components and the NgRx store improved maintainability. Components remain decoupled from actions and selectors, allowing development teams to refactor state schemas without altering template markup.
3. **Design Token Scalability:** Centralizing the design system inside a single, structured color token sheet simplified layout development. Component styles are clean and theme-agnostic, demonstrating that robust CSS architectures prevent styling duplication.

6.3 Limitations

While NEST is a robust application, several limitations are identified:

- **Lack of Real-Time Subscriptions:** All updates (such as feed posts and shed requests) rely on HTTP requests and store refreshes. The lack of WebSocket integration prevents real-time notifications, requiring manual page refreshes or periodic polling.
- **SQLite Persistence Boundaries:** The SQLite database is excellent for local staging, testing, and single-host deployments. However, it lacks the concurrent transaction scaling needed for multi-block, high-throughput enterprise deployments.
- **Local File Storage Boundaries:** Profile and post attachments are saved directly to local directory systems on the API server. This approach works well for local deployments, but lacks the durability and horizontal scaling provided by cloud object stores (e.g., AWS S3).

6.4 Future Work

To address these limitations and expand the platform's capabilities, several future enhancements are planned:

1. **WebSocket Real-Time Notification Integration:** Integrate Socket.io on the Express backend and RxJS WebSocket subjects on the Angular client to enable instant, real-time chats, active borrowing requests, and parking alerts.
2. **Enterprise Relational Databases and Cloud Storage:** Migrate persistence to PostgreSQL to support concurrent queries, and transition static uploads to secure Amazon S3 or Google Cloud Storage buckets.
3. **Progressive Web Application (PWA) Capabilities:** Configure service workers and web manifest files to support offline caching, background sync, and native push notifications on Android and iOS devices.
4. **Internationalization (i18n):** Integrate Angular's localization libraries to provide support for English and Romanian, broadening the application's accessibility.

In conclusion, NEST demonstrates how structured, hyper-local platforms can support mutual aid and community connection. The architectural patterns, reactive flows, and security designs implemented in this project provide a stable foundation for future local community engineering.

Bibliography

- [1] Robert D. Putnam. *Bowling Alone: The Collapse and Revival of American Community*. Simon and Schuster, 2000.
- [2] Keith Hampton and Barry Wellman. Neighboring in Netville: How the internet supports community and social capital in a wired suburb. *City & Community*, 2(4):277–311, 2003.
- [3] Christina A. Masden, Catherine Grevet, Rebecca E. Grinter, Eric Gilbert, and W. Keith Edwards. Tensions in scaling-up community social media: A multi-neighborhood study of Nextdoor. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, pages 3239–3248, 2014.
- [4] Google LLC. Angular Developer Documentation. <https://angular.dev/>, 2024. Accessed: 2026-05-04.
- [5] Roy Thomas Fielding. *Architectural Styles and the Design of Network-based Software Architectures*. PhD thesis, University of California, Irvine, 2000. Chapter 5 defines Representational State Transfer (REST).
- [6] Ian Sommerville. *Software Engineering*. Pearson Education, 10 edition, 2016.
- [7] Dan Abramov and Andrew Clark. Live react: Hot reloading with time travel. In *ReactEurope Conference*, 2015. Introduced the Redux architecture for predictable state containers.
- [8] NgRx Team. NgRx – Reactive State for Angular. <https://ngrx.io/docs>, 2024. Accessed: 2026-05-04.
- [9] Angular Team. Angular Signals RFC. <https://github.com/angular/angular/discussions/49685>, 2023. Accessed: 2026-05-10.
- [10] Erich Gamma, Richard Helm, Ralph Johnson, and John Vlissides. *Design Patterns: Elements of Reusable Object-Oriented Software*. Addison-Wesley Professional, 1994.

- [11] Martin Fowler. *Patterns of Enterprise Application Architecture*. Addison-Wesley Professional, 2002.
- [12] OpenJS Foundation. Express.js – Fast, Unopinionated, Minimalist Web Framework for Node.js. <https://expressjs.com/>, 2024. Accessed: 2026-05-04.
- [13] Michael B. Jones, John Bradley, and Nat Sakimura. JSON Web Token (JWT). RFC 7519, Internet Engineering Task Force, 2015. <https://datatracker.ietf.org/doc/html/rfc7519>.
- [14] Niels Provos and David Mazières. A future-adaptable password scheme. In *Proceedings of the USENIX Annual Technical Conference*, pages 81–91, 1999.
- [15] Ramez Elmasri and Shamkant B. Navathe. *Fundamentals of Database Systems*. Pearson, 7 edition, 2015.
- [16] Prisma Data, Inc. Prisma – Next-generation Node.js and TypeScript ORM. <https://www.prisma.io/docs>, 2024. Accessed: 2026-05-10.
- [17] MDN Web Docs. Using CSS Custom Properties (Variables). https://developer.mozilla.org/en-US/docs/Web/CSS/Using_CSS_custom_properties, 2024. Accessed: 2026-05-15.
- [18] Jakob Nielsen and Robert L. Mack. Usability inspection methods. In *Conference Companion on Human Factors in Computing Systems*. John Wiley & Sons, 1994.