

ОБЪЕКТНО- ОРИЕНТИРОВАННОЕ ПРОГРАММИРОВАНИЕ





TEMPLATES IN C++

LANGUAGE C

```
#define max(x,y) ((x) > (y) ? (x) : (y))
```

```
#define min(x,y) ((x) < (y) ? (x) : (y))
```

LANGUAGE C++

```
inline int max(int x, int y)      { return x > y ? x : y; }
inline long max(long x, long y)   { return x > y ? x : y; }
inline float max(float x, float y) { return x > y ? x : y; }
inline double max(double x, double y) { return x > y ? x : y; }
```

```
// .....???????
```

FUNCTION TEMPLATES

```
template <parameter-list> function-declaration
```


FUNCTION TEMPLATES

```
template <parameter-list> function-declaration
```

```
template <typename T>  
inline T const &max(T const &x, T const &y) {  
    return x > y ? x : y;  
}
```

```
template <class T>  
inline T const &min(T const &x, T const &y) {  
    return x < y ? x : y;  
}
```

FUNCTION TEMPLATES

template <parameter-list> function-declaration

```
template <typename T>
inline T const &max(T const &x, T const &y) {
    return x > y ? x : y;
}
```


typename and class are equivalent.

```
template <class T>
inline T const &min(T const &x, T const &y) {
    return x < y ? x : y;
}
```

```
template <typename T>
inline T const &min(T const &x, T const &y) {
    return x < y ? x : y;
}
```

A compiler is
looking for *min*
function.

Finds this template
and infers type *T* by
type of function
arguments.



```
int a = 10;
int b = min(a, 7);
```



```
template <typename T>
inline T const &min(T const &x, T const &y) {
    return x < y ? x : y;
}
```

A compiler is
looking for *min*
function.

Finds this template
and infers type *T* by
type of function
arguments.

```
int a = 10;
int b = min(a, 7);
```

Template
instantiation

```
inline int const &min(int const &x, int const &y) {
    return x < y ? x : y;
}
```

```
template <typename T>
inline T const &min(T const &x, T const &y) {
    return x < y ? x : y;
}
```

A compiler is
looking for *min*
function.

Finds this template
and infers type *T* by
type of function
arguments.

```
int a = 10;
int b = min(a, 7);
```

Template
instantiation

Instance Function
Substitution

```
inline int const &min(int const &x, int const &y) {
    return x < y ? x : y;
}
```

```
min(1, 1.2);
```

```
min(double(1), 1.2);
```

```
min<double>(1, 1.2);
```

```
// Error: different types
```

```
// OK. typecasting
```

```
// OK. explicit type T
```


MULTIPLE PARAMETERS

```
template <typename T1, typename T2>
inline T1 const &min(T1 const &x, T2 const &y) {
    return x < y ? x : y;
}
// .....
```

```
min(1, 1.2);           // OK. The return type is determined
                        // by the type of x.
```

```
template <typename RT, typename T1, typename T2>
inline RT const &max(T1 const &x, T2 const &y) {
    return x > y ? x : y;
}
// .....
```

```
max<double>(4, 4.2);   // Type inference is not possible for RT
```



FUNCTION TEMPLATE OVERLOADING

```
inline int const &max(int const &x, int const &y) {  
    return x > y ? x : y;  
}
```

```
template <typename T>  
inline T const &max(T const &x, T const &y) {  
    return x > y ? x : y;  
}
```

```
template <typename T>  
inline T const &max(T const &x, T const &y, T const &z) {  
    return max(max(x,y), z);  
}
```

```
int main() {  
    max(7, 42, 68);           // use template with 3 arguments  
    max(7.0, 42.0);           // max<double> (template argument deduction)  
    max('a', 'b');           // max<char> (template argument deduction)  
    max(7, 42);               // usual function  
    max<>(7, 42);              // max<int> (template argument deduction)  
    max<double>(7, 42);        // max<double>  
    max('a', 42.7);           // usual function with 2 int arguments  
}
```

```
// From <algorithm>
```

```
template<class InpIt, class OutIt>  
OutIt copy(InpIt first, InpIt last, OutIt result)  
{  
    while (first != last) {  
        *result = *first;  
        ++result; ++first;  
    }  
  
    return result;  
}
```


Templates

```
graph TD; A[Templates] --> B[Function templates]; A --> C[Class templates];
```

The diagram illustrates the classification of templates. At the top is a rounded orange rectangle labeled 'Templates'. Two arrows originate from the bottom center of this rectangle, pointing downwards and outwards to two separate rounded orange rectangles. The rectangle on the left is labeled 'Function templates' and the one on the right is labeled 'Class templates'. All text is in a bold, white, sans-serif font.

Function templates

Class templates

CLASS TEMPLATES

```
template <typename T>
class Stack {
    std::vector<T> elems;
public:
    void push(T const &);
    void pop();
    T top() const;

    bool empty() const {
        return elems.empty()
    }
};
```

```
template <typename T>
void Stack<T>::push(T const &elem) {
    elems.push_back(elem);
}
```

```
template <typename T>
void Stack<T>::pop() {
    if (elems.empty())
        throw std::out_of_range("empty stack");

    elems.pop_back();
}
```

```
template <typename T>
T Stack<T>::top() const {
    if (elems.empty())
        throw std::out_of_range("empty stack");

    elems.back();
}
```

```
int main() {  
    try {  
        Stack<int> intStack;  
        Stack<std::string> stringStack;  
  
        intStack.push(7);  
        stringStack.push("hello");  
  
        stringStack.pop();  
        stringStack.pop();  
    }  
  
    catch (std::exception const &ex) {  
        std::cerr << "Exception " <<  
        ex.what() << std::endl;  
        return -1;  
    }  
}
```


FUNCTION TEMPLATE SPECIALIZATION

```
template<typename T>
inline void exchange(T *a, T *b)
{
    T tmp(*a);
    *a = *b;
    *b = tmp;
}

// ....
void swap_arrays(Array<int> *a1, Array<int> *a2) {
    exchange(a1, a2);
}
```


Как заставить **exchange**
ИСПОЛЬЗОВАТЬ
Array::exchange_with?

```
template<typename T>
class Array {
    T *data;

public:
    // ...
    void exchange_with(Array<T> *b) {
        T *tmp = data;
        data = b->data;
        b->data = tmp;
    }
};
```

```
// template 1
template<typename T>
inline void quick_exchange(T *a, T *b)
{
    T tmp(*a);
    *a = *b;
    *b = tmp;
}
```

«More specialized template»
for a C++ compiler



```
// template 2
template<typename T>
inline void quick_exchange(Array<T> *a, Array<T> *b)
{
    a->exchange_with(b);
}
```

```
void demo(Array<int> *a1, Array<int> *a2) {
    int x = 1, y = 2;

    quick_exchange(&x, &y);    // template 1
    quick_exchange(a1, a2);    // template 2
}
```

CLASS TEMPLATE SPECIALIZATION

```
template <typename T>
class Storage8 {
    T objects[8];

public:
    void set(int idx, const T &t) {
        objects[idx] = t;
    }

    const T& operator[](int idx) {
        return objects[idx];
    }
};
```

Storage8<bool> can be optimized.


```
template <>
class Storage8<bool> {
    unsigned char bits;

public:
    void set(int idx, bool t) {
        unsigned char mask = 1 << idx;

        if (t)
            bits |= mask;
        else
            bits &= ~mask;
    }

    bool operator[](int idx) {
        return bits & (1 << idx);
    }
};
```

PARTIAL TEMPLATE SPECIALIZATION

```
template <typename T>
class List {
public:
    // ...
    void append(T const &);
    inline size_t length() const;
    // ...
};
```

- Класс **List** будет инстанцироваться для всех вариантов **T**. В большом проекте это может привести к разбуханию кода (**code bloat**).
- С низкоуровневой точки зрения реализации **List<int *>::append()** и **List<void *>::append()** идентичны.
- Нельзя ли использовать этот факт для оптимизации списков указателей?

```
// Explicit or full specialization of List<void *>
template<>
class List<void *> {
    // ...
    void append(void *p);
    inline size_t length() const;
    // ...
};
```

```
// Partial specialization of List<T *>
template <typename T>
class List<T *> {
    List<void *> impl;
public:
    // ...
    void append(T *p) { impl.append(p); }
    inline size_t length() const { return impl.length(); }
    // ...
};
```


MEMBER TEMPLATES

```
template <typename T>
class Vector {
    T *base;
public:
    // ...

    // Dynamic polymorphism
    void print(ostream &os) {
        for (auto const &v : *this)
            os << v;
    }

    // Static polymorphism
    template <typename Out>
    void print(Out &out) {
        for (auto const &v : *this)
            out << v;
    }
};
```

TRAITS CLASSES

- Шаблоны позволяют иметь произвольное количество аргументов.
- Можно настроить любой аспект поведения класса или функции.
- Но передавать всегда и везде по 100 аргументов неудобно...

```
template <typename T>
inline T accum(const T *beg, const T *end) {
    T total = T(); // T() возвращает ноль
                    // Но лучше писать T{}
    while (beg != end)
        total += *beg++;

    return total;
}
```

////////

```
int num[] = { 1, 2, 3, 4, 5 };
int avg1 = accum(&num[0], &num[5]) / 5; // 3
```

```
char name[] = "templates";
int len = sizeof(name) - 1;
int avg2 = accum(&name[0], &name[len]) / len; // -5
```



WAT

- Переменная **total** имеет тип **char** (8 бит), которого не хватает для суммирования.
- Можно тип суммы сделать аргументом шаблона... но это очень неудобно.
- Воспользуемся другим подходом.

```
template <typename T>
class AccumulationTraits;
```

```
template<>
class AccumulationTraits<char> {
public:
    typedef int AccT;
};
```

```
template<>
class AccumulationTraits<short> {
public:
    typedef int AccT;
};
```

```
template<>
class AccumulationTraits<int> {
public:
    typedef long AccT;
};
```

```
// unsigned int -> unsigned long
// float -> double
// .....
```

```
template <typename T>
inline typename AccumulationTraits<T>::AccT
accum(const T *beg, const T *end) {
    typedef typename AccumulationTraits<T>::AccT AccT;

    AccT total = AccT(); // AccT() возвращает нулевое значение

    while (beg != end)
        total += *beg++;

    return total;
}
```

```
char name[] = "templates";
int len = sizeof(name) - 1;
int avg2 = accum(&name[0], &name[length]) / len; // 108
```



```

template <typename T>
class AccumulationTraits;

template<>
class AccumulationTraits<char> {
public:
    typedef int AccT;
    static AccT zero() { return 0; }
};

template<>
class AccumulationTraits<short> {
public:
    typedef int AccT;
    static AccT zero() { return 0; }
};

template<>
class AccumulationTraits<int> {
public:
    typedef long AccT;
    static AccT zero() { return 0; }
};

template <typename T>
inline typename AccumulationTraits<T>::AccT accum(const T *beg, const T *end) {
    typedef typename AccumulationTraits<T>::AccT AccT;

    AccT total = AccumulationTraits<T>::zero();

    while (beg != end)
        total += *beg++;

    return total;
}

```

**Member function
zero()**

```
template <typename T, typename AT = AccumulationTraits<T> >  
inline typename AT::AccT accum(const T *beg, const T *end) {  
    // ...  
}
```

Traits as template parameters

TRAITS CLASSES

- Вместо того чтобы свойства (*типы, константы, ...*) делать параметрами шаблона по **T**, помещаем их в дополнительный класс свойств (**Traits**).
- Создаем набор полных специализаций **Traits** для всех нужных **T**.

#include <type_traits>

```
#include <iostream>
#include <array>
#include <string>
#include <type_traits>
```

```
using namespace std;
```

```
int main() {
    cout << boolalpha;
    cout << "is_array:" << endl;
    cout << "int: " << std::is_array<int>::value << endl;
    cout << "int[3]: " << std::is_array<int[3]>::value << endl;
    cout << "array<int,3>: " << std::is_array<array<int,3>>::value << endl;
    cout << "string: " << std::is_array<string>::value << endl;
    cout << "string[3]: " << std::is_array<string[3]>::value << endl;
    return 0;
}
```

```
is_array:
int: false
int[3]: true
array<int,3>: false
string: false
string[3]: true
```

POLICY CLASSES

```
class SumPolicy {  
public:  
    template <typename T1, typename T2>  
    static void accumulate(T1 &total, const T2 &value) {  
        total += value;  
    }  
};
```

**Операция суммирования
вынесена в Policy**

```
template <typename T,  
        typename Policy = SumPolicy,  
        typename Traits = AccumulationTraits<T> >  
inline  
typename Traits::AccT accum(const T *beg, const T *end) {  
    typename Traits::AccT total = Traits::zero();  
  
    while (beg != end) {  
        Policy::accumulate(total, *beg);  
        ++beg;  
    }  
  
    return total;  
}
```



```

class MultPolicy {
public:
    template <typename T1, typename T2>
    static void accumulate(T1 &total, const T2 &value) {
        total *= value;
    }
};

```

Умножение

Тонкая настройка суммирования

```

template <bool use_compound_op = true>
class SumPolicy {
public:
    template <typename T1, typename T2>
    static void accumulate(T1 &total, const T2 &value) {
        total += value;
    }
};

template <>
class SumPolicy<false> {
public:
    template <typename T1, typename T2>
    static void accumulate(T1 &total, const T2 &value) {
        total = total + value;
    }
};

```



```
#include <functional>
```

```
#include <iostream>          // std::cout
```


```
int main() {  
    int first[] = { 1, 2, 3, 4, 5};  
    int second[] = { 10, 20, 30, 40, 50};  
    int results[5];  
  
    for (int i = 0; i < 5; ++i)  
        results[i] = first[i] + second[i];  
  
    for (int i = 0; i < 5; i++)  
        std::cout << results[i] << ' ';  
  
    std::cout << '\n';  
    return 0;  
}
```

```
#include <iostream>      // std::cout
#include <functional>     // std::plus
#include <algorithm>      // std::transform
```

```
int main() {
    int first[]  = { 1, 2, 3, 4, 5};
    int second[] = { 10, 20, 30, 40, 50};
    int results[5];
```

```
    std::transform(first, first+5, second, results,
                    std::plus<int>());
```

```
    for (int i = 0; i < 5; i++)
        std::cout << results[i] << ' ' ;
```



How fix?

```
    std::cout << '\n';
    return 0;
```

```
}
```



```
#include <iostream>        // std::cout
#include <functional>       // std::plus
#include <algorithm>        // std::transform

int main() {
    int first[] = { 1, 2, 3, 4, 5};
    int second[] = { 10, 20, 30, 40, 50};
    int results[5];

    std::transform(first, first+5, second, results,
                    std::plus<int>());

    std::copy(result, result+5,
               std::ostream_iterator<int>(std::cout, ' '));

    std::cout << '\n';
    return 0;
}
```

```

template <class _Arg1, class _Arg2, class _Result>
struct binary_function
{
    typedef _Arg1 first_argument_type;    ///< the type of the first argument
                                           ///< (no surprises here)

    typedef _Arg2 second_argument_type;   ///< the type of the second argument
    typedef _Result result_type;          ///< type of the return type
};

```

```

template <class _Tp>
struct plus : public binary_function<_Tp, _Tp, _Tp> {
    _Tp operator()(const _Tp& __x, const _Tp& __y) const {
        return __x + __y;
    }
};

```

```
#include <iostream>
#include <functional>
```

```
int main() {
    int ary[] = { 1, 2, 3, 4, 5 }, res[5];

    using namespace std::placeholders;    // _1, _2, _3, ...

    auto inc_10 = std::bind(std::plus<int>(), _1, 10);

    std::transform(ary, ary+5, res, inc_10);

    for (int x: res)
        std::cout << x << std::endl;    // 11... 12... 13... 14... 15
    return 0;
}
```

Currying


```
bool all_under_20 = std::all_of(ary, ary + 5,  
    std::bind(std::less<int>(), _1, 20));
```

```
bool all_under_20 = std::all_of(ary, ary + 5,  
    [](int n) { return n < 20; });
```

Lambda-expression

```
// Сколько элементов вектора v принадлежат отрезку [loBo, upBo)?
size_t rangeMatch(const vector<int> &v, int loBo, int upBo) {
    return std::count_if(v.begin(), v.end(),
        [loBo, upBo](int _n) {
            return loBo <= _n && _n < upBo;
        });
}
```

"Capturing" variables


```
[loBo, upBo](int _n) {  
    return loBo <= _n && _n < upBo;  
}
```

// примерно соответствует:

```
struct AutomaticallyGenerated {  
    AutomaticallyGenerated(int lo, int up)  
        : loBo(lo), upBo(up) {}  
  
    bool operator()(int _n) {  
        return loBo <= _n && _n < upBo;  
    }  
  
    int loBo, upBo;  
};
```

```

#include <iostream>
#include <functional>

int main() {
    int ary[] = { 1, 2, 3, 4, 5 }, res[5];

    auto incGen = [] (int _val) -> std::function<int (int)> {
        return [_val] (int _n) -> int { return _n + _val; };
    };

    auto inc_10 = incGen(10);

    std::transform(ary, ary+5, res, inc_10);

    for (int x: res)
        std::cout << x << std::endl;    // 11... 12... 13... 14... 15

    return 0;
}

```

Lambda-expression generates lambda-expressions

SFINAE

```
struct Bar{
    typedef double internalType;
};

template <typename T>
typename T::internalType foo(const T& t) {
    std::cout << "foo<T>" << std::endl;
    return 0;
}

int main(){
    foo(Bar());
    foo(0);    // error
               // no matching function for call to 'foo(int)'
               // ...
               // template argument deduction/substitution failed:
}
```

Substitution **F**ailure Is **N**ot **A**n **E**rror

SFINAE

Name Lookup

Reject if substitution fails...


Template Argument Deduction

Final Viable Function Set

Selection of the best viable function

Compiling a function call...

*Error when cannot find the
single best candidate...*



ENABLE_IF

```
std::enable_if<condition, T>::type

template <typename T>
typename std::enable_if<std::is_arithmetic<T>::value, T>::type
foo(T t) {
    std::cout << "foo<arithmetic T>" << std::endl;
    return t;
}
```

ITERATORS

```
// Until C++17
class num_iterator :
    std::iterator<std::forward_iterator_tag, int>
{
    int i;
public:
    explicit num_iterator(int pos = 0) : i{ pos } {}

    int operator*() const { return i; }

    num_iterator& operator++() {
        ++i;
        return *this;
    }

    bool operator!=(const num_iterator &other) const
    {
        return i != other.i;
    }

    bool operator==(const num_iterator &other) const
    {
        return !(*this != other);
    }
};
```

```
// Since C++17 std::iterator - deprecated
class num_iterator
{
    int i;
public:
    explicit num_iterator(int pos = 0) :
        i{ pos } {}

    ...
};

namespace std {

    template <>
    struct iterator_traits<num_iterator> {
        using iterator_category =
            std::forward_iterator_tag;
        using value_type = int;
        //using pointer = ...;
        //using reference = ...;
        //using difference_type = ...;
    };
}
```


КОНЕЦ ПЕРВОЙ ЛЕКЦИИ

