python

Quiz · Lilian Sw · 40 questions · ★ 5.0 (1 rating) · Updated 6 Jul 2026

python

Question 1 of 40 1

For each statement about try statements, select True or False.

Select one or more of the following:

- A try statement can have a finally clause and an except clause.
- A try statement can have one or more finally clauses.
- A try statement can have one or more except clauses.
- A try statement can have a finally clause without an except clause.

This quiz has question types that open in the usual player.

Questions in this quiz (40)

1 For each statement about try statements, select True or False.

A A try statement can have one or more except clauses.

B A try statement can have a finally clause without an except clause.

C A try statement can have a finally clause and an except clause.

D A try statement can have one or more finally clauses.

---

2 You are writing a Python program to ask the user to enter a number and determine if the number is 1 digit 2 digits, or
more than 2 digits long. You need to write the program.
How should you complete the code? To answer, select the appropriate code segments in the answer area.

```
num = int(input("Enter a number with 1 or 2 digits: "))
digits = 0;
[blank_start][1][blank_end]
digits = "1"
[blank_start][2][blank_end]
digits = 2
[blank_start][3][blank_end]
digits = ">2"
print(digits + " digits.")
```

A if num >-10 and num< 10:

B if num > -100 and num < 100:

C if num > -100 and num < 100:

D elif num > -100 and num < 100:

E if num > -10 and num < 10:

F elif num > -10 and num < 10:

G else:

H elif:

---

3 You are creating a Python program that compares numbers. You write the following code. Line numbers are included for reference only.

01 num1 = eval(input ("Please enterthe first number: "))
02 num2 = eval(input ("Please enter the second number: "))
03 ifnum1 == num2:
04 print("The two numbers are equal.")
05 if num1 <= num2:
06 print("Number 1 is less than number 2.")
07 if num1> num2:
08 print("Number1 is greater than number 2.")
09 if num2 = num1:
10 print("The two numbers are thesame.")

You need to ensure that the comparisons are accurate. For each statement, select True or False. Note: You will receive partial credit for each correct selection.

A The print statement at line 04 will print only if the two numbers are equal in value.

B The print statement at line 06 will print only if num1 is less than num2.

C The print statement at line 08 will print only if num1 is greater than num2.

D The statement at line 09 is an invalid comparison.

---

4 You create the following Python function to calculate the power of a number. Line numbers are included for reference only.

01 # The calc_power function calculates exponents
02 # x is the base
03 # y is the exponent
04 # The value of x raised to the y power is returned
05 def calc_power(x, y):
06 comment = "# Return the value"
07 return x ** y # raise x to the y power

For each statement, select True or False.

A Python will not check the syntax of lines 01 through 04.

B The pound sign (#) is optional for lines 02 and 03.

C The string in line 06 will be interpreted as a comment.

D Line 07 contains an inline comment.

---

5 You are writing a function that increments the player score in a game.
The function has the following requirements:
- If no value is specified for points, then points start at one.
- If bonus is True, then points must be doubled.
You write the following code. Line numbers are included for reference only.

```
01 def increment_score(score, bonus, points):
02 if bonus == True:
03 points = points * 2
04 score = score + points
05 return score
06 points = 5
07 score = 10
08 new_score = increment_score(score, True, points)
```

For each statement, select True or False.
Note: You will receive partial credit for each correct selection.

A To meet the requirements, you must change line 01 to: def increment_score(score, bonus, points = 1).

B If you do not change line 01 and the function is called with only two parameters, an error occurs.

C Line 03 will also modify the value of the variable points declared at line 06.

---

6 A friend asks you to refactor and document the following Python code:

```
value1 = 9
value2 = 4
answer = (value1 % value2 * 10) // 2.0 ** 3.0 + value2
```

You run the code.
What is the result?

A The value 5.0 is displayed.

B A syntax error occurs.

C The value 129 is displayed.

D The value 5.667 is displayed.

---

7 The following function calculates the value of an expression that uses an exponent.
Line numbers are included for reference only.

```
01 def calc_power(a, b):
02 return a ** b
03 base = input("Enter the number for the base: ")
04 exponent = input("Enter the number for the exponent: ")
05 result = calc_power(base, exponent)
06 print("The result is " + result)
```

For each statement, select True or False.

A The code will generate an error in line 03 and line 04.

B The code will generate an error in line 02 and line 05.

C The code will correctly output data to the console.

---

8 The Script.py file contains the following code:

```
import sys
print(sys.argv[2])
```

You run the following command:

```
python Script.py Cheese Bacon Bread
```

What is the output of the command?

A Bread

B Script.py

C Cheese

D Bacon

---

9 Review the following code:

```
x = "oranges"
y = "apples"
z = "bananas"
data = "{1} and {0}and {2}"
print(data.format(z, y, x))
```

What is the output of the print statement?

A oranges and apples and bananas

B apples and bananas and oranges

C bananas and oranges and apples

D apples and oranges and bananas

---

10 What does the following statement do?\n\ndata = input()

- **A** Allows a user to enter text in the console
- **B** Creates an HTML input element
- **C** Displays all input peripheral devices on the computer
- **D** Displays a message box that allows user input

---

11 You develop a Python application for your company.
You want to add notes to your code so other team members will understand it.
What should you do?

- **A** Place the notes after # on any line.
- **B** Place the notes after // on any line.
- **C** Place the notes within /* and */ in any code segment.
- **D** Place the notes within in any code segment.

---

12 For each statement about the following function, select True or False.

```
def
grosspay(hours=40, rate=25, pieces=0, piecerate=0, salary=0):
overtime=0
if pieces > 0
return pieces * piecerate
if salary > 0:
pass
if hours > 40:
overtime = (hours-40) * (1.5 * rate)
return overtime + (40 * rate)
else:
return hours * rate
```

Note: You will receive partial credit for each correct selection.

- **A** A function call of grosspay() will create a syntax error.
- **B** A function call of grosspay(salary=50000) will return nothing.
- **C** A function call of grosspay(pieces=500, piecerate=4) will return a result of 2000.

---

13 You are building a Python program that displays all prime numbers from 2 to 100. (A prime number is any number that is divisible only by itself and 1.)
Complete the code by moving the appropriate code segments from the list on the left to the correct locations on the right.
[blank_start]1[blank_end]
for i in range(2, p):
if p % i == 0:
is_prime = False
[blank_start]2[blank_end]
if is_prime == True:
print(p)
[blank_start]3[blank_end]
[blank_start]4[blank_end]
[blank_start]5[blank_end]

A p =2 while p <= 100: is_prime = True
B for i in range(2, p):if p %i == 0: false
C for i in range (2, p): if p/i == 0: fals
D break
E p = p + 1
F p = 2 is_prime = True while p
G continue

---

14 You are creating an eCommerce script that accepts input from the user and outputs the data in a comma-delimited format.
You write the following code to accept input:
item = input("Enter the item name:")
sales = int(input("Enter the quantity: "))
The output must meet the following requirements:
- Enclose strings in double quotes.
- Do not enclose numbers in quotes or other characters.
- Separate items by commas.
You need to complete the code to meet the requirements.
Which two code segments could you use? Each correct answer presents a complete solution. (Choose 2.)

A print(item +',' + sales)
B print("{0},{1}".format(item, sales))
C print('{0}",{1}'.format(item, sales))
D print(' + item + "",", ,, sales)

---

15 Review the following code segment:

```
f= open("python.txt", "a")
f.write("This is a line of text.")
f.close()
```

For each statement about the code segment, select True or False.

A A file named python.txt is created if it does not exist.

B The data in the file will be overwritten.

C Other code can open the file after this code runs.

---

16 A bicycle company is creating a program that allows customers to log the number of miles biked.
The program will send messages based on how many miles the customer logs.
You write the following Python code. Line numbers are included for reference only.

```
01
02 name = input("What is your name?")
03 return name
04
05 calories = miles * calories_per_mile
06 return calories
07 distance = int(input("How many miles did you bike this week? "))
08 burn rate = 50
09 biker = get_name()
10 calories_burned = calc_calories(distance, burn_rate)
11 print(biker, ", you burned about ", calories_burned, " calories.")
```

You need to define the two required functions.
Which two code segments should you use for line 01 and line 04?
Each correct answer presents part of the solution. (Choose 2.)

A 01 def get_name():

B 01 def get_name(biker):

C 01 def get_name(name):

D 04 def calc_calories():

E 04 def calc_calories(miles, burn_rate):

F 04 def calc_calories(miles, calories_per_mile):

---

17 You work on a team that is developing a game.
You need to write code that generates a random number that meets the following requirements:
- The number is a multiple of 5.
- The lowest number is 5.
- The highest number is 100.
Which two code segments will meet the requirements? Each correct answer presents a complete solution. (Choose 2.)

A from random import randrange print(randrange(0, 100, 5))

B from random import randint print(randint(0, 20) * 5)

C from random import randint print(randint(1, 20) * 5)

D from random import randrange print(randrange(5, 105, 5))

18

You are creating a function to calculate admission fees by using Python. Admission fees are calculated based on the
following rules:

. Anyone under age 5 = free admission
. Anyone age 5 or older who is in school = 10 USD
. Anyone age 5 to 17 who is not in school = 20 USD
. Anyone older than age 17 who is not in school = 50 USD
How should you complete the code? To answer, select the appropriate code segments in the answer area.

```
def admission_fee(age, school):
rate = 0
[blank_start][1][blank_end]
rate = 10
[blank_start][2][blank_end]
[blank_start][3][blank_end]
rate = 20
else:
rate = 50
return rate
```

A if age >= 5 and school == True:

B if age >= 5 and age <= 17:

C if age >= 5 and school == False:

D elif age >= 5 and school == False:

E else age >= 5 and school == False:

F elif age >= 5 and school == True:

G if age >= 5 and school == True:

H if age >= 5 and school == False:

I if age <= 17:

---

19 You develop a Python application for your company. How should you complete the code so that the print statements are
accurate? To answer, select the appropriate code segments in the answer area.

```
numList = [1,2,3,4,5]
alphaList = ["a","b","c","d","e"]
[blank_start][1][blank_end]
print("The values in numList are equal to alphaList")
[blank_start][2][blank_end]
print("The values in numList are not equal to alphaList")
```

A if numList == alphaList:

B if numList == alphaList

C else:

D else

E if numList == alphaList:

F if numList == alphaList

G else:

H else

20 A coworker wrote a program that inputs names into a database. Unfortunately, the program reversed the letters in each name.

You need to write a Python function that outputs the characters in a name in the correct order.

Complete the code by selecting the code segment from each drop-down list.

```
# Function reverses characters in a string.
# returns new string in reversed order.

def reverse_name(backward_name):
forward_name = ""
length = [blank_start]1[blank_end]
while length >= 0:
forward_name += [blank_start]2[blank_end]
length = length - 1
return forward name

print(reverse_name("nohtyp"))
```

A backwards_name:

B len(backwards_name) - 1

C range(0, len(backwards_name),-1)

D range(len(backwards_name)-1,-1,-1):

E backwards_name[index-1]

F backwards_name[len(forward_name)-1]

G backwards_name[len(backward_name)- len(f

H backward_name[length]

21 Review the following code segment:

```
product = 2
n =5
while (n != 0):
product *= n
print (product)
n -= 1
if n == 3:
break
```

How many lines of output does the code print?

A 1

B 2

C 3

D 4

---

22 You write the following code to determine a student's final grade based on their current grade (grade) and rank (rank):

```
grade = 76
rank = 3

if grade > 80 and rank >= 3:
grade += 10
elif grade >= 70 and rank > 3:
grade += 5
else:
grade -= 5

print(grade)
```

What value will print?

A 71

B 76

C 81

D 86

---

23 You write the following function to read a data file and print each line of the file. Line numbers are included for reference only.

```
01 def read_file(file):
02 line = None
03 if os.path.isfile(file):
04 data = open(file,'r')
05 for line in data:
06 print(line)
```

When you run the program, you receive an error on line 03.

What is causing the error?

A You need to import the os library.

B The isfile method does not accept one parameter.

C The isfile method does not exist in the path object.

D The path method does not exist in the os object.

24 You are designing a decision structure to convert student's numeric grades ('grade') to letter grades ('letter_grade').
The program must assign letter grades as specified in the following table:
Percentage range Letter grade
90 through 100 A
80 through 89 B
70 through 79 C
65 through 69 D
0 through 64 F

For example, if the user enters a 90, the output should be "'Your letter grade is A".
Likewise, if a user enters an 89, the output should be "'Your letter grade is B".
Complete the code by selecting the correct code segment from each drop-down list.
** 'python
#Letter Grade Converter
grade = int(input("Enter a numeric grade"))

[blank_start]1[blank_end] # dropdown 1
letter_grade = 'A'
[blank_start]2[blank_end] # dropdown 2
letter_grade = 'B'
[blank_start]3[blank_end] # dropdown 3
letter_grade = 'C'
[blank_start]4[blank_end] # dropdown 4
letter_grade = 'D'
else:
letter_grade = 'F'

A if grade >= 90:

B if grade > 80:

C if grade > 70:

D if grade > 65:

E if grade >= 80 and grade <90:

F if grade >= 80:

G if grade >= 70:

H if grade >= 65:

I if grade >= 70 and grade < 80:

J elif grade > 90:

K elif grade > 70:

L elif grade > 65:

M if grade >= 65 and grade < 70:

N elif grade >= 80:

O elif grade >= 70:

P elif grade >= 65:

---

25 You are developing a Python application for your company.
You need to accept input from the user and print that information to the user's screen.
You start with the following code. Line numbers are included for reference only:
01 print("What is your name?")
02
03 print(name)
Which code should you write at line 02?

A input(name)

B name = input

C name = input()

D input("name")

---

26 Students are attending an activity night at their school. The following function tells students where to go for their activities:

```
def roomAssignment(student, year):
"""Assign rooms to students"*"
if year == 1:
print(f"In{student.title()}, please report to room 115")
elif year == 2:
print(f"In{student.title()}, please report to room 210")
elif year == 3
print(f"In{student.title()}, please report to room 320")
elif year == 4
print(f"In{student.title()}, please report to room 405")
elif year == 5:
print(f"In{student.title()}, please report to room 515")
else:
print(f"In{student.title()}, please report to room 625")
```

Which two code segments can be used to call the function? (Choose 2.)
Each correct code segment is a complete solution.

A
```
name = input('What is your name?')
grade = 0
while grade not in (1, 2, 3, 4, 5, 6):
grade = int(input('What grade are you in (1-6)?'))
roomAssignment(name, year=grade)
```

B
```
name = input('What is your name?')
grade = 0
while grade not in (1, 2, 3, 4, 5, 6):
grade = int(input('What grade are you in (1-6)?'))
roomAssignment(student, year)
```

C `roomAssignment('Sherlock Sassafrass', 4)`

D `roomAssignment(year=6, name='Minnie George')`

---

27 You are developing a Python application for your school. The application must read and write data to a text file.
If the file does not exist, the application must create it. If the file contains content, the application must delete the content.
Which code segment should you use?

A `open("local_data", "w")`

B `open("local_data", "r")`

C `open("local_data", "w+")`

D `open("local_data", "r+")`

---

28 A bank must generate a report that shows the average balance for all customers each day. The report must truncate the decimal portion of the balance.
Which two code segments achieve the goal? Each correct answer presents a complete solution. (Choose 2.)

A average_balance = float(total_deposits // number_of_customers)

B average_balance = total_deposits ** number_of_customers

C average_balance = int(total_deposits / number_of_customers)

D average_balance = total_deposits // number_of_customers

---

29 You are creating a function that manipulates a number passed into the function as a float value. The function must perform the following tasks: . Take the absolute value of the float. . Remove any decimal points after the integer. Which two math functions should you use? Each correct answer is part of the solution. (Choose 2.)

A math.floor(x)

B math.fabs(x)

C math.fmod(x)

D math.frexp(x)

---

30 You develop a Python application for your company. A list named employees contains 200 employee names, the last five being company management. You need to slice the list to display all employees excluding management. Which two code segments should you use? Each correct answer presents a complete solution. (Choose 2.)

A employees[1 :- 5]

B employees[0 :- 5]

C employees[1 :- 4]

D employees[0 :- 4]

E employees[:- 5]

---

31 The following function calculates the value of an expression that uses an exponent. Line numbers are included for reference only.

```
01 def calc_power(a, b):
02 return a ** b
03 base = input("Enter the number for the base: ")
04 exponent = input("Enter the number for the exponent: ")
05 result = calc_power(base, exponent)
06 print("The result is " + result)
```

For each statement, select True or False.

A The code will generate an error in line 03 and line 04.(F)

B The code will generate an error in line 02 and line 05.

C The code will correctly output data to the console.(F)

---

32 You are developing a Python application for your company. You write the following code:

```
numList = [1, 2, 3, 4, 5]
alphaList = ["a", "b", "c", "d","e"]
print(numList is alphaList)
print(numList == alphaList)
numList = alphaList
print(numList is alphaList)
print(numList == alphaList)
```

Evaluate the code and answer the questions by selecting the correct option from each drop-down list.

What is displayed after the first print? [blank_start]False[blank_end]

What is displayed after the second print? [blank_start]False[blank_end]

What is displayed after the third print? [blank_start]True[blank_end]

What is displayed after the fourth print? [blank_start]True[blank_end]

A False

B True

C False

D True

E False

F True

G False

H True

---

33 The Script.py file contains the following code:

```
import sys
print(sys.argv[2])
```

You run the following command:

```
python Script.py Cheese Bacon Bread
```

What is the output of the command?

A Bacon

B Script.py

C Bread

D Cheese

---

34 Review the following code segment:

```
f= open("python.txt", "a")
f.write("This is a line of text.")
f.close()
```

For each statement about the code segment, select True or False.

A file named python.txt is created if it does not exist.

[blank_start]1[blank_end]

The data in the file will be overwritten.

[blank_start]2[blank_end]

Other code can open the file after this code runs.

[blank_start]3[blank_end]

A Yes

B No

C Yes

D No

E Yes

F No

---

35 You are writing a function that increments the player score in a game.

The function has the following requirements:

· If no value is specified for points, then points start at one.

. If bonus is True, then points must be doubled.

You write the following code. Line numbers are included for reference only:

01 def increment_score(score, bonus, points):

02 if bonus == True:

03 points = points * 2

04 score = score + points

05 return score

06 points = 5

07 score = 10

08 new_score = increment_score(score, True, points)

For each statement, select True or False.

To meet the requirements, you must change line 01 to: def increment_score(score, bonus, points =1):

[blank_start]1[blank_end]

If you do not change line 01 and the function is called with only two parameters, an error occurs.

[blank_start]2[blank_end]

Line 03 will also modify the value of the variable points declared at line 06.

[blank_start]3[blank_end]

A Yes

B No

C Yes

D No

E Yes

F No

36 Review the following program. Line numbers are for reference only:

```
def petStore(category, species, breed = "none"):
print(f"InYou have selected an animal from the {category} category.")
if breed == "none":
print(f"The {category} you selected is a {species}")
else:
print(f"The {category} you selected is a {species} {breed}")
category = input("Enter dog, cat, or bird:")
species = input("Enter species:")
if category == "dog" or category == "cat":
breed = input("Enter breed:")
petStore(category, species, breed)
else:
petStore(category, species)
petStore(breed="Maltese", species="Canine", category="dog")
petStore("bird", species="Scarlet Macaw")
```

For each statement about the program, select True or False.

The function returns a value.

[blank_start]1[blank_end]

The function calls at lines 12 and 15 are valid.

[blank_start]2[blank_end]

The function calls at lines 14 and 16 will result in an error.

[blank_start]3[blank_end]

A Yes

B No

C Yes

D No

E Yes

F No

---

37 You are writing code to generate a random integer with a minimum value of 5 and a maximnum value of 11.

Which two functions should you use? Each correct answer presents a complete solution. (Choose 2.)

A random.randint(5, 12)

B random.randrange(5, 11, 1)

C random.randint(5, 11)

D random.randrange(5, 12, 1)

---

38 A bank is migrating their legacy bank transaction code to Python.
The bank hires you to document the migrated code.
Which documentation syntax is correct?

A def get_balance():In # Returns the current balance of the bank account\n return balance

B // Returns the current balance of the bank account\ndef get_balance():In return balance

C def get_balance():In /* Returns the current balance of the bank account *An return balance

D Returns the current balance of the bank accountIndef get_balance():In return balance

---

39 You are creating an eCommerce script that accepts input from the user and outputs the data in a comma-delimited format.
You write the following code to accept input:
item = input("Enter the item name: ")
sales = int(input("Enter the quantity: "))
The output must meet the following requirements:
· Enclose strings in double quotes.
· Do not enclose numbers in quotes or other onaracters.
· Separate items by commas.
Which two code segments could you use? Each correct answer presents a complete solution.
(Choose 2.)

A print(item +',' + sales)

B print("0",{1}'.format(item, sales))

C print(" + item +"",',', sales)

D print("{0}",{1}'.format(item, sales))

---

40 You are creating a program that accepts user input. The program must cast the input into an integer, and properly handle the error if it cannot do so.
while True:
[blank_start]try[blank_end]
x = int(input("Please enter a number: "))
[blank_start]break[blank_end]
except: ValueError:
print("Not a valid number. Try again ... ")

A try:
B else:
C except:
D raise:
E finally:
F try:
G else:
H except:
I raise:
J finally:

Information

Description	Quiz on python, created by Lilian Sw on 15/06/2026.
Author	Lilian Sw
Language	English
Views	891
History	Created on 15 Jun 2026 · updated on 6 Jul 2026
Rating	5.0 out of 5 · 1 rating ☆ ☆ ☆ ☆ ☆ Rate this quiz

Report this quiz