

4. Functional Programming

Roadmap

- > Functional vs. Imperative Programming
- > Pattern Matching
- > Referential Transparency
- > Lazy Evaluation
- > Recursion
- > Higher Order and Curried Functions



References

- > *“Conception, Evolution, and Application of Functional Programming Languages,”* Paul Hudak, ACM Computing Surveys 21/3, 1989, pp 359-411.
- > *“A Gentle Introduction to Haskell,”* Paul Hudak and Joseph H. Fasel
— www.haskell.org/tutorial/
- > *Report on the Programming Language Haskell 98 A Non-strict, Purely Functional Language,* Simon Peyton Jones and John Hughes [editors], February 1999
— www.haskell.org
- > *Real World Haskell,* Bryan O'Sullivan, Don Stewart, and John Goerzen
— book.realworldhaskell.org/read/

Roadmap

- > **Functional vs. Imperative Programming**
- > Pattern Matching
- > Referential Transparency
- > Lazy Evaluation
- > Recursion
- > Higher Order and Curried Functions



A Bit of History

<i>Lambda Calculus</i> (Church, 1932-33)	formal model of computation
<i>Lisp</i> (McCarthy, 1960)	symbolic computations with lists
<i>APL</i> (Iverson, 1962)	algebraic programming with arrays
<i>ISWIM</i> (Landin, 1966)	let and where clauses equational reasoning; birth of “pure” functional programming ...
<i>ML</i> (Edinburgh, 1979)	originally meta language for theorem proving
<i>SASL, KRC, Miranda</i> (Turner, 1976-85)	lazy evaluation
<i>Haskell</i> (Hudak, Wadler, et al., 1988)	“Grand Unification” of functional languages ...

Programming without State

Imperative style:

```
n := x;  
a := 1;  
while n>0 do  
begin a:= a*n;  
      n := n-1;  
end;
```

Declarative (functional) style:

```
fac n =  
    if      n == 0  
    then    1  
    else    n * fac (n-1)
```

*Programs in pure functional languages have no explicit state.
Programs are constructed entirely by composing expressions.*

Pure Functional Programming Languages

Imperative Programming:

> Program = Algorithms + Data

Functional Programming:

> Program = Functions \circ Functions

What is a Program?

— A program (computation) is a *transformation* from input data to output data.

Key features of pure functional languages

1. All programs and procedures are *functions*
2. There are *no variables or assignments* — only input parameters
3. There are *no loops* — only recursive functions
4. The value returned by a function *depends only on the values of its parameters*
5. Functions are *first-class values*

What is Haskell?

Haskell is a general purpose, purely functional programming language incorporating many recent innovations in programming language design. Haskell provides higher-order functions, non-strict semantics, static polymorphic typing, user-defined algebraic datatypes, pattern-matching, list comprehensions, a module system, a monadic I/O system, and a rich set of primitive datatypes, including lists, arrays, arbitrary and fixed precision integers, and floating-point numbers. Haskell is both the culmination and solidification of many years of research on lazy functional languages.

— The Haskell 98 report

“Hello World” in Hugs

```
hello() = print "Hello World"
```

Roadmap

- > Functional vs. Imperative Programming
- > **Pattern Matching**
- > Referential Transparency
- > Lazy Evaluation
- > Recursion
- > Higher Order and Curried Functions



Pattern Matching

Haskell supports multiple styles for specifying case-based function definitions:

Patterns:

```
fac' 0 = 1
fac' n = n * fac' (n-1)

-- or: fac' (n+1) = (n+1) * fac' n
```

Guards:

```
fac'' n | n == 0 = 1
        | n >= 1 = n * fac'' (n-1)
```

Lists

Lists are *pairs* of elements and lists of elements:

- > `[]` — stands for the empty list
- > `x:xs` — stands for the list with `x` as the head and `xs` as the rest of the list

The following short forms make lists more convenient to use

- > `[1, 2, 3]` — is syntactic sugar for `1:2:3:[]`
- > `[1..n]` — stands for `[1, 2, 3, ..., n]`

Using Lists

Lists can be *deconstructed* using patterns:

```
head (x:_)    = x
```

```
len [ ]       = 0
```

```
len (_:xs)    = 1 + len xs
```

```
prod [ ]      = 1
```

```
prod (x:xs)   = x * prod xs
```

```
fac''' n      = prod [1..n]
```

Roadmap

- > Functional vs. Imperative Programming
- > Pattern Matching
- > **Referential Transparency**
- > Lazy Evaluation
- > Recursion
- > Higher Order and Curried Functions



Referential Transparency

A function has the property of referential transparency if *its value depends only on the values of its parameters*.

👉 Does $f(x) + f(x)$ equal $2 * f(x)$? In C? In Haskell?

Referential transparency means that “*equals can be replaced by equals*”.

In a pure functional language, all functions are referentially transparent, and therefore *always yield the same result* no matter how often they are called.

Evaluation of Expressions

Expressions can be (formally) evaluated by substituting arguments for formal parameters in function bodies:

```

fac 4
↙ if 4 == 0 then 1 else 4 * fac (4-1)
↙ 4 * fac (4-1)
↙ 4 * (if (4-1) == 0 then 1 else (4-1) * fac (4-1-1))
↙ 4 * (if 3 == 0 then 1 else (4-1) * fac (4-1-1))
↙ 4 * ((4-1) * fac (4-1-1))
↙ 4 * ((4-1) * (if (4-1-1) == 0 then 1 else (4-1-1) * ...))
↙ ...
↙ 4 * ((4-1) * ((4-1-1) * ((4-1-1-1) * 1)))
↙ ...
↙ 24

```

Of course, real functional languages are not implemented by syntactic substitution ...

Roadmap

- > Functional vs. Imperative Programming
- > Pattern Matching
- > Referential Transparency
- > **Lazy Evaluation**
- > Recursion
- > Higher Order and Curried Functions



Lazy Evaluation

“Lazy”, or “normal-order” evaluation only evaluates expressions when they are actually needed. Clever implementation techniques (Wadsworth, 1971) allow replicated expressions to be shared, and thus avoid needless recalculations.

So:

```
sqr n = n * n
```

```
sqr (2+5) ↙ (2+5) * (2+5) ↙ 7 * 7 ↙ 49
```

Lazy evaluation allows some functions to be evaluated even if they are passed incorrect or non-terminating arguments:

```
ifTrue True x y = x  
ifTrue False x y = y
```

```
ifTrue True 1 (5/0) ↙ 1
```

Lazy Lists

Lazy lists are *infinite data structures* whose values are generated by need:

```
from n = n : from (n+1)
```

```
from 100 ↙ [100,101,102,103,....]
```

```
take 0 _ = [ ]
```

```
take _ [ ] = [ ]
```

```
take (n+1) (x:xs) = x : take n xs
```

```
take 2 (from 100)
```

```
↙ take 2 (100:from 101)
```

```
↙ 100:(take 1 (from 101))
```

```
↙ 100:(take 1 (101:from 102))
```

```
↙ 100:101:(take 0 (from 102))
```

```
↙ 100:101:[ ]
```

```
↙ [100,101]
```

NB: The lazy list (*from n*) has the special syntax: *[n..]*

Programming lazy lists

Many sequences are naturally implemented as lazy lists.

Note the top-down, declarative style:

```
fibs = 1 : 1 : fibsFollowing 1 1
      where fibsFollowing a b =
              (a+b) : fibsFollowing b (a+b)
```

```
take 10 fibs
```

```
↙ [ 1, 1, 2, 3, 5, 8, 13, 21, 34, 55 ]
```

👉 *How would you re-write `fibs` so that $(a+b)$ only appears once?*

Declarative Programming Style

```

primes = primesFrom 2
primesFrom n = p : primesFrom (p+1)
  where p = nextPrime n
nextPrime n
  | isPrime n      = n
  | otherwise      = nextPrime (n+1)
isPrime 2          = True
isPrime n          = notDivisible primes n
notDivisible (k:ps) n
  | (k*k) > n      = True
  | (mod n k) == 0 = False
  | otherwise      = notDivisible ps n

```

```
take 100 primes ↩ [ 2, 3, 5, 7, 11, 13, ... 523, 541 ]
```

Roadmap


- > Functional vs. Imperative Programming
- > Pattern Matching
- > Referential Transparency
- > Lazy Evaluation
- > **Recursion**
- > Higher Order and Curried Functions



Tail Recursion

Recursive functions can be less efficient than loops because of the *high cost of procedure calls* on most hardware.

A tail recursive function calls itself only as its last operation, so the recursive call can be *optimized away* by a modern compiler since it needs only a single run-time stack frame:



Tail Recursion ...

A recursive function can be converted to a tail-recursive one by representing partial computations as explicit function parameters:

```
sfac s n = if    n == 0
            then s
            else sfac (s*n) (n-1)
```

```
sfac 1 4 ↙ sfac (1*4) (4-1)
           ↙ sfac 4 3
           ↙ sfac (4*3) (3-1)
           ↙ sfac 12 2
           ↙ sfac (12*2) (2-1)
           ↙ sfac 24 1
           ↙ ...
           ↙ 24
```

Multiple Recursion

Naive recursion may result in unnecessary recalculations:

```
fib 1      = 1
fib 2      = 1
fib (n+2)  = fib n + fib (n+1) — NB: Not tail-recursive!
```

Efficiency can be regained by *explicitly passing calculated values*:

```
fib' 1      = 1
fib' n      = a      where (a,_) = fibPair n
fibPair 1   = (1,0)
fibPair (n+2) = (a+b,a)
              where (a,b) = fibPair (n+1)
```

 *How would you write a tail-recursive Fibonacci function?*

Roadmap

- > Functional vs. Imperative Programming
- > Pattern Matching
- > Referential Transparency
- > Lazy Evaluation
- > Recursion
- > **Higher Order and Curried Functions**



Higher Order Functions

Higher-order functions treat other *functions as first-class values* that can be composed to produce new functions.

```
map f [ ]      = [ ]  
map f (x:xs)   = f x : map f xs
```

```
map fac [1..5]  
↙ [1, 2, 6, 24, 120]
```

NB: `map fac` is a new function that can be applied to lists:

```
mfac = map fac
```

```
mfac [1..3]  
↙ [1, 2, 6]
```

Anonymous functions

Anonymous functions can be written as “lambda abstractions”.
The function `(\x -> x * x)` behaves exactly like `sqr`:

```
sqr x = x * x
```

```
sqr 10  
↙ 100  
(\x -> x * x) 10  
↙ 100
```

Anonymous functions are first-class values:

```
map (\x -> x * x) [1..10]  
↙ [1, 4, 9, 16, 25, 36, 49, 64, 81, 100]
```

Curried functions

A Curried function [named after the logician H.B. Curry] *takes its arguments one at a time*, allowing it to be treated as a higher-order function.

```
plus x y      = x + y      -- curried addition
```

```
plus 1 2
↙ 3
```

```
plus' (x,y)   = x + y      -- normal addition
```

```
plus' (1,2)
↙ 3
```

Understanding Curried functions

`plus x y = x + y` *is the same as:* `plus x = \y -> x+y`

In other words, `plus` is *a function of one argument that returns a function* as its result.

`plus 5 6` *is the same as:* `(plus 5) 6`

In other words, we invoke `(plus 5)`, obtaining a function,

`\y -> 5 + y`

which we then pass the argument `6`, yielding `11`.

Using Curried functions

Curried functions are useful because we can bind their arguments incrementally

```
inc  = plus 1           -- bind first argument to 1
```

inc 2

↙ 3

```
fac  = sfac 1           -- binds first argument of
```

```
    where sfac s n      -- a curried factorial
```

```
        | n == 0      = s
```

```
        | n >= 1      = sfac (s*n) (n-1)
```


Currying

The following (pre-defined) function takes a binary function as an argument and turns it into a curried function:

```
curry f a b = f (a, b)

plus(x,y)    = x + y           -- not curried!
inc          = (curry plus) 1








sfac(s, n)   = if n == 0       -- not curried
              then s
              else sfac (s*n, n-1)

fac = (curry sfac) 1           -- bind first argument
```






To be continued ...

- > Enumerations
- > User data types
- > Type inference
- > Type classes

What you should know!

-  *What is referential transparency? Why is it important?*
-  *When is a function tail recursive? Why is this useful?*
-  *What is a higher-order function? An anonymous function?*
-  *What are curried functions? Why are they useful?*
-  *How can you avoid recalculating values in a multiply recursive function?*
-  *What is lazy evaluation?*
-  *What are lazy lists?*

Can you answer these questions?

-  *Why don't pure functional languages provide loop constructs?*
-  *When would you use patterns rather than guards to specify functions?*
-  *Can you build a list that contains both numbers and functions?*
-  *How would you simplify fibs so that $(a+b)$ is only called once?*
-  *What kinds of applications are well-suited to functional programming?*

License

<http://creativecommons.org/licenses/by-sa/3.0/>



Attribution-ShareAlike 3.0 Unported

You are free:

to Share — to copy, distribute and transmit the work

to Remix — to adapt the work

Under the following conditions:

Attribution. You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work).

Share Alike. If you alter, transform, or build upon this work, you may distribute the resulting work only under the same, similar or a compatible license.

For any reuse or distribution, you must make clear to others the license terms of this work. The best way to do this is with a link to this web page.

Any of the above conditions can be waived if you get permission from the copyright holder.

Nothing in this license impairs or restricts the author's moral rights.