

磁电转换特性

励磁电流 (mA)	Vout (mV)	方向(1增/-1减)	励磁电流 (mA)	Vout (mV)	方向(1增/-1减)
-200		1	200		-1
-180		1	180		-1
-160		1	160		-1
-140		1	140		-1
-120		1	120		-1
-100		1	100		-1
-80		1	80		-1
-60		1	60		-1
-40		1	40		-1
-20		1	20		-1
0		1	0		-1
20		1	-20		-1
40		1	-40		-1
60		1	-60		-1
80		1	-80		-1
100		1	-100		-1
120		1	-120		-1
140		1	-140		-1
160		1	-160		-1
180		1	-180		-1
200		1	-200		-1

内部磁阻特性

工作电压 U (V)
2

励磁电流 (mA)	状态 A 回路电流 (mA)	状态 B 回路电流 (mA)	励磁电流 (mA)	状态 A 回路电流 (mA)	状态 B 回路电流 (mA)
-200			200		
-180			180		
-160			160		
-140			140		
-120			120		
-100			100		
-80			80		
-60			60		
-40			40		
-20			20		
0			0		
20			-20		
40			-40		
60			-60		
80			-80		
100			-100		
120			-120		
140			-140		
160			-160		
180			-180		
200			-200		

选做：无接触电流测量（选做）

[illegible]