

零电流法测普朗克常数

波长 λ (nm)	US1 (V)	US2 (V)	US3 (V)	US4 (V)
365				
405				
436				
546				
577				

436 nm 伏安特性

UAK (V)	I (10 ⁻¹³ A)	UAK (V)	I (10 ⁻¹³ A)
-4		9	
-3.5		10	
-3		11	
-2.5		12	
-2		13	
-1.5		14	
-1		15	
-0.5		16.5	
0		18	
1		19.5	
2		21	
3		22.5	
4		24	
5		25.5	
6		27	
7		28.5	
8		30	

546 nm 伏安特性

UAK (V)	I (10 ⁻¹³ A)	UAK (V)	I (10 ⁻¹³ A)
-4		9	
-3.5		10	
-3		11	
-2.5		12	
-2		13	
-1.5		14	
-1		15	
-0.5		16.5	
0		18	
1		19.5	
2		21	
3		22.5	
4		24	
5		25.5	
6		27	
7		28.5	
8		30	

饱和电流与光强

波长 (nm)	光阑 Φ (mm)	I1 (10 ⁻¹⁰ A)	I2 (10 ⁻¹⁰ A)	I3 (10 ⁻¹⁰ A)
436	2			
436	4			
436	8			
546	2			
546	4			
546	8			

选做：补偿法测普朗克常数（选做）

光阑 Φ (mm)
4

波长 λ (nm)	US1 (V)	US2 (V)	US3 (V)
365			
405			
436			
546			
577			