



# Android lecture 6

## Release process


2023

Lukáš Prokop

Simona Kurňavová



# Application release



# Gather materials for release

- **Cryptographic keys**
  - Apps in store are digitally signed, by developer certificate
  - Identify app developer
  - Self-signed certificate is enough
  - Needs to end after 22 October 2033 (>25 years recommended)
  - Protect your private key and password, it is not possible to update application if it is lost
- **End-user license agreement (EULA)**
  - User should know if you gather some data
  - Not required but recommended
  - GDPR

# Gather material for release

- **Application icon**
  - Visible in launcher, settings or other applications
  - High-res assets for google play store listing
- **Misc. materials**
  - Promo and marketing materials
  - Promotional text and graphic for store listing
- **Changelog**

# Before release

- **Delete unused parts (sources, resources, assets)**
- **Package name**
  - <https://play.google.com/store/apps/details?id=com.avast.android.mobilesecurity>
- **Turn off debug features**
  - Delete Log.\* calls
  - Remove android:debuggable flag from AndroidManifest
  - Remove Debug or Trace calls
  - If you using WebView ensure that debug is disabled, otherwise is possible to inject js code
- **Clean up your directories, checks if libraries doesn't include some unnecessary files to your \*.apk (\*.proto, java manifests, ...)**

# Configure application for release


- **Review**
  - permissions - remove unnecessary
  - App icon and label
  - Version code and version name
  - Used URLs test vs. production backend
- **Check compatibility**
  - Support of multiple screens
  - Tablet mode

# Build application for release

- **Signing**
  - Manually
    - Using Keytool and Jarsigner from JDK
  - Configure sign options in gradle
  - Android studio
  - Sign scheme v2 <https://source.android.com/security/apksigning/v2>
  - Sign scheme v3 <https://source.android.com/security/apksigning/v3>
  - Sign scheme v4 <https://source.android.com/security/apksigning/v4>
- **Obfuscation**
  - Use proguard to obfuscate your code, it is really easy to decompile application and find how it works, endpoints
- **Consider**
  - Who has access to your sign key
  - Signing server

# Signing

- Sign vs upload key





# Prepare external servers and resources

- Ensure that backend is running
- Check if app is switched to prod environment

# Testing your application for release

- Regression test
- Test new features
- If it is possible test it on multiple devices, android versions
- Test multiple languages, including RTL
- Check lint for several issues

# Publishing

- **Google play store**
  - Registration cost 25 USD
  - Reporting about installs
  - Crashes
    - If user sends it
  - Cloud test lab
    - Run monkey tests on multiple devices before releasing
  - Alpha/Beta groups
  - Distribution specific domain - internal apps
  - Staged rollout
  - API - import crash reports to bug tracker, upload new APK, ...


# Publishing

- **Email, Web page**
  - Untrusted sources - security risk
  - Manual Updates
- **3rd party distribution**
  - Amazon
  - F-droid


# After publish

- Monitor new crashes
- New permission slows down spreading between users on API < 23 (Marshmallow 6.0)
- Not good idea publish app before weekend or vacation


# Build process and APK structure



# Build process



# Support java 8 features (d8)






# Building android apps limitations

- **Dex limit 64k methods**
  - Shrink unused methods and classes (libraries)
    - You need to specify what is entry point, build dependency graph. Classes which are not part of graph are removed, unused methods as well
    - When you work on library, provide proguard rules together with library
  - Sometimes is better copy some classes from library into application
    - for example guava library
- **Google doesn't allow code side load**


# Multidex

- Native support since API-21 for older version support library
- Try to avoid using multidex, it slows down application start
- Splits classes to multiple dex files
- on API>=21 dex files are converted to single .oat file (ART runtime)
- Main dex file loaded when app is started
- Loading of additional dex files is performed during initialization
- Dex files are in app folder
- <https://www.blackhat.com/docs/ldn-15/materials/london-15-Welton-Abusing-Android-Apps-And-Gaining-Remote-Code-Execution.pdf>

# Apk structure



# AppBundle



# Proguard/R8

- **Shrink** - smaller code, faster build
- **Optimize** - faster code, removing static conditions
- **Obfuscate** - make it harder to read

# Decompile apk

- **Unzip the apk**
- **Dex2Jar to convert classes.dex to jar archive**
  - <https://github.com/pxb1988/dex2jar>
- **jd-gui to view decompiled classes**
  - <http://jd.benow.ca/>
- **BytecodeViewer**
  - <https://bytecodeviewer.com/>
- **Android studio apk analyzer**
  - Easy to check resources
  - Compare multiple apk

# Android and SW development - best practices

- Keep strings, dimensions, colors, ... in resources
- Create libs for parts used in multiple projects (simplify maintenance, speed-up builds)
- Use git
- Do code reviews
- Write tests

# Build flavors/Build variants

- Whitelabel apps
- Debug variant of the app



---

# Thank you

Lukáš Prokop  
Simona Kurňavová

[Lukas.Prokop@gendigital.com](mailto:Lukas.Prokop@gendigital.com)

[Simona.Kurnavova@gendigital.com](mailto:Simona.Kurnavova@gendigital.com)

