

# Applying Genetic Programming to Bytecode and Assembly

Eric Collom

Division of Science and Mathematics  
University of Minnesota, Morris  
Morris, Minnesota, USA

29 April '14,  
UMM Senior Seminar



# The big picture

- Evolving whole programs is hard to do with source code.
- Evolving whole programs with bytecode and assembly is not as hard.

# Outline


- 1 Background
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs
- 4 Using Instruction-level Code to Automate Bug Repair
- 5 Conclusions

# Outline

- 1 Background
  - EC
  - Java Bytecode and the JVM
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs
- 4 Using Instruction-level Code to Automate Bug Repair
- 5 Conclusions


# What is Evolutionary Computation?

- EC is a technique that is used to automate computer problem solving.
- Loosely emulates evolutionary biology.




Charles Darwin

<http://tinyurl.com/lqwj3wt>




# How does it work

- Continuous Optimization
- Selection is driven by the *fitness* of individuals
- Genetic Operators mimic sexual reproduction and mutation




# Genetic Programming

- Uses the EC technique to evolve programs
- The population is programs



# Genetic Programming


## ■ Tournament Selection






# Genetic Programming

- Crossover
- Mutation




# Crossover



Crossover with Java Bytecode

# Mutation



Crossover with Java Bytecode





# Outline

- 1 Background
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs
- 4 Using Instruction-level Code to Automate Bug Repair
- 5 Conclusions

# Source Code Constraints

- While it would be useful, it is difficult to apply evolution to an entire program in source code
  - Source code is made to simplify reading and writing programs
  - Source code does not represent the semantic constraints of the program.

# Source Code Constraints

```
float x;  int y = 7;
if (y >= 0)
    x = y;
else
    x = -y;
System.out.println(x);
```

(a)

```
int x = 7;  float y;
if (y >= 0) {
    y = x;
    x = y;
}
System.out.println(z);
```

(b)

Both (a) and (b) are valid syntactically. However (b) is invalid semantically.



# Source Code Constraints

- EAs are usually designed to avoid dealing with semantic constraints

```
class Robot{  
...  
    double robotSpeed(){  
        double evolvedVariable = valueFromEA;  
        return (robot.location + evolvedVariable)/2;  
    }  
...  
}
```

# Instruction-Level Code Constraints

- Consists of a smaller alphabets
- Simpler syntactically
- Less semantic constraints to violate

# Instruction-level Code Benefits

- Do not need to understand the structure of the program being evolved
- Can evolve a lot from a little
- If there is a compiler for it we can evolve it


# Outline

- 1 Background
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs**
  - How it Works
  - Results
- 4 Using Instruction-level Code to Automate Bug Repair
- 5 Conclusions

# Selecting Offspring


- There is still a chance to produce non-compilable code
- Solution: add restrictions to code selection
  - Stack and Frame Depth
  - Variable Types
  - Control Flow

# Good Crossover



How it works

# Bad Crossover



# Results

- The array sum problem
  - Started with a zero fitness seed program
  - Counted function calls to check for a non-halting state

```
int sumlistrec(List list){  
    int sum = 0;  
    if(list.isEmpty())  
        sum += sumlistrec(list);  
    else  
        sum += list.get(0)/2 + sumlistrec(  
            list.subList(1, list.size()));  
    return sum;  
}
```



# Results

```
int sumlistrec(List list) {  
    int sum = 0;  
    if (list.isEmpty())  
        sum = sum;  
    else  
        sum += ((Integer)list.get(0)).intValue() +  
               sumlistrec(list.subList(1,  
                                       list.size()));  
    return sum;  
}
```

# Outline

- 1 Background
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs
- 4 Using Instruction-level Code to Automate Bug Repair**
  - How it Works
  - Results
- 5 Conclusions



# Selecting Offspring

- Each instruction is given a weight
- The weight is determined by what tests execute that instruction
- Each experiment started with one negative test case and multiple positive test cases

# Non-Halting Offspring

- Only executed by failing test: weight = 1.0
- Executed by negative test and one positive: weight = 0.1
- Not executed by negative test case: weight = 0

# Outline

- 1 Background
- 2 Why Evolve Instruction-Level Code
- 3 FINCH:Evolving Programs
- 4 Using Instruction-level Code to Automate Bug Repair
- 5 Conclusions**

# Conclusions

# References