

Chapter 10: Elementary Data Structures


Section 10.3: Representing Rooted Trees

- Trees are composed by tree nodes.
- Each tree node has a key field and some other pointer fields pointing to other nodes. Number of pointer fields in a tree node may be different for different types of trees.
- A tree T has an attribute $T.root$: a pointer to the root of the tree.

Binary Trees

For each node x , there are 3 pointer fields and one data field

- $x.p$ is a pointer to x 's parent.
- $x.left$ is a pointer to x 's left child.
- $x.right$ is a pointer to x 's right child.
- $x.data$ is a pointer to x 's satellite data



```

public class BinaryTree<T> {
    private Node<T> root;

    // Note that the generic variable for Node must be different than the one
    // for BinaryTree, otherwise it will cause a compile error.
    public class Node<S> {
        private Node<S> parent;
        private Node<S> left;
        private Node<S> right;
        private S data; //arbitrary data
        //...
    }
    //...
}

```

Rooted Tree with Bounded Branches

We can represent a general tree that has a bounded number of branches by using an array of pointers. Let the bound be r (also know as the **degree**). A node in such a tree will have the following fields:

- $x.p$ is a pointer to x 's parent.
- $x.child[1:r]$ is a pointer to x 's children, up to r of them.
- $x.data$ is a pointer to x 's satellite data

In general, this would be space inefficient as most of the child pointers will be NIL. But it provides an easy and fast way to access the i child of any node.

Assume that the array of child pointers starts at 0. We will denote r using the variable degree in the code below.

```

public class ArbitraryTree<T> {
    private Node<T> root;
    private int degree;


    public Tree(int degree) {
        this.degree = degree;
    }
    public class Node<S> {
        private Node<S> parent;
        private Node<S> child[];
        private S data; //arbitrary data

        //...
    }
    //...
}

```

Rooted Trees with Unbounded Branches

- Each node can have any number of children.
- Using **left-child, right-sibling representation** allows us to represent an arbitrary tree using only three pointers per node.
- Three pointer fields for each node x .
 - $x.p$ is a pointer to x 's parent.
 - $x.left$ is a pointer to x 's left-most child.
 - $x.right$ is a pointer to the sibling of x immediately to the right.



- Write the Java class declaration for the left-child right-sibling representation of an arbitrary tree.

Recommended Exercises


- **Exercise 10.3-1.** Left as an exercise for the reader.
- **Inclass - Exercise 10.3-2.** Let us develop a simple recursive solution for printing key (or data) of each node in a binary tree.

```
PrintAll (root)
// Print the data of each node in the subtree at root
```

- **Exercise 10.3-4.** Write a simple $O(n)$ recursive solution for printing key (or data) of each node in a tree with unbounded branches, represented using the left-child right-sibling representation.

Tree Traversals

- A **tree traversal** is a systematic way of visiting all the nodes in a tree exactly once. Tree traversals are used in many applications. For example, we can use a tree traversal to print the key of each node in a tree (like we did above).
- We will discuss three types of tree traversals: **preorder**, **inorder**, and **postorder**.
- For a binary tree, we can define the three types of traversals as follows:
 - **Preorder**: Visit the root, then recursively visit the left subtree, and finally recursively visit the right subtree.
 - **Inorder**: Recursively visit the left subtree, then visit the root, and finally recursively visit the right subtree.
 - **Postorder**: Recursively visit the left subtree, then recursively visit the right subtree, and finally visit the root.
- For a tree with unbounded branches, we can define the three types of traversals as follows:
 - **Preorder**: Visit the root, then recursively visit each child from left to right.
 - **Inorder**: Recursively visit the first $\lceil n/2 \rceil$ children from left to right, then visit the root, and finally recursively visit the remaining $\lfloor n/2 \rfloor$ children from left to right.
 - **Postorder**: Recursively visit each child from left to right, and finally visit the root.



inorder traversal

$d \rightarrow b \rightarrow e \rightarrow a \rightarrow f \rightarrow c \rightarrow g$

preorder traversal

$a \rightarrow b \rightarrow d \rightarrow e \rightarrow c \rightarrow f \rightarrow g$

postorder traversal

$d \rightarrow e \rightarrow b \rightarrow f \rightarrow g \rightarrow c \rightarrow a$

- **Recommended Exercises:**

- Write a simple $O(n)$ recursive solution for printing key (or data) of each node in a binary tree using preorder, inorder, and postorder traversals.
- Show the output from your three procedures for a binary tree of your choice.