

# Chapter 1: Introduction

# What is a Distributed System?

# What is a Distributed System?

- ▶ A *distributed system* is a collection of independent computers that appears to its users as a single coherent system.

## Examples (1)

The image shows the Netflix logo, which consists of the word "NETFLIX" in a bold, white, sans-serif font. The letters have a 3D effect with a black drop shadow. The logo is centered on a solid red rectangular background.

# Examples (1)



<http://techblog.netflix.com/2012/06/netflix-operations-part-i-going.html>

*The Internet is just a world passing around notes in a classroom. –Jon Stewart*


# Examples (2)




Google Search

I'm Feeling Lucky

## Examples (2)



## Examples (2)





# Examples (3)

- ▶ Google search, GMail, Google Docs, et al

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al

## Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella



# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)

## Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)
- ▶ Git: distributed version control system.

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)
- ▶ Git: distributed version control system.
- ▶ SETI: a distributed computing project in which volunteers donate idle computer power to analyze radio signals for signs of extraterrestrial intelligence.

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)
- ▶ Git: distributed version control system.
- ▶ SETI: a distributed computing project in which volunteers donate idle computer power to analyze radio signals for signs of extraterrestrial intelligence.
- ▶ Folding@home (FAH or F@h): a distributed computing project for disease research that simulates protein folding, computational drug design, and other types of molecular dynamics.

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)
- ▶ Git: distributed version control system.
- ▶ SETI: a distributed computing project in which volunteers donate idle computer power to analyze radio signals for signs of extraterrestrial intelligence.
- ▶ Folding@home (FAH or F@h): a distributed computing project for disease research that simulates protein folding, computational drug design, and other types of molecular dynamics.
- ▶ Bitcoin: decentralized digital currency

# Examples (3)

- ▶ Google search, GMail, Google Docs, et al
- ▶ Amazon
- ▶ Facebook, Twitter, EBay
- ▶ LinkedIn, WhatsApp, Instagram, Snapchat, Uber
- ▶ Hadoop, Hive, Zookeeper, et al
- ▶ No-SQL Databases like HBase, Cassandra, MongoDB, et al
- ▶ **Distributed file systems**: NFS (Network File System), Google File System (GFS), Hadoop Distributed File System (HDFS), Amazon S3, Lustre, GlusterFS, Parallel Virtual File System (PVFS)
- ▶ **P2P: Peer to Peer**: Bit Torrent, Gnutella
- ▶ Domain Name System (DNS)
- ▶ Git: distributed version control system.
- ▶ SETI: a distributed computing project in which volunteers donate idle computer power to analyze radio signals for signs of extraterrestrial intelligence.
- ▶ Folding@home (FAH or F@h): a distributed computing project for disease research that simulates protein folding, computational drug design, and other types of molecular dynamics.
- ▶ Bitcoin: decentralized digital currency
- ▶ Virtually every substantial website!

# In-class Exercise

- ▶ Walk through architecture of various distributed systems ranging from: single server/client, multiple server/clients to point to point.


# How to Implement a Distributed System?

- ▶ In order to support a single system view on multiple computers and networks, we need a layer of abstraction implemented in software that is logically placed in the middle of higher layer of users and applications and the lower layer of operating systems and networks. We call this layer the **middleware**.



# How to Implement a Distributed System?

- ▶ In order to support a single system view on multiple computers and networks, we need a layer of abstraction implemented in software that is logically placed in the middle of higher layer of users and applications and the lower layer of operating systems and networks. We call this layer the **middleware**.



# Goals of a Distributed System?

- ▶ Makes resources accessible

# Goals of a Distributed System?

- ▶ Makes resources accessible
- ▶ Reasonably hides the fact that resources are distributed across a network (*Transparency*)

# Goals of a Distributed System?

- ▶ Makes resources accessible
- ▶ Reasonably hides the fact that resources are distributed across a network (*Transparency*)
- ▶ Open

# Goals of a Distributed System?

- ▶ Makes resources accessible
- ▶ Reasonably hides the fact that resources are distributed across a network (*Transparency*)
- ▶ Open
- ▶ Scalable

- ▶ Benefits

# Making Resources Accessible

- ▶ Benefits
  - ▶ Better economics by sharing expensive resources
  - ▶ Easier to collaborate and exchange information
  - ▶ Create virtual organizations where geographically dispersed people can work together using groupware
  - ▶ Enables electronic commerce
- ▶ Problems

# Making Resources Accessible

## ► Benefits

- Better economics by sharing expensive resources
- Easier to collaborate and exchange information
- Create virtual organizations where geographically dispersed people can work together using groupware
- Enables electronic commerce

## ► Problems

- Eavesdropping or intrusion on communication
- Tracking of communication to build a profile



# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located
Migration	Hide that a resource may move to another location

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located
Migration	Hide that a resource may move to another location
Relocation	Hide that a resource may move to another location while in use

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located
Migration	Hide that a resource may move to another location
Relocation	Hide that a resource may move to another location while in use
Replication	Hide that a resource has multiple copies

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located
Migration	Hide that a resource may move to another location
Relocation	Hide that a resource may move to another location while in use
Replication	Hide that a resource has multiple copies
Concurrency	Hide that a resource may be shared by several competitive users

# Transparency

Type	Description
Access	Hide differences in data representation and how a resource is accessed
Location	Hide where a resource is located
Migration	Hide that a resource may move to another location
Relocation	Hide that a resource may move to another location while in use
Replication	Hide that a resource has multiple copies
Concurrency	Hide that a resource may be shared by several competitive users
Failure	Hide the failure and recovery of a resource

# Degree of Transparency

Completely hiding the distribution aspects from users is not always a good idea in a distributed system.



# Degree of Transparency

Completely hiding the distribution aspects from users is not always a good idea in a distributed system.

- ▶ Attempting to mask a server failure before trying another one may slow down the system

# Degree of Transparency

Completely hiding the distribution aspects from users is not always a good idea in a distributed system.

- ▶ Attempting to mask a server failure before trying another one may slow down the system
- ▶ Expecting several replicas to be always consistent could degrade performance unacceptably

# Degree of Transparency

Completely hiding the distribution aspects from users is not always a good idea in a distributed system.

- ▶ Attempting to mask a server failure before trying another one may slow down the system
- ▶ Expecting several replicas to be always consistent could degrade performance unacceptably
- ▶ For mobile and embedded devices, it may be better to expose distribution rather than trying to hide it

# Degree of Transparency

Completely hiding the distribution aspects from users is not always a good idea in a distributed system.

- ▶ Attempting to mask a server failure before trying another one may slow down the system
- ▶ Expecting several replicas to be always consistent could degrade performance unacceptably
- ▶ For mobile and embedded devices, it may be better to expose distribution rather than trying to hide it
- ▶ Signal transmission is limited by the speed of light as well as the speed of intermediate switches

# Openness

An **open** distributed system offers services according to standard rules that describe the syntax and semantics of those services.

# Openness

An **open** distributed system offers services according to standard rules that describe the syntax and semantics of those services.

- ▶ Use of standard protocols.

An **open** distributed system offers services according to standard rules that describe the syntax and semantics of those services.

- ▶ Use of standard protocols.
- ▶ Services are described via **interfaces**, which are often describe via an **Interface Definition Language (IDL)**. Interfaces only specify syntax so semantics is left to the ambiguities of natural language.

An **open** distributed system offers services according to standard rules that describe the syntax and semantics of those services.

- ▶ Use of standard protocols.
- ▶ Services are described via **interfaces**, which are often describe via an **Interface Definition Language (IDL)**. Interfaces only specify syntax so semantics is left to the ambiguities of natural language.
- ▶ Interoperability, Portability, Extensibility.
- ▶ Separating policy from mechanism. For example: *caching* in a web browser.



# Scalability

Scalability can be measured against three dimensions.

# Scalability

Scalability can be measured against three dimensions.

- ▶ **Size**: be able to easily add more users and resources to a system

Scalability can be measured against three dimensions.

- ▶ **Size**: be able to easily add more users and resources to a system
- ▶ **Geographical**: be able to handle users and resources that are far apart

Scalability can be measured against three dimensions.

- ▶ **Size**: be able to easily add more users and resources to a system
- ▶ **Geographical**: be able to handle users and resources that are far apart
- ▶ **Administrative**: be able to manage even if it spans independent administrative organizations

**Centralized** versus **distributed** implementations.

# Centralized Solutions with Scalability Problems

# Centralized Solutions with Scalability Problems

- ▶ Centralized services.

# Centralized Solutions with Scalability Problems

- ▶ Centralized services.
- ▶ Centralized data.

# Centralized Solutions with Scalability Problems

- ▶ Centralized services.
- ▶ Centralized data.
- ▶ Centralized algorithms.



Characteristics of decentralized algorithms:

Characteristics of decentralized algorithms:

- ▶ No machine has complete information about the system state.

Characteristics of decentralized algorithms:

- ▶ No machine has complete information about the system state.
- ▶ Machines make decisions based only on local information.

Characteristics of decentralized algorithms:

- ▶ No machine has complete information about the system state.
- ▶ Machines make decisions based only on local information.
- ▶ Failure of one machine does not ruin the algorithm.

Characteristics of decentralized algorithms:

- ▶ No machine has complete information about the system state.
- ▶ Machines make decisions based only on local information.
- ▶ Failure of one machine does not ruin the algorithm.
- ▶ There is no implicit assumption that a global clock exists.

**In-class exercise.** Simulate a centralized and a distributed algorithm for the same problem in class!

# Scaling Techniques

# Scaling Techniques

- ▶ **Hiding communication latencies:** Examples would be asynchronous communication as well as pushing code down to clients (E.g. Javascript)

# Scaling Techniques

- ▶ **Hiding communication latencies:** Examples would be asynchronous communication as well as pushing code down to clients (E.g. Javascript)
- ▶ **Distribution:** Taking a component, splitting into smaller parts, and subsequently spreading them across the system. (E.g. Domain Name System)



# Scaling Techniques

- ▶ **Hiding communication latencies:** Examples would be asynchronous communication as well as pushing code down to clients (E.g. Javascript)
- ▶ **Distribution:** Taking a component, splitting into smaller parts, and subsequently spreading them across the system. (E.g. Domain Name System)
- ▶ **Replication:** Replicating components increases availability, helps balance the load leading to better performance, helps hide latencies for geographically distributed systems. **Caching** is a special form of replication.

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change
- ▶ Latency is zero

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change
- ▶ Latency is zero
- ▶ Bandwidth is infinite



# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change
- ▶ Latency is zero
- ▶ Bandwidth is infinite
- ▶ Transport cost is zero

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change
- ▶ Latency is zero
- ▶ Bandwidth is infinite
- ▶ Transport cost is zero
- ▶ There is one administrator

# Distributed System Development Pitfalls

False assumptions made by first time developer (*formulated by Peter Deutsch*).

- ▶ The network is reliable
- ▶ The network is secure
- ▶ The network is homogeneous
- ▶ The topology does not change
- ▶ Latency is zero
- ▶ Bandwidth is infinite
- ▶ Transport cost is zero
- ▶ There is one administrator

“A distributed system is one in which the failure of a computer you didn't even know existed can render your own computer unusable.”  
—Leslie Lamport

# Types of Distributed Systems

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems
- ▶ *Distributed Information Systems*

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems
- ▶ *Distributed Information Systems*
  - ▶ Transaction Processing Systems
  - ▶ Enterprise Application Integration



# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems
- ▶ *Distributed Information Systems*
  - ▶ Transaction Processing Systems
  - ▶ Enterprise Application Integration
- ▶ *Distributed Pervasive Systems*

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems
- ▶ *Distributed Information Systems*
  - ▶ Transaction Processing Systems
  - ▶ Enterprise Application Integration
- ▶ *Distributed Pervasive Systems*
  - ▶ Home Systems
  - ▶ Electronic Health Care Systems
  - ▶ Sensor Networks

# Types of Distributed Systems

- ▶ *Distributed Computing Systems*
  - ▶ Cluster Computing Systems
  - ▶ Grid Computing Systems
- ▶ *Distributed Information Systems*
  - ▶ Transaction Processing Systems
  - ▶ Enterprise Application Integration
- ▶ *Distributed Pervasive Systems*
  - ▶ Home Systems
  - ▶ Electronic Health Care Systems
  - ▶ Sensor Networks

**In-class Exercise:** Classify the examples we have seen so far into the three categories above.

# Cluster Computing

# Cluster Computing

- ▶ A **computer cluster** is primarily used to run a single program in parallel on multiple machines. The program relies on parallel libraries and frameworks such as MPI, MapReduce and others.

# Cluster Computing


- ▶ A **computer cluster** is primarily used to run a single program in parallel on multiple machines. The program relies on parallel libraries and frameworks such as MPI, MapReduce and others.
- ▶ A *computer cluster* consists of a collection of compute and I/O nodes that are controlled and accessed from a single master node. The master allocates nodes to a parallel program, maintains a queue of submitted jobs and provides an interface to manage the cluster.

# Cluster Computing

- ▶ A **computer cluster** is primarily used to run a single program in parallel on multiple machines. The program relies on parallel libraries and frameworks such as MPI, MapReduce and others.
- ▶ A *computer cluster* consists of a collection of compute and I/O nodes that are controlled and accessed from a single master node. The master allocates nodes to a parallel program, maintains a queue of submitted jobs and provides an interface to manage the cluster.
- ▶ A cluster usually has a dedicated high-speed interconnection network and an optional administrative network.

# Cluster Computing

- ▶ A **computer cluster** is primarily used to run a single program in parallel on multiple machines. The program relies on parallel libraries and frameworks such as MPI, MapReduce and others.
- ▶ A *computer cluster* consists of a collection of compute and I/O nodes that are controlled and accessed from a single master node. The master allocates nodes to a parallel program, maintains a queue of submitted jobs and provides an interface to manage the cluster.
- ▶ A cluster usually has a dedicated high-speed interconnection network and an optional administrative network.





# Transaction Processing Systems (1)

Transaction primitives:

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ `BEGIN_TRANSACTION`

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ `BEGIN_TRANSACTION`
- ▶ `END_TRANSACTION`

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

ACID characteristic properties of transactions:

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

ACID characteristic properties of transactions:

- ▶ **Atomic**: To the outside world, the transaction happens indivisibly

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

ACID characteristic properties of transactions:

- ▶ **Atomic**: To the outside world, the transaction happens indivisibly
- ▶ **Consistent**: The transaction does not violate system invariants



# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

ACID characteristic properties of transactions:

- ▶ **Atomic**: To the outside world, the transaction happens indivisibly
- ▶ **Consistent**: The transaction does not violate system invariants
- ▶ **Isolated**: Concurrent transactions do not interfere with each other

# Transaction Processing Systems (1)

Transaction primitives:

- ▶ BEGIN\_TRANSACTION
- ▶ END\_TRANSACTION
- ▶ ABORT\_TRANSACTION
- ▶ READ, WRITE

ACID characteristic properties of transactions:

- ▶ **Atomic**: To the outside world, the transaction happens indivisibly
- ▶ **Consistent**: The transaction does not violate system invariants
- ▶ **Isolated**: Concurrent transactions do not interfere with each other
- ▶ **Durable**: Once a transaction commits, the changes are permanent

# Transaction Processing Systems (1)

Transaction primitives:


- ▶ `BEGIN_TRANSACTION`
- ▶ `END_TRANSACTION`
- ▶ `ABORT_TRANSACTION`
- ▶ `READ`, `WRITE`

**ACID** characteristic properties of transactions:


- ▶ **Atomic**: To the outside world, the transaction happens indivisibly
- ▶ **Consistent**: The transaction does not violate system invariants
- ▶ **Isolated**: Concurrent transactions do not interfere with each other
- ▶ **Durable**: Once a transaction commits, the changes are permanent

Transactions can be **nested**. Durability applies to top-level transactions only. For example: an airline and a hotel database.

# Transaction Processing Systems (2)



# Enterprise Application Integration



Middleware as a communication facilitator for enterprise application integration.

# Distributed Pervasive Systems

Requirements for pervasive systems:

- ▶ Embrace contextual changes.
- ▶ Encourage ad hoc composition.
- ▶ Recognize sharing as the default.

Examples: Home systems, Body Area Networks, Sensor Networks.

# Chapter 1: Recommended Exercises

- ▶ **Problem 1.** What is the role of middleware in a distributed system?
- ▶ **Problem 2.** Explain what is meant by transparency, and give examples of different types of transparency.
- ▶ **Problem 3.** Scalability can be achieved by applying different techniques. What are these techniques?
- ▶ **Problem 4.** Give further examples of distributed pervasive systems.