Networks and Network Programming

```
Edit View Go Capture Analyze Statistics Telephony Tools Internals Help
    218 7.578#51000 31.12.64.208
                                                                                         192,168,0,10
                                                                                                                                     | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 
          225 7,573980000 31,12,64,208
                                                                                              192,160,0,10
                                                                                              31,12,64,208
                                                                                               192,168,0.10
                                                                                               192,168.0.10
                                                                                                                                                                 66 36256-60 [ACK] 566-1 ACK-127905 NLN-1439 Len-0 T5VaL+130558996 T56CC-3446276552
1320 80-36256 [PSH, ACK] Sequi27905 Ackul VCru54 Lenu1254 T5vaLu3468276574 T5ecru13055
                                                                                                                                                                   1320 80-35256 [PSH, ACK] Seg=129159 Ack=1 Win=54 Lan=1254 TSHal=3448276574 TSecr=1305
                                                                                                                                                                           1000 90-36056 [P94, 80K] Sept130813 Acks1 Vern54 Lens1254 TSvaltn348827609 TSecro100587
66 30256-80 [AO] Sept1 Acks121667 Nin=1494 Lens0 TSvalt-300550004 TSecr=344827609
                                                                                                                                                                                  00 [TCP Out-Of-Order] 80-90256 [PSH, ADK] 509+150520 Adket Wine54 Len-1254 TSHAT-9
86 36256-80 [ADK] 50941 Adkul95428 Wine1409 LeneD TSVALH30556205 TSecru3448276680
  > Frame 231: 1220 bytes on wire (10560 bits), 1320 bytes captured [10560 bits] on interface 0
  - Transmission Control Protocol, Src Port: 80 (80), bet Port: 8056 (8056), Seq: 10080, sck: 1, Len:
           Destination Port: 36256 (36256)
          ITCP Segment Len; 12541
           Sequence number: 132520 (relative sequence number)
          [Next sequence number: 134174 [relative sequence number)]
           Acknowledgment number: 1 (relative ack number)
       + .... 0000 0001 1000 = Flags: 0x018 (PSH, ACK)
           Window size value: 54
          [Calculated window size: 54]
          [Window size scaling factor: -1 (unknown)]
⊕ # enp6s0: «Iwe capture in progres... Packets: 1160 - Displayed: 1160 (100.0%)
                                                                                                                                                                                                                                                                                                                                                                                                                                Profile: Default
```

Wireshark screenshot of network traffic

Networking

- Hardware
- Protocols
- Software

The network is the computer. (John Gage)

► Network Topology

Network Topology

Links: wired or wireless

- Network Topology
 - Links: wired or wireless
 - ► Nodes:
 - interfaces

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points

- Network Topology
 - Links: wired or wireless
 - ► Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - ► Data: packets

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - ► Data: packets
- ► Protocols

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)
 - Cellular standards


- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)
 - Cellular standards
- Software
 - OSI seven layer model


- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)
 - Cellular standards
- Software
 - OSI seven layer model
 - Services, Ports

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)
 - Cellular standards
- Software
 - OSI seven layer model
 - Services, Ports
 - Security: SSL (Secure Sockets Layer), TLS (Transport Layer Security)

- Network Topology
 - Links: wired or wireless
 - Nodes:
 - interfaces
 - repeaters/hubs
 - bridges/switches/access points
 - routers
 - modems
 - firewalls
 - Data: packets
- Protocols
 - Internet (Internet Protocol), TCP (Transmission Control Protocol), UDP (User Datagram Protocol), SCTP (Stream Control Transmission Protocol)
 - ► IEEE 802: Ethernet, Wireless LAN (Local Area Network)
 - Cellular standards
- Software
 - OSI seven layer model
 - Services, Ports
 - Security: SSL (Secure Sockets Layer), TLS (Transport Layer Security)
 - Servers and clients









Networking Options

Network type	maximum bandwidth	latency	
	(Mbits/second)	(microsecs)	
Fast Ethernet	100	200	
Gigabit Ethernet	1000	20–62	
10 Gigabit Ethernet	10,000	4	
Infiniband	2,000-290,000	0.5–5	

Networking Options

Network type	maximum bandwidth	latency	
	(Mbits/second)	(microsecs)	
Fast Ethernet	100	200	
Gigabit Ethernet	1000	20-62	
10 Gigabit Ethernet	10,000	4	
Infiniband	2,000-290,000	0.5–5	

► Ethernet is the most cost-effective choice. Ethernet is a packet-based serial multi-drop network requiring no centralized control. All network access and arbitration control is performed by distributed mechanisms.

Networking Options

Network type	maximum bandwidth	latency	
	(Mbits/second)	(microsecs)	
Fast Ethernet	100	200	
Gigabit Ethernet	1000	20–62	
10 Gigabit Ethernet	10,000	4	
Infiniband	2,000-290,000	0.5–5	

- Ethernet is the most cost-effective choice. Ethernet is a packet-based serial multi-drop network requiring no centralized control. All network access and arbitration control is performed by distributed mechanisms.
- Internet backbone uses specialized hardware and has speeds up to 500G/s. Experimental systems are available for much higher speeds.

Ethernet Protocol

In an Ethernet network, machines use the Carrier Sense Multiple Access with Collision Detect (CSMA/CD) protocol for arbitration when multiple machines try to access the network at the same time.

Ethernet Protocol

- ▶ In an Ethernet network, machines use the Carrier Sense Multiple Access with Collision Detect (CSMA/CD) protocol for arbitration when multiple machines try to access the network at the same time.
 - If packets collide, then the machines choose a random number from the interval (0, k) and try again.

Ethernet Protocol

- ▶ In an Ethernet network, machines use the Carrier Sense Multiple Access with Collision Detect (CSMA/CD) protocol for arbitration when multiple machines try to access the network at the same time.
 - If packets collide, then the machines choose a random number from the interval (0, k) and try again.
 - ▶ On subsequent collisions, the value *k* is doubled each time, making it a lot less likely that a collision would occur again. This is an example of an *exponential backoff protocol*.

The Ethernet packet has the format shown below.

Ethernet Packet Format

Preamble 10101010	Synch	Destination Address	Source Address	Туре	Data	Frame Check Sequence
62 bits	2 bits	6 bytes	6 bytes	2 bytes	16-1500 bytes	4 bytes
			/			
				by higher		
			level	software		

The Ethernet packet has the format shown below.

Preamble 10101010		Destination Address	Source Address	Туре	Data	Frame Check Sequence
62 bits	2 bits	6 bytes	6 bytes	2 bytes	16–1500 bytes	4 bytes
				by highe	r	

▶ Note that the Maximum Transmission Unit (MTU) is 1500 bytes. Messages larger than that must be broken into smaller packets by higher layer network software.

The Ethernet packet has the format shown below.

Preamble 10101010		Destination Address	Source Address	Туре	Data	Frame Check Sequence
62 bits	2 bits	6 bytes	6 bytes	2 bytes	16-1500 bytes	4 bytes
				by higher		

- Note that the Maximum Transmission Unit (MTU) is 1500 bytes. Messages larger than that must be broken into smaller packets by higher layer network software.
- ➤ Some switches accept Jumbo packets (up to 9000 bytes), which can improve the performance significantly.

The Ethernet packet has the format shown below.

Preamble 10101010		Destination Address	Source Address	Туре	Data	Frame Check Sequence
62 bits	2 bits	6 bytes	6 bytes	2 bytes	16-1500 bytes	4 bytes
				by higher		

- Note that the Maximum Transmission Unit (MTU) is 1500 bytes. Messages larger than that must be broken into smaller packets by higher layer network software.
- ➤ Some switches accept Jumbo packets (up to 9000 bytes), which can improve the performance significantly.
- ► For many network drivers under Linux, the MTU can be set on the fly without reloading the driver!

The Ethernet packet has the format shown below.

Preamble 10101010		Destination Address	Source Address	Туре	Data	Frame Check Sequence
62 bits	2 bits	6 bytes	6 bytes	2 bytes	16–1500 bytes	4 bytes
				by highe		

- Note that the Maximum Transmission Unit (MTU) is 1500 bytes. Messages larger than that must be broken into smaller packets by higher layer network software.
- ➤ Some switches accept Jumbo packets (up to 9000 bytes), which can improve the performance significantly.
- ► For many network drivers under Linux, the MTU can be set on the fly without reloading the driver!

Use the program wireshark to watch live Ethernet packets on your network!

Network Topology Design

Ranges of possibilities.

Shared multi-drop passive cable, or

Network Topology Design

Ranges of possibilities.

- ► Shared multi-drop passive cable, or
- ► Tree structure of hubs and switches, or

Network Topology Design

Ranges of possibilities.

- ▶ Shared multi-drop passive cable, or
- Tree structure of hubs and switches, or
- Custom complicated switching technology, or

Network Topology Design

Ranges of possibilities.

- Shared multi-drop passive cable, or
- Tree structure of hubs and switches, or
- Custom complicated switching technology, or
- One big switch.

Network Topology Options

Hubs and Switches.

▶ Direct wire. Two machines can be connected directly by a Ethernet cable (usually a Cat 5e cable) without needing a hub or a switch. With multiple NICs per machine, we can create networks but then we need to specify routing tables to allow packets to get through. The machines will end up doing double-duty as routers.

Network Topology Options

Hubs and Switches.

- ▶ Direct wire. Two machines can be connected directly by a Ethernet cable (usually a Cat 5e cable) without needing a hub or a switch. With multiple NICs per machine, we can create networks but then we need to specify routing tables to allow packets to get through. The machines will end up doing double-duty as routers.
- ▶ Hubs and Repeaters All machines are visible from all machines and the CSMA/CD protocol is still used. A hub/repeater receives signals, cleans and amplifies, redistributes to all nodes.

Network Topology Options

Hubs and Switches.

- ▶ Direct wire. Two machines can be connected directly by a Ethernet cable (usually a Cat 5e cable) without needing a hub or a switch. With multiple NICs per machine, we can create networks but then we need to specify routing tables to allow packets to get through. The machines will end up doing double-duty as routers.
- ▶ Hubs and Repeaters All machines are visible from all machines and the CSMA/CD protocol is still used. A hub/repeater receives signals, cleans and amplifies, redistributes to all nodes.
- Switches. Accepts packets, interprets destination address fields and send packets down only the segment that has the destination node. Allows half the machines to communicate directly with the other half (subject to bandwidth constraints of the switch hardware). Multiple switches can be connected in a tree or sometimes other schemes. The root switch can become a bottleneck. The root switch can be a higher bandwidth switch.

Switches can be managed or unmanaged. Managed switches are more expensive but they also allow many useful configurations. Here are some examples.

Port trunking (a.k.a Cisco EtherChannel). Allows up to 4 ports to be treated as one logical port. For example, this would allow a 4 Gbits/sec connection between two Gigabit switches.

- Port trunking (a.k.a Cisco EtherChannel). Allows up to 4 ports to be treated as one logical port. For example, this would allow a 4 Gbits/sec connection between two Gigabit switches.
- Linux Channel Bonding. Channel bonding means to bond together multiple NICs into one logical network connection. This requires the network switch to support some form of port trunking. Supported in the Linux kernel.

- Port trunking (a.k.a Cisco EtherChannel). Allows up to 4 ports to be treated as one logical port. For example, this would allow a 4 Gbits/sec connection between two Gigabit switches.
- Linux Channel Bonding. Channel bonding means to bond together multiple NICs into one logical network connection. This requires the network switch to support some form of port trunking. Supported in the Linux kernel.
- Switch Meshing. Allows up to 24 ports between switches to be treated as a single logical port, creating a very high bandwidth connection. useful for creating custom complicated topologies.

- Port trunking (a.k.a Cisco EtherChannel). Allows up to 4 ports to be treated as one logical port. For example, this would allow a 4 Gbits/sec connection between two Gigabit switches.
- Linux Channel Bonding. Channel bonding means to bond together multiple NICs into one logical network connection. This requires the network switch to support some form of port trunking. Supported in the Linux kernel.
- Switch Meshing. Allows up to 24 ports between switches to be treated as a single logical port, creating a very high bandwidth connection. useful for creating custom complicated topologies.
- ▶ Stackable, high bandwidth switches. Stackable switches with special high bandwidth interconnect in-between the switches. For example, Cisco has 24-port Gigabit stackable switches with a 32 Gbits/sec interconnect. Up to 8 such switches can be stacked together. All the stacked switches can be controlled by one switch and managed as a single switch. If the controlling switch fails, the remaining switches hold an election and a new controlling switch is elected. Baystack also has stackable switches with a 40 Gbits/sec interconnect.

Network Interface Cards

► The Ethernet card, also known as the Network Interface Controller (NIC), contains the Data Link Layer and the Physical Layer (the two lowest layers of networking). Each Ethernet card has a unique hardware address that is know as its MAC address (MAC stands for Media Access Controller). The MAC address is usually printed on the Ethernet card.

Network Interface Cards

- ► The Ethernet card, also known as the Network Interface Controller (NIC), contains the Data Link Layer and the Physical Layer (the two lowest layers of networking). Each Ethernet card has a unique hardware address that is know as its MAC address (MAC stands for Media Access Controller). The MAC address is usually printed on the Ethernet card.
- ► The command ifconfig can be used to determine the MAC address from software. (Use ipconfig on Windows OS)

Network Interface Cards

- ► The Ethernet card, also known as the Network Interface Controller (NIC), contains the Data Link Layer and the Physical Layer (the two lowest layers of networking). Each Ethernet card has a unique hardware address that is know as its MAC address (MAC stands for Media Access Controller). The MAC address is usually printed on the Ethernet card.
- ► The command ifconfig can be used to determine the MAC address from software. (Use ipconfig on Windows OS)
- Another issue to consider is that having multi-processor boards may cause more load on the network cards in each node. Certain network cards have multiple network processors in them, making them better candidates for multi-processor motherboards.

Networking Models

▶ UUCP (Unix to Unix CoPy). Mostly over telephone lines to support mail and USENET news network. UUCP does not support remote login, rpc or distributed file systems.

Networking Models

- UUCP (Unix to Unix CoPy). Mostly over telephone lines to support mail and USENET news network. UUCP does not support remote login, rpc or distributed file systems.
- ► The ARPANET Reference Model (ARM) was the network model that led to the ISO OSI seven layer standardized model.

Networking Models

- ► UUCP (Unix to Unix CoPy). Mostly over telephone lines to support mail and USENET news network. UUCP does not support remote login, rpc or distributed file systems.
- The ARPANET Reference Model (ARM) was the network model that led to the ISO OSI seven layer standardized model.
- ▶ ISO Open System Interconnection (OSI). A reference model for networking prescribes seven layers of network protocols and strict methods of communication between them. Most systems implement simplified version of the OSI model. The ARPANET Reference Model (ARM) can be seen as a simplified OSI model.

Network Models (contd.)

ISO	ARM	4.2 BSD Layers	Example
application	process	user programs/libraries	ssh
presentation	applications		
session		sockets	sock_stream
transport	host-host	protocols	TCP/IP
network	network interface	network interface	Ethernet driver
data link			
hardware	network hardware	network hardware	interlan controller

▶ Protocols are the rules or standard that defines the syntax, semantics and synchronization of communication and possible error recovery methods. Protocols may be implemented by hardware, software, or a combination of both.

- ▶ Protocols are the rules or standard that defines the syntax, semantics and synchronization of communication and possible error recovery methods. Protocols may be implemented by hardware, software, or a combination of both.
- Examples of protocols:
 - ► Internet Protocol (IP), Transmission Control Protocol (TCP), User Datagram Protocol (UDP), Stream Control Transmission Protocol (SCTP)

- ▶ Protocols are the rules or standard that defines the syntax, semantics and synchronization of communication and possible error recovery methods. Protocols may be implemented by hardware, software, or a combination of both.
- Examples of protocols:
 - Internet Protocol (IP), Transmission Control Protocol (TCP), User Datagram Protocol (UDP), Stream Control Transmission Protocol (SCTP)
 - HyperText Transfer Protocol (HTTP), File Transfer Protocol (FTP)

- ▶ Protocols are the rules or standard that defines the syntax, semantics and synchronization of communication and possible error recovery methods. Protocols may be implemented by hardware, software, or a combination of both.
- Examples of protocols:
 - Internet Protocol (IP), Transmission Control Protocol (TCP), User Datagram Protocol (UDP), Stream Control Transmission Protocol (SCTP)
 - HyperText Transfer Protocol (HTTP), File Transfer Protocol (FTP)
 - Java Remote Method Invocation (RMI), Distributed Component Object Model (DCOM)

▶ The most prevalent protocol in networks is the IP (Internet Protocol). There are two higher-level protocols that run on top of the IP protocol. These are TCP (Transmission Control Protocol) and UDP (User Datagram Protocol).

- ▶ The most prevalent protocol in networks is the IP (Internet Protocol). There are two higher-level protocols that run on top of the IP protocol. These are TCP (Transmission Control Protocol) and UDP (User Datagram Protocol).
- ► Two versions of the IP protocol: IPv4 protocol has 32-bit addresses while the IPv6 protocol has 128-bit addresses. IP address range is divided into networks along an address bit boundary.

- ▶ The most prevalent protocol in networks is the IP (Internet Protocol). There are two higher-level protocols that run on top of the IP protocol. These are TCP (Transmission Control Protocol) and UDP (User Datagram Protocol).
- ► Two versions of the IP protocol: IPv4 protocol has 32-bit addresses while the IPv6 protocol has 128-bit addresses. IP address range is divided into networks along an address bit boundary.
- The portion of the address that remains fixed within a network is called the network address and the remainder is the host address.

- ▶ The most prevalent protocol in networks is the IP (Internet Protocol). There are two higher-level protocols that run on top of the IP protocol. These are TCP (Transmission Control Protocol) and UDP (User Datagram Protocol).
- ► Two versions of the IP protocol: IPv4 protocol has 32-bit addresses while the IPv6 protocol has 128-bit addresses. IP address range is divided into networks along an address bit boundary.
- The portion of the address that remains fixed within a network is called the network address and the remainder is the host address.
- ▶ The address with all 0's in the host address, for example 192.168.1.0, is the network address and cannot be assigned to any machine. The address with all 1's in the host address, for example 192.168.1.255, is the network broadcast address.

► A machine can refer to itself with the name localhost, which has a special IP address for it:

```
127.0.0.1 (IPv4)
::1 (IPv6)
```

► A machine can refer to itself with the name localhost, which has a special IP address for it:

```
127.0.0.1 (IPv4)
::1 (IPv6)
```

- Three IP ranges are reserved for private networks.
 - ► 10.0.0.0 10.255.255.255
 - ► 172.16.0.0 172.31.255.255
 - ► 192.168.0.0 − 192.168.255.255

► A machine can refer to itself with the name localhost, which has a special IP address for it:

```
127.0.0.1 (IPv4)
::1 (IPv6)
```

- ► Three IP ranges are reserved for private networks.
 - ► 10.0.0.0 10.255.255.255
 - ► 172.16.0.0 172.31.255.255
 - 192.168.0.0 192.168.255.255
- These addresses are permanently unassigned, not forwarded by Internet backbone routers and thus do not conflict with publicly addressable IP addresses.

A socket is an endpoint of communication.

- ► A socket is an endpoint of communication.
- A socket in use usually has an address bound to it.

- ► A socket is an endpoint of communication.
- A socket in use usually has an address bound to it.
- The nature of the address depends upon the communication domain of the socket.

- ► A socket is an endpoint of communication.
- A socket in use usually has an address bound to it.
- The nature of the address depends upon the communication domain of the socket.
- Processes communicating in the same domain use the same address format.

- ► A socket is an endpoint of communication.
- A socket in use usually has an address bound to it.
- The nature of the address depends upon the communication domain of the socket.
- Processes communicating in the same domain use the same address format.

Typical communication domains:

domain type	symbolic name	address format
Unix domain	AF_Unix	pathnames
Internet domain	$AF_{-}INET$	Internet address and port number

► *Stream sockets.* Reliable, duplex, sequenced data streams. e.g. pipes, TCP protocol

- ➤ *Stream sockets.* Reliable, duplex, sequenced data streams. e.g. pipes, TCP protocol
- Sequenced packet sockets. Reliable, duplex, record boundaries

- Stream sockets. Reliable, duplex, sequenced data streams.
 e.g. pipes, TCP protocol
- Sequenced packet sockets. Reliable, duplex, record boundaries
- Datagram sockets. Unreliable, unsequenced, variable size packets

- ► Stream sockets. Reliable, duplex, sequenced data streams. e.g. pipes, TCP protocol
- Sequenced packet sockets. Reliable, duplex, record boundaries
- Datagram sockets. Unreliable, unsequenced, variable size packets
- Reliably delivered message sockets.

Types of Sockets

- Stream sockets. Reliable, duplex, sequenced data streams.
 e.g. pipes, TCP protocol
- Sequenced packet sockets. Reliable, duplex, record boundaries
- Datagram sockets. Unreliable, unsequenced, variable size packets
- Reliably delivered message sockets.
- Raw sockets. Allows access to TCP, IP or Ethernet protocol

Client-Server Setup Using Sockets

Server side	Client side
create a socket	
bind to an address	create a socket
listen for connections	connect to a server
accept a connection	
read/write to client	read/write to server
close	close or shutdown (input and/or output)

▶ Port numbers in the range 1-255 are reserved in TCP/IP protocol for well known servers. In addition, Linux/Unix reserve the ports 1-1023 for superuser processes. Ports from 1024 to 65535 are available for user processes.

- ▶ Port numbers in the range 1-255 are reserved in TCP/IP protocol for well known servers. In addition, Linux/Unix reserve the ports 1-1023 for superuser processes. Ports from 1024 to 65535 are available for user processes.
- ► The file /etc/services contains the port numbers for well known servers. For example:
 - port 7 is used for echoing the data sent by a client back
 - port 21 is used by the FTP (File Transfer Protocol) client/server
 - ▶ port 22 is used by SSH (Secure Shell Protocol) client/server
 - port 37 is reserved for getting the time from a system
 - ▶ port 80 is used by the HTTP (HyperText Transfer Protocol) daemon
 - port 443 is used by the HTTP over TLS/SSL (Transport Layer Security/Secure Sockets Layer for secure connections) (represented as the https:// protocol)

- ▶ Port numbers in the range 1-255 are reserved in TCP/IP protocol for well known servers. In addition, Linux/Unix reserve the ports 1-1023 for superuser processes. Ports from 1024 to 65535 are available for user processes.
- ► The file /etc/services contains the port numbers for well known servers. For example:
 - port 7 is used for echoing the data sent by a client back
 - port 21 is used by the FTP (File Transfer Protocol) client/server
 - ▶ port 22 is used by SSH (Secure Shell Protocol) client/server
 - port 37 is reserved for getting the time from a system
 - port 80 is used by the HTTP (HyperText Transfer Protocol) daemon
 - port 443 is used by the HTTP over TLS/SSL (Transport Layer Security/Secure Sockets Layer for secure connections) (represented as the https:// protocol)
- ► The configuration directory /etc/systemd.d/ contains several directories and files, one per service type, that control what is provided by the super-daemon systemd under Linux. The super-daemon invokes secondary daemons as needed.

- ▶ Port numbers in the range 1-255 are reserved in TCP/IP protocol for well known servers. In addition, Linux/Unix reserve the ports 1-1023 for superuser processes. Ports from 1024 to 65535 are available for user processes.
- ► The file /etc/services contains the port numbers for well known servers. For example:
 - port 7 is used for echoing the data sent by a client back
 - port 21 is used by the FTP (File Transfer Protocol) client/server
 - ▶ port 22 is used by SSH (Secure Shell Protocol) client/server
 - port 37 is reserved for getting the time from a system
 - ▶ port 80 is used by the HTTP (HyperText Transfer Protocol) daemon
 - port 443 is used by the HTTP over TLS/SSL (Transport Layer Security/Secure Sockets Layer for secure connections) (represented as the https:// protocol)
- ► The configuration directory /etc/systemd.d/ contains several directories and files, one per service type, that control what is provided by the super-daemon systemd under Linux. The super-daemon invokes secondary daemons as needed.
- Systemd subsumes xinetd, an older super daemon that was internet specific (xinetd stands for extended internet daemon).

Servers

Design types:

► A single-threaded server handles one connection at a time.

Servers

Design types:

- A single-threaded server handles one connection at a time.
- ► A multi-threaded server accepts connections and passes them off to their own threads for processing.

Servers

Design types:

- A single-threaded server handles one connection at a time.
- ► A multi-threaded server accepts connections and passes them off to their own threads for processing.
- A multi-process server forks off a copy of itself after a connection to handle the client, while the original server process goes back to accept further connections.

ServerSocket(): Creates an unbound server socket.

- ServerSocket(): Creates an unbound server socket.
- ServerSocket(int port): Creates a server socket, bound to the specified port.

- ServerSocket(): Creates an unbound server socket.
- ServerSocket(int port): Creates a server socket, bound to the specified port.
- ServerSocket(int port, int backlog): Creates a server socket and binds it to the specified local port number, with the specified backlog.

- ServerSocket(): Creates an unbound server socket.
- ServerSocket(int port): Creates a server socket, bound to the specified port.
- ServerSocket(int port, int backlog): Creates a server socket and binds it to the specified local port number, with the specified backlog.
- ► ServerSocket(int port, int backlog, InetAddress bindAddr): Create a server with the specified port, listen backlog, and local IP address to bind to.

- ServerSocket(): Creates an unbound server socket.
- ServerSocket(int port): Creates a server socket, bound to the specified port.
- ServerSocket(int port, int backlog): Creates a server socket and binds it to the specified local port number, with the specified backlog.
- ServerSocket(int port, int backlog, InetAddress bindAddr): Create a server with the specified port, listen backlog, and local IP address to bind to.
- accept(): Listen for a connection to be made and accept it. Blocking call.
- See Java docs for other methods.

Socket(): Creates an unconnected socket, with the system-default type of SocketImpl.

- Socket(): Creates an unconnected socket, with the system-default type of SocketImpl.
- Socket(String host, int port): Creates a stream socket and connects it to the specified port number on the named host.

- Socket(): Creates an unconnected socket, with the system-default type of SocketImpl.
- Socket(String host, int port): Creates a stream socket and connects it to the specified port number on the named host.
- ServerSocket(int port): Creates a server socket, bound to the specified port.

- Socket(): Creates an unconnected socket, with the system-default type of SocketImpl.
- Socket(String host, int port): Creates a stream socket and connects it to the specified port number on the named host.
- ServerSocket(int port): Creates a server socket, bound to the specified port.
- Commonly used methods: connect(), getOutputStream(), getInputStream(), close(), bind() etc
- See Java docs for other methods.

► A server creates a ServerSocket object for a specific port and uses the accept() method to wait for a connection.

- ► A server creates a ServerSocket object for a specific port and uses the accept() method to wait for a connection.
- ► The client uses (hostname, port number) pair to locate the server.

- ► A server creates a ServerSocket object for a specific port and uses the accept() method to wait for a connection.
- ► The client uses (hostname, port number) pair to locate the server.
- ► The server accepts the client's request and creates a Socket object for communicating with the client. There is a separate Socket object created for each client request accepted.

- ► A server creates a ServerSocket object for a specific port and uses the accept() method to wait for a connection.
- ► The client uses (hostname, port number) pair to locate the server.
- The server accepts the client's request and creates a Socket object for communicating with the client. There is a separate Socket object created for each client request accepted.
- Now the server and the client can read/write to the streams associated with the sockets.

- ► A server creates a ServerSocket object for a specific port and uses the accept() method to wait for a connection.
- ► The client uses (hostname, port number) pair to locate the server.
- The server accepts the client's request and creates a Socket object for communicating with the client. There is a separate Socket object created for each client request accepted.
- Now the server and the client can read/write to the streams associated with the sockets.
- ► Always open OutputStream before InputStream on a socket to avoid deadlock and synchronization problems.

Client Example (Java)

```
try {
    Socket server = new Socket("www.party.com",1234);
    OutputStream out = server.getOutputStream();
    InputStream in = server.getInputStream();
    out.write(42); //write a byte
    //write a newline or carriage return delimited string
    PrintWriter pout = new PrintWriter(out, true);
    pout.println("Hello!");
   //read a byte
    Byte response = in.read();
    //read a newline or carriage return delimited string
    BufferedReader bin = new BufferedReader (
        new InputStreamReader(in));
    String answer = bin.readLine();
   //send a serialized Java object
    ObjectOutputStream oout = new ObjectOutputStream(out);
    oout.writeObject(new java.util.Date());
    oout.flush();
    server.close();
} catch (IOException e) {System.err.println(e);}
```

Server Example (Java)

```
trv {//meanwhile. on www.partv.com...
    ServerSocket listener = new ServerSocket(1234);
    while (!finished) {
        Socket client = listener.accept();
        OutputStream out = client.getOutputStream();
        InputStream in = client.getInputStream();
        Byte someByte = in.read(); //read a byte
        //read a newline/carriage return delimited string
        BufferedReader bin =
             new BufferedReader(new InputStreamReader(in));
        String someString = bin.readLine():
        out.write(42); //write a byte
        PrintWriter pout = new PrintWriter(out, true);
        pout.println("Goodbye!");
        //read a serialized Java object
        ObjectInputStream oin = new ObjectInputStream(in);
        Date date = (Date) oin.readObject();
        client.close():
        //...
    listener.close():
 catch (IOException e) {System.err.println(e);}
```

► Each connection is uniquely identified by a five-tuple: source IPaddr, source port, destination IPaddr, destination port, protocol

- ► Each connection is uniquely identified by a five-tuple: source IPaddr, source port, destination IPaddr, destination port, protocol
- A client that uses a Socket to connect to a well-known port on a ServerSocket but does not specify local port gets a random unused local port.

- ► Each connection is uniquely identified by a five-tuple: source IPaddr, source port, destination IPaddr, destination port, protocol
- A client that uses a Socket to connect to a well-known port on a ServerSocket but does not specify local port gets a random unused local port.
- ▶ Once the server accepts the connection, a new socket is created and returned by the accept() method. This has the same port as the server port but since the client is different, it is a unique connection. Hence each connection the server accepts leads to a new socket with a unique connection.

- ► Each connection is uniquely identified by a five-tuple: source IPaddr, source port, destination IPaddr, destination port, protocol
- A client that uses a Socket to connect to a well-known port on a ServerSocket but does not specify local port gets a random unused local port.
- Once the server accepts the connection, a new socket is created and returned by the accept() method. This has the same port as the server port but since the client is different, it is a unique connection. Hence each connection the server accepts leads to a new socket with a unique connection.
- A server can connect on the same port with either TCP or UDP protocols.

- ► Each connection is uniquely identified by a five-tuple: source IPaddr, source port, destination IPaddr, destination port, protocol
- A client that uses a Socket to connect to a well-known port on a ServerSocket but does not specify local port gets a random unused local port.
- Once the server accepts the connection, a new socket is created and returned by the accept() method. This has the same port as the server port but since the client is different, it is a unique connection. Hence each connection the server accepts leads to a new socket with a unique connection.
- A server can connect on the same port with either TCP or UDP protocols.
- ► Thus, all the data coming into a specific network interface gets handed off to an appropriate connection.

See the folder and subfolders in sockets.

➤ Single-threaded server and client (in package tcp.singlethreaded): TimeServer.java, TimeClient.java

- Single-threaded server and client (in package tcp.singlethreaded): TimeServer.java, TimeClient.java
- ► The remaining examples are in the tcp.multithreaded. Use the same basic client as above.

- Single-threaded server and client (in package tcp.singlethreaded): TimeServer.java, TimeClient.java
- ► The remaining examples are in the tcp.multithreaded. Use the same basic client as above.
- ► Multi-threaded server: TimeServer.java

- Single-threaded server and client (in package tcp.singlethreaded):
 TimeServer.java, TimeClient.java
- ► The remaining examples are in the tcp.multithreaded. Use the same basic client as above.
- ► Multi-threaded server: TimeServer.java
- ► The SecurityManager can impose arbitrary restrictions on applications as to what hosts they may or may not talk to, and whether they can listen for connections.

- Single-threaded server and client (in package tcp.singlethreaded):
 TimeServer.java, TimeClient.java
- ► The remaining examples are in the tcp.multithreaded. Use the same basic client as above.
- ► Multi-threaded server: TimeServer.java
- The SecurityManager can impose arbitrary restrictions on applications as to what hosts they may or may not talk to, and whether they can listen for connections.
- ► Improved Multi-threaded server (adds limit on number of threads, simpler class design): TimeServerImproved.java

- Single-threaded server and client (in package tcp.singlethreaded):
 TimeServer.java, TimeClient.java
- ► The remaining examples are in the tcp.multithreaded. Use the same basic client as above.
- ► Multi-threaded server: TimeServer.java
- ► The SecurityManager can impose arbitrary restrictions on applications as to what hosts they may or may not talk to, and whether they can listen for connections.
- ► Improved Multi-threaded server (adds limit on number of threads, simpler class design): TimeServerImproved.java
- Server implemented using an Executor: TimeServerExecutor.java

▶ Use netstat -ni to find information on the network interfaces.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- ► Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- ► Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.
- ▶ Use lsof -w -n -i tcp:<port num> gives the pid of the process using that port so you can kill a process that didn't clean up or properly release the port. Use lsof -w -n -i tcp to list all active processes listening on a TCP port.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- ► Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.
- ► Use lsof -w -n -i tcp:<port num> gives the pid of the process using that port so you can kill a process that didn't clean up or properly release the port. Use lsof -w -n -i tcp to list all active processes listening on a TCP port.
- ► Use /sbin/ifconfig eth0 to get details on the interface eth0. Running ifconfig without any options gives details on all interfaces.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- ► Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.
- ► Use lsof -w -n -i tcp:<port num> gives the pid of the process using that port so you can kill a process that didn't clean up or properly release the port. Use lsof -w -n -i tcp to list all active processes listening on a TCP port.
- ► Use /sbin/ifconfig eth0 to get details on the interface eth0.

 Running ifconfig without any options gives details on all interfaces.
- Use ping to check if a machine is alive.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- ► Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.
- ► Use lsof -w -n -i tcp:<port num> gives the pid of the process using that port so you can kill a process that didn't clean up or properly release the port. Use lsof -w -n -i tcp to list all active processes listening on a TCP port.
- ► Use /sbin/ifconfig eth0 to get details on the interface eth0.

 Running ifconfig without any options gives details on all interfaces.
- Use ping to check if a machine is alive.
- ▶ Use ip neighbour to to find all machines on a local area network.

- ▶ Use netstat -ni to find information on the network interfaces.
- ► Use netstat -rn to see the routing table.
- ► Use netstat -nap to see the processes that are using specific interfaces and ports. You need to be superuser to be able to see complete process information. Nice way of determining who has a port bound up!
- Use netstat -s to see a summary of network statistics. For example, netstat -s -udp summarizes all UDP traffic.
- ► Use lsof -w -n -i tcp:<port num> gives the pid of the process using that port so you can kill a process that didn't clean up or properly release the port. Use lsof -w -n -i tcp to list all active processes listening on a TCP port.
- ► Use /sbin/ifconfig eth0 to get details on the interface eth0.

 Running ifconfig without any options gives details on all interfaces.
- Use ping to check if a machine is alive.
- ▶ Use ip neighbour to to find all machines on a local area network.
- Use wireshark to watch network packets in real time! You will need superuser access to be able to use wireshark fully.

▶ The client will send a serialized object to the server. This object represents a request. The server will send an serialized object back as an reply that represents the response.

- ▶ The client will send a serialized object to the server. This object represents a request. The server will send an serialized object back as an reply that represents the response.
- ▶ We will use a base class Request for the various kinds of requests.

```
public class Request implements java.io.Serializable {}
public class DateRequest extends Request {}
public class WorkRequest extends Request {
    public Object execute() {return null;}
}
```

- ▶ The client will send a serialized object to the server. This object represents a request. The server will send an serialized object back as an reply that represents the response.
- ▶ We will use a base class Request for the various kinds of requests.

```
public class Request implements java.io.Serializable {}
public class DateRequest extends Request {}
public class WorkRequest extends Request {
   public Object execute() {return null;}
}
```

► The client sends a WorkRequest object to the server to get the server to perform work for the client. The server calls the request object's execute method and returns the resulting object as a response.

- ▶ The client will send a serialized object to the server. This object represents a request. The server will send an serialized object back as an reply that represents the response.
- ▶ We will use a base class Request for the various kinds of requests.

```
public class Request implements java.io.Serializable {}
public class DateRequest extends Request {}
public class WorkRequest extends Request {
   public Object execute() {return null;}
}
```

- ► The client sends a WorkRequest object to the server to get the server to perform work for the client. The server calls the request object's execute method and returns the resulting object as a response.
- ► A sample work request class: MyCalculation.java

- ▶ The client will send a serialized object to the server. This object represents a request. The server will send an serialized object back as an reply that represents the response.
- ▶ We will use a base class Request for the various kinds of requests.

```
public class Request implements java.io.Serializable {}
public class DateRequest extends Request {}
public class WorkRequest extends Request {
   public Object execute() {return null;}
}
```

- ▶ The client sends a WorkRequest object to the server to get the server to perform work for the client. The server calls the request object's execute method and returns the resulting object as a response.
- ► A sample work request class: MyCalculation.java
- ► The Server.java, Client.java classes that tie it all together.

➤ Start the server on one host: on plainoldearth.net: java Server 1234

- ▶ Start the server on one host: on plainoldearth.net: java Server 1234
- ► Start the client anywhere on the Internet. E.g. on restaurant.endofuniverse.net:

```
java Client plainoldearth.net 1234
```

- Start the server on one host: on plainoldearth.net: java Server 1234
- ► Start the client anywhere on the Internet. E.g. on restaurant.endofuniverse.net:
 java Client plainoldearth.net 1234
- Note that the server machine must have all the classes that the client has in order to be able to execute them on the client's behalf. That may be an unreasonable assumption since you may want to serve many kinds of clients without having to store all their classes.

- Start the server on one host: on plainoldearth.net: java Server 1234
- ► Start the client anywhere on the Internet. E.g. on restaurant.endofuniverse.net:
 java Client plainoldearth.net 1234
- Note that the server machine must have all the classes that the client has in order to be able to execute them on the client's behalf. That may be an unreasonable assumption since you may want to serve many kinds of clients without having to store all their classes.
- ▶ It is possible to overcome this restriction with the help of reflection? (More on this later...)

Socket and ServerSocket Options

- ServerSocket and Socket classes have several useful options.
- ► For example: we can set a timeout on a socket, we can set the receive buffer sizes, etc.
- See examples ServerSocketOptions.java and ClientSocketOptions.java in the package tcp.socketoptions.

A servent is both a server and a client.

► A servent is both a server and a client. This is a *portmanteau* derived from the terms server and client; it is a play on the word "servant."

- ▶ A servent is both a server and a client. This is a portmanteau derived from the terms server and client; it is a play on the word "servant."
- ► For example: breakfast + lunch = brunch, motor + hotel = motel, spoon + fork = spork, smoke + fog = smog.

- ➤ A servent is both a server and a client. This is a portmanteau derived from the terms server and client; it is a play on the word "servant."
- ► For example: breakfast + lunch = brunch, motor + hotel = motel, spoon + fork = spork, smoke + fog = smog.
- Sketch the setup for two servers that act as both server and client with each other.

- ➤ A servent is both a server and a client. This is a portmanteau derived from the terms server and client; it is a play on the word "servant."
- ► For example: breakfast + lunch = brunch, motor + hotel = motel, spoon + fork = spork, smoke + fog = smog.
- Sketch the setup for two servers that act as both server and client with each other.
- ► A servent style time server example! TimeServent.java

► A datagram is a discrete amount of data transmitted in one chunk or packet.

- A datagram is a discrete amount of data transmitted in one chunk or packet.
- Datagrams are not guaranteed to be delivered, nor are they guaranteed to arrive in the right order. Even duplicate datagrams might arrive.

- A datagram is a discrete amount of data transmitted in one chunk or packet.
- Datagrams are not guaranteed to be delivered, nor are they guaranteed to arrive in the right order. Even duplicate datagrams might arrive.
- Datagrams use the UDP protocol, which is more lightweight than the TCP protocol.

- A datagram is a discrete amount of data transmitted in one chunk or packet.
- Datagrams are not guaranteed to be delivered, nor are they guaranteed to arrive in the right order. Even duplicate datagrams might arrive.
- Datagrams use the UDP protocol, which is more lightweight than the TCP protocol.
- Domain Name Service (DNS) and Network File System (NFS) use UDP.

- A datagram is a discrete amount of data transmitted in one chunk or packet.
- Datagrams are not guaranteed to be delivered, nor are they guaranteed to arrive in the right order. Even duplicate datagrams might arrive.
- Datagrams use the UDP protocol, which is more lightweight than the TCP protocol.
- Domain Name Service (DNS) and Network File System (NFS) use UDP.
- Example: UdpServer1.java and UdpClient1.java in package tcp.udp.
- ► This example also illustrates shutdown hooks, which is a method that is called asynchronously when a server receives a terminate signal (such as with Ctrl-c).

► How to implement a chat program?

- ► How to implement a chat program?
- ► How to implement a chat program with photos, video and sound?

- ► How to implement a chat program?
- ▶ How to implement a chat program with photos, video and sound?
- How to implement a web server?

- How to implement a chat program?
- How to implement a chat program with photos, video and sound?
- ► How to implement a web server?
- ➤ A server could run a proxy that lets the application communicate indirectly with anyone the server likes and allows. How would you design a proxy server?

The HTTP Protocol and Web Servers

➤ A Web Server implements at least the HTTP protocol. In order to talk to a Web server, a client program (e.g. a web browser) must speak the HTTP protocol.

The HTTP Protocol and Web Servers

- ➤ A Web Server implements at least the HTTP protocol. In order to talk to a Web server, a client program (e.g. a web browser) must speak the HTTP protocol.
- ▶ Details of the HTTP protocol can be found at the home page for the World Wide Web consortium (www.w3.org). The formal definition can be found in the corresponding RFC 2616

The HTTP Protocol and Web Servers

- ➤ A Web Server implements at least the HTTP protocol. In order to talk to a Web server, a client program (e.g. a web browser) must speak the HTTP protocol.
- ▶ Details of the HTTP protocol can be found at the home page for the World Wide Web consortium (www.w3.org). The formal definition can be found in the corresponding RFC 2616
 - RFC Request for Comments is a memorandum developed typically by the Internet Engineering Task Force (IETF) that describes methods, behaviors, or innovations related to the Internet.

The HTTP Protocol and Web Servers

- ➤ A Web Server implements at least the HTTP protocol. In order to talk to a Web server, a client program (e.g. a web browser) must speak the HTTP protocol.
- ▶ Details of the HTTP protocol can be found at the home page for the World Wide Web consortium (www.w3.org). The formal definition can be found in the corresponding RFC 2616
 - RFC Request for Comments is a memorandum developed typically by the Internet Engineering Task Force (IETF) that describes methods, behaviors, or innovations related to the Internet.
- Requests/Methods in the HTTP Protocol:

```
GET GET GET /sample.html HTTP/1.0)
HEAD pathname> (same as GET except only metadata is returned)
POST <string>
```

(the server accepts the entity enclosed in the request) (useful for running server side scripts)

The HTTP Protocol and Web Servers

- ➤ A Web Server implements at least the HTTP protocol. In order to talk to a Web server, a client program (e.g. a web browser) must speak the HTTP protocol.
- ▶ Details of the HTTP protocol can be found at the home page for the World Wide Web consortium (www.w3.org). The formal definition can be found in the corresponding RFC 2616
 - RFC Request for Comments is a memorandum developed typically by the Internet Engineering Task Force (IETF) that describes methods, behaviors, or innovations related to the Internet.
- Requests/Methods in the HTTP Protocol:

```
GET <pathname> HTTP/x.y (e.g. GET /sample.html HTTP/1.0)
HEAD <pathname> (same as GET except only metadata is returned)
POST <string>
```

(the server accepts the entity enclosed in the request) (useful for running server side scripts)

► Response from server:

HTTP-Version status-code reason-phrase <CR><LF>

Selected status codes in the HTTP Protocol

Status codes:

201 Created

301 Moved permanently 305 Use Proxy

307 Temporary redirect

400 Bad request (bad syntax)

401 Unauthorized

402 Payment required

403 Forbidden

404 Not found

500 Internal server error

501 Not implemented

503 Service unavailable

505 HTTP version not supported

Example: TinyHttpd.java, Client.java

- Example: TinyHttpd.java, Client.java
- ➤ To run the server, go to the folder sockets folder and run the following command:

```
java tinyhttpd. TinyHttpd 5005
```

- Example: TinyHttpd.java, Client.java
- ► To run the server, go to the folder sockets folder and run the following command:
 - java tinyhttpd.TinyHttpd 5005
- ► Then use a web browser and point to localhost:5005 or use the provided client program.
 - java tinyhttpd.Client localhost 5005

- Example: TinyHttpd.java, Client.java
- ➤ To run the server, go to the folder sockets folder and run the following command:
 - java tinyhttpd. TinyHttpd 5005
- ► Then use a web browser and point to localhost:5005 or use the provided client program.
 - java tinyhttpd.Client localhost 5005
- Warning! This web server will serve files without any protection from a system!

Java has a built-in security manager, which if activated gives a pretty basic level of access (that is, not much). The security manager can be activated with a command line option.

```
java -Djava.security.manager TinyHttpd
```

Java has a built-in security manager, which if activated gives a pretty basic level of access (that is, not much). The security manager can be activated with a command line option.

```
java -Djava.security.manager TinyHttpd
```

However, we want to give access to create and use sockets. So we create a policy file (using the tool policytool that comes with the Java toolkit).

Java has a built-in security manager, which if activated gives a pretty basic level of access (that is, not much). The security manager can be activated with a command line option.

```
java -Djava.security.manager TinyHttpd
```

However, we want to give access to create and use sockets. So we create a policy file (using the tool policytool that comes with the Java toolkit).

► Add the following after the catch for FileNotFoundException.

catch (SecurityException e) {pout.println("403 Forbidden");}

Java has a built-in security manager, which if activated gives a pretty basic level of access (that is, not much). The security manager can be activated with a command line option.

```
java -Djava.security.manager TinyHttpd
```

However, we want to give access to create and use sockets. So we create a policy file (using the tool policytool that comes with the Java toolkit).

- ► Add the following after the catch for FileNotFoundException.

 catch (SecurityException e) {pout.println("403 Forbidden");}
- Recompile and run the server as follows.

```
java -Djava.security.manager
-Djava.security.policy=mysecurity.policy TinyHttpd 5005
```

Adding a Custom Security Manager to TinyHttpd

```
class TinyHttpdSecurityManager extends SecurityManager {
 public void checkAccess(Thread g) {};
 public void checkListen(int port) {};
 public void checkLink(String lib) {};
 public void checkPropertyAccess(String key) {};
 public void checkAccept(String host, int port) {};
 public void checkWrite(FileDescriptor fd) {};
 public void checkRead(FileDescriptor fd ) {};
 public void checkRead(String s) {
    if (new File(s).isAbsolute() || (s.indexOf("..") != -1))
     throw new SecurityException("Access to file: " + s
                                           + " denied."):
//add the following to the TinyHttpd at the start of the
//main method but after creating the ServerSocket
System.setSecurityManager(new TinyHttpdSecurityManager());
```

Use a buffer and send large amount of data in several passes.

- Use a buffer and send large amount of data in several passes.
- Generate linked listings for directories (if no index.html was found).

- Use a buffer and send large amount of data in several passes.
- Generate linked listings for directories (if no index.html was found).
- ► Log all requests in a log file. A sample entry is shown below (taken from the access log of Apache web server):

```
66.249.69.87 - [28/Jan/2016:23:16:04 -0700]

"GET /~amit/teaching/555/cs455-555.html HTTP/1.1" 200 7343 "-"

"Mozilla/5.0 (compatible; Googlebot/2.1;

+http://www.google.com/bot.html)"
```

- Use a buffer and send large amount of data in several passes.
- Generate linked listings for directories (if no index.html was found).
- ► Log all requests in a log file. A sample entry is shown below (taken from the access log of Apache web server):

 66.249.69.87 [28/Jan/2016:23:16:04 -0700]

```
66.249.69.87 - [28/Jan/2016:23:16:04 -0700]

"GET /~amit/teaching/555/cs455-555.html HTTP/1.1" 200 7343 "-"

"Mozilla/5.0 (compatible; Googlebot/2.1;

+http://www.google.com/bot.html)"
```

► Add other kinds of requests (other than GET)

- Use a buffer and send large amount of data in several passes.
- Generate linked listings for directories (if no index.html was found).
- Log all requests in a log file. A sample entry is shown below (taken from the access log of Apache web server):

```
66.249.69.87 - [28/Jan/2016:23:16:04 -0700]

"GET /~amit/teaching/555/cs455-555.html HTTP/1.1" 200 7343 "-"

"Mozilla/5.0 (compatible; Googlebot/2.1;

+http://www.google.com/bot.html)"
```

- Add other kinds of requests (other than GET)
- Use the Executor interface to manage the threads

- Use a buffer and send large amount of data in several passes.
- Generate linked listings for directories (if no index.html was found).
- ► Log all requests in a log file. A sample entry is shown below (taken from the access log of Apache web server):

```
66.249.69.87 - [28/Jan/2016:23:16:04 -0700]

"GET /~amit/teaching/555/cs455-555.html HTTP/1.1" 200 7343 "-"

"Mozilla/5.0 (compatible; Googlebot/2.1;

+http://www.google.com/bot.html)"
```

- Add other kinds of requests (other than GET)
- Use the Executor interface to manage the threads
- Use scalable I/O with java.nio package.

Scalable I/O with java.nio package

Nonblocking and selectable network communications are used to create services that can handle high volumes of simultaneous client requests.

Scalable I/O with java.nio package

- Nonblocking and selectable network communications are used to create services that can handle high volumes of simultaneous client requests.
- ▶ Starting one thread per client request can consume a lot of resources. One strategy is to use nonblocking I/O operations to manage a lot of communications from a single thread. The second strategy is to use a configurable pool of threads, taking advantage of machines with many processors.

Scalable I/O with java.nio package

- Nonblocking and selectable network communications are used to create services that can handle high volumes of simultaneous client requests.
- Starting one thread per client request can consume a lot of resources. One strategy is to use nonblocking I/O operations to manage a lot of communications from a single thread. The second strategy is to use a configurable pool of threads, taking advantage of machines with many processors.
- ► The java.nio package provides selectable channels. A selectable channel allows for the registration of a special kind of listener called a selector that can check the readiness of the channel for operations such as reading and writing or accepting or creating network connections.

Create a selector object.

```
Selector selector = Selector.open();
```

Create a selector object.

```
Selector selector = Selector.open();
```

▶ To register one or more channels with the selector, set them to nonblocking mode.

```
SelectableChannel channelA = ...;
channelA.configureBlocking(false);
```

Create a selector object.

```
Selector selector = Selector.open();
```

▶ To register one or more channels with the selector, set them to nonblocking mode.

```
SelectableChannel channelA = ...;
channelA.configureBlocking(false);
```

► Then, we register the channels.

```
int interestOps = SelectionKey.OP_READ | SelectionKey.OP_WRITE;
SelectionKey key = channelA.register(selector, interestOps);
```

Create a selector object.

```
Selector selector = Selector.open();
```

▶ To register one or more channels with the selector, set them to nonblocking mode.

```
SelectableChannel channelA = ...;
channelA.configureBlocking(false);
```

► Then, we register the channels.

```
int interestOps = SelectionKey.OP_READ | SelectionKey.OP_WRITE;
SelectionKey key = channelA.register(selector, interestOps);
```

► The possible values of interest ops are: OP_READ, OP_WRITE, OP_CONNECT and OP_ACCEPT. These values can be OR'd together to express interest in one or more operations.

Create a selector object.

```
Selector selector = Selector.open();
```

▶ To register one or more channels with the selector, set them to nonblocking mode.

```
SelectableChannel channelA = ...;
channelA.configureBlocking(false);
```

► Then, we register the channels.

```
int interestOps = SelectionKey.OP_READ | SelectionKey.OP_WRITE;
SelectionKey key = channelA.register(selector, interestOps);
```

- The possible values of interest ops are: OP_READ, OP_WRITE, OP_CONNECT and OP_ACCEPT. These values can be OR'd together to express interest in one or more operations.
- Once one or more channels are registered with the Selector, we can perform a select operations by using one of the select() methods.

```
int readyCount = selector.select(); //block until a channel is ready
int readyCount = selector.selectNow(); //returns immediately
int readyCount = selector.select(50); //timeout of 50 millisecs
while (selector.select(50) == 0);
```

Checking for ready channels

Once select() comes back with a non-zero ready count, then we can get the set of ready channels from the Selector with the selectedKeys() method and iterate through them.

Checking for ready channels

Once select() comes back with a non-zero ready count, then we can get the set of ready channels from the Selector with the selectedKeys() method and iterate through them.

```
Set readySet = selector.selectedKeys();
for (Iterator itr = readySet.iterator(); itr.hasNext();) {
    SelectionKey key = (SelectionKey) itr.next();
    itr.remove(); //remove the key from the ready set
    //use the key in the application
}
```

► The LargerHttpd is a nonblocking web server that uses SocketChannels and a pool of threads to service requests.

- ➤ The LargerHttpd is a nonblocking web server that uses SocketChannels and a pool of threads to service requests.
- Example: LargerHttpd.java, HttpdConnection.java, ClientQueue.java.

- ➤ The LargerHttpd is a nonblocking web server that uses SocketChannels and a pool of threads to service requests.
- Example: LargerHttpd.java, HttpdConnection.java, ClientQueue.java.
- A single thread executes the main loop that accepts new connections and checks the readiness of existing client connections for reading or writing.

- ► The LargerHttpd is a nonblocking web server that uses SocketChannels and a pool of threads to service requests.
- Example: LargerHttpd.java, HttpdConnection.java, ClientQueue.java.
- A single thread executes the main loop that accepts new connections and checks the readiness of existing client connections for reading or writing.
- Whenever a client needs attention, it places the job in a queue where threads from our thread pool wait to service it.
- Run it as follows (on one line!):

```
java -Djava.security.manager
-Djava.security.policy=mysecurity.policy
LargerHttpd <port> <maxthreads>
```

▶ Modify the object server example to be single threaded.

- Modify the object server example to be single threaded.
- Modify the object server example to use the Executor interface.

- Modify the object server example to be single threaded.
- Modify the object server example to use the Executor interface.
- Create a EC2 virtual machine using AWS (Amazon Web Services) and run the object server on it. Connect with your laptop or a lab machine as a client.

- Modify the object server example to be single threaded.
- Modify the object server example to use the Executor interface.
- Create a EC2 virtual machine using AWS (Amazon Web Services) and run the object server on it. Connect with your laptop or a lab machine as a client.
- Convert the object server example to send JSON objects instead of Java objects.

- Modify the object server example to be single threaded.
- Modify the object server example to use the Executor interface.
- Create a EC2 virtual machine using AWS (Amazon Web Services) and run the object server on it. Connect with your laptop or a lab machine as a client.
- Convert the object server example to send JSON objects instead of Java objects.
- ▶ Write a Ping Pong program (two processes) using sockets and an object to represent the ping-pong ball. (Homework 1)

- Modify the object server example to be single threaded.
- Modify the object server example to use the Executor interface.
- Create a EC2 virtual machine using AWS (Amazon Web Services) and run the object server on it. Connect with your laptop or a lab machine as a client.
- Convert the object server example to send JSON objects instead of Java objects.
- Write a Ping Pong program (two processes) using sockets and an object to represent the ping-pong ball. (Homework 1)
- Write a singlethreaded port scanner. The program is a client program that attempts to connect with all ports in the range 1-65535 and reports on the ones that are found open. Then write a multithreaded version and test to see how much faster it is than the singlethreaded version.