

Spark on Clusters

Spark Cluster Options

- ▶ **Standalone** – a simple cluster manager included with Spark that makes it easy to set up a cluster.
- ▶ **Apache Mesos** – a general cluster manager that can also run Hadoop MapReduce and service applications.
- ▶ **Hadoop YARN** – the resource manager in Hadoop 2.
- ▶ **Kubernetes** – an open-source system for automating deployment, scaling, and management of containerized applications.

Standalone Cluster (1)

- ▶ Spark needs to be installed on the master and all of the nodes. For the lab, install Spark on [bugs](#) and also on [onyx](#). Since all onyx nodes share the home file system, there is no need to install Spark on the nodes.
- ▶ Start the master (typically, we would use [bugs.boisestate.edu](#))

```
[amit@bugs ~]$ start-master.sh
starting org.apache.spark.deploy.master.Master, logging to /
  home/amit/spark-install/spark/logs/spark-amit-org.apache
  .spark.deploy.master.Master-1-bugs.boisestate.edu.out
```

- ▶ Once started, the master will print out a [spark://HOST:PORT](#) URL for itself, which you can use to connect workers to it, or pass as the “master” argument to [SparkContext](#) or to [spark-submit](#).

```
[amit@bugs ~]$ cat /home/amit/spark-install/spark/logs/spark
-amit-org.apache.spark.deploy.master.Master-1-bugs.
boisestate.edu.out | grep spark:
19/11/13 23:48:56 INFO Master: Starting Spark master at
spark://bugs.boisestate.edu:7077
```

- ▶ The master's web UI is at <http://localhost:8080>, where we can also find the master's URL.

Standalone Cluster (2)

- ▶ Start one or more workers on multiple nodes by passing in the Spark URL of the master. We need password-less ssh access.

```
[amit@bugs ~]$ ssh onyxnode01
```

```
Last login: Tue Nov 12 14:27:47 2019 from bugs.boisestate.edu
```

```
[amit@onyxnode01 ~]$ start-slave.sh spark://bugs.boisestate.edu:7077
```

```
starting org.apache.spark.deploy.worker.Worker, logging to /
home/amit/spark-install/spark/logs/spark-amit-org.apache
.spark.deploy.worker.Worker-1-onyxnode01.boisestate.edu.
out
```

- ▶ Once you have started a worker, look at the master's web UI. You should see the new node listed there, along with its number of CPUs and memory (minus one gigabyte left for the OS).
- ▶ We can now run Spark jobs on the cluster. For example:

```
[amit@bugs wordcount(master)]$ spark-submit --class "
WordCount" --master spark://bugs.boisestate.edu:7077
wordcount-basic.jar input 2> log 1> output
```

- ▶ Finally, we can stop the master and worker daemons.

```
[amit@bugs ~]$ ssh onyxnode01 stop-slave.sh
stopping org.apache.spark.deploy.worker.Worker
[amit@bugs ~]$ stop-master.sh
stopping org.apache.spark.deploy.master.Master
```

Standalone Cluster (3)

- We can automate the start/stop of a standalone cluster. Add the names of the worker nodes to the file `~/spark-install/spark/conf/slaves`. Then use the `start-all.sh` and `stop-all.sh` scripts.

```
[amit@bugs ~]$ start-all.sh
starting org.apache.spark.deploy.master.Master, logging to /
  home/amit/spark-install/spark/logs/spark-amit-org.apache
    .spark.deploy.master.Master-1-bugs.boisestate.edu.out
onynode03.boisestate.edu: starting org.apache.spark.deploy.
  worker.Worker, logging to /home/amit/spark-install/spark
    /logs/spark-amit-org.apache.spark.deploy.worker.Worker
      -1-onynode03.boisestate.edu.out
onynode01.boisestate.edu: starting org.apache.spark.deploy.
  worker.Worker, logging to /home/amit/spark-install/spark
    /logs/spark-amit-org.apache.spark.deploy.worker.Worker
      -1-onynode01.boisestate.edu.out
```

```
[amit@bugs ~]$ stop-all.sh
onynode03.boisestate.edu: stopping org.apache.spark.deploy.
  worker.Worker
onynode01.boisestate.edu: stopping org.apache.spark.deploy.
  worker.Worker
stopping org.apache.spark.deploy.master.Master
```

Standalone Cluster with HDFS

- ▶ A spark program running on local host can connect with Hadoop HDFS running in pseudo-distributed mode on the same local host.
- ▶ A spark program running on a standalone cluster needs to connect with Hadoop HDFS running on a cluster, typically the same cluster.
- ▶ Here is a simple setup to get Hadoop working on a cluster of fixed nodes. First we need to configure Hadoop to run in real distributed mode.

```
cd CS535-resources
git pull --rebase
cd examples/Hadoop/local-scripts
setmode.sh distributed
```

- ▶ Edit the `~/hadoop-install/hadoop/etc/hadoop/slaves` file to add the names of the nodes in the standalone cluster. Edit the file `~/hadoop-install/hadoop/etc/hadoop/master` to add `bugs.boisestate.edu` as the master.
- ▶ Then we create the HDFS filesystem and start the HDFS servers and load the input files. We don't need to start YARN (unless we want to submit spark jobs to YARN, which is possible).

```
hdfs namenode -format
start-dfs.sh
hdfs dfsadmin -report
hdfs dfs -mkdir -p /user/amit
hdfs dfs -put input input
```

- ▶ Now run the Spark program that accesses the HDFS. The submit command will stay the same.