



UNICOM
ENERGY STORAGE SYSTEM

Liquid Cooling ES All-in-one Cabinet

ES232/115K-A/EU



Advantages and Features



Three-level topology, conversion efficiency up to 99.0%



CATL long-life LFP battery cells, cycle life > 8000 times



Support off-grid operation, providing backup power for critical loads



Liquid-cooling temperature control design, battery-pack temperature difference < 3°C, auxiliary power consumption reduced by 30%, extending system lifespan by 2+ years*



Modular expansion, supports up to 20 units in parallel



Modular expansion, supports up to 20 units in parallel

Specifications

Product Model	ES232/115K-A/EU
DC Side	
Cell Type	LFP/280Ah
Rated Energy	232.96kWh
Rated Battery Voltage	832Vdc
Operating Voltage Range	655Vdc~949Vdc
Max. DC Current	140A
Battery Configuration	1P260S
Number of Battery Packs	5
Charge/Discharge C-Rate	≤0.5P
On-grid Side	
Rated Output Power	115kW
Rated Output Voltage	400Vac
Rated Output Current	193A
Rated Output Voltage Range	-20%~15%
Rated Grid Frequency	50Hz/60Hz (±5Hz)
Output Power Factor	-1~+1
Grid Connection Method	3L+N+PE
Adaptation to Grid Types	TT/TN
Topology	Transformerless
Efficiency	
Max. Efficiency	90%
General Data	
Surge Protection	DC Type II / AC Type II
Pollution Level	Class II
Corrosion Protection Rating	C3, C5 (Optional)
Fire Control	Perfluorohexanone
Ingress Protection	IP55
Installation Method	Outdoor installation
Battery Cooling Concept	Liquid cooling
Running Temperature	-30°C~+60°C (Derating above 50°C)
Operating Surroundings Humidity	0~95% (No condensation)
Permissible Altitude	4000m (Derating above 2000m)
Cabinet Size (WxHxD mm)	1120*2379*1400mm
Weight	≤2700kg
Display	LED+Web+APP
Interface	CAN, RS485, Ethernet, 4G
Safety EMC / Standard	EN 62477-1, EN 61000-6-2, EN 61000-6-4, EN 50581, IEC 62474, IEC 62321