



Discussion Forums

Week 4

SUBFORUMS

All

Assignment: Multi-class Classification
and Neural Networks

← Week 4



ex3 tutorial for predict()

Tom Mosher · Mentor · a year ago · Edited

Here is an outline for forward propagation using the vectorized method. This is an implementation of the formula in Figure 2 on Page 11 of ex3.pdf.

1. Add a column of 1's to X (the first column), and it becomes 'a1'.
2. Multiply by Theta1 and you have 'z2'.
3. Compute the sigmoid() of 'z2', then add a column of 1's, and it becomes 'a2'.
4. Multiply by Theta2, compute the sigmoid() and it becomes 'a3'.
5. Now use the `max(a3, [], 2)` function to return two vectors - one of the highest value for each row, and one with its index. Ignore the highest values. Keep the vector of the indexes where the highest values were found. These are your predictions.

Note: When you multiply by the Theta matrices, you'll have to use transposition to get a result that is the correct size.

Note: The predictions must be returned as a column vector - size (m x 1). If you return a row vector, the script will not compute the accuracy correctly.

Note: Not getting the correct results? In the hidden layer, be sure you use sigmoid() first, then add the bias unit.

----- dimensions of the variables -----

a1 is (m x n), where 'n' is the number of features including the bias unit

Theta1 is (h x n) where 'h' is the number of hidden units

a2 is (m x (h + 1))

Theta2 is (c x (h + 1)), where 'c' is the number of labels.

a3 is (m x c)

p is a vector of size (m x 1)

👍 36 Upvote · Follow 18 · Reply to Tom Mosher

🔒 This thread is closed. You cannot add any more responses.

Earliest Top Most Recent



Krishnang Dalal · 8 months ago



I get test case oneVSall correct. I get 94.62% prediction accuracy for predictoneVSall. But when I am submitting the entire assignment it does not calculate scores for the regularized Logistic Regression and One-vs-All Classifier Training. It even doesn't give wrong feedback. What could be the issue?

👍 0 Upvote · Hide 1 Reply



Tom Mosher · Mentor · 8 months ago



The issue is that your code does not work correctly for the test case that the submit grader uses. Your code must work correctly for any data set.

I recommend you read the Tutorials and use the additional test cases in the Resources menu.

👍 0 Upvote

H

Harpreet · 8 months ago



How do I calculate Theta1 and Theta2, if it was not provided to us.

👍 1 Upvote · Hide 3 Replies



Tom Mosher · Mentor · 8 months ago



That is what we learn in Week 5.

👍 1 Upvote

L

L.L. · 8 months ago · Edited by moderator



Thanks for your reply, but I have a little question, you said that $a1$ is $m \times n$, and Theta1 is $(h \times n)$, so I think they can not be multiplied, because maybe $n \neq h$ or $m \neq n$, so it should be **{mentor edit: code removed}**

👍 1 Upvote



Tom Mosher · Mentor · 8 months ago



Perhaps you overlooked this line in the tutorial:

Note: When you multiply by the Theta matrices, you'll have to use transposition to get a result that is the correct size.

The tutorial leaves a few things for the student to figure out. Otherwise, it would be merely a cookbook.

👍 3 Upvote

A

Alexandr · 10 months ago



Hi Tom,

Thanks for helpful tutorials. I finished assignment but did not understand why we use indices instead of max values of $a3$.

Thanks,

👍 0 Upvote · Hide 6 Replies



Tom Mosher · Mentor · 10 months ago



We don't really care what the maximum value is.

We want to find which classifier gives us the maximum value.

👍 2 Upvote

Julius Jacobson · 8 months ago



JJ

Julius Jacobson · 9 months ago

My result for this test is off by one value. My vector returns the correct values save for the last number of my vector p. I get a '1' instead of a '2'. Any ideas as to what could be causing this miscalculation?

 0 Upvote

Julius Jacobson · 9 months ago

JJ

Here is the offending row of a3:

0.633861 0.582628 0.522118 0.458987

 0 Upvote

Tom Mosher Mentor · 9 months ago

Here are my results for that test case:

```
1 >> p = predict(Theta1, Theta2, X)
2 stopped in C:\Users\Tom\mL-od\machine-learning-ex3\ex3\predict.m
   at line 29
3 29: [v p] = max(a3, [], 2);
4 m = 8
5 debug> a3
6 a3 =
7
8     0.53036    0.54588    0.55725    0.56352
9     0.54459    0.54298    0.53754    0.52875
10    0.49979    0.49616    0.49288    0.49024
11    0.41357    0.42199    0.43736    0.45844
12    0.37321    0.40368    0.44349    0.48911
13    0.42073    0.45935    0.50210    0.54464
14    0.50962    0.53216    0.55173    0.56659
15    0.54882    0.55033    0.54738    0.54021
```

 2 Upvote

JJ

Julius Jacobson · 9 months ago

Thanks again for the reply! I figured out what was wrong with my code. I am sure there is a place in Machine Learning heaven reserved for you!

 0 Upvote

Tom Mosher Mentor · 9 months ago

Good news!

 0 Upvote

XL

Xinghou Liu · 10 months ago

Hi Tom,


I am working on the predict.m, following you steps, I got the correct output:

'Training Set Accuracy: 97.520000'

I couldn't find any errors from the codes and I am pretty sure they are logically correct with your tips.

But after I submit the codes, they don't passed the assignment.

Any ideas on how can this happen?

 0 Upvote · Hide 1 Reply

Tom Mosher Mentor · 10 months ago

There is an error in your code. It does not work correctly with the test case that the submit grader uses.

Try the additional test case, in this thread:

https://www.coursera.org/learn/machine-learning/discussions/iyd75Nz_EeWBhgpcuSiffw

👍 0 Upvote

LL

lennie leong · a year ago

Hi Tom / mentors,

I am working on predict.m currently.

Using Tom's tutorial as a guide for the assignment, In Tom's tutorial guide, it mentions " Add a column of 1's to X (the first column), and it becomes 'a1'."

Currently, I have X that's a 16x2 matrix. By adding a column of 1's to X, does this mean that it still remains as 16x2 matrix with the first column filled with 1's.

Or, is it a matrix with 16x3 with the first column filled with 1's?

Thank you mentors for help in advanced!

👍 0 Upvote · Hide 1 Reply



Tom Mosher Mentor · a year ago

Add a column of 1's. Don't overwrite an existing feature with 1's.

👍 0 Upvote

IC

Irena Chanis · a year ago

Hi Tom,

i don't understand exactly how the size of the hidden layer (h) is determined (25 in the example). it seems it's arbitrary & not connected to input or output data. Couldn't understand it through the course videos also...

Another question: is it OK that i get the all history cost details of each iteration (attached Pic) for both NN and Multi class classification sections? (was able to submit all the tasks).

thanks,

```
Iteration    5 | Cost: 3.611087e-01
Iteration    6 | Cost: 3.598573e-01
Iteration    7 | Cost: 3.598359e-01
Iteration    8 | Cost: 3.598130e-01
Iteration    9 | Cost: 3.598122e-01
Iteration   10 | Cost: 3.598119e-01
Iteration   11 | Cost: 3.598119e-01
Iteration   12 | Cost: 3.598119e-01
```

Irena.

👍 0 Upvote · Hide 1 Reply



Tom Mosher Mentor · a year ago

The course doesn't discuss how to set the number of hidden layer units. It is more art than science. There are lots of rules-of-thumb and no general agreement, other than it is typically a value between the number of input features and the number of output classifications. Experimentation is a good idea.

The iteration and cost values from `fmincg()` are supposed to all be printed on one line. It doesn't matter if they are on separate lines, but perhaps it is being caused by a missing semicolon somewhere in your cost function.

Just guessing, but it might also be due to how your command console is configured. You didn't mention whether you were using MATLAB or Octave, or what version, or if you're using the GUI or the CLI interface. You may be able to adjust some configuration setting.

4 Upvote



Sunil Skanda · a year ago

```

Iteration 1 | Cost: 4.202132e-01
Iteration 2 | Cost: 3.970300e-01
Iteration 3 | Cost: 3.673914e-01
Iteration 4 | Cost: 3.662284e-01
Iteration 5 | Cost: 3.611007e-01
Iteration 6 | Cost: 3.598573e-01
Iteration 7 | Cost: 3.598559e-01
Iteration 8 | Cost: 3.598130e-01
Iteration 9 | Cost: 3.598122e-01
Iteration 10 | Cost: 3.598119e-01
Iteration 11 | Cost: 3.598119e-01
Iteration 12 | Cost: 3.598119e-01
Iteration 13 | Cost: 3.598119e-01
Iteration 14 | Cost: 3.598119e-01
Iteration 15 | Cost: 3.598119e-01
Iteration 16 | Cost: 3.598119e-01

!! Submission failed: unexpected error: Error using horzcat
Dimensions of matrices being concatenated are not consistent.
!! Please try again later.

```

This is what I got when I tried to submit my code

0 Upvote · Hide 6 Replies



Tom Mosher Mentor · a year ago

Don't add bias to the Theta matrices - just to the input and hidden layer features.

The `horzcat()` error means you are not adding the columns of 1's correctly - it means "horizontal concatenation".

0 Upvote



Tom Mosher Mentor · a year ago · Edited

I recommend you study the tutorial. It tells you exactly what to do.

All you need to figure out is the order of operands and where to use transposition.

1 Upvote



Tom Mosher Mentor · a year ago

Also try testing your code using the test cases in this thread:

<https://www.coursera.org/learn/machine-learning/discussions/0SxufTSrEeWPACIACw4G5w>

0 Upvote



Sunil Skanda · a year ago

Thanks. So, z_2 equals a_1 multiplied by Θ_1 right ?

0 Upvote



Tom Mosher · Mentor · a year ago



Yes. You will need to use the correct order of the operands and add a transposition.

0 Upvote



Sunil Skanda · a year ago



1.Thanks. All I had was a minor error in using parantheses. Thanks for the help Tom!.

2. The pdf suggested that some interaction session will launch the images. I didn't find any.

3. We wrote a code similar to the predictOnevsAll function. But, I didn't get the prediction result(Training Set Accuracy) as expected.

Again Thanks for the help.

0 Upvote



Sunil Skanda · a year ago



Do we need to add bias unit to theta and theta as well?

0 Upvote · Reply



Sunil Skanda · a year ago



How man hidden units are there ?

0 Upvote · Hide 5 Replies



Tom Mosher · Mentor · a year ago · Edited



Everything you need to know is provided via the Theta matrices.

0 Upvote



Sunil Skanda · a year ago



Ok. I wrote the code for predict.m as instructed and ran it in Matlab. But, It just stops after the prediction results for the previous function.

0 Upvote



Tom Mosher · Mentor · a year ago



Per the tutorial, we're just doing a couple of matrix multiplications and running the sigmoid function. There's nothing there that should cause execution to stop.

If you're using for-loops, all sorts of havoc can occur.

1 Upvote



Sunil Skanda · a year ago



Yea, That's what I thought. I think I must have made a mistake in adding ones to the matrix X and the others. Can you tell me how to do that?

0 Upvote



Tom Mosher · Mentor · a year ago



Add a column of 1's to a matrix:

Add a column of 1's to a matrix.

```

1 Q = magic(3)
2 m = size(Q,1)
3 Q = [ones(m,1) Q]

```

3 Upvote



Bernadberoy Remi · a year ago

I think there is a small error at point 2. Should be:

2. Multiply by Theta1 and it becomes 'z2'. Take the sigmoid and it becomes 'a2'.

3. Add a column of 1's to 'a2'

0 Upvote · Hide 5 Replies



Tom Mosher Mentor · a year ago · Edited

I disagree. It is not a2 until you add the bias units, just as X becomes a1 after you add its bias unit.

2 Upvote



Bernadberoy Remi · a year ago

Ok but $z2 = \text{theta1} * a1$ without sigmoid. We take the sigmoid afterward, don't we?

0 Upvote



Tom Mosher Mentor · a year ago

Add the bias unit after computing the sigmoid. Otherwise, $\text{sigmoid}(1)$ would turn it into 0.73106.

6 Upvote



jeevesh sharma · a year ago

Thnx this comment got me out of my agony, i was adding the bias before calculating sigmoid.

2 Upvote

AG

Atul Kumar Gupta · 8 months ago

Your comment helped me too . Thanks

0 Upvote



Hyatt Baker · a year ago

Well that was very helpful, thanks!

0 Upvote · Reply

CJ

Carsten Just · a year ago

Hi Tom a matlab technical question that i have had trouble with: when i, in the EX3 assignment, perform the predictOneVsAll function, from where do i get the all_theta input? when i run the OneVsAll funtion, the output is not stored anywhere.... Can you help?

Best

Carsten

0 Upvote · Hide 2 Replies



Tom Mosher · Mentor · a year ago



Read the ex3.m script. It calls your oneVsAll() function, saves the return value, and passes it to the prediction function.

👍 1 Upvote



Carsten Just · a year ago



Oki thanks. Tried to just run the function itself... thanks!

👍 0 Upvote