

# Creating a RESTful API using express.js and creating a database and index in MongoDB.

**Name** : MUDRABOINA.VENKATA SIVA KUMAR

**Email Id** : kumarmudraboina333@gmail.com


**Phone no** : 6303454484

**Roll NO** : 21HU5A0410

**College Name:** Chebrolu Engineering College

**Source Code:**

**index.js file :**




The screenshot shows a VS Code editor with a project structure on the left and a code editor in the center. The project structure includes a 'crud' folder with subfolders 'api', 'db', 'model', 'routers', and 'client'. The 'api' folder contains 'index.js', 'emp.controller.js', 'connectToDB.js', 'emp.model.js', 'user.routes.js', and 'index.js'. The 'db' folder contains 'connectToDB.js'. The 'model' folder contains 'emp.model.js'. The 'routers' folder contains 'user.routes.js'. The 'client' folder contains 'client'. The 'node\_modules' folder is also visible. The 'index.js' file is selected in the Explorer. The code in the editor is as follows:

```
1 import path from 'path';
2 import express from 'express';
3 import { config } from 'dotenv';
4 import { connectToDB } from '../db/connectToDB.js';
5 config();
6 import userRoute from '../routers/user.routes.js'
7
8
9 const __dirname = path.resolve();
10 const app = express();
11
12 app.use(express.json());
13
14 app.use("/api/user", userRoute);
15
16 app.use(express.static(path.join(__dirname, "client/dist")));
17
18 app.get("/*", (req, res) => {
19   res.sendFile(path.join(__dirname, "client", "dist", "index.html"))
20 })
21
22 const PORT = process.env.PORT || 5000
23 app.listen(PORT, () => {
24   connectToDB();
25   console.log("Server is running on PORT : ", PORT)
26 })
```

The terminal output shows the command 'nodemon api/index.js' and the following messages:

```
[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

**MONGODB CONNECTION:**




The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', and 'client'. The file 'JS connectToDB.js' is selected in the 'db' folder. The editor displays the code for 'connectToDB.js', which imports 'mongoose' and defines a 'connectToDB' function. The terminal at the bottom shows the command 'nodemon api/index.js' and the output of the application, including a message 'DB connected successfully'.

```
1 import mongoose from 'mongoose';
2
3 export function connectToDB(){
4   mongoose.connect(process.env.CONN_STR)
5     .then(()=>{
6       console.log("DB connected successfully")
7     })
8     .catch((err)=>{
9       console.log("Error while connecting to DB : ",err.message);
10    })
11 }
```

```
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

## MODEL:



The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with folders like 'api', 'controllers', 'db', 'model', 'routers', and 'client'. The file 'JS emp.model.js' is selected in the 'model' folder. The editor displays the code for 'emp.model.js', which imports 'mongoose' and defines a 'userSchema' and a 'User' model. The terminal at the bottom shows the command 'nodemon api/index.js' and the output of the application, including a message 'DB connected successfully'.

```
1 import mongoose from 'mongoose';
2
3 const userSchema = new mongoose.Schema({
4   username:{
5     type:String,
6     unique:true,
7     required:true
8   },
9   empname:{
10    type:String,
11    required:true
12  },
13  email:{
14    type:String,
15    required:true
16  },
17  role:{
18    type:String,
19    required:true
20  },
21  salary:{
22    type: Number,
23    required: true,
24  }
25 },{timestamps:true})
26
27 const Emp = mongoose.model("User",userSchema);
28
29 export default Emp;
```

```
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

## ROUTES:

The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with a 'crud' folder containing 'api', 'controllers', 'db', 'model', 'routers', and 'index.js'. The 'routers' folder is expanded, showing 'user.routes.js' selected. The main editor displays the content of 'user.routes.js'.

```
api > routers > JS user.routes.js > @ router
1 import express from 'express'
2 import { create, readAll, read, remove, update, } from '../controllers/emp.controller.js';
3
4 const router = express.Router();
5
6 router.post('/create', create);
7 router.get("/readall", readAll);
8 router.get("/read/:id", read);
9 router.put('/update/:id', update);
10 router.delete('/remove/:id', remove);
11
12 export default router;
```

The terminal at the bottom shows the command to run the application and its output:

```
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

## CONTROLLERS: CREATE:

The screenshot shows the VS Code editor with the file explorer on the left. The file explorer shows a project structure with a 'crud' folder containing 'api', 'controllers', 'db', 'model', 'routers', and 'index.js'. The 'controllers' folder is expanded, showing 'emp.controller.js' selected. The main editor displays the content of 'emp.controller.js'.

```
api > controllers > JS emp.controller.js > @ remove
1 import Emp from "../model/emp.model.js";
2
3 export async function create(req,res){
4   try {
5     const {username,empname,email,role,salary} = req.body;
6
7     console.log(req.body);
8     const emp = await Emp.findOne({username});
9
10    if(emp) return res.status(400).json({error:"username is already exists"});
11
12    const newEmp = new Emp({
13      username,
14      empname,
15      email,
16      role,
17      salary
18    });
19
20    if(newEmp){
21
22      await newEmp.save();
23
24      res.status(201).json({
25        _id : newEmp._id,
26        username : newEmp.username,
27        empname : newEmp.empname,
28        email : newEmp.email,
29        role : newEmp.role,
30        salary : newEmp.salary
31      });
32    }else{
33      res.status(400).json({error:"Invalid emp data"});
34    }
35  } catch (error) {
36    console.log("Error in create controller : ",error,message);
37    res.status(500).json({message : error.message});
38  }
39 }
40
41 }
```

## READALL:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 > export async function read(req,res){ ...
58 }
59
60 export async function readAll(req,res){
61   try {
62     const emps = await Emp.find();
63
64     if(!emps || !emps.length ) return res.status(404).json({error:" no emp data found!"});
65
66     res.status(201).json({
67       emps
68     })
69   } catch (error) {
70     console.log("Error in create controller : ",error.message);
71     res.status(500).json({error:"Internal server Error"})
72   }
73 }
74
75
76
77 > export async function update(req,res){ ...
94 }
95
96 > export async function remove(req,res){ ...
110 }
```

READONE:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){ ...
40 }
41
42 export async function read(req,res){
43   try {
44     const {id} = req.params;
45
46     const emp = await Emp.findById({_id:id});
47
48     if(!emp) return res.status(404).json({error:"emp not found!"});
49
50     res.status(201).json({
51       emp
52     })
53   } catch (error) {
54     console.log("Error in create controller : ",error.message);
55     res.status(500).json({error:"Internal server Error"})
56   }
57 }
58
59
60 > export async function readAll(req,res){ ...
75 }
76
77 > export async function update(req,res){ ...
94 }
95
96 > export async function remove(req,res){ ...
110 }
```

UPDATE:

The screenshot shows the VS Code editor with the file explorer on the left displaying a project structure for a CRUD application. The main editor window shows the `emp.controller.js` file. The `update` function is implemented as follows:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){...
40 }
41
42 > export async function read(req,res){...
58 }
59
60 > export async function readAll(req,res){...
75 }
76
77 export async function update(req,res){
78   try {
79     const {id} = req.params;
80
81     const emp = await Emp.findById({_id:id});
82
83     if(!emp) return res.status(404).json({error:"emp not found!"});
84
85     const newEmp = await Emp.findByIdAndUpdate({_id:id},{...req.body},{new:true});
86
87     res.status(201).json({
88       newEmp
89     })
90   } catch (error) {
91     console.log("Error in create controller : ",error.message);
92     res.status(500).json({error:"Internal server Error"})
93   }
94 }
95
96 > export async function remove(req,res){...
110 }
```

The status bar at the bottom indicates the cursor is at line 96, column 39.

## DELETE:

The screenshot shows the VS Code editor with the file explorer on the left. The main editor window shows the `emp.controller.js` file. The `remove` function is implemented as follows:

```
api > controllers > JS emp.controller.js > remove
1  import Emp from "../model/emp.model.js";
2
3  > export async function create(req,res){...
40 }
41
42 > export async function read(req,res){...
58 }
59
60 > export async function readAll(req,res){...
75 }
76
77 > export async function update(req,res){...
94 }
95
96 export async function remove(req,res){
97   try {
98     const {id} = req.params;
99
100    await Emp.findByIdAndDelete({_id:id});
101
102    res.status(201).json({
103      id,
104      message : `deleted successfully..`,
105    })
106  } catch (error) {
107    console.log("Error in create controller : ",error.message);
108    res.status(500).json({error:"Internal server Error"})
109  }
110 }
```


The status bar at the bottom indicates the cursor is at line 96, column 39.

## HOW TO RUN ON LOCALLY:

- 1 . Create a folder as any name.
- 2 . Open that folder in any code editor (vs code).
- 3 . Open terminal (ctrl + ~) on code editor.
- 4 . Type this code to get code locally. `git clone https://github.com/4727yesuraju/crud.git`
- 5 . Now move to crud folder (`cd crud` in terminal)
- 6 . Ignore client folder.
- 7 . Here crud is root folder.
- 8 . In root folder create a `.env` file and create a `PORT` and `CONN_STR` variables and assign value.

ex : `PORT = 3000` ( commonly any number between 3000 - 8080).

`CONN_STR = your mongodb_connection_string`



--- trouble in above process?: simply

paste this code in `.env` file.

`PORT = 5000`

`CONN_STR=mongodb+srv://4727yesuraju:rough@cluster0.wbclvtg.mongodb.net`



`/?retry Writes=true&w=majority&appName=Cluster0`

9 . After in terminal (in crud folder as root folder) type this command to server.

`npm i` (installing all dependencies) `npm run dev` (to run server)

10. if you get below message in terminal then your server will running Successfully

```
PS C:\Users\4727y\OneDrive\Desktop\internshala\crud> npm run dev

> crud@1.0.0 dev
> nodemon api/index.js

[nodemon] 3.1.0
[nodemon] to restart at any time, enter `rs`
[nodemon] watching path(s): *.*
[nodemon] watching extensions: js,mjs,cjs,json
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```

route and its functionality:

For this use any API using tools like Postman or Thunder Client. i

use THUNDER CLIENT.

**CREATE ROUTE :**

1 . This route is used to create a new employee in database with a below fields. username, empname, email, role, salary

2 . in thunder client click on new request and select this options method as post url as `http://localhost:5000/api/user/create`

pass this json data as a body as your required value.

```
{
  "username": "jack",
  "empname": "jack rider",
  "email": "jack@gmail.com",
  "role": "Front End Developer",
  "salary": 60000
}
```

}

3 . finally press send to insert data in mongodb data base and get a inserted data as a response.

4 . If user is already in db it will return User is already exist as response.

for more details visit below output images...

#### **READONE:**

1 . This route is used to read specific user info by passing that user id as a param.

method as get

url as

<http://localhost:5000/api/user/read/65ed7b3d76e1dcc9a51654ca>

2 . After sending you will get that specific user details as response.

#### **READALL :**

1 . Read all route is used to get all the user data existing in the mongodb data base .

method as get

url as <http://localhost:5000/api/user/readall>

2 . After sending you will get that all user details as response.

#### **UPDATE :**

1 . This route is used to update specific user by passing that user id as a param. method as put

url as <http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca>

2 . After sending you will get updated user details as response.

#### **DELETE :**


1 . This route is used to delete specific user by passing that user id as a param. method as delete

url as <http://localhost:5000/api/user/delete/65ed7b3d76e1dcc9a51654ca> 2 . After sending you will deleted successfully as response.


#### **OUTPUT :**

#### **CREATE A NEW USER :**







## CREATING USER WITH EXISTING USERNAME :



## READONE :



**READ ALL :**



**UPDATE :**

Thunder Client interface showing a PUT request to `http://localhost:5000/api/user/update/65ed7b3d76e1dcc9a51654ca`. The request body is a JSON object:

```
1 {
2   "empname": "jack rider",
3   "email": "jack123@gmail.com",
4   "role": "MERN STACK Developer",
5   "salary": 100000
6 }
```

The response status is 201 Created, Size: 246 Bytes, Time: 213 ms. The response body is a JSON object:

```
1 {
2   "newEmp": {
3     "_id": "65ed7b3d76e1dcc9a51654ca",
4     "username": "jack",
5     "empname": "jack rider",
6     "email": "jack123@gmail.com",
7     "role": "MERN STACK Developer",
8     "salary": 100000,
9     "createdAt": "2024-03-10T09:19:57.171Z",
10    "updatedAt": "2024-03-10T09:22:55.106Z",
11    "__v": 0
12  }
13 }
```

The terminal shows an error in the create controller:

```
empname: 'jack rider',
email: 'jack@gmail.com',
role: 'Front End Developer',
salary: 60000
}
Error in create controller : Cast to ObjectId failed for value "{ _id: '65ed625bbd510e515f6767d' }" (type Object) at path "_id" for model "User"
```

## DELETE :

Thunder Client interface showing a DELETE request to `http://localhost:5000/api/user/remove/65ed7b3d76e1dcc9a51654ca`. The request body is empty. The response status is 201 Created, Size: 68 Bytes, Time: 111 ms. The response body is a JSON object:

```
1 {
2   "id": "65ed7b3d76e1dcc9a51654ca",
3   "message": "deleted successfully.."
4 }
```

The terminal shows the server status:

```
Node.js v20.11.0
[nodemon] app crashed - waiting for file changes before starting...
[nodemon] restarting due to changes...
[nodemon] starting `node api/index.js`
Server is running on PORT : 5000
DB connected successfully
```