

Package ‘radiant’

April 1, 2015

Title Business Analytics using R and Shiny

Version 0.1.89

Date 2015-4-1

Description A platform-independent browser-based interface for business analytics in R, based on the Shiny package.

Depends R (>= 3.1.0),
lubridate (>= 1.3.3),
ggplot2 (>= 1.0.0),
dplyr (>= 0.4.1),
magrittr (>= 1.5)

Imports car (>= 2.0.22),
MASS (>= 7.3),
gridExtra (>= 0.9.1),
AlgDesign (>= 1.1.7.3),
GPArotation (>= 2014.11.1),
psych (>= 1.4.8.11),
wordcloud (>= 2.5),
markdown (>= 0.7.4),
knitr (>= 1.8),
ggdendro (>= 0.1.15),
broom (>= 0.3.6),
tidyr (>= 0.2.0),
pryr (>= 0.1),
htmlwidgets (>= 0.3.2),
rpivotTable (>= 0.1.2.6),
shiny (>= 0.11.1),
shinyAce (>= 0.2.1)

Suggests rmarkdown (>= 0.4.2),
ggvis (>= 0.4),
testthat (>= 0.9.1)

URL <https://github.com/vnijs/radiant>, <http://vnijs.github.io/radiant/>

BugReports <https://github.com/vnijs/radiant/issues>

License AGPL-3 | file LICENSE

LazyData true

R topics documented:

ca_the_table	3
changedata	4
city	5
compare_means	5
compare_props	6
computer	7
conjoint	8
conjoint_profiles	9
correlation	9
cross_tabs	10
diamonds	11
ff_design	11
full_factor	12
getdata	13
glm_reg	13
hier_clus	14
kmeans_clus	15
kurtosi	16
launcher	16
mac_launcher	17
mds	17
mergedata	18
mp3	19
newspaper	20
plot.compare_means	20
plot.compare_props	21
plot.conjoint	21
plot.correlation	22
plot.cross_tabs	23
plot.full_factor	24
plot.glm_predict	24
plot.glm_reg	25
plot.hier_clus	26
plot.kmeans_clus	27
plot.mds	28
plot.pmap	29
plot.pre_factor	30
plot.regression	30
plot.reg_predict	32
plot.single_mean	33
plot.single_prop	33
pmap	34
predict.glm_reg	35
predict.regression	36
pre_factor	37
print.arrange	37
radiant	38
regression	38
rndnames	39
sample_size	40

sampling	41
save_factors	42
save_glm_resid	42
save_membership	43
save_reg_resid	44
set_class	44
shopping	45
sig_stars	45
single_mean	46
single_prop	47
skew	47
sshh	48
sshhr	48
state_init	49
state_multiple	49
state_single	50
summary.compare_means	51
summary.compare_props	52
summary.conjoint	52
summary.conjoint_profiles	53
summary.correlation	54
summary.cross_tabs	54
summary.full_factor	55
summary.glm_reg	56
summary.hier_clus	57
summary.kmeans_clus	57
summary.mds	58
summary.pmap	59
summary.pre_factor	60
summary.regression	60
summary.sample_size	61
summary.sampling	62
summary.single_mean	63
summary.single_prop	63
test_check	64
titanic	65
titanic_pred	65
toothpaste	66
var_check	66
visualize	67
win_launcher	68

Index**69**

ca_the_table

*Function to calculate the PW and IW table for conjoint***Description**

Function to calculate the PW and IW table for conjoint

Usage

```
ca_the_table(model, dat, ca_indep_var)
```

Arguments

model	Tidied model results (broom) output from conjoint passed on by <code>summary.conjoint</code>
dat	Conjoint data
ca_indep_var	Independent variables used in the conjoint regression

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[summary.conjoint](#) to summarize results
[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(dataset = "mp3", ca_dep_var = "Rating", ca_indep_var = "Memory:Shape")
ca_the_table(result$model, result$dat, result$ca_indep_var)
```

changedata

Change data

Description

Change data

Usage

```
changedata(dataset, vars = c(), var_names = names(vars))
```

Arguments

dataset	Name of the dataframe to change
vars	New variables to add to the data.frame
var_names	Names for the new variables to add to the data.frame

Value

None

Examples

```
## Not run:
r_data <- list()
r_data$dat <- data.frame(a = 1:20)
changedata("dat",20:1, "b")
head(r_data$dat)

## End(Not run)
```

city	<i>City distances</i>
------	-----------------------

Description

City distances

Usage

```
data(city)
```

Format

A data frame with 45 rows and 3 variables

Details

Distance in miles between nine cities in the USA. The dataset is used to illustrate multi-dimensional scaling (MDS). Description provided in attr(city,"description")

compare_means	<i>Compare means for two or more variables</i>
---------------	--

Description

Compare means for two or more variables

Usage

```
compare_means(dataset, cm_var1, cm_var2, data_filter = "",
  cm_paired = "independent", cm_alternative = "two.sided",
  cm_sig_level = 0.95, cm_adjust = "none")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
cm_var1	A numeric variable or factor selected for comparison
cm_var2	One or more numeric variables for comparison. If <code>cm_var1</code> is a factor only one variable can be selected and the mean of this variable is compared across (factor) levels of <code>cm_var1</code>
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
cm_paired	Are samples indepent ("independent") or not ("paired")
cm_alternative	The alternative hypothesis ("two.sided", "greater" or "less")
cm_sig_level	Span of the confidence interval
cm_adjust	Adjustment for multiple comparisons ("none" or "bonf" for Bonferroni)

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

Value

A list of all variables defined in the function as an object of class `compare_means`

See Also

[summary.compare_means](#) to summarize results

[plot.compare_means](#) to plot results

Examples

```
result <- compare_means("diamonds", "cut", "price")
```

compare_props

Compare proportions across groups

Description

Compare proportions across groups

Usage

```
compare_props(dataset, cp_var1, cp_var2, data_filter = "", cp_levels = "",
  cp_alternative = "two.sided", cp_sig_level = 0.95, cp_adjust = "none")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
cp_var1	A grouping variable to split the data for comparisons
cp_var2	The variable to calculate proportions for
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
cp_levels	The factor level selected for the proportion comparison
cp_alternative	The alternative hypothesis ("two.sided", "greater" or "less")
cp_sig_level	Span of the confidence interval
cp_adjust	Adjustment for multiple comparisons ("none" or "bonf" for Bonferroni)

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

Value

A list of all variables defined in the function as an object of class `compare_props`

See Also

[summary.compare_props](#) to summarize results

[plot.compare_props](#) to plot results

Examples

```
result <- compare_props("titanic", "pclass", "survived")
```

computer

Perceptions of computer (re)sellers

Description

Perceptions of computer (re)sellers

Usage

```
data(computer)
```

Format

A data frame with 5 rows and 8 variables

Details

Perceptions of computer (re)sellers. The dataset is used to illustrate perceptual maps. Description provided in `attr(computer,"description")`

conjoint	<i>Conjoint analysis</i>
----------	--------------------------

Description

Conjoint analysis

Usage

```
conjoint(dataset, ca_dep_var, ca_indep_var, data_filter = "",
  ca_rev = FALSE)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
ca_dep_var	The dependent variable (e.g., profile ratings)
ca_indep_var	Independent variables in the regression
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
ca_rev	Reverse the values of the dependent variable ('ca_dep_var')

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint`

See Also

[summary.conjoint](#) to summarize results

[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(dataset = "mp3", ca_dep_var = "Rating", ca_indep_var = "Memory:Shape")
```

conjoint_profiles	Create fractional factorial design for conjoint analysis
-------------------	--

Description

Create fractional factorial design for conjoint analysis

Usage

```
conjoint_profiles(dataset)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
---------	--

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `conjoint_profiles`

See Also

[summary.conjoint_profiles](#) to summarize results

Examples

```
ca_prof <- readLines(system.file("examples/profiles-movie.txt", package='radiant'))
result <- conjoint_profiles("ca_prof")
```

correlation	Calculate correlations for two or more variables
-------------	--

Description

Calculate correlations for two or more variables

Usage

```
correlation(dataset, cor_var, data_filter = "", cor_type = "pearson")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
cor_var	Variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
cor_type	Type of correlations to calculate. Options are "pearson", "spearman", and "kendall". "pearson" is the default

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

Value

A list with all variables defined in the function as an object of class `compare_means`

See Also

[summary.correlation](#) to summarize results

[plot.correlation](#) to plot results

Examples

```
result <- correlation("diamonds",c("price","carat","clarity"))
result <- correlation("diamonds",c("price:table"))
```

cross_tabs

Evaluate associations between categorical variables

Description

Evaluate associations between categorical variables

Usage

```
cross_tabs(dataset, ct_var1, ct_var2, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
ct_var1	A categorical variable
ct_var2	Another categorical variable
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

Value

A list of all variables used in `cross_tabs` as an object of class `cross_tabs`

See Also

`summary.cross_tabs` to summarize results

`plot.cross_tabs` to plot results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
```

diamonds	<i>Diamond prices</i>
----------	-----------------------

Description

Diamond prices

Usage

```
data(diamonds)
```

Format

A data frame with 3000 rows and 10 variables

Details

A sample of 3,000 from the diamonds dataset bundled with ggplot2. Description provided in `attr(diamonds,"description")`

ff_design	<i>Function to generate a fractional factorial design</i>
-----------	---

Description

Function to generate a fractional factorial design

Usage

```
ff_design(attr, trial = 0, rseed = 172110)
```

Arguments

<code>attr</code>	Attributes used to generate profiles
<code>trial</code>	Number of trials that have already been run
<code>rseed</code>	Random seed to use

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

See Also

[conjoint_profiles](#) to calculate results
[summary.conjoint_profiles](#) to summarize results

full_factor	<i>Factor analysis (PCA)</i>
-------------	------------------------------

Description

Factor analysis (PCA)

Usage

```
full_factor(dataset, ff_var, data_filter = "", ff_meth = "PCA",
  ff_number = 2, ff_rotation = "varimax")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
ff_var	Variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
ff_meth	Factor extraction method to use
ff_number	Number of factors to extract
ff_rotation	Apply varimax rotation or no rotation ("varimax" or "none")

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `full_factor`

See Also

[summary.full_factor](#) to summarize results
[plot.full_factor](#) to plot results

Examples

```
result <- full_factor("diamonds",c("price","carat","table","x","y"))
result <- full_factor("diamonds",c("price","carat","table","x","y"), ff_meth = "maxlik")
summary(result)
```

getdata

*Get data for analysis functions***Description**

Get data for analysis functions

Usage

```
getdata(dataset, vars = "", na.rm = TRUE, filt = "", slice = "")
```

Arguments

dataset	Name of the dataframe
vars	Variables to extract from the dataframe
na.rm	Remove rows with missing values (default is TRUE)
filt	Filter to apply to the specified dataset. For example "price > 10000" if dataset is "diamonds" (default is "")
slice	Select a slice of the specified dataset. For example "1:10" for the first 10 rows or "n()-10:n()" for the last 10 rows (default is ""). Not in Radiant GUI

Value

Data.frame with specified columns and rows

Examples

```
r_data <- list()
r_data$dat <- mtcars
getdata("dat", "mpg:vs", filt = "mpg > 20", slice = "1:5")
```

glm_reg

*Generalized linear models (GLM)***Description**

Generalized linear models (GLM)

Usage

```
glm_reg(dataset, glm_dep_var, glm_indep_var, data_filter = "",
  glm_levels = "", glm_link = "logit", glm_int_var = "", glm_check = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
glm_dep_var	The dependent variable in the logit (probit) model
glm_indep_var	Independent variables in the model
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
glm_levels	The level in the dependent variable defined as <code>_success_</code>
glm_link	Link function for <code>_glm_</code> ('logit' or 'probit'). 'logit' is the default
glm_int_var	Interaction term to include in the model (not implement)
glm_check	Optional output or estimation parameters. "vif" to show the multicollinearity diagnostics. "confint" to show coefficient confidence interval estimates. "odds" to show odds ratios and confidence interval estimates. "standardize" to output standardized coefficient estimates. "stepwise" to apply step-wise selection of variables

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

Value

A list with all variables defined in `glm_reg` as an object of class `glm_reg`

See Also

`summary.glm_reg` to summarize the results
`plot.glm_reg` to plot the results
`predict.glm_reg` to generate predictions
`plot.glm_predict` to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), glm_levels = "Yes")
```

hier_clus

Hierarchical cluster analysis

Description

Hierarchical cluster analysis

Usage

```
hier_clus(dataset, hc_vars, data_filter = "", hc_dist = "sq.euclidian",
  hc_meth = "ward.D")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
hc_vars	Vector of variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
hc_dist	Distance
hc_meth	Method

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

Value

A list of all variables used in `hier_clus` as an object of class `hier_clus`

See Also

[summary.hier_clus](#) to summarize results

[plot.hier_clus](#) to plot results

Examples

```
result <- hier_clus("shopping", hc_vars = c("v1:v6"))
```

kmeans_clus	<i>K-means cluster analysis</i>
-------------	---------------------------------

Description

K-means cluster analysis

Usage

```
kmeans_clus(dataset, km_vars, data_filter = "", km_hc_init = TRUE,
  km_dist = "sq.euclidian", km_meth = "ward.D", km_seed = 1234,
  km_nr_clus = 2)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
km_vars	Vector of variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
km_hc_init	Use centers from <code>hier_clus</code> as the starting point
km_dist	Distance for <code>hier_clus</code>
km_meth	Method for <code>hier_clus</code>
km_seed	Random see to use for <code>kmeans</code> if <code>km_hc_init</code> is FALSE
km_nr_clus	Number of clusters to extract

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

Value

A list of all variables used in `kmeans_clus` as an object of class `kmeans_clus`

See Also

[summary.kmeans_clus](#) to summarize results

[plot.kmeans_clus](#) to plot results

[save_membership](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", c("v1:v6"))
```

kurtosi	<i>Exporting the kurtosi function from the psych package</i>
---------	--

Description

Exporting the kurtosi function from the psych package

launcher	<i>Create a launcher for Mac (.command)</i>
----------	---

Description

Create a launcher for Mac (.command)

Usage

```
launcher(app = c("marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("marketing", "quant", or "base"). Default is "marketing"
-----	--

Details

On Mac (Windows) a file named `radiant.command` (`radiant.bat`) will be put on the desktop. Double-click the file to launch the specified Radiant app

See Also

[mac_launcher](#) to create a shortcut on mac

[mac_launcher](#) to create a shortcut on windows

mac_launcher	Create a launcher for Mac (.command)
--------------	--------------------------------------

Description

Create a launcher for Mac (.command)

Usage

```
mac_launcher(app = c("marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("marketing", "quant", or "base"). Default is "marketing"
-----	--

Details

On Mac a file named 'radiant.command' will be put on the desktop. Double-click the file to launch the specified Radiant app

Examples

```
if (interactive()) {
  if(Sys.info()["sysname"] != "Darwin") {
    mac_launcher()
    fn <- paste0("/Users/", Sys.getenv("USER"), "/Desktop/radiant.command")
    if(!file.exists(fn))
      stop("Mac launcher not created")
    else
      unlink(fn)
  }
}
```

mds	(Dis)similarity based brand maps (MDS)
-----	--

Description

(Dis)similarity based brand maps (MDS)

Usage

```
mds(dataset, mds_id1, mds_id2, mds_dis, data_filter = "",
      mds_method = "metric", mds_dim_number = 2)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
mds_id1	A character variable or factor with unique entries
mds_id2	A character variable or factor with unique entries
mds_dis	A numeric measure of brand dissimilarity
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
mds_method	Apply metric or non-metric MDS
mds_dim_number	Number of dimensions

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class `mds`

See Also

[summary.mds](#) to summarize results

[plot.mds](#) to plot results

Examples

```
result <- mds("city","from","to","distance")
result <- mds("diamonds","clarity","cut","price")
summary(result)
```

mergedata

Merge datasets using dplyr's join functions

Description

Merge datasets using dplyr's join functions

Usage

```
mergedata(dataset, dataset2, merge_vars = "", merge_type = "inner_join",
  merge_name = paste0("merged_", dataset))
```

Arguments

<code>dataset</code>	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
<code>dataset2</code>	Dataset name (string) to merge with <code>'dataset'</code> . This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
<code>merge_vars</code>	Variables used to merge/join <code>'dataset'</code> and <code>'dataset2'</code>
<code>merge_type</code>	The main join types from the dplyr package are provided. <code>'inner_join'</code> returns all rows from x with matching values in y, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. <code>'left_join'</code> returns all rows from x, and all columns from x and y. If there are multiple matches between x and y, all match combinations are returned. <code>'semi_join'</code> returns all rows from x with matching values in y, keeping just columns from x. A semi join differs from an inner join because an inner join will return one row of x for each matching row of y, whereas a semi join will never duplicate rows of x. <code>'anti_join'</code> returns all rows from x without matching values in y, keeping only columns from x
<code>merge_name</code>	Name for the merged dataset

Details

See <http://vnijs.github.io/radiant/base/merge.html> for an example in Radiant

Value

If (reactive) list `'r_data'` exists the merged dataset added as `'merge_name'`. Else the merged dataset will be returned as `'merge_name'`

Examples

```
mergedata("titanic", "titanic_pred", c("pclass", "sex", "age")) %>% head
```

mp3	<i>Conjoint data for MP3 players</i>
-----	--------------------------------------

Description

Conjoint data for MP3 players

Usage

```
data(mp3)
```

Format

A data frame with 18 rows and 6 variables

Details

Conjoint data for MP3 players. Description provided in `attr(mp3, "description")`

newspaper	<i>Newspaper readership</i>
-----------	-----------------------------

Description

Newspaper readership

Usage

```
data(newspaper)
```

Format

A data frame with 580 rows and 2 variables

Details

Newspaper readership data for 580 consumers. Description provided in attr(newspaper,"description")

plot.compare_means	<i>Plot method for the compare_means function</i>
--------------------	---

Description

Plot method for the compare_means function

Usage

```
## S3 method for class 'compare_means'
plot(x, cm_plots = "bar", shiny = FALSE, ...)
```

Arguments

x	Return value from compare_means
cm_plots	One or more plots ("bar", "box", or "density")
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

See Also

[compare_means](#) to calculate results
[summary.compare_means](#) to summarize results

Examples

```
result <- compare_means("diamonds","cut","price")
plot(result, cm_plots = c("bar","density"))
```

plot.compare_props	<i>Plot method for the compare_props function</i>
--------------------	---

Description

Plot method for the compare_props function

Usage

```
## S3 method for class 'compare_props'  
plot(x, cp_plots = "props", shiny = FALSE, ...)
```

Arguments

x	Return value from compare_props
cp_plots	One or more plots of proportions or counts ("props" or "counts")
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

See Also

[compare_props](#) to calculate results
[summary.compare_props](#) to summarize results

Examples

```
result <- compare_props("titanic", "pclass", "survived")  
plot(result, cp_plots = c("props", "counts"))
```

plot.conjoint	<i>Plot method for the conjoint function</i>
---------------	--

Description

Plot method for the conjoint function

Usage

```
## S3 method for class 'conjoint'  
plot(x, ca_plots = "pw", ca_scale_plot = FALSE,  
      shiny = FALSE, ...)
```

Arguments

x	Return value from conjoint
ca_plots	Show either the part-worth ("pw") or importance-weights ("iw") plot
ca_scale_plot	Scale the axes of the part-worth plots to the same range
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results
[summary.conjoint](#) to summarize results

Examples

```
result <- conjoint(dataset = "mp3", ca_dep_var = "Rating", ca_indep_var = "Memory:Shape")
plot(result, ca_scale_plot = TRUE)
plot(result, ca_plots = "iw")
```

plot.correlation	<i>Plot method for the correlation function</i>
------------------	---

Description

Plot method for the correlation function

Usage

```
## S3 method for class 'correlation'
plot(x, ...)
```

Arguments

x	Return value from correlation
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

See Also

[correlation](#) to calculate results
[summary.correlation](#) to summarize results

Examples

```
result <- correlation("diamonds", c("price", "carat", "clarity"))
plot(result)
```

plot.cross_tabs	<i>Plot method for the cross_tabs function</i>
-----------------	--

Description

Plot method for the cross_tabs function

Usage

```
## S3 method for class 'cross_tabs'
plot(x, ct_check = "", shiny = FALSE, ...)
```

Arguments

x	Return value from cross_tabs
ct_check	Show plots for variables ct_var1 and ct_var2. "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "dev_perc" for the percentage difference between the observed and expected frequencies (i.e., $(o - e) / e$)
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

See Also

[cross_tabs](#) to calculate results

[summary.cross_tabs](#) to summarize results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
plot(result, ct_check = c("observed", "expected", "chi_sq"))
```

plot.full_factor	<i>Plot method for the full_factor function</i>
------------------	---

Description

Plot method for the full_factor function

Usage

```
## S3 method for class 'full_factor'
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from <code>full_factor</code>
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

See Also

`full_factor` to calculate results
`plot.full_factor` to plot results

Examples

```
result <- full_factor("diamonds", c("price", "carat", "table"))
plot(result)
result <- full_factor("computer", "HighEnd:Business")
summary(result)
```

plot.glm_predict	<i>Plot method for the predict.glm_reg function</i>
------------------	---

Description

Plot method for the predict.glm_reg function

Usage

```
## S3 method for class 'glm_predict'
plot(x, glm_xvar = "", glm_facet_row = ".",
      glm_facet_col = ".", glm_color = "none", glm_conf_level = 0.95, ...)
```


Arguments

x	Return value from <code>predict.glm_reg</code> .
glm_xvar	Variable to display along the X-axis of the plot
glm_facet_row	Create vertically arranged subplots for each level of the selected factor variable
glm_facet_col	Create horizontally arranged subplots for each level of the selected factor variable
glm_color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
glm_conf_level	Confidence level to use for prediction intervals (.95 is the default). Note that the error bars for predictions are approximations at this point.
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

`glm_reg` to generate the result
`summary.glm_reg` to summarize results
`plot.glm_reg` to plot results
`predict.glm_reg` to generate predictions

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex","age"), glm_levels = "Yes")
pred <- predict(result, glm_predict_cmd = "pclass = levels(pclass)")
plot(pred, glm_xvar = "pclass")
pred <- predict(result, glm_predict_cmd = "age = 0:100")
plot(pred, glm_xvar = "age")
pred <- predict(result, glm_predict_cmd = "pclass = levels(pclass), sex = levels(sex)")
plot(pred, glm_xvar = "pclass", glm_color = "sex")
pred <- predict(result, glm_predict_cmd = "pclass = levels(pclass), age = seq(0,100,20)")
plot(pred, glm_xvar = "pclass", glm_color = "age")
plot(pred, glm_xvar = "age", glm_color = "pclass")
pred <- predict(result, glm_predict_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,20)")
plot(pred, glm_xvar = "age", glm_color = "sex", glm_facet_col = "pclass")
plot(pred, glm_xvar = "age", glm_color = "pclass", glm_facet_col = "sex")
pred <- predict(result, glm_predict_cmd="pclass=levels(pclass), sex=levels(sex), age=seq(0,100,5)")
plot(pred, glm_xvar = "age", glm_color = "sex", glm_facet_col = "pclass")
plot(pred, glm_xvar = "age", glm_color = "pclass", glm_facet_col = "sex")
```

plot.glm_reg

Plot method for the glm_reg function

Description

Plot method for the `glm_reg` function

Usage

```
## S3 method for class 'glm_reg'
plot(x, glm_plots = "", glm_conf_level = 0.95,
     glm_coef_int = FALSE, shiny = FALSE, ...)
```

Arguments

x	Return value from glm_reg
glm_plots	Plots to produce for the specified GLM model. Use "" to avoid showing any plots (default). "hist" shows histograms of all variables in the model. "scatter" shows scatter plots (or box plots for factors) for the dependent variable with each independent variable. "dashboard" is a series of four plots used to visually evaluate model. "coef" provides a coefficient plot
glm_conf_level	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
glm_coef_int	Include the intercept in the coefficient plot (TRUE or FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

[glm_reg](#) to generate results
[plot.glm_reg](#) to plot results
[predict.glm_reg](#) to generate predictions
[plot.glm_predict](#) to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), glm_levels = "Yes")
plot(result, glm_plots = "coef")
```

plot.hier_clus

Plot method for the hier_clus function

Description

Plot method for the hier_clus function

Usage

```
## S3 method for class 'hier_clus'
plot(x, hc_plots = c("scree", "diff"), hc_cutoff = 0.02,
     shiny = TRUE, ...)
```

Arguments

x	Return value from hier_clus
hc_plots	Plots to return. "diff" shows the percentage change in within-cluster heterogeneity as respondents are group into different number of clusters, "dendro" shows the dendrogram, "scree" shows a scree plot of within-cluster heterogeneity
hc_cutoff	For large datasets plots can take time to render and become hard to interpret. By selection a cutoff point (e.g., 0.05 percent) the initial steps in hierachical cluster analysis are removed from the plot
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

See Also

[summary.hier_clus](#) to summarize results
[plot.hier_clus](#) to plot results

Examples

```
result <- hier_clus("shopping", hc_vars = c("v1:v6"))
plot(result, hc_plots = c("diff", "scree"), hc_cutoff = .05)
plot(result, hc_plots = "dendro", hc_cutoff = 0)
```

plot.kmeans_clus	<i>Plot method for kmeans_clus</i>
------------------	------------------------------------

Description

Plot method for kmeans_clus

Usage

```
## S3 method for class 'kmeans_clus'
plot(x, shiny = FALSE, ...)
```

Arguments

x	Return value from kmeans_clus
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[summary.kmeans_clus](#) to summarize results
[save_membership](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", km_vars = c("v1:v6"))  
plot(result)
```

plot.mds

Plot method for the mds function

Description

Plot method for the mds function

Usage

```
## S3 method for class 'mds'  
plot(x, mds_rev_dim = "", mds_fontsz = 1.3, ...)
```

Arguments

x	Return value from mds
mds_rev_dim	Flip the axes in plots
mds_fontsz	Font size to use in plots
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results
[summary.mds](#) to plot results

Examples

```
result <- mds("city","from","to","distance")  
plot(result)  
plot(result, mds_rev_dim = 1:2)  
plot(result, mds_rev_dim = 1:2, mds_fontsz = 2)
```

`plot.pmap`*Plot method for the pmap function*

Description

Plot method for the pmap function

Usage

```
## S3 method for class 'pmap'  
plot(x, pmap_plot = "", pmap_scaling = 2.1,  
      pmap_fontsz = 1.3, ...)
```

Arguments

<code>x</code>	Return value from pmap
<code>pmap_plot</code>	Components to include in the plot ("brand", "attr"). If data on preferences is available use "pref" to add preference arrows to the plot
<code>pmap_scaling</code>	Arrow scaling in the brand map
<code>pmap_fontsz</code>	Font size to use in plots
<code>...</code>	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

See Also

[pmap](#) to calculate results

[summary.pmap](#) to plot results

Examples

```
result <- pmap("computer", "Brand", "HighEnd:Business")  
plot(result, pmap_plot = "brand")  
plot(result, pmap_plot = c("brand", "attr"))  
plot(result, pmap_plot = c("brand", "attr"))  
plot(result, pmap_scaling = 1, pmap_plot = c("brand", "attr"))  
result <- pmap("computer", "Brand", "HighEnd:Dated",  
               pmap_pref = c("Innovative", "Business"))  
plot(result, pmap_plot = c("brand", "attr", "pref"))
```

plot.pre_factor	<i>Plot method for the pre_factor function</i>
-----------------	--

Description

Plot method for the pre_factor function

Usage

```
## S3 method for class 'pre_factor'  
plot(x, ...)
```

Arguments

x	Return value from pre_factor
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[summary.pre_factor](#) to summarize results

Examples

```
result <- pre_factor("diamonds",c("price","carat","table"))  
plot(result)
```

plot.regression	<i>Plot method for the regression function</i>
-----------------	--

Description

Plot method for the regression function

Usage

```
## S3 method for class 'regression'  
plot(x, reg_plots = "", reg_lines = "",  
      reg_conf_level = 0.95, reg_coef_int = FALSE, shiny = FALSE, ...)
```

Arguments

x	Return value from regression
reg_plots	Regression plots to produce for the specified regression model. Enter "" to avoid showing any plots (default). "hist" to show histograms of all variables in the model. "correlations" for a visual representation of the correlation matrix selected variables. "scatter" to show scatter plots (or box plots for factors) for the dependent variables with each independent variable. "dashboard" for a series of six plots that can be used to evaluate model fit visually. "resid_pred" to plot the independent variables against the model residuals. "coef" for a coefficient plot with adjustable confidence intervals. "leverage" to show leverage plots for each independent variable
reg_lines	Optional lines to include in the select plot. "line" to include a line through a scatter plot. "loess" to include a polynomial regression fit line. To include both use c("line","loess")
reg_conf_level	Confidence level used to estimate confidence intervals (.95 is the default)
reg_coef_int	Include the intercept in the coefficient plot (TRUE, FALSE). FALSE is the default
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the results

[summary.regression](#) to summarize results

[predict.regression](#) to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
plot(result, reg_plots = "dashboard")
plot(result, reg_plots = "dashboard", reg_lines = c("line","loess"))
plot(result, reg_plots = "coef", reg_coef_int = TRUE)
plot(result, reg_plots = "coef", reg_conf_level = .99, reg_coef_int = TRUE)
plot(result, reg_plots = "hist")
plot(result, reg_plots = "scatter", reg_lines = c("line","loess"))
plot(result, reg_plots = "correlations")
plot(result, reg_plots = "leverage")
plot(result, reg_plots = "resid_pred", reg_lines = "line")
```

plot.reg_predict	<i>Plot method for the predict.regression function</i>
------------------	--

Description

Plot method for the predict.regression function

Usage

```
## S3 method for class 'reg_predict'
plot(x, reg_xvar = "", reg_facet_row = ".",
     reg_facet_col = ".", reg_color = "none", reg_conf_level = 0.95, ...)
```

Arguments

x	Return value from predict.regression .
reg_xvar	Variable to display along the X-axis of the plot
reg_facet_row	Create vertically arranged subplots for each level of the selected factor variable
reg_facet_col	Create horizontally arranged subplots for each level of the selected factor variable
reg_color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
reg_conf_level	Confidence level to use for prediction intervals (.95 is the default). Note that the error bars for predictions are approximations at this point.
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the result
[summary.regression](#) to summarize results
[plot.regression](#) to plot results
[predict.regression](#) to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
pred <- predict(result, reg_predict_cmd = "carat = 1:10")
plot(pred, reg_xvar = "carat")
result <- regression("diamonds", "price", c("carat","clarity"), reg_int_var = "carat:clarity")
dpred <- getdata("diamonds") %>% slice(1:100)
pred <- predict(result, reg_predict_data = "dpred")
plot(pred, reg_xvar = "carat", reg_color = "clarity")
```

plot.single_mean	<i>Plot method for the single_mean function</i>
------------------	---

Description

Plot method for the single_mean function

Usage

```
## S3 method for class 'single_mean'  
plot(x, sm_plots = "hist", shiny = FALSE, ...)
```

Arguments

x	Return value from single_mean
sm_plots	Plots to generate. "hist" shows a histogram of the data along with vertical lines that indicate the sample mean and the confidence interval. "simulate" shows the location of the sample mean and the comparison value (sm_comp_value). Simulation is used to demonstrate the sampling variability in the data under the null-hypothesis
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

See Also

[single_mean](#) to generate the result
[summary.single_mean](#) to summarize results

Examples

```
result <- single_mean("diamonds", "price", sm_comp_value = 3500)  
plot(result, sm_plots = c("hist", "simulate"))
```

plot.single_prop	<i>Plot method for the single_prop function</i>
------------------	---

Description

Plot method for the single_prop function

Usage

```
## S3 method for class 'single_prop'  
plot(x, sp_plots = "hist", shiny = FALSE, ...)
```

Arguments

x	Return value from <code>single_prop</code>
sp_plots	Plots to generate. "hist" shows a histogram of the data along with vertical lines that indicate the sample proportion and the confidence interval. "simulate" shows the location of the sample proportion and the comparison value (sp_comp_value). Simulation is used to demonstrate the sampling variability in the data under the null-hypothesis
shiny	Did the function call originate inside a shiny app
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_prop.html for an example in Radiant

See Also

`single_prop` to generate the result
`summary.single_prop` to summarize the results

Examples

```
result <- single_prop("diamonds", "clarity", sp_levels = "IF", sp_comp_value = 0.05)
plot(result, sp_plots = c("hist", "simulate"))
```

pmap	<i>Attribute based brand maps</i>
------	-----------------------------------

Description

Attribute based brand maps

Usage

```
pmap(dataset, pmap_brand, pmap_attr, data_filter = "", pmap_pref = "",
      pmap_dim_number = 2)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
pmap_brand	A character variable with brand names
pmap_attr	Names of numeric variables
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
pmap_pref	Names of numeric brand preference measures
pmap_dim_number	Number of dimensions

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

Value

A list of all variables defined in the function as an object of class pmap

See Also

[summary.pmap](#) to summarize results

[plot.pmap](#) to plot results

Examples

```
result <- pmap("computer", "Brand", "HighEnd:Business")
```

predict.glm_reg

Predict method for the glm_reg function

Description

Predict method for the glm_reg function

Usage

```
## S3 method for class 'glm_reg'
predict(object, glm_predict_cmd = "",
        glm_predict_data = "", ...)
```

Arguments

object	Return value from glm_reg
glm_predict_cmd	Generate predictions using a command. For example, 'pclass = levels(pclass)' would produce predictions for the different levels of factor 'pclass'. To add another variable use a ',' (e.g., 'pclass = levels(pclass), age = seq(0,100,20)')
glm_predict_data	Provide the name of a dataframe to generate predictions (e.g., "titanic"). The dataset must contain all columns used in the estimation
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

[glm_reg](#) to generate the result

[summary.glm_reg](#) to summarize results

[plot.glm_reg](#) to plot results

[plot.glm_predict](#) to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", c("pclass","sex"), glm_levels = "Yes")
predict(result, glm_predict_cmd = "pclass = levels(pclass)")
predict(result, glm_predict_cmd = "sex = c('male','female')")
```

predict.regression	<i>Predict method for the regression function</i>
--------------------	---

Description

Predict method for the regression function

Usage

```
## S3 method for class 'regression'
predict(object, reg_predict_cmd = "",
        reg_predict_data = "", reg_conf_level = 0.95, reg_save_pred = FALSE,
        ...)
```

Arguments

object	Return value from regression
reg_predict_cmd	Command used to generate data for prediction
reg_predict_data	Name of the dataset to use for prediction
reg_conf_level	Confidence level used to estimate confidence intervals (.95 is the default)
reg_save_pred	Save predicted values to a csv file
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the result
[summary.regression](#) to summarize results
[plot.regression](#) to plot results

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
predict(result, reg_predict_cmd = "carat = 1:10")
predict(result, reg_predict_cmd = "clarity = levels(clarity)")
result <- regression("diamonds", "price", c("carat","clarity"), reg_int_var = c("carat:clarity"))
dpred <- getdata("diamonds") %>% slice(1:10)
predict(result, reg_predict_data = "dpred")
```

pre_factor	<i>Evaluate if data are appropriate for PCA / Factor analysis</i>
------------	---

Description

Evaluate if data are appropriate for PCA / Factor analysis

Usage

```
pre_factor(dataset, pf_var, data_filter = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
pf_var	Variables to include in the analysis
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

Value

A list with all variables defined in the function as an object of class `pre_factor`

See Also

`summary.pre_factor` to summarize results
`plot.pre_factor` to plot results

Examples

```
result <- pre_factor("diamonds",c("price","carat","table"))
```

print.arrange	<i>Exporting the print.arrange method from the gridExtra package</i>
---------------	--

Description

Exporting the print.arrange method from the gridExtra package

radiant	<i>radiant</i>
---------	----------------

Description

radiant

Launch Radiant in the default browser

Usage

```
radiant(app = c("marketing", "quant", "base"))
```

Arguments

app	Choose the app to run. Either "base", "quant", or "marketing". "marketing" is the default
-----	---

Details

See <http://vnijs.github.io/radiant> for documentation and tutorials

Examples

```
if (interactive()) {
  radiant()
}
```

regression	<i>Linear regression using OLS</i>
------------	------------------------------------

Description

Linear regression using OLS

Usage

```
regression(dataset, reg_dep_var, reg_indep_var, data_filter = "",
  reg_int_var = "", reg_check = "")
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
reg_dep_var	The dependent variable in the regression
reg_indep_var	Independent variables in the regression
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
reg_int_var	Interaction terms to include in the model
reg_check	"standardize" to see standardized coefficient estimates. "stepwise" to apply step-wise selection of variables in estimation

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

A list of all variables used in regression as an object of class regression

See Also

`summary.regression` to summarize results

`plot.regression` to plot results

`predict.regression` to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
result <- regression("diamonds", "price", c("carat","clarity"), reg_check = "standardize")
```

<code>rndnames</code>	<i>100 random names</i>
-----------------------	-------------------------

Description

100 random names

Usage

```
data(rndnames)
```

Format

A data frame with 100 rows and 2 variables

Details

A list of 100 random names generated by listofrandomnames.com. Description provided in `attr(rndnames,"description")`

sample_size	<i>Sample size calculation</i>
-------------	--------------------------------

Description

Sample size calculation

Usage

```
sample_size(ss_type = "mean", ss_mean_err = 2, ss_mean_s = 10,
            ss_prop_err = 0.1, ss_prop_p = 0.5, ss_z = 1.96, ss_incidence = 1,
            ss_response = 1, ss_pop_correction = "no", ss_pop_size = 1000000)
```

Arguments

ss_type	Choose "mean" or "proportion"
ss_mean_err	Acceptable Error for Mean
ss_mean_s	Standard deviation for Mean
ss_prop_err	Acceptable Error for Proportion
ss_prop_p	Initial proportion estimate for Proportion
ss_z	Z-value
ss_incidence	Incidence rate (i.e., fraction of valid respondents)
ss_response	Response rate
ss_pop_correction	Apply correction for population size ("yes","no")
ss_pop_size	Population size

Details

See http://vnijs.github.io/radiant/quant/sample_size.html for an example in Radiant

Value

A list of variables defined in sample_size as an object of class sample_size

See Also

[summary.sample_size](#) to summarize results

Examples

```
result <- sample_size(ss_type = "mean", ss_mean_err = 2, ss_mean_s = 10)
```

sampling	<i>Simple random sampling</i>
----------	-------------------------------

Description

Simple random sampling

Usage

```
sampling(dataset, smp_var, smp_sample_size, data_filter = "",  
         smp_print_full = TRUE)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
smp_var	The variable to sample from
smp_sample_size	Number of units to select
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
smp_print_full	Print full sampling frame. Default is TRUE

Details

See <http://vnijs.github.io/radiant/quant/sampling.html> for an example in Radiant

Value

A list of variables defined in sampling as an object of class `sampling`

See Also

[summary.sampling](#) to summarize results

Examples

```
result <- sampling("rndnames", "Names", 10)
```

save_factors	Save factor scores to active dataset
--------------	--------------------------------------

Description

Save factor scores to active dataset

Usage

```
save_factors(object)
```

Arguments

object	Return value from full_factor
--------	---

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

Examples

```
## Not run:
result <- full_factor("diamonds",c("price","carat","table"))
save_factors(result)
head(dat)

## End(Not run)
```

save_glm_resid	Save residuals generated in the glm_reg function
----------------	--

Description

Save residuals generated in the glm_reg function

Usage

```
save_glm_resid(object)
```

Arguments

object	Return value from glm_reg
--------	---

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

Examples

```
## Not run:
result <- glm_reg("titanic", "survived", "pclass", glm_levels = "Yes")
save_glm_resid(result)

## End(Not run)
```

save_membership	<i>Add a cluster membership variable to the active dataset</i>
-----------------	--

Description

Add a cluster membership variable to the active dataset

Usage

```
save_membership(object)
```

Arguments

object	Return value from kmeans_clus
--------	---

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[summary.kmeans_clus](#) to summarize results
[plot.kmeans_clus](#) to plot results

Examples

```
## Not run:
result <- kmeans_clus("shopping", km_vars = c("v1:v6"))
save_membership(result)

## End(Not run)
```

save_reg_resid	<i>Save regression residuals</i>
----------------	----------------------------------

Description

Save regression residuals

Usage

```
save_reg_resid(object)
```

Arguments

object	Return value from regression
--------	--

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Examples

```
## Not run:
result <- regression("diamonds", "price", c("carat","clarity"))
save_reg_resid(result)

## End(Not run)
```

set_class	<i>Alias used to set the class for analysis function return</i>
-----------	---

Description

Alias used to set the class for analysis function return

Usage

```
set_class()
```

Examples

```
foo <- function(x) x^2 %>% set_class(c("foo", class(.)))
```

`shopping`*Shopping attitudes*

Description

Shopping attitudes

Usage`data(shopping)`**Format**

A data frame with 20 rows and 7 variables

DetailsAttitudinal data on shopping for 20 consumers. Description provided in `attr(shopping,"description")`

`sig_stars`*Add stars '***' to a data.frame (from broom's 'tidy' function) based on p.values*

Description

Add stars '***' to a data.frame (from broom's 'tidy' function) based on p.values

Usage`sig_stars(pval)`**Arguments**`pval` Vector of p-values**Details**

Add stars to output from broom's 'tidy' function

Value

A vector of stars

Examples`sig_stars(c(.0009, .049, .009, .4, .09))`

single_mean	<i>Compare a sample mean to a population mean</i>
-------------	---

Description

Compare a sample mean to a population mean

Usage

```
single_mean(dataset, sm_var, data_filter = "", sm_comp_value = 0,
  sm_alternative = "two.sided", sm_sig_level = 0.95)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
sm_var	The variable selected for the mean comparison
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
sm_comp_value	Population value to compare to the sample mean
sm_alternative	The alternative hypothesis ("two.sided", "greater", or "less")
sm_sig_level	Span for the confidence interval

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

Value

A list of variables defined in `single_mean` as an object of class `single_mean`

See Also

`summary.single_mean` to summarize results

`plot.single_mean` to plot results

Examples

```
single_mean("diamonds", "price")
```

single_prop	<i>Compare a sample proportion to a population proportion</i>
-------------	---

Description

Compare a sample proportion to a population proportion

Usage

```
single_prop(dataset, sp_var, data_filter = "", sp_levels = "",
  sp_comp_value = 0.5, sp_alternative = "two.sided", sp_sig_level = 0.95)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
sp_var	The variable selected for the proportion comparison
data_filter	Expression entered in, e.g., Data > View to filter the dataset in Radiant. The expression should be a string (e.g., "price > 10000")
sp_levels	The factor level selected for the proportion comparison
sp_comp_value	Population value to compare to the sample proportion
sp_alternative	The alternative hypothesis ("two.sided", "greater", or "less")
sp_sig_level	Span of the confidence interval

Details

See http://vnij.s.github.io/radiant/quant/single_prop.html for an example in Radiant

Value

A list of variables used in `single_prop` as an object of class `single_prop`

See Also

[summary.single_prop](#) to summarize the results
[plot.single_prop](#) to plot the results

Examples

```
result <- single_prop("diamonds", "clarity", sp_levels = "IF", sp_comp_value = 0.05)
```

skew	<i>Exporting the skew function from the psych package</i>
------	---

Description

Exporting the skew function from the psych package

`ssh`*Hide warnings and messages and return invisible*

Description

Hide warnings and messages and return invisible

Usage

```
ssh(...)
```

Arguments

... Inputs to keep quiet

Details

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

Examples

```
ssh( library(dplyr) )
```

`sshhr`*Hide warnings and messages and return result*

Description

Hide warnings and messages and return result

Usage

```
sshhr(...)
```

Arguments

... Inputs to keep quiet

Details

Adapted from <http://www.onthelambda.com/2014/09/17/fun-with-rprofile-and-customizing-r-startup/>

Examples

```
sshhr( library(dplyr) )
```

state_init	<i>Set initial value for shiny input</i>
------------	--

Description

Set initial value for shiny input

Usage

```
state_init(inputvar, init = "")
```

Arguments

inputvar	Name shiny input
init	Initial value to use if state value for input not set

Details

Useful for radio button or checkbox

Value

value for inputvar

See Also

[state_single](#)
[state_multiple](#)

Examples

```
r_state <- list()
state_init("test")
state_init("test",0)
r_state$test <- c("a","b")
state_init("test",0)
```

state_multiple	<i>Set initial values for shiny input from a list of values</i>
----------------	---

Description

Set initial values for shiny input from a list of values

Usage

```
state_multiple(inputvar, vals, init = character(0))
```

Arguments

inputvar	Name shiny input
vals	Possible values for inputvar
init	Initial value to use if state value for input not set

Details

Useful for select input with multiple = TRUE and when you want to use inputs selected for another tool

Value

value for inputvar

See Also

[state_init](#)
[state_single](#)

Examples

```
r_state <- list()
state_multiple("test", 1:10, 1:3)
r_state$test <- 8:10
state_multiple("test", 1:10, 1:3)
```

state_single	<i>Set initial value for shiny input from a list of values</i>
--------------	--

Description

Set initial value for shiny input from a list of values

Usage

```
state_single(inputvar, vals, init = character(0))
```

Arguments

inputvar	Name shiny input
vals	Possible values for inputvar
init	Initial value to use if state value for input not set

Details

Useful for select input with multiple = FALSE

Value

value for inputvar

See Also

[state_init](#)
[state_multiple](#)

Examples

```
r_state <- list()
state_single("test",1:10,1)
r_state$test <- 8
state_single("test",1:10,1)
```

summary.compare_means *Summary method for the compare_means function*

Description

Summary method for the compare_means function

Usage

```
## S3 method for class 'compare_means'
summary(object, ...)
```

Arguments

object	Return value from compare_means
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_means.html for an example in Radiant

See Also

[compare_means](#) to calculate results
[plot.compare_means](#) to plot results

Examples

```
result <- compare_means("diamonds","cut","price")
summary(result)
```

summary.compare_props *Summary method for the compare_props function*

Description

Summary method for the compare_props function

Usage

```
## S3 method for class 'compare_props'  
summary(object, ...)
```

Arguments

object	Return value from compare_props
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/compare_props.html for an example in Radiant

See Also

[compare_props](#) to calculate results
[plot.compare_props](#) to plot results

Examples

```
result <- compare_props("titanic", "pclass", "survived")  
summary(result)
```

summary.conjoint *Summary method for the conjoint function*

Description

Summary method for the conjoint function

Usage

```
## S3 method for class 'conjoint'  
summary(object, ca_vif = FALSE, ...)
```

Arguments

object	Return value from conjoint
ca_vif	Shows multicollinearity diagnostics.
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/conjoint.html> for an example in Radiant

See Also

[conjoint](#) to generate results

[plot.conjoint](#) to plot results

Examples

```
result <- conjoint(dataset = "mp3", ca_dep_var = "Rating", ca_indep_var = "Memory:Shape")
summary(result, ca_vif = TRUE)
```

summary.conjoint_profiles

Summary method for the conjoint_profiles function

Description

Summary method for the conjoint_profiles function

Usage

```
## S3 method for class 'conjoint_profiles'
summary(object, ...)
```

Arguments

object	Return value from conjoint_profiles
...	further arguments passed to or from other methods.

Details

See http://vnijs.github.io/radiant/marketing/conjoint_profiles.html for an example in Radiant

See Also

[conjoint_profiles](#) to calculate results

Examples

```
ca_prof <- readLines(system.file("examples/profiles-movie.txt", package='radiant'))
result <- conjoint_profiles("ca_prof")
summary(result)
```

summary.correlation	<i>Summary method for the correlation function</i>
---------------------	--

Description

Summary method for the correlation function

Usage

```
## S3 method for class 'correlation'
summary(object, cor_cutoff = 0, ...)
```

Arguments

object	Return value from correlation
cor_cutoff	Show only correlations larger than the cutoff in absolute value. Default is a cutoff of 0
...	further arguments passed to or from other methods.

Details

See <http://vnijs.github.io/radiant/quant/correlation.html> for an example in Radiant

See Also

[correlation](#) to calculate results

[plot.correlation](#) to plot results

Examples

```
result <- correlation("diamonds", c("price", "carat", "clarity"))
summary(result, cor_cutoff = .3)
```

summary.cross_tabs	<i>Summary method for the cross_tabs function</i>
--------------------	---

Description

Summary method for the cross_tabs function

Usage

```
## S3 method for class 'cross_tabs'
summary(object, ct_check = "", ...)
```

Arguments

object	Return value from cross_tabs
ct_check	Show table(s) for variables ct_var1 and ct_var2. "observed" for the observed frequencies table, "expected" for the expected frequencies table (i.e., frequencies that would be expected if the null hypothesis holds), "chi_sq" for the contribution to the overall chi-squared statistic for each cell (i.e., $(o - e)^2 / e$), "dev_std" for the standardized differences between the observed and expected frequencies (i.e., $(o - e) / \sqrt{e}$), and "dev_perc" for the percentage difference between the observed and expected frequencies (i.e., $(o - e) / e$)
...	further arguments passed to or from other methods.

Details

See http://vnijs.github.io/radiant/quant/cross_tabs.html for an example in Radiant

See Also

[cross_tabs](#) to calculate results
[plot.cross_tabs](#) to plot results

Examples

```
result <- cross_tabs("newspaper", "Income", "Newspaper")
summary(result, ct_check = c("observed", "expected", "chi_sq"))
```

summary.full_factor	<i>Summary method for the full_factor function</i>
---------------------	--

Description

Summary method for the full_factor function

Usage

```
## S3 method for class 'full_factor'
summary(object, ff_cutoff = 0, ff_sort = FALSE, ...)
```

Arguments

object	Return value from full_factor
ff_cutoff	Show only loadings with (absolute) values above ff_cutoff (default = 0)
ff_sort	Sort factor loadings
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/full_factor.html for an example in Radiant

See Also

[full_factor](#) to calculate results

[plot.full_factor](#) to plot results

Examples

```
result <- full_factor("diamonds",c("price","carat","depth","table","x"))
summary(result)
summary(result, ff_cutoff = 0, ff_sort = FALSE)
summary(result, ff_cutoff = 0, ff_sort = TRUE)
summary(result, ff_cutoff = .5, ff_sort = TRUE)
```

summary.glm_reg

Summary method for the glm_reg function

Description

Summary method for the glm_reg function

Usage

```
## S3 method for class 'glm_reg'
summary(object, glm_sum_check = "", glm_conf_level = 0.95,
        glm_test_var = "", ...)
```

Arguments

object	Return value from glm_reg
glm_sum_check	Optional output or estimation parameters. "rsme" to show the root mean squared error. "sumsquares" to show the sum of squares table. "vif" to show multi-collinearity diagnostics. "confint" to show coefficient confidence interval estimates.
glm_conf_level	Confidence level to use for coefficient and odds confidence intervals (.95 is the default)
glm_test_var	Variables to evaluate in model comparison (i.e., a competing models Chi-squared test)
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/glm_reg.html for an example in Radiant

See Also

[glm_reg](#) to generate the results

[plot.glm_reg](#) to plot the results

[predict.glm_reg](#) to generate predictions

[plot.glm_predict](#) to plot prediction output

Examples

```
result <- glm_reg("titanic", "survived", "pclass", glm_levels = "Yes")
summary(result, glm_test_var = "pclass")
res <- glm_reg("titanic", "survived", c("pclass", "sex"), glm_int_var="pclass:sex", glm_levels="Yes")
summary(res, glm_sum_check = c("vif", "confint", "odds"))
```

summary.hier_clus

*Summary method for the hier_clus function***Description**

Summary method for the hier_clus function

Usage

```
## S3 method for class 'hier_clus'
summary(object, ...)
```

Arguments

object	Return value from hier_clus
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/hier_clus.html for an example in Radiant

See Also

[summary.hier_clus](#) to summarize results
[plot.hier_clus](#) to plot results

Examples

```
result <- hier_clus("shopping", hc_vars = c("v1:v6"))
summary(result)
```

summary.kmeans_clus

*Summary method for kmeans_clus***Description**

Summary method for kmeans_clus

Usage

```
## S3 method for class 'kmeans_clus'
summary(object, ...)
```

Arguments

object	Return value from kmeans_clus
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/kmeans_clus.html for an example in Radiant

See Also

[kmeans_clus](#) to generate results
[plot.kmeans_clus](#) to plot results
[save_membership](#) to add cluster membership to the selected dataset

Examples

```
result <- kmeans_clus("shopping", km_vars = c("v1:v6"))  
summary(result)
```

summary.mds

<i>Summary method for the mds function</i>
--

Description

Summary method for the mds function

Usage

```
## S3 method for class 'mds'  
summary(object, mds_round = 1, ...)
```

Arguments

object	Return value from mds
mds_round	Rounding to use for output (default = 0). +1 used for coordinates. +2 used for stress measure. Not currently accessible in Radiant
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/mds.html> for an example in Radiant

See Also

[mds](#) to calculate results
[plot.mds](#) to plot results

Examples

```
result <- mds("city", "from", "to", "distance")
summary(result)
summary(result, mds_round = 2)
```

summary.pmap

*Summary method for the pmap function***Description**

Summary method for the pmap function

Usage

```
## S3 method for class 'pmap'
summary(object, pmap_cutoff = 0, ...)
```

Arguments

object	Return value from pmap
pmap_cutoff	Show only loadings with (absolute) values above pmap_cutoff (default = 0)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/marketing/pmap.html> for an example in Radiant

See Also

[pmap](#) to calculate results

[plot.pmap](#) to plot results

Examples

```
result <- pmap("computer", "Brand", "HighEnd:Business")
summary(result)
summary(result, pmap_cutoff = .3)
result <- pmap("computer", "Brand", "HighEnd:Dated", pmap_pref = c("Innovative", "Business"))
summary(result)
```

summary.pre_factor	<i>Summary method for the pre_factor function</i>
--------------------	---

Description

Summary method for the pre_factor function

Usage

```
## S3 method for class 'pre_factor'
summary(object, ...)
```

Arguments

object	Return value from pre_factor
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/marketing/pre_factor.html for an example in Radiant

See Also

[pre_factor](#) to calculate results
[plot.pre_factor](#) to plot results

Examples

```
result <- pre_factor("diamonds",c("price","carat","table"))
summary(result)
result <- pre_factor("computer","HighEnd:Business")
summary(result)
```

summary.regression	<i>Summary method for the regression function</i>
--------------------	---

Description

Summary method for the regression function

Usage

```
## S3 method for class 'regression'
summary(object, reg_sum_check = "",
        reg_conf_level = 0.95, reg_test_var = "", ...)
```

Arguments

object	Return value from regression
reg_sum_check	Optional output or estimation parameters. "rsme" to show the root mean squared error. "sumsquares" to show the sum of squares table. "vif" to show multi-collinearity diagnostics. "confint" to show coefficient confidence interval estimates.
reg_conf_level	Confidence level used to estimate confidence intervals (.95 is the default)
reg_test_var	Variables to evaluate in model comparison (i.e., a competing models F-test)
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

See Also

[regression](#) to generate the results
[plot.regression](#) to plot results
[predict.regression](#) to generate predictions

Examples

```
result <- regression("diamonds", "price", c("carat","clarity"))
summary(result, reg_sum_check = c("rmse","sumsquares","vif","confint"), reg_test_var = "clarity")
result <- regression("shopping", "v1", c("v2","v3"))
summary(result, reg_test_var = "v2")
```

summary.sample_size	<i>Summary method for the sample_size function</i>
---------------------	--

Description

Summary method for the sample_size function

Usage

```
## S3 method for class 'sample_size'
summary(object, ...)
```

Arguments

object	Return value from sample_size
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/sample_size for an example in Radiant

See Also

[sample_size](#) to generate the results

Examples

```
result <- sample_size(ss_type = "mean", ss_mean_err = 2, ss_mean_s = 10)
summary(result)
```

summary.sampling	<i>Summary method for the sampling function</i>
------------------	---

Description

Summary method for the sampling function

Usage

```
## S3 method for class 'sampling'
summary(object, ...)
```

Arguments

object	Return value from sampling
...	further arguments passed to or from other methods

Details

See <http://vnijs.github.io/radiant/quant/sampling> for an example in Radiant

See Also

[sampling](#) to generate the results

Examples

```
result <- sampling("rndnames", "Names", 10)
summary(result)
```

summary.single_mean	<i>Summary method for the single_mean function</i>
---------------------	--

Description

Summary method for the single_mean function

Usage

```
## S3 method for class 'single_mean'  
summary(object, ...)
```

Arguments

object	Return value from single_mean
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_mean.html for an example in Radiant

See Also

[single_mean](#) to generate the results
[plot.single_mean](#) to plot results

Examples

```
result <- single_mean("diamonds", "price")  
summary(result)
```

summary.single_prop	<i>Summary method for the single_prop function</i>
---------------------	--

Description

Summary method for the single_prop function

Usage

```
## S3 method for class 'single_prop'  
summary(object, ...)
```

Arguments

object	Return value from single_prop
...	further arguments passed to or from other methods

Details

See http://vnijs.github.io/radiant/quant/single_prop.html for an example in Radiant

See Also

`single_prop` to generate the results

`plot.single_prop` to plot the results

Examples

```
result <- single_prop("diamonds", "clarity", sp_levels = "IF", sp_comp_value = 0.05)
summary(result)
```

test_check

Add interaction terms to list of test variables if needed

Description

Add interaction terms to list of test variables if needed

Usage

```
test_check(test_var, int_var)
```

Arguments

test_var List of variables to use for testing for `_regression_` or `_glm_`

int_var Interaction terms specified

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

'test_var' is a vector of variables to test

Examples

```
test_check("a", c("a:b", "b:c"))
```

titanic	<i>Survival data for the Titanic</i>
---------	--------------------------------------

Description

Survival data for the Titanic

Usage

```
data(titanic)
```

Format

A data frame with 1309 rows and 11 variables

Details

Survival data for the Titanic. Description provided in `attr(titanic,"description")`

titanic_pred	<i>Predict survival</i>
--------------	-------------------------

Description

Predict survival

Usage

```
data(titanic_pred)
```

Format

A data frame with 6 rows and 3 variables

Details

Prediction data.frame for `glm_reg` based on the Titanic dataset

toothpaste	<i>Toothpaste attitudes</i>
Description	
Toothpaste attitudes	
Usage	
data(toothpaste)	
Format	
A data frame with 60 rows and 10 variables	
Details	
Attitudinal data on toothpaste for 60 consumers. Description provided in attr(toothpaste,"description")	
var_check	<i>Check if main effects for all interaction effects are included in the model If ':' is used to select a range _indep_var_ is updated</i>

Description

Check if main effects for all interaction effects are included in the model If ':' is used to select a range _indep_var_ is updated

Usage

```
var_check(indep_var, cn, int_var = "")
```

Arguments

indep_var	List of independent variables provided to _regression_ or _glm_
cn	Column names for all independent variables in _dat_
int_var	Interaction terms specified

Details

See <http://vnijs.github.io/radiant/quant/regression.html> for an example in Radiant

Value

'vars' is a vector of right-hand side variables, possibly with interactions, 'indep_var' is the list of independent variables, and int_var are interaction terms

Examples

```
var_check("a:d", c("a", "b", "c", "d"))
var_check(c("a", "b"), c("a", "b"), "a:c")
```

visualize

Visualize data using ggplot2 <http://docs.ggplot2.org/current/>**Description**Visualize data using ggplot2 <http://docs.ggplot2.org/current/>**Usage**

```
visualize(dataset, viz_xvar, viz_yvar = "none", data_filter = "",
  viz_type = "hist", viz_facet_row = ".", viz_facet_col = ".",
  viz_color = "none", viz_bins = 10, viz_smooth = 1, viz_check = "",
  viz_axes = "", shiny = FALSE)
```

Arguments

dataset	Dataset name (string). This can be a dataframe in the global environment or an element in an <code>r_data</code> list from Radiant
viz_xvar	One or more variables to display along the X-axis of the plot
viz_yvar	Variable to display along the Y-axis of the plot (default = "none")
data_filter	Expression used to filter the dataset. This should be a string (e.g., "price > 10000")
viz_type	Type of plot to create. One of Histogram ('hist'), Density ('density'), Scatter ('scatter'), Line ('line'), Bar ('bar'), or Box-plot ('box')
viz_facet_row	Create vertically arranged subplots for each level of the selected factor variable
viz_facet_col	Create horizontally arranged subplots for each level of the selected factor variable
viz_color	Adds color to a scatter plot to generate a heat map. For a line plot one line is created for each group and each is assigned a different colour
viz_bins	Number of bins used for a histogram (not accessible in Radiant)
viz_smooth	Adjust the flexibility of the loess line for scatter plots (not accessible in Radiant)
viz_check	Add a regression line ("line"), a loess line ("loess"), or jitter ("jitter") to a scatter plot
viz_axes	Flip the axes in a plot ("flip") or apply a log transformation (base e) to the y-axis ("log_y") or the x-axis ("log_x")
shiny	Did the function call originate inside a shiny app

DetailsSee <http://vnijs.github.io/radiant/base/visualize.html> for an example in Radiant**Value**

Generated plots

Examples

```
visualize("diamonds", "carat", "price", viz_type = "scatter", viz_check = "loess")
visualize("diamonds", "price:x", viz_type = "hist")
visualize("diamonds", "carat:x", viz_yvar = "price", viz_type = "scatter")
```

win_launcher	<i>Create a launcher for Windows (.bat)</i>
--------------	---

Description

Create a launcher for Windows (.bat)

Usage

```
win_launcher(app = c("marketing", "quant", "base"))
```

Arguments

app	App to run when the desktop icon is double-clicked ("marketing", "quant", or "base"). Default is "marketing"
-----	--

Details

On Windows a file named 'radiant.bat' will be put on the desktop. Double-click the file to launch the specified Radiant app

Examples

```
if (interactive()) {  
  if(Sys.info()["sysname"] != "Windows") {  
    win_launcher()  
    fn <- paste0(Sys.getenv("USERPROFILE"), "/Desktop/radiant.bat")  
    if(!file.exists(fn))  
      stop("Windows launcher not created")  
    else  
      unlink(fn)  
  }  
}
```

Index

*Topic **datasets**

- city, [5](#)
- computer, [7](#)
- diamonds, [11](#)
- mp3, [19](#)
- newspaper, [20](#)
- rndnames, [39](#)
- shopping, [45](#)
- titanic, [65](#)
- titanic_pred, [65](#)
- toothpaste, [66](#)

ca_the_table, [3](#)

changedata, [4](#)

city, [5](#)

compare_means, [5](#), [20](#), [51](#)

compare_props, [6](#), [21](#), [52](#)

computer, [7](#)

conjoint, [4](#), [8](#), [22](#), [52](#), [53](#)

conjoint_profiles, [9](#), [12](#), [53](#)

correlation, [9](#), [22](#), [54](#)

cross_tabs, [10](#), [23](#), [55](#)

diamonds, [11](#)

ff_design, [11](#)

full_factor, [12](#), [24](#), [42](#), [55](#), [56](#)

getdata, [13](#)

glm_reg, [13](#), [25](#), [26](#), [35](#), [42](#), [56](#)

hier_clus, [14](#), [27](#), [57](#)

kmeans_clus, [15](#), [27](#), [28](#), [43](#), [58](#)

kurtosi, [16](#)

launcher, [16](#)

mac_launcher, [16](#), [17](#)

mds, [17](#), [28](#), [58](#)

mergedata, [18](#)

mp3, [19](#)

newspaper, [20](#)

plot.compare_means, [6](#), [20](#), [51](#)

plot.compare_props, [7](#), [21](#), [52](#)

plot.conjoint, [4](#), [8](#), [21](#), [53](#)

plot.correlation, [10](#), [22](#), [54](#)

plot.cross_tabs, [11](#), [23](#), [55](#)

plot.full_factor, [12](#), [24](#), [24](#), [56](#)

plot.glm_predict, [14](#), [24](#), [26](#), [35](#), [56](#)

plot.glm_reg, [14](#), [25](#), [25](#), [26](#), [35](#), [56](#)

plot.hier_clus, [15](#), [26](#), [27](#), [57](#)

plot.kmeans_clus, [16](#), [27](#), [43](#), [58](#)

plot.mds, [18](#), [28](#), [58](#)

plot.pmap, [29](#), [35](#), [59](#)

plot.pre_factor, [30](#), [37](#), [60](#)

plot.reg_predict, [32](#)

plot.regression, [30](#), [32](#), [36](#), [39](#), [61](#)

plot.single_mean, [33](#), [46](#), [63](#)

plot.single_prop, [33](#), [47](#), [64](#)

pmap, [29](#), [34](#), [59](#)

pre_factor, [30](#), [37](#), [60](#)

predict.glm_reg, [14](#), [25](#), [26](#), [35](#), [56](#)

predict.regression, [31](#), [32](#), [36](#), [39](#), [61](#)

print.arrange, [37](#)

radiant, [38](#)

radiant-package (radiant), [38](#)

regression, [31](#), [32](#), [36](#), [38](#), [44](#), [61](#)

rndnames, [39](#)

sample_size, [40](#), [61](#), [62](#)

sampling, [41](#), [62](#)

save_factors, [42](#)

save_glm_resid, [42](#)

save_membership, [16](#), [28](#), [43](#), [58](#)

save_reg_resid, [44](#)

set_class, [44](#)

shopping, [45](#)

sig_stars, [45](#)

single_mean, [33](#), [46](#), [63](#)

single_prop, [34](#), [47](#), [63](#), [64](#)

skew, [47](#)

sshh, [48](#)

sshr, [48](#)

state_init, [49](#), [50](#), [51](#)

state_multiple, [49](#), [49](#), [51](#)

state_single, [49](#), [50](#), [50](#)

`summary.compare_means`, 6, 20, 51
`summary.compare_props`, 7, 21, 52
`summary.conjoint`, 4, 8, 22, 52
`summary.conjoint_profiles`, 9, 12, 53
`summary.correlation`, 10, 22, 54
`summary.cross_tabs`, 11, 23, 54
`summary.full_factor`, 12, 55
`summary.glm_reg`, 14, 25, 35, 56
`summary.hier_clus`, 15, 27, 57, 57
`summary.kmeans_clus`, 16, 28, 43, 57
`summary.mds`, 18, 28, 58
`summary.pmap`, 29, 35, 59
`summary.pre_factor`, 30, 37, 60
`summary.regression`, 31, 32, 36, 39, 60
`summary.sample_size`, 40, 61
`summary.sampling`, 41, 62
`summary.single_mean`, 33, 46, 63
`summary.single_prop`, 34, 47, 63

`test_check`, 64
`titanic`, 65
`titanic_pred`, 65
`toothpaste`, 66

`var_check`, 66
`visualize`, 67

`win_launcher`, 68