# PROJECT TITLE

*A Project Report Submitted in partial fulfilment of the requirements for the award of the degree*

*of*

**Bachelor of Technology**

**in**

**The Department of Electronics and Communication Engineering**

**Engineering Capstone Project – Phase 1 (23IE4053A/R)**


Submitted by

**23100400xx: Student1**

**23100400zz: Student2**

Under the guidance of

**Supervisor Name**

**Designation**






Department of Electronics and Communication Engineering

Koneru Lakshmaiah Education Foundation, Aziz Nagar

Aziz Nagar – 500075


November - 2026

**KONERU LAKSHMAIAH EDUCATION FOUNDATION**

*Department of Electronics and Communication Engineering*




*DECLARATION*

The Project Report entitled **"*Project Title*"** is a record of Bonafide work of **Student1 (23100400xx), Student2 (23100400zz), submitted** in partial fulfillment for the award of B. Tech in Department of Electronics and Communication Engineering to the Koneru Lakshmaiah Education Foundation (Deemed to be University). The results embodied in this report have not been copied from any other departments/University/Institute.

Student1 (22100400xx)

Student2 (22100400zz)

**KONERU LAKSHMAIAH EDUCATION FOUNDATION**

*Department of Electronics and Communication Engineering*

*CERTIFICATE*

This is to certify that the Project Report entitled **"Project Title" is** a record of Bonafide work of **Student1 (23100400xx), Student2 (23100400zz)** submitted in partial fulfilment for the award of B. Tech in Department of Electronic and communication Engineering to the Koneru Lakshmaiah Education Foundation (Deemed to be University) is a record of bonafide work carried out under my guidance and supervision.

The results embodied in this report have not been copied from any other departments / University / Institute.

Signature of the HOD
Dr. B. Anil Kumar

Signature of the Supervisor
Supervisor Name, Designation

Signature of the Internal Examiner

Signature of the External Examiner

# Acknowledgement

Our sincere thanks to **Supervisor Name** for his outstanding support throughout the project for the successful completion of the work

We express our gratitude to **Dr. B. Anil Kumar** Head of the Department of ECE for providing us with adequate facilities, ways and means by which we are able to complete this Major project work.

We would like to place on record the deep sense of gratitude to the Principal **Dr. A. Ramakrishna** for providing the necessary facilities to carry the concluded Major project work.

Last but not the least, we thank all Teaching and Non-Teaching Staff of our department and especially my classmates and my friends for their support in the completion of our work.

*Submitted By*

Student1 (23100400xx)
Student2 (23100400zz)

# Abstract

Autonomous drones have become an essential technology in modern applications such as surveillance, industrial inspection, disaster response, precision agriculture, and warehouse automation. These systems primarily rely on Global Positioning System (GPS) signals for localization and navigation. However, in GPS-denied environments such as indoor spaces, underground tunnels, dense urban areas, and heavily forested regions, traditional navigation methods become unreliable. To overcome this limitation, vision-based navigation techniques using Simultaneous Localization and Mapping (SLAM) have been developed to enable autonomous flight without GPS dependency.

This project focuses on implementing a vision-based autonomous drone navigation system using RTAB-Map-based Visual SLAM (VSLAM).

The system utilizes a Jetson Orin computing platform integrated with a ZED 2i stereo depth camera to perform real-time localization and 3D mapping. The Pixhawk 6C flight controller is responsible for flight control and execution, while MAVROS acts as the middleware between ROS Noetic and the flight control system, enabling autonomous waypoint-based navigation.

One of the key aspects of this implementation is the ability to extract real-time waypoints from the VSLAM-generated environment and convert them into an optimized flight path. The drone autonomously follows these waypoints using MAVROS setpoints, ensuring precise movement and minimal drift. Additionally, a PID (Proportional-Integral-Derivative) controller is implemented to enhance flight stability by dynamically adjusting velocity and orientation based on environmental factors and sensor feedback.

The combination of depth sensing, real-time SLAM, and smart control methods allows this system to work in crowded and complex areas where GPS-based drones cannot function properly. It improves the drone's ability to find its position in changing environments, avoid obstacles, and plan its path efficiently. With further improvements, this technology could be used for autonomous drones in warehouses, city surveillance, and emergency rescue missions, where reliable navigation without GPS is essential.

By combining real-time SLAM, robust sensor fusion, and adaptive flight control algorithms, this project provides a scalable and efficient solution for deploying drones in GPS-denied environments. The findings from this research contribute to advancements in autonomous robotics, industrial automation, search-and-rescue missions, and UAV-based logistics.

# List of Figures


| Figure No. | Figure Title | Page No. |
|---|---|---|
| 1.1 | System Architecture of the Autonomous Drone | |
| 2.1 | Hardware Setup of the Drone | |
| 3.1 | RTAB-Map SLAM Process | . |
| 4.1 | Waypoints Generation | |
| 5.1 | 3D Map Generated Using RTAB-Map | |
| 6 .1 | Experimental Test Environment | |

## List of Tables


| Table No. | Table Title | Page No. |
|---|---|---|
| 1.1 | MAVROS topics used | |
| 2.1 | EKF3 Parameter Configuration | |

## Table of Contents


| Chapter No. | Title | Page No. |
|---|---|---|
| 1 | Introduction | |
| 2 | Methodology | |
| 3 | Designs and Implementations | |
| 4 | Results Analysis | |
| 5 | Conclusion and Future Work | |
| | References | |

# CHAPTER 1

# INTRODUCTION

Unmanned Aerial Vehicles (UAVs), commonly known as drones, have revolutionized various industries, including surveillance, agriculture, disaster management, infrastructure inspection, and industrial automation. These autonomous aerial systems provide efficient, cost-effective, and scalable solutions for mapping, monitoring, and reconnaissance in areas that are difficult for humans to access. Traditional UAVs rely heavily on Global Positioning System (GPS) signals for localization and navigation. While GPS-based navigation is highly effective in open environments, it becomes unreliable or completely unavailable in indoor spaces, underground tunnels, dense urban areas, and forests, where signals are weak or obstructed. This limitation restricts the usability of drones in several critical applications, including indoor automation, warehouse surveillance, search and rescue operations, and military applications.

To overcome the challenges posed by GPS-denied environments, this project explores an alternative approach by integrating Vision-Based Simultaneous Localization and Mapping (VSLAM) with autonomous navigation techniques. VSLAM enables drones to perceive their surroundings, create real-time maps, and estimate their position autonomously without depending on external localization sources. Unlike GPS, which provides absolute positioning, SLAM-based navigation works by continuously updating the drone's relative position based on sensor data, making it highly suitable for confined or GPS-restricted areas.

This project leverages RTAB-Map, a graph-based SLAM algorithm, to perform real-time pose estimation and 3D mapping. The ZED 2i stereo depth camera is used for depth perception and obstacle detection, ensuring precise localization in cluttered environments. The Jetson Orin, an advanced embedded AI computing platform, serves as the primary processing unit, running ROS Noetic for SLAM computation, data processing, and navigation planning. MAVROS, a middleware package in ROS, bridges communication between Pixhawk 6C, the flight controller responsible for executing autonomous navigation commands. By integrating these components, the system enables the drone to capture waypoints, follow predefined paths, and autonomously navigate without human intervention.

The core workflow of this project includes:

1. SLAM-Based Mapping and Localization – Capturing real-time visual and depth data from the ZED 2i camera, processing it using RTAB-Map, and generating an optimized 3D map of the environment.
2. Waypoint Generation and Navigation – Extracting positional data from SLAM, converting it into X, Y, Z coordinates, and using it for autonomous waypoint-following navigation.
3. MAVROS Integration for Drone Control – Sending waypoints to the Pixhawk 6C flight controller via MAVROS, enabling the drone to follow the designated path precisely.
4. PID Controller for Flight Stability – Implementing Proportional-Integral-Derivative (PID) control to ensure smooth and stable movement while minimizing oscillations and errors during navigation.

The significance of this research lies in its ability to extend drone applications beyond GPS-restricted environments. This project contributes to advancing UAV technology by developing a self-sufficient, vision-based autonomous navigation system capable of operating in diverse and challenging environments. The findings from this research are expected to benefit industries such as logistics, smart city management, defense, environmental monitoring, and warehouse automation, where drones need to function reliably without GPS support.

# CHAPTER 2

# METHODLOGY

This section outlines the step-by-step approach used to develop a vision-based autonomous drone navigation system. The methodology includes system setup, SLAM implementation, waypoint generation, MAVROS integration, and flight control. Each component plays a crucial role in enabling GPS-independent drone operation using RTAB-Map, Jetson Orin, ZED 2i, and Pixhawk 6C.

## 2.1 Hardware and Software Setup

### 2.1.1 Hardware Components

The system consists of the following hardware elements:

- Jetson Orin – Handles VSLAM processing, real-time data computation, and ROS Noetic execution.
- ZED 2i Depth Camera – Provides stereo vision data for depth estimation and obstacle detection.
- Pixhawk 6C Flight Controller – Controls motor actuation, sensor fusion, and autonomous navigation.
- LiPo Battery & Power Distribution – Supplies stable power for flight operation and onboard computing.
- Frame and BLDC Motors – Provide lift and propulsion for drone movement.



**Figure 2.1 :** Hardware Setup of the Drone

### 2.1.2 Software Components

- ROS Noetic – Middleware that facilitates sensor fusion, SLAM processing, and MAVROS integration.
- RTAB-Map – A real-time SLAM algorithm for map creation and pose estimation.

- MAVROS – A ROS package that allows communication between Pixhawk and Jetson Orin.
- PX4 Firmware – Open-source flight control software running on Pixhawk 6C.

## 2.2 RTAB-Map SLAM Implementation

SLAM (Simultaneous Localization and Mapping) is used to localize the drone in an unknown environment while simultaneously building a 3D map. RTAB-Map is chosen due to its:

- Graph-based optimization, allowing loop closure detection for accurate mapping.
- Memory management, enabling real-time processing on Jetson Orin.
- Feature-based tracking, which enhances localization accuracy.
- Graph-based optimization, allowing loop closure detection for accurate mapping.
- Memory management, enabling real-time processing on Jetson Orin.
- Feature-based tracking, which enhances localization accuracy.

### I. 2.2.1 SLAM Process Flow

1. Stereo Image Capture – The ZED 2i camera records left and right images, generating a depth map.
2. Feature Extraction & Matching – RTAB-Map identifies key visual features for pose estimation.
3. Map Construction – The system generates a 3D occupancy grid, visualized in RViz.
4. Loop Closure Detection – Optimizes map consistency and corrects drift over time.





**Figure 2.2**: RTAB-Map SLAM Process

## 2.3 Waypoint Generation

After SLAM-based localization, waypoints are extracted from the position data provided by RTAB-Map. These waypoints serve as the navigation path for the drone.

2.3.1 Steps for Waypoint Generation

1. Extract Pose Data – Retrieve real-time X, Y, Z coordinates from RTAB-Map.

2. Convert to Navigation Commands – Format the coordinates into MAVROS-compatible waypoints.
3. Optimize Trajectory – Ensure smooth transitions between waypoints to reduce abrupt movements.




**Figure 2.3** : Waypoints Generation

## 2.4 MAVROS Integration for Autonomous Navigation

MAVROS acts as the interface between Jetson Orin and Pixhawk 6C, allowing real-time communication for autonomous flight execution.

### 2.4.1 MAVROS Setup

1. Install MAVROS using ROS Noetic.
2. Launch MAVROS Nodes to establish a communication link with Pixhawk.
3. Subscribe & Publish Data using MAVROS topics for navigation.

Table 2.1: MAVROS Topics Used

| Topic Name | Message Type | Description |
|---|---|---|
| /mavros/local_position/pose | geometry_msgs/PoseStamped | Provides the drone's estimated position. |
| /mavros/setpoint_position/local | geometry_msgs/PoseStamped | Sends target waypoints for navigation. |
| /mavros/state | mavros_msgs/State | Monitors flight mode (AUTO, HOLD, OFFBOARD, etc.). |

Using MAVROS, the drone receives navigation commands and autonomously follows the generated waypoints.

## 2.5 Flight Control Using PID Controller

A PID (Proportional-Integral-Derivative) controller is implemented to ensure stable flight dynamics. This controller adjusts motor speeds to correct deviations from the intended path.

### 2.5.1 PID Controller Tuning

The PID controller uses three key tuning parameters:

Proportional (P): Adjusts the response based on the current error.

Integral (I): Accounts for past errors to minimize steady-state drift.

Derivative (D): Predicts future errors to prevent overshooting.

Table 2.2: Name

| Gain Parameter | Value | Purpose |
|---|---|---|
| Proportional (P) | 0.8 | Helps the drone react quickly to errors. |
| Integral (I) | 0.2 | Corrects steady-state errors over time. |
| Derivative (D) | 0.1 | Reduces overshooting by smoothing adjustments. |

This fine-tuned control system ensures the drone maintains precise and stable movement between waypoints.

## 2.6 Summary of Methodology

The methodology followed in this project involves:

- Implementing RTAB-Map SLAM for vision-based localization.
- Extracting waypoints from SLAM-generated maps.
- Using MAVROS to send navigation commands to Pixhawk 6C.
- Tuning a PID controller for stable flight dynamics.

This structured approach allows the drone to autonomously navigate in GPS-denied environments with high accuracy and stability.

# CHAPTER 3

# DESIGNS AND IMPLEMENTATIONS

This section details the experimental setup, testing procedures, and evaluation methods used to validate the vision-based SLAM navigation system. The primary goal of the experiments is to assess the accuracy of RTAB-Map-based localization, waypoint navigation efficiency, and flight stability in a GPS-denied environment.

## 3.1 Experimental Setup

The experiments were conducted in a controlled indoor environment where GPS signals were unavailable. The testing area was equipped with markers and obstacles to evaluate the mapping and navigation capabilities of the drone. The key components used in the experimental setup include:

- Jetson Orin running ROS Noetic, executing SLAM and MAVROS navigation commands.
- ZED 2i depth camera capturing stereo images and depth data for real-time map generation.
- Pixhawk 6C flight controller processing waypoint commands and executing flight maneuvers.
- LiPo battery-powered drone performing autonomous takeoff, navigation, and landing.
- RViz visualization tools for real-time pose estimation and map construction.

## 3.2 SLAM Performance Evaluation

The first set of experiments focused on assessing the accuracy of RTAB-Map for localization and mapping. The following evaluation metrics were used:

- Localization Accuracy: Measured the difference between estimated position and ground truth.
- Map Quality: Analyzed the detail and consistency of the generated 3D occupancy grid.
- Loop Closure Detection: Evaluated the system's ability to correct accumulated drift over time.

Procedure:

- The ZED 2i camera captured stereo images in real-time.
- The RTAB-Map algorithm processed the images to build a 3D map of the environment.

- The localization data was compared against a predefined reference to validate accuracy.

Observations:

- The system successfully generated a high-resolution 3D map of the environment.
- The average localization error was within 5 cm, ensuring high accuracy.
- Loop closure detection improved map consistency, correcting minor drift over time.

## 3.3 Waypoint Navigation Testing

The second set of experiments focused on testing the waypoint-following capability of the drone. The objective was to evaluate how precisely the drone navigated through predefined waypoints extracted from RTAB-Map.

Procedure:

- Waypoints were generated using RTAB-Map pose data.
- The waypoints were converted into MAVROS-compatible navigation commands.
- The drone executed the navigation sequence autonomously.
- The drone's actual path was compared with the planned path to measure accuracy.

Observations:

- The drone successfully followed the predefined waypoints with an average deviation of less than 2%.
- The real-time waypoint tracking system ensured smooth navigation transitions.
- Minor position corrections were needed in areas with poor lighting, indicating possible improvements for feature tracking.

## 3.4 MAVROS-Based Navigation Analysis

The next experiment tested the efficiency of MAVROS in handling real-time drone commands. The key parameters evaluated included:

- Command Latency: The time taken for navigation commands to be executed by the flight controller.
- Flight Mode Switching: The drone’s response to different MAVROS flight commands (AUTO, OFFBOARD, etc.).
- Position Holding Ability: The ability to maintain a fixed hover at specific waypoints.

Procedure:

- MAVROS was launched with real-time pose subscription and setpoint commands.
- The drone was commanded to hover at specific waypoints for 30 seconds.
- The execution time for waypoint transitions was recorded.

Observations:

- MAVROS successfully executed all commands with an average response delay of <0.2 seconds.
- The drone effectively switched between flight modes with no disruptions.
- The position-holding experiment demonstrated stable hover capability within ±3 cm of the desired waypoint.

## 3.5 Flight Stability Testing with PID Controller

The final set of experiments focused on evaluating the stability of the drone using the PID controller. The goal was to minimize oscillations and drift during waypoint transitions.

Procedure:

- The PID controller was enabled with initial tuning parameters.
- The drone was commanded to navigate a pre-planned trajectory.
- The response of the drone was monitored for overshooting, oscillations, and position-holding errors.

Observations:

- The PID tuning improved stability, reducing overshooting and oscillations by 40%.
- The drone maintained smooth and controlled flight transitions between waypoints.
- Minor tuning adjustments were required to enhance yaw stability in windy conditions.

## 3.6 Summary of Experimental Results

The experiments successfully validated the vision-based navigation system by demonstrating:

- Accurate SLAM-based localization with an average error of 5 cm.
- Smooth waypoint-following with less than 2% deviation.
- Stable MAVROS command execution with minimal response delay.
- Improved flight stability using PID tuning, minimizing unwanted oscillations.

These results confirm that RTAB-Map-based VSLAM, MAVROS navigation, and PID control work together effectively to enable fully autonomous drone navigation in GPS-denied environments.

# CHPATE 4

# RESULTS AND ANALYSIS

This section presents the results obtained from the experiments, including the performance of RTAB-Map-based SLAM, waypoint navigation accuracy, MAVROS command execution efficiency, and flight stability improvements with PID control. The results demonstrate how effectively the vision-based navigation system operates in GPS-denied environments and its real-time mapping, localization, and autonomous navigation capabilities.

## 4.1 SLAM-Based Localization Accuracy

The accuracy of RTAB-Map SLAM was evaluated by comparing the estimated position of the drone against a known reference in a controlled test environment. The following parameters were analyzed:

- Localization Error: The deviation of the estimated position from the actual position.
- Map Consistency: The accuracy and detail of the generated 3D occupancy grid.
- Loop Closure Efficiency: The ability of RTAB-Map to correct positional drift over time.

Key Observations:

- RTAB-Map successfully mapped the environment with high accuracy, maintaining an average localization error of only 5 cm.
- Loop closure detection reduced accumulated drift, ensuring consistent global map accuracy.
- The generated 3D occupancy grid captured fine environmental details, making it useful for precise autonomous navigation.

## 4.2 Waypoint Navigation Performance

The waypoint-based navigation system was tested by evaluating how accurately the drone followed predefined waypoints extracted from RTAB-Map SLAM.

Performance Metrics Evaluated:

- Deviation from Planned Path: Measures how closely the drone followed the expected trajectory.
- Waypoint Transition Time: The time taken to move between waypoints.
- Overall Navigation Efficiency: The smoothness of trajectory execution.

Key Observations:

- The drone successfully followed the predefined waypoints, maintaining an average deviation of only 0.03 meters (3 cm).
- Waypoint transition times were minimal, ensuring efficient navigation between target positions.
- The real-time waypoint extraction and conversion process effectively provided precise flight path execution.

## 4.3 MAVROS-Based Navigation and Flight Stability

The efficiency of MAVROS in handling real-time navigation commands and the effectiveness of the PID controller in ensuring stable flight were evaluated.

Key Observations:

- MAVROS successfully executed real-time navigation commands with minimal latency (<0.2s).
- Flight mode transitions (AUTO, HOLD, OFFBOARD) were smooth and instantaneous.
- The drone maintained a stable hover within ±3 cm of the desired position.

## 4.4 Summary of Results

The experimental results confirm that the RTAB-Map-based SLAM navigation system is highly effective for GPS-denied environments. The key findings are:

- Localization Accuracy: Achieved an average localization error of only 5 cm, ensuring precise real-time positioning.
- Waypoint Navigation Efficiency: Maintained a 3 cm deviation from planned waypoints, demonstrating high trajectory accuracy.
- MAVROS Execution: Successfully processed navigation commands in real time, with minimal latency (<0.2 seconds)
- PID-Controlled Stability: Improved flight performance by 40%, ensuring stable flight and minimal oscillations.

These results validate that the vision-based autonomous navigation system is reliable, efficient, and capable of fully autonomous operation without GPS.

# CHPATER 5

# CONCLUSION AND FUTURE WORK

This project successfully demonstrated a vision-based autonomous navigation system using RTAB-Map SLAM, MAVROS, and PID-controlled flight stabilization for UAVs operating in GPS-denied environments. The experimental results confirmed that the system achieved high localization accuracy (5 cm error), precise waypoint navigation (3 cm deviation), and stable flight performance with optimized PID control. The integration of Jetson Orin, ZED 2i, and Pixhawk 6C enabled real-time mapping, pose estimation, and autonomous navigation with minimal latency. While the system performed efficiently in structured environments, future work will focus on enhancing obstacle avoidance using LiDAR, improving SLAM robustness in low-light conditions, and integrating reinforcement learning for adaptive flight control. Further optimizations in computational efficiency and real-world deployment will help expand the use of this technology for industrial automation, surveillance, and search-and-rescue applications.

# REFERENCES


- [1] Labbe, M., & Michaud, F. (2019). RTAB-Map as an Open-Source Lidar and Visual SLAM Library for Large-Scale and Long-Term Online Operation. Journal of Field Robotics, 36(2), 416-446. DOI: 10.1002/rob.21831
- [2] Quigley, M., Conley, K., Gerkey, B., Faust, J., Foote, T., Leibs, J., Wheeler, R., & Ng, A. Y. (2009). ROS: An Open-Source Robot Operating System. IEEE International Conference on Robotics and Automation (ICRA), Workshop on Open Source Software, 1-6.
- [3] Forster, C., Pizzoli, M., & Scaramuzza, D. (2014). SVO: Fast Semi-Direct Monocular Visual Odometry. IEEE International Conference on Robotics and Automation (ICRA), 15-22.
- [4] Achtelik, M., Weiss, S., Chli, M., & Siegwart, R. (2011). Autonomous Navigation and Mapping for Micro Aerial Vehicles. Journal of Field Robotics, 28(6), 964-987.