Hex Inverted Buffers with Open-Collector Outputs



ORDERING INFORMATION
SL74LS06N Plastic
SL74LS06D SOIC
T_A = 0° to 70° C for all packages

This device contains hex inverted buffers with open-collector. It performs the Boolean function $Y=\overline{A}$ in positive Logic.

- High Output Voltage (30 V)
- High Speed (t_{PD} = 8.5 ns typical)
- Low Power Dissipation (P_D = 18 mW per Gate)

LOGIC DIAGRAM



PIN 14 =V_{CC}
PIN 7 = GND

PIN ASSIGNMENT



FUNCTION TABLE

Inputs	Output
A	Y
H	L
L	H

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
V_{CC}	Supply Voltage	7.0	V
V_{IN}	Input Voltage	5.5	V
V_{OUT}	Output Voltage	30	V
Tstg	Storage Temperature Range	-65 to +150	°C

*Maximum Ratings are those values beyond which damage to the device may occur.
Functional operation should be restricted to the Recommended Operating Conditions.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
V_{CC}	Supply Voltage	4.75	5.25	V
V_{IH}	High Level Input Voltage	2.0		V
V_{IL}	Low Level Input Voltage		0.8	V
V_{OH}	High Level Output Voltage		30	V
I_{OL}	Low Level Output Current		40	mA
T_A	Ambient Temperature Range	0	+70	°C

DC ELECTRICAL CHARACTERISTICS over full operating conditions

Symbol	Parameter	Test Conditions		Guaranteed Limit		Unit
				Min	Max	
V_{IK}	Input Clamp Voltage	V_{CC} = min, I_{IN} = -18 mA			-1.5	V
I_{OH}	High Level Output Current	V_{CC} = min, V_{OH}= max			250	µA
V_{OL}	Low Level Output Voltage	V_{CC} = min, I_{OL} = 16 mA			0.4	V
		V_{CC} = min, I_{OL} = 40 mA			0.7	
I_{IH}	High Level Input Current	V_{CC} = max, V_{IN} = 2.7 V			20	µA
		V_{CC} = max, V_{IN} = 5.5 V			1	mA
I_{IL}	Low Level Input Current	V_{CC} = max, V_{IN} = 0.4 V			-0.2	mA
I_{CC}	Supply Current	V_{CC} = max	Total with outputs high		18	mA
			Total with outputs low		60	

AC ELECTRICAL CHARACTERISTICS (T_A = 25°C, V_{CC} = 5.0 V, C_L = 15 pF, R_L = 110 Ω, t_r = 15 ns, t_f = 6.0 ns)

Symbol	Parameter	Min	Max	Unit
t_{PLH}	Propagation Delay, Input A to Output Y		15	ns
t_{PHL}	Propagation Delay, Input A to Output Y		20	ns



Figure 1. Switching Waveforms



NOTE A. C_L includes probe and jig capacitance.

Figure 2. Test Circuit