

Useful HTML tags and their attributes

< B > Body tag and attributes

<BODY>...</BODY>	Contains the viewed portion of the document
<BODY bgcolor="color">	Sets the color of the background in hexadecimal code
<BODY background="filename.xxx">	Sets an image as a page's background (wallpaper)
<BODY text="color">	Specifies the color of normal text in hexadecimal code
<BODY link="color">	Specifies the default color of unvisited links in hexadecimal code
<BODY alink="color">	Specifies the color of links on click in hexadecimal code
<BODY vlink="color">	Specifies the color of followed links in hexadecimal code

< F > Font tag and attributes

...	Changes font attributes for text within the tags
...	Sets the font to a size from 1 to 7, with 1 the smallest and 7 the largest
...	Sets the font face
...	Sets the font color using hexadecimal code

< I > Image tag and attributes

	Embeds an image in the document at the location of the tag
	Adds an image with a text description
	Aligns an image to the left, right, center, bottom, or top
	Sets the size of the border around an image
	Sets the height of an image
	Sets the width of an image
	Sets a horizontal margin to be placed around an image
	Sets a vertical margin to be placed around an image
	Designates an image as a client-side image map

< A > Anchor tag and attributes

<A>...	Designates the origin and destination of a hyperlink
...	Creates a hyperlink
...	Links to a target location in the current page
...	Links to a target location in a page outside your site
...	Sets a target location within a document
...	Creates a mailto link
Optional Attributes	
...	Specifies where the linked-to document is to be placed
...	Sets up a relationship between the linked-to document and the current page
...	Sets up a reverse relationship between the current page and the linked-to document

<T> Table tag and attributes

<TABLE>...</TABLE>	Generates a table
<TABLE border="pixels">	Sets the size of cell borders
<TABLE cellspacing="pixels">	Sets the amount of space between cells
<TABLE cellpadding="pixels">	Sets the amount of space between a border and cell content
<TABLE height="pixels" or "%">	Sets the height of a table
<TABLE width="pixels" or "%">	Sets the width of a table
<TD>...</TD>	Defines a table data cell
<TD colspan="columns">	Sets a cell to span columns
<TD rowspan="rows">	Sets a cell to span rows
<TD nowrap>	Prevents the lines within a cell from wrapping
<TH>...</TH>	Defines a table header with bold, centered table data
<TR>...</TR>	Defines a table row
<TR align="?"> or <TD align="?">	Aligns the contents of a row or cell to the left, right, or center
<TR valign="?"> or <TD valign="?">	Sets the vertical alignment of a row or cell to the top, middle, or bottom

<FR> Frame tag and attributes

<FRAMESET>...</FRAMESET>	Specifies the layout of subsections in the main browser window
<FRAMESET rows="value,value">	Defines the rows within a frameset
<FRAMESET cols="value,value">	Defines the columns within a frameset
<NOFRAMES>...</NOFRAMES>	Provides alternate content for browsers that do not support frames
<FRAME src="?">	Defines the appearance and content of a single frame
<FRAME name="name">	Labels the frame for targeting by other frames
<FRAME marginwidth="#">	Sets the margin width of a frame
<FRAME marginheight="#">	Sets the margin height of a frame
<FRAME scrolling="value">	Creates a frame scrollbar
<FRAME noresize>	Prevents the resizing of a frame

<FO> Form tag and attributes

<FORM>...</FORM>	Generates a container for all form elements
<FORM action="url">	Designates the path of the script to process input from the form
<FORM method="get post">	Instructs the browser how to interact with the form URL
<FORM accept="media type">	Defines which MIME types are supported by the server processing the form
<FORM accept-charset="text">	Defines which character sets are supported by the server processing the form
<FORM enctype="media type">	Defines the format of the submitted data
<OPTION>	Defines each menu item
<SELECT name="NAME">...</SELECT>	Generates a pull-down menu
<INPUT type="checkbox">	Generates a check box
<INPUT type="hidden">	Conceals a field from view
<INPUT type="image">	Generates an image that acts like a Submit button
<INPUT type="password">	Generates a one-line password box
<INPUT type="radio">	Generates a radio button
<INPUT type="text">	Generates a one-line text box
<INPUT type="submit">	Generates a Submit button (send form)
<INPUT type="reset">	Generates a Reset button (clear form)