

Features

- ◆ Strong corrosion resistance;
- ◆ Resistant to various solvents, acids and bases;
- ◆ High temperature resistance, excellent flame retardancy, no molten drops by fire;
- ◆ Resistance to fracture, no fibers loss;
- ◆ Can be made into panel filter.

Application

- ◆ It is mainly used for primary filtration in ventilation equipment, dust removal equipment and air supply systems in various high temperature and fireproof environments.

Technical parameters

Main material	Special flame retardant synthetic fibers	Flame retardant grade	Class3(JACA No.11A-2003)
Filtration Class	G2、G3、G4(EN779)	Smoke density Oxygen index	200(TB/3237)
Average weighting efficiency	90%(ASHRAE52.1-1992)	Oxygen index	≥32(TB/3237)
Filter object	Coarse dust and foreign matter ≥5 μm	Humidity resistance (relative humidity)	≤100%RH

Specification

Model	Size	Thickness (mm)	Weight (g/m ²)	Dust holding capacity (g/m ²)	Rated Air velocity (m/s)	Rated air flow (m ³ /h)	Temperature resistance (°C)	I.N.P (Pa)	F.N.P (Pa)
RT-HT180	1.6m*20m	10	250	450	1	3600	<180	25	250
RT-HT240	500mm*500mm	20	450	600	1	3600	<240	45	250
	800mm*800mm	20	450	600	1	3600	<240	45	250