

V-Type Paint Filter Paper



Features

- ◆ Whirlpool airflow guide design, high filtering efficiency;
- ◆ V-shaped depth bearing, high dust holding capacity and low pressure;
- ◆ Simple installation;
- ◆ Simply recycle paint particles and dust particles;
- ◆ Reproducible paper, environmental and high efficiency;
- ◆ Long service life and low replacement frequency.

Application

- ◆ It is used in the discharge and filtration of paint mist or industrial oil mist in painting systems.

Technical parameters

Main material	Excellent double layer kraft paper	Filter object	Paint particles and dust particles
Stretch folding distance	50mm	Flame retardant grade	F1(DIN 53438)
Aperture	25mm	Temperature resistance	≤80°C
Pitch-row	20mm	Temp. short peak	100°C

Specifications

Model	Length (m)	Width (m)	Thickness (mm)	Rated air velocity (m/s)	Work time (h)	EFF.	Adsorptivity ability (kg/m ²)	Remark
RT-V60	10	0.75/0.9/1/1.2	60	0.5-1	240-250	85%	13	Without Synthetic
RT-V65	10	1.25	65	0.5-1	240-250	85%	13	Without Synthetic
RT-VS60	10	0.75/0.9/1/1.2	60	0.5-1	240-250	93%	16	With Synthetic
RT-VS65	10	1.25	65	0.5-1	240-250	93%	16	With Synthetic
RT-VP60	10	0.75/0.9/1/1.2	60	0.5-1	180-220	93%	18	Paper Tape
RT-VF65	10	1.25	65	0.7-1.4	180-220	93%	27	Flame Retardant

Note: other specification can be customized according to requirements.

Schematic of Inert Separation:

