



Application

Suitable for pre-filtration of various ventilation systems, air-conditioning systems and dust removal systems.

Feartures

- Resistant to fracture, high elasticity
- Step by step encryption of filter fibres and stratified filtration
- Large dust holding capacity and stable performance
- Long using life
- Silicone free
- Available to supply in cut pad or rolls
- Washable.

Technical Parameters

Main material	Polyester fiber (PET)	Flammability rating	F1 (DIN 53438)/B1 (GB/T 17591-2006)
Filtration class	G2, G3, G4 (EN779)	Dust holding capacity	300g/m², 400g/m², 500g/m², 600g/m²
Filter object	Coarse dust and foreign matter ≥5 μm	Temperature resistance	100°C
Final resistance	250 Pa (Suggestion)	Temp. short peak	120°C
Average weight efficiency	95% (ASHRAE52.1-1992)	Humidity resistance	100%

Specifications

Model	Filtration class	Thickness (mm)	Weight (g/m²)	I.N.P (Pa)	Rated air velocity (m/s)	Rated air flow (m³/h)
RT-C05	G2	5	120	15	1,5	5400
RT-C10	G3	10	150	18	1,5	5400
RT-C15	G4	15	180	22	1,5	5400
RT-C18	G4	18	200	25	1,5	5400
RT-C20	G4	20	220	28	1,5	5400
RT-C22	G4	22	250	30	1,5	5400