



Application

It is mainly used for primary filtration in ventilation equipment, dust removal equipment and air supply systems in various high temperature and fireproof environments.

Feartures

- Strong corrosion resistance
- Resistant to various solvents, acids and bases
- High temperature resistance, excellent flame retardant, no molten drops by fire
- Resistance to fracture, no fibres loss
- Can be made into panel filter.

Technical Parameters

Main material	Special flame retardant synthetic fibers	Flame retardant grade	Class3(JACA No.11A-2003)
Filtration class	G2、 G3.G4(EN779	Smoke density Oxygen index	200(TB/3237)
Average weighting efficiency	90%(ASHRAE52.1-1992)	Oxygen index	≥32(TB/3237)
Filter object	Coarse dust and foreign matter ≥5μm	Humidity resistance (relative humidity)	<100%RH

Specifications

Model	Size	I.N.P (Pa)	F.N.P (Pa)	Thickness (mm)	Weight (g/m²)	Dust holding capacity (g/m²)	Rated air velocity (m/s)	Rated air flow (m³/h)	Temperature resistance (°C)
RT-HT180	1.6m*20m	25	250	10	250	450	1	3600	<180
RT-HT240	500mm*500mm	45	250	20	450	600	1	3600	<240
RT-HT240	800mm*800mm	45	250	20	450	600	1	3600	<240