



Specifications

Model	Size (mm)	Rated airflow (m³/h)	I.N.P (Pa)	F.N.P (Pa)	Filter object (µm)	EFF. (%)	Filtration Class	Filter area (m²)
RT-DP2805-10	305*610*292	900/1300	<100/130	<350/500	0,3	85≤E<95	E10	9,55
RT-DP8805-10	610*610*292	1800/2600	<100/130	<350/500	0,3	85≤E<95	E10	17,9
RT-DPB005-10	1220*610*292	3400/4800	<100/130	<350/500	0,3	85≤E<95	E10	35,21
RT-DPB005-10	1220*915*292	4200/6800	<100/130	<350/500	0,3	85≤E<95	E10	52,99
RT-DP2805-11	305*610*292	900/1300	<120/150	<350/500	0,3	95≤E<99.5	E11	9,55
RT-DP8805-11	610*610*292	1800/2600	<120/150	<350/500	0,3	95≤E<99.5	E11	17,9
RT-DPB005-11	1220*610*292	3400/4800	<120/150	<350/500	0,3	95≤E<99.5	E11	35,21
RT-DPB005-11	1220*915*292	4200/6800	<120/150	<350/500	0,3	95≤E<99.5	E11	52,99
RT-DP2805-12	305*610*292	900/1300	<140/170	<350/500	0,3	99.5≤E<99.95	E12	9,55
RT-DP8805-12	610*610*292	1800/2600	<140/170	<350/500	0,3	99.5≤E<99.95	E12	17,9
RT-DPB005-12	1220*610*292	3400/4800	<140/170	<350/500	0,3	99.5≤E<99.95	E12	35,21
RT-DPB005-12	1220*915*292	4200/6800	<140/170	<350/500	0,3	99.5≤E<99.95	E12	52,99
RT-DP2805-13	305*610*292	900/1300	<180/220	<350/500	0,3	99.95≤E<99.995	H13	9,55
RT-DP8805-13	610*610*292	1800/2600	<180/220	<350/500	0,3	99.95≤E<99.995	H13	17,9
RT-DPB005-13	1220*610*292	3400/4800	<180/220	<350/500	0,3	99.95≤E<99.995	H13	35,21
RT-DPB005-13	1220*915*292	4200/6800	<180/220	<350/500	0,3	99.95≤E<99.995	H13	52,99
RT-DP2805-14	305*610*292	900/1300	<200/240	<350/500	0,3	99.995≤E<99.9995	H14	9,55
RT-DP8805-14	610*610*292	1800/2600	<200/240	<350/500	0,3	99.995≤E<99.9995	H14	17,9
RT-DPB005-14	1220*610*292	3400/4800	<200/240	<350/500	0,3	99.995≤E<99.9995	H14	35,21
RT-DPB005-14	1220*915*292	4200/6800	<200/240	<350/500	0,3	99.995≤E<99.9995	H14	52,99

Three Dimensional View

