





Change History

Changes between document issues are cumulative. The latest document issue contains all the changes made in earlier issues.

Issue 13 (2016-04-28)

This issue is the thirteenth official release, and includes the following changes:

Update the **namedParameters** field in the request Header for **balanceUpdate** in 5.1 **balanceUpdate**.

Issue 12 (2016-01-28)

This issue is the twelfth official release, and includes the following changes:

Add the **namedParameters** field in the request Header for **balanceUpdate** in 5.1 **balanceUpdate**.

Issue 11 (2015-11-20)

This issue is the eleventh official release, and includes the following changes:

Password encryption algorithm supports SHA256.

Issue 10 (2015-06-18)

This issue is the tenth official release, and includes the following changes:

Update the description of **enduserDAAccountId** in **getBalance** message header.

Issue 09 (2014-12-05)

This issue is the ninth official release, and includes the following changes:

Add the fields **faultcode** and **faultstring** for Service Error and Policy Error.

Issue 08 (2014-05-19)

This issue is the eighth official release, and includes the following changes:

Update Chapter 3.1 for changing fields in **getBalance** message header parameters and **getBalanceResponse** message.

Issue 07 (2014-05-04)

This issue is the seventh official release, and includes the following changes:

Change the description of **serviceld** and **bundleId**.

Issue 06 (2014-02-15)

This issue is the sixth official release, and includes the following changes:

Add the fields **endUserDAAccountId**, **extensionInfo**, **expiryDate**, and **description** for **getBalance**.

Issue 05 (2013-12-23)

This issue is the fifth official release, and includes the following changes:

Add the fake ID function in Phase2.3 version.

To use the fake ID function, SPs must modify their systems to change all mobile numbers involved in old and new services to fake IDs so that numbers sent by the SP systems to the SDP are all fake IDs. The SDP converts the received fake IDs to mobile numbers for service processing.

SPs must obtain the mapping between mobile numbers involved in old services and fake IDs from the MTN carrier.



Change History

If SPs still use mobile numbers when the fake ID function is enabled, service processing will fail.

Issue 04 (2013-11-19)

This issue is the fourth official release, and includes the following changes:

Add the Appendix including details about currency, atomic charging unit, ISO 4217 codes and OpCoID list.

Issue 03 (2013-09-22)

This issue is the third official release, and includes the following changes:

Change the format from the Huawei style to MTN style.

Issue 02 (2013-08-05)

This issue is the second official release, and includes the following changes:

Update Chapter 3 ,4 ,5 for adding **bundleID** field.

Issue 01 (2013-06-22)

This issue is the first official release.



Contents

1 Overview	1
1.1 Scenario	1
1.1.1 Obtaining Account Balance Information	1
1.1.2 Querying the Expiration Date for the Balance	2
1.1.3 Recharging using direct payment	3
1.1.4 Recharging using a voucher	3
1.1.5 Querying Users' Operation Records	4
1.1.6 Querying Users' Balance Types	5
1.2 Interface List	6
2 Error Definition	8
2.1 Service Error	8
2.2 Policy Error	9
3 Obtaining Account Balance Information	11
3.1 getBalance	11
4 Querying the Expiration Date for the Balance	22
4.1 getCreditExpiryDate	22
5 Recharging using direct payment	32
5.1 balanceUpdate	32
6 Recharging using a voucher	43
6.1 voucherUpdate	43
7 Querying Users' Operation Records	52
7.1 getHistory	52
8 Querying Users' Balance Types	62
8.1 getBalanceTypes	62
9 Appendix	71
9.1 The Currency and Atomic Charging Unit of each OpCo country	71
9.2 ISO 4217 Codes for the representation of currencies and funds	72
9.3 OpCoID List	72

01

Overview

1.1 Scenario

Pre-paid subscribers, whether they have subscribed to pre-paid telephony, SMS, or data service, have credits with their service providers; the consumption of services will lead to reduction of their credit, or the credit may expire. Therefore, from time to time, subscribers may have to recharge their accounts. This occurs through an application that interfaces with the subscriber either directly or indirectly. Examples of direct interaction are voice prompts and WAP/web pages, or even SMS. Typically, such multi-modal applications either request a currency amount and, e.g. credit card information, or a voucher number plus credentials. The voucher number and credentials are then validated and causes a pre-determined currency amount to be transferred. The Parlay X Account Management API described in the present document supports account querying, direct recharging and recharging through vouchers. As a side effect, it may prevent subscribers from having their account balance credits expire.

1.1.1 Obtaining Account Balance Information

Introduction

Partner invokes SDP's API `getBalance` to send the request for obtaining the subscriber's account balance.


Obtaining Account Balance Information

Figure 1-1 shows the process for a Partner to get the account balance.



1 Overview

Figure 1-1 Obtaining Account Balance Information



The process is as follows:

1. Partner invokes SDP's API `getBalance` to send the request for obtaining the subscriber's account balance.
2. SDP returns the result to the Partner.

1.1.2 Querying the Expiration Date for the Balance

Introduction

Partner invokes the SDP's `getCreditExpiryDate` API to obtain the account balance expiration date.

Querying the Expiration Date for the Balance

Figure 1-2 shows the process for a Partner to obtain the account balance expiration date.

Figure 1-2 Querying the Expiration Date for the Balance





1 Overview

The process is as follows:

1. Partner invokes the getCreditExpiryDate API to send a request to SDP querying the account balance expiration date.
2. SDP returns the result to Partner.

1.1.3 Recharging using direct payment


Introduction

Partner invokes the SDP's balanceUpdate API to recharge using direct payment.

Recharging Using Direct Payment

Figure 1-3 shows the process of recharging using direct payment.

Figure 1-3 Recharging Using Direct Payment



The process is as follows:

1. Partner invokes the balanceUpdate API to send a request of recharging using direct payment for a subscriber.
2. SDP returns the result to Partner.

1.1.4 Recharging using a voucher

Introduction

Partners invoke the voucherUpdate interface provided by the SDP to recharge users' accounts using a voucher.




1 Overview

Recharging Using a Voucher

Figure 1-4 shows the process of recharging using a voucher.

Figure 1-4 Recharging Using a Voucher



The process is as follows:

1. Partner invokes the voucherUpdate API to send a request of recharging using a voucher for a subscriber
2. SDP returns the result to Partner.

1.1.5 Querying Users' Operation Records

Introduction

Partner invokes the SDP's getHistory API to query the history records of a subscriber's account.


Querying Users' Operation Records

Figure 1-5 shows the process of querying the history records of a subscriber's account.



1 Overview

Figure 1-5 Querying Users' Operation Records



The process is as follows:

1. Partner invokes the getHistory API to send a request of querying the history records of a subscriber's account.
2. SDP returns the result to Partner.

1.1.6 Querying Users' Balance Types

Introduction


The partner invokes the getBalanceTypes interface provided by the SDP to query users' balance types.

Querying Users' Balance Types

Figure 1-6 shows the process of querying users' balance types.



1 Overview

Figure 1-6 Querying Users' Balance Types

The process is as follows:

1. The partner uses the getBalanceTypes interface to send a request to the SDP to query a user's balance type.
2. The SDP sends the result to the partner.

1.2 Interface List

This topic describes Account Management capability interfaces provided by the SDP. Table 1-1 lists the Account Management capability interfaces provided by the SDP.

Table 1-1 Account Management Parlay X 3.0 Interface List

Function	Interface	Description
Obtaining account balance information	getBalance	The SDP functions as the server and provides the interface for partners. The interface is used to get the balance of a subscriber's account.
Querying the expiration date for the balance	getCreditExpiryDate	The SDP functions as the server and provides the interface for partners. The interface is used to query the expiration date for the balance.
Recharging using direct payment	balanceUpdate	The SDP functions as the server and provides the interface for partners. The interface is used to recharge for a subscriber using direct payment.
Recharging using a voucher	voucherUpdate	The SDP functions as the server and provides the interface for partners. The interface is used to recharge for a subscriber using a voucher.



1 Overview

Function	Interface	Description
Querying users' operation records	getHistory	The SDP functions as the server and provides the interface for partners. The interface is used to query the operation records of a subscriber's account.
Querying users' balance types	getBalanceTypes	The SDP functions as the server and provides the interface for partners. The interface is used to query users' balance types.

02

Error Definition

2.1 Service Error

A service error is an error caused by service interfaces.

Table 2-1 defines the fields in a service error response sent by the server to the client.

Table 2-1 Service error fields

Parameter	Type	Mandatory or Optional	Description
faultcode	xsd:string	Mandatory	Result code. [Format] SVCABCD In the format, SVC identifies a service error response, and ABCD is a number ranging from 0001 to 9999. [Example] SVC0001
faultstring	xsd:string	Mandatory	Error description. The value can contain the variable %# in definition. When sending a response, the server replaces the variable %# with the value of variables . [Example] Waiting for response timed out, message type is OutwardGetLocReq.
messageId	xsd:string	M	ID of an error message. The value is a character string starting with SVC . [Format] SVCABCD <ul style="list-style-type: none">• SVC indicates that the message is an error message.• ABCD is a number ranging from 0001 to 9999.



2 Error Definition

text	xsd:string	M	Error message description, which can contain the variables % and #.
variables	xsd:string [0..unbounded]	O	Values of the variables used in the text value.

2.2 Policy Error

A policy error indicates an error reported by the server because of SLA violation.

Table 2-2 defines the fields in a policy error response sent by the server to the client.

Table 2-2 Policy error fields

Parameter	Type	Mandatory or Optional	Description
faultcode	xsd:string	Mandatory	Result code. [Format] POLABCD In the format, POL identifies a policy error response, and <i>ABCD</i> is a number ranging from 0001 to 9999. [Example] POL0006
faultstring	xsd:string	Mandatory	Error description. The value can contain the variable %# in definition. When sending a response, the server replaces the variable %# with the value of variables . [Example] GroupAddr is not supported
messageId	xsd:string	M	ID of an error message. The value is a character string starting with POL . [Format] POL[ABCD] <ul style="list-style-type: none"> POL indicates that the message is an error message. ABCD is a number ranging from 0001 to 9999.
text	xsd:string	M	Error message description, which can contain the variables % and #.



2 Error Definition

variables	xsd:string [0..unbounded]	O	Values of the variables used in the text value.
-----------	------------------------------	---	--

03

Obtaining Account Balance Information

3.1 getBalance

The SDP functions as the server and provides the interface for partners. Partners use it to get the balance of a subscriber's account.

Request URI

http://IP:Port/AccountManagementService/services/AccountManagement/v3

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 3-1 describes the parameters in the message header of the getBalance interface.

Table 3-1 getBalance message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>



3 Obtaining Account Balance Information

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> • SHA-256: spPassword = Base64(SHA-256(spld + Password + timeStamp)) • MD5: spPassword = MD5(spld + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> • spld and timeStamp: authentication ID and timestamp. • Password: password for partners to access the SDP. <ul style="list-style-type: none"> – For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. – For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE</p> <p>To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example]</p> <p>e6434ef249df55c7a21a0b45758a39bb</p>



3 Obtaining Account Balance Information

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The serviceId must be contained during invocation of a service interface developed by service partners and other partners, and must not be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



3 Obtaining Account Balance Information

Parameter	Type	Mandatory or Optional	Description
bundleID	xsd:string	O	<p>Bundle ID.</p> <p>When SDP creates a capability bundle, SDP allocates a bundleID to capability bundle.</p> <p>The bundleID must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p> NOTE</p> <ul style="list-style-type: none"> When an API partner invokes the getbalance interface, this parameter is mandatory. The bundleID is allocated only after an API product bundle is released. Therefore, ensure that the corresponding product bundle has been released on the SDP management portal before using the interface. <p>[Example] 256000039</p>
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator.</p> <p>[Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639



3 Obtaining Account Balance Information

Parameter	Type	Mandatory or Optional	Description
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <p>• Fake ID: Prefix-opcoid-sequence [Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserDAAccountid	xsd:int (1 to 2147483647)	O	<p>Contain the Specific DA Account identifier.</p> <p>If endUserDAAccountid is NOT provided, SDP will return main balance ONLY.</p> <p>If endUserDAAccountid is provided and NOT 0, SDP will return main balance and ONE dedicatedAccount Information specified in the request.</p> <p>If endUserDAAccountid provided is 0, SDP will return main balance and ALL dedicatedAccounts belonging to the subscriber.</p>

getBalanceRequest

Table 3-2 describes the input parameters in the **getBalanceRequest** message.



3 Obtaining Account Balance Information

Table 3-2 getBalanceRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	<p>Contains the end user's credentials for authorizing access to the account. [Example]</p> <p>1212</p>

getBalanceResponse

Table 3-3 describes the parameters in the **getBalanceResponse** message.

Table 3-3 getBalanceResponse parameters

Parameter	Type	Description
result	Balance [1...unbounded]	<p>It is a set of Balance records, where each record specifies a balance type and the associated amount.</p> <p>For the error codes, see Table 3-4.</p>

Table 3-4 Balance parameters

Parameter	Type	Description
accountID	xsd:string	<p>ID of the returned balance. 0 for Main Account. Dedicated AccountID for DA Account.</p>
balanceType	xsd:string	<p>Identifies the type of balance. A user account may have multiple types of balances for different usage, for example, voice, SMS, and game</p>



3 Obtaining Account Balance Information

Parameter	Type	Description
		services.
amount	xsd:decimal	Amount of balance.
expiryDate	xsd:dateTime	Expiry Date of the account.
description	xsd:string	Description of the account.
extensionInfo	NamedParameterList	Extended parameter.

Table 3-5 NamedParameter

Parameter	Mandatory/ Optional	Type	Description
key	M	String	Name of the extended parameter.
value	M	String	Value of the extended parameter.

Table 3-6 NamedParameterList

Parameter	Mandatory/ Optional	Type	Description
NamedParameters	Optional	NamedParameter[]	List of extended parameters.

Error Code

Table 3-7 describes the error codes that the SDP may return.

Table 3-7 getBalance error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.
SVC0901	SPID is null!	The spId value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spId value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.



3 Obtaining Account Balance Information

Error Code	Description	Cause
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spid in the request header does not exist in the SDP.



3 Obtaining Account Balance Information

Error Code	Description	Cause
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp's status is pause.	The Partner is in the paused state.
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of getBalance messages in typical scenarios are as follows:

- When a service partner sends the request message:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:serviceId>35000001000119</tns:serviceId>
      <tns:OA>8613900000001</tns:OA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
</soapenv:Envelope>
```



3 Obtaining Account Balance Information

```
<tns:FA>8613900000001</tns:FA>
</tns:RequestSOAPHeader>
</soapenv:Header>
<soapenv:Body>
  <loc:getBalance>
    <loc:endUserIdentifier>8613812345678</loc:endUserIdentifier>
    <loc:endUserPin>1212</loc:endUserPin>
  </loc:getBalance>
</soapenv:Body>
</soapenv:Envelope>
```

- When an API partner sends the request message:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:bundleID>256000039</tns:bundleID>
      <tns:OA>8613900000001</tns:OA>
      <tns:FA>8613900000001</tns:FA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
  <soapenv:Body>
    <loc:getBalance>
      <loc:endUserIdentifier>8613812345678</loc:endUserIdentifier>
      <loc:endUserPin>1212</loc:endUserPin>
    </loc:getBalance>
  </soapenv:Body>
</soapenv:Envelope>
```

- The following is an example of the response:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getBalanceResponse
xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
      <ns1:result>
        <accountID>0</accountID>
        <balanceType>SMS</balanceType>
        <amount>600</amount>
        <expiryDate>2004-02-15T02:44:14</expiryDate>
        <description>temperat iras</description>
        <extensionInfo>
          <item>
            <key>turbine corripuit</key>
            <value>regemque dedit</value>
```




3 Obtaining Account Balance Information

```
</item>
</extensionInfo>
</ns1:result>
</ns1:getBalanceResponse>
</soapenv:Body>
</soapenv:Envelope>
```

04

Querying the Expiration Date for the Balance

4.1 *getCreditExpiryDate*

The SDP functions as the server and provides the interface for partners. Partners use it to get the account balance expiration date.

Request URI

`http://IP:Port/AccountManagementService/services/AccountManagement/v3`

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 4-1 describes the parameters in the message header of the *getCreditExpiryDate* interface.



4 Querying the Expiration Date for the Balance

Table 4-1 getCreditExpiryDate message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, set the authentication mode and password during registration. If the password is forgotten, contact the carrier to retrieve the password.• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>




4 Querying the Expiration Date for the Balance

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> SHA-256: spPassword = Base64(SHA-256(spId + Password + timeStamp)) MD5: spPassword = MD5(spId + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> spId and timeStamp: authentication ID and timestamp. Password: password for partners to access the SDP. <ul style="list-style-type: none"> For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example] e6434ef249df55c7a21a0b45758a39bb</p>



4 Querying the Expiration Date for the Balance

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The serviceId must be contained during invocation of a service interface developed by service partners and other partners, and must not be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



4 Querying the Expiration Date for the Balance

Parameter	Type	Mandatory or Optional	Description
bundleID	xsd:string	O	<p>Bundle ID.</p> <p>When SDP creates a capability bundle, SDP allocates a bundleID to capability bundle.</p> <p>The bundleID must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p> NOTE</p> <ul style="list-style-type: none"> When an API partner invokes the getCreditExpiryDate interface, this parameter is mandatory. The bundleID is allocated only after an API product bundle is released. Therefore, ensure that the corresponding product bundle has been released on the SDP management portal before using the interface. <p>[Example] 256000039</p>
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator.</p> <p>[Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639



4 Querying the Expiration Date for the Balance

Parameter	Type	Mandatory or Optional	Description
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639

getCreditExpiryDateRequest

Table 4-2 describes the input parameters in the **getCreditExpiryDateRequest** message.

Table 4-2 getCreditExpiryDateRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	<p>Contains the end user's credentials for authorizing access to the account. [Example]</p> <p>1212</p>



4 Querying the Expiration Date for the Balance

getCreditExpiryDateResponse

Table 4-3 describes the parameters in the **getBalanceResponse** message.

Table 4-3 getCreditExpiryDateResponse parameters

Parameter	Type	Description
result	BalanceExpireDetails [1...unbounded]	It is a BalanceExpireDetails array that consists of types with a string and a date field. i.e. Balance type and date balance will expire respectively. For the error codes, see Table 4-4.

Table 4-4 BalanceExpireDetails parameters

Parameter	Type	Description
balanceType	xsd:string	Identifies the type of balance. End user accounts may have one or more balances for different types of usage (e.g. Voice, SMS, gaming etc)
date	xsd:dateTime	It is the date the identified balance will expire. Do not specify if the balance does not expire

Error Code

Table 4-5 describes the error codes that the SDP may return.

Table 4-5 getCreditExpiryDate error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.
SVC0901	SPID is null!	The spId value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spId value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.



4 Querying the Expiration Date for the Balance

Error Code	Description	Cause
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spId in the request header does not exist in the SDP.
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.



4 Querying the Expiration Date for the Balance

Error Code	Description	Cause
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp 's status is pause.	The Partner is in the paused state.
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of getCreditExpiryDate messages in typical scenarios are as follows:

- When a service partner sends the request message:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:serviceId>35000001000119</tns:serviceId>
      <tns:OA>8613900000001</tns:OA>
      <tns:FA>8613900000001</tns:FA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
  <soapenv:Body>
    <loc:getCreditExpiryDate>
      <loc:endUserIdentifier>8613812345678</loc:endUserIdentifier>
    </loc:getCreditExpiryDate>
  </soapenv:Body>
</soapenv:Envelope>
```



4 Querying the Expiration Date for the Balance

```
<loc:endUserPin>1212</loc:endUserPin>
</loc:getCreditExpiryDate>
</soapenv:Body>
</soapenv:Envelope>
```

- When an API partner sends the request message:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:OA>8613900000001</tns:OA>
      <tns:FA>8613900000001</tns:FA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
  <soapenv:Body>
    <loc:getCreditExpiryDate>
      <loc:endUserIdentifier>8613812345678</loc:endUserIdentifier>
      <loc:endUserPin>1212</loc:endUserPin>
    </loc:getCreditExpiryDate>
  </soapenv:Body>
</soapenv:Envelope>
```

- The following is an example of the response:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getCreditExpiryDateResponse
xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v2_2/local">
      <ns1:result>
        <balanceType>SMS</balanceType>
        <date>20130101T02:29:03+0000</date>
      </ns1:result>
    </ns1:getCreditExpiryDateResponse>
  </soapenv:Body>
</soapenv:Envelope>
```

05

Recharging using direct payment

5.1 *balanceUpdate*

The SDP functions as the server and provides the interface for partners. Partners use it to recharge using direct payment.

Request URI

`http://IP:Port/AccountManagementService/services/AccountManagement/v3`

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 5-1 describes the parameters in the message header of the *balanceUpdate* interface.



5 Recharging using direct payment

Table 5-1 balanceUpdate message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, set the authentication mode and password during registration. If the password is forgotten, contact the carrier to retrieve the password.• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>




5 Recharging using direct payment

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> SHA-256: spPassword = Base64(SHA-256(spId + Password + timeStamp)) MD5: spPassword = MD5(spId + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> spId and timeStamp: authentication ID and timestamp. Password: password for partners to access the SDP. <ul style="list-style-type: none"> For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE</p> <p>To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example]</p> <p>e6434ef249df55c7a21a0b45758a39bb</p>



5 Recharging using direct payment

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The bundleId must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



5 Recharging using direct payment

Parameter	Type	Mandatory or Optional	Description
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
namedParameters	NamedParameterList	O	<p>Extended information. For the NamedParameterList information, see Table 5-2.</p>

Table 5-2 NamedParameterList parameters

Parameter	Type	Length	Level of Requirement	Description
item	NamedParameter[0...unbounded]	-	Optional	<p>Data type corresponding to the extended field, which consists of key and value.</p> <p>For the NamedParameters information, see Table 5-3.</p>



5 Recharging using direct payment

Table 5-3 NamedParameter parameters

Parameter	Type	Length	Level of Requirement	Description
key	String	-	Mandatory	ID of the extended field. The value is specified by the SDP. [Example] try
value	String	-	Mandatory	Value of the key. [Example] true

Table 5-4 Extended parameters transmitted in extensionInfo

Key		Value		
Parameter	Type	Length	Level of Requirement	Description
validateSubscriberLocation	int	4	Conditional	The parameter is used in a refill request to indicate if a validation of the subscriber location should be performed or not. <ul style="list-style-type: none"> ● 0 (false) (default value) Do not perform validation ● 1 (true) Perform validation [Example] 0

balanceUpdateRequest

Table 5-5 describes the input parameters in the **balanceUpdateRequest** message.



5 Recharging using direct payment

Table 5-5 balanceUpdateRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	<p>Contains the end user's credentials for authorizing access to the account. [Example]</p> <p>1212</p>
referenceCode	xsd:string	M	Textual information to uniquely identify the request, e.g. in case of disputes.
balanceType	xsd:string	M	<p>Identifies the type of balance.</p> <p>End user accounts may have one or more balances for different types of usage (e.g. Voice, SMS, gaming etc).</p>
amount	xsd:decimal	M	Currency amount that should be added to the end user's account.
period	xsd:int	O	<p>The balance is requested to expire in the number of days indicated by this parameter. The operator's policies may overrule this parameter.</p> <p> NOTE</p> <p>If this optional parameter is not present, the operator's policy on balance expiration is always in effect.</p>

balanceUpdateResponse

None.



5 Recharging using direct payment

Error Code

Table 5-6 describes the error codes that the SDP may return.

Table 5-6 balanceUpdate error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.
SVC0901	SPID is null!	The spId value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spId value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.



5 Recharging using direct payment

Error Code	Description	Cause
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spId in the request header does not exist in the SDP.
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp 's status is pause.	The Partner is in the paused state.



5 Recharging using direct payment

Error Code	Description	Cause
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of balanceUpdate messages in typical scenarios are as follows:

- The following is an example of request:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:serviceId>35000001000119</tns:serviceId>
      <tns:OA>8613900000001</tns:OA>
      <tns:FA>8613900000001</tns:FA>
      <tns:namedParameters>
        <tns:item>
          <tns:key>validateSubscriberLocation</v2:key>
          <tns:value>1</v2:value>
        </tns:item>
      </tns:namedParameters>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
  <soapenv:Body>
    <loc:balanceUpdate>
      <loc:endUserIdentifier>8613812345678</loc:endUserIdentifier>
      <loc:endUserPin>1212</loc:endUserPin>
      <loc:referenceCode>121</loc:referenceCode>
      <loc:balanceType>SMS</loc:balanceType>
      <loc:amount>60</loc:amount>
      <loc:period>10</loc:period>
    </loc:balanceUpdate>
  </soapenv:Body>
</soapenv:Envelope>
```

- The following is an example of the response:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:balanceUpdateResponse
xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v3_1/local"/>
  </soapenv:Body>
</soapenv:Envelope>
```



5 Recharging using direct payment

06

Recharging using a voucher

6.1 *voucherUpdate*

The SDP functions as the server and provides the interface for partners. Partners use it to recharge using a voucher.

Request URI

`http://IP:Port/AccountManagementService/services/AccountManagement/v3`

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 6-1 describes the parameters in the message header of the *voucherUpdate* interface.



6 Recharging using a voucher

Table 6-1 voucherUpdate message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, set the authentication mode and password during registration. If the password is forgotten, contact the carrier to retrieve the password.• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>




6 Recharging using a voucher

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> • SHA-256: spPassword = Base64(SHA-256(spld + Password + timeStamp)) • MD5: spPassword = MD5(spld + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> • spld and timeStamp: authentication ID and timestamp. • Password: password for partners to access the SDP. <ul style="list-style-type: none"> – For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. – For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE</p> <p>To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example]</p> <p>e6434ef249df55c7a21a0b45758a39bb</p>



6 Recharging using a voucher

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The bundleId must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



6 Recharging using a voucher

Parameter	Type	Mandatory or Optional	Description
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639

voucherUpdateRequest

Table 6-2 describes the input parameters in the **voucherUpdateRequest** message.



6 Recharging using a voucher

Table 6-2 voucherUpdateRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	<p>Contains the end user's credentials for authorizing access to the account. [Example]</p> <p>1212</p>
referenceCode	xsd:string	M	Textual information to uniquely identify the request, e.g. in case of disputes.
voucherIdentifier	xsd:string	M	This parameter identifies the voucher.
voucherPin	xsd:decimal	O	Contains the voucher's credentials for authentication.

voucherUpdateResponse

None.

Error Code

Table 6-3 describes the error codes that the SDP may return.

Table 6-3 getBalance error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.



6 Recharging using a voucher

Error Code	Description	Cause
SVC0901	SPID is null!	The spId value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spId value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.



6 Recharging using a voucher

Error Code	Description	Cause
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spId in the request header does not exist in the SDP.
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp 's status is pause.	The Partner is in the paused state.
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of voucherUpdate messages in typical scenarios are as follows:

- The following is an example of request:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
```



6 Recharging using a voucher

```
<tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
  <tns:spId>011104</tns:spId>
  <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
  <tns:timeStamp>20120809114701</tns:timeStamp>
  <tns:serviceId>35000001000119</tns:serviceId>
  <tns:OA>35713111113</tns:OA>
  <tns:FA>35713111113</tns:FA>
</tns:RequestSOAPHeader>
</soapenv:Header>
<soapenv:Body>
  <loc:voucherUpdate>
    <loc:endUserIdentifier>35713111113</loc:endUserIdentifier>
    <loc:endUserPin>1212</loc:endUserPin>
    <loc:referenceCode>131</loc:referenceCode>
    <loc:voucherIdentifier>141</loc:voucherIdentifier>
    <loc:voucherPin>11</loc:voucherPin>
  </loc:voucherUpdate>
</soapenv:Body>
</soapenv:Envelope>
```

- The following is an example of the response:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:voucherUpdateResponse
      xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v3_1/local"/>
  </soapenv:Body>
</soapenv:Envelope>
```

07

Querying Users' Operation Records

7.1 *getHistory*

The SDP functions as the server and provides the interface for partners. Partners use it to query the history records of a subscriber's account.

Request URI

`http://IP:Port/AccountManagementService/services/AccountManagement/v3`

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 7-1 describes the parameters in the message header of the *getHistory* interface.



7 Querying Users' Operation Records

Table 7-1 getHistory message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, set the authentication mode and password during registration. If the password is forgotten, contact the carrier to retrieve the password.• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>




7 Querying Users' Operation Records

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> • SHA-256: spPassword = Base64(SHA-256(spId + Password + timeStamp)) • MD5: spPassword = MD5(spId + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> • spId and timeStamp: authentication ID and timestamp. • Password: password for partners to access the SDP. <ul style="list-style-type: none"> – For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. – For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE</p> <p>To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example]</p> <p>e6434ef249df55c7a21a0b45758a39bb</p>



7 Querying Users' Operation Records

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The bundleId must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



7 Querying Users' Operation Records

Parameter	Type	Mandatory or Optional	Description
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639

getHistoryRequest

Table 7-2 describes the input parameters in the **getHistoryRequest** message.

Table 7-2 getHistoryRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence



7 Querying Users' Operation Records

Parameter	Type	Mandatory or Optional	Description
			<p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	<p>Contains the end user's credentials for authorizing access to the account.</p> <p>[Example]</p> <p>1212</p>
date	xsd:dateTime	O	<p>This parameter indicates the desired starting date for the entries to be returned.</p> <p>[Format]</p> <p>[<i>-</i>]YYYY-MM-DDThh:mm:ss.ms[Z](+ -)hh:mm], in which, <i>-</i> is optional, YYYY indicates the year, MM indicates the month, DD indicates the day, hh indicates the hour, mm indicates the minute, ss indicates the second, and ms indicates millisecond (1 ms = 0.001 s). The following time formats are supported:</p> <ul style="list-style-type: none"> Local time <p>The value 2012-01-01T12:12:12.001 indicates that the local time is 12 minutes, 12 seconds, and 1 millisecond past twelve on Jan. 1, 2012.</p> Adjusted time <p>The value 2012-01-01T12:12:12.001+02:00 indicates that the UTC time is the local time minus 2. That is, the UTC time is 2012-01-01T10:12:12.001Z.</p> UTC time <p>The value 2012-01-01T10:12:12.001Z indicates that the UTC time is 12 minutes, 12 seconds, and 1 millisecond past ten on Jan. 1, 2012.</p> <p> NOTE If this parameter is not present, it is up to the discretion of the service to decide this date.</p>
maxEntries	xsd:int	O	<p>This parameter indicates the maximum number of entries that shall be returned.</p> <p> NOTE If this parameter is not present, it is up to the discretion of the service to decide how many entries to return.</p>



7 Querying Users' Operation Records

getHistoryResponse

Table 7-3 describes the parameters in the **getHistoryResponse** message.

Table 7-3 getHistoryResponse parameters

Parameter	Type	Description
result	DatedTransaction [0 .. unbounded]	It is a DatedTransaction array that consists of types with a date field and a string field, which are the date of the occurrence and the transaction details respectively. For the error codes, see Table 7-4.

Table 7-4 DatedTransaction parameters

Parameter	Type	Description
transactionDate	xsd:dateTime	The date the transaction occurred.
transactionDetails	xsd:string	The transaction details.

Error Code

Table 7-5 describes the error codes that the SDP may return.

Table 7-5 getHistory error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.
SVC0901	SPID is null!	The spId value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spId value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.



7 Querying Users' Operation Records

Error Code	Description	Cause
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spid in the request header does not exist in the SDP.
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.



7 Querying Users' Operation Records

Error Code	Description	Cause
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp 's status is pause.	The Partner is in the paused state.
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of getHistory messages in typical scenarios are as follows:

- The following is an example of request:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:serviceId>35000001000119</tns:serviceId>
      <tns:OA>35713111113</tns:OA>
      <tns:FA>35713111113</tns:FA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
  <soapenv:Body>
    <loc:getHistory>
      <loc:endUserIdentifier>35713111113</loc:endUserIdentifier>
      <loc:endUserPin>1212</loc:endUserPin>
      <loc:date>2012-01-01T12:12:12.001Z</loc:date>
    </loc:getHistory>
  </soapenv:Body>
</soapenv:Envelope>
```




7 Querying Users' Operation Records

```

        <loc:maxEntries>2</loc:maxEntries>
    </loc:getHistory>
</soapenv:Body>
</soapenv:Envelope>

```

- The following is an example of the response:

```

<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getHistoryResponse
      xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
      <ns1:result>
        <transactionDate>2012-06-06T12:12:12.001Z</transactionDate>
        <transactionDetails>ok</transactionDetails>
      </ns1:result>
      <ns1:result>
        <transactionDate>2012-06-08T12:12:12.001Z</transactionDate>
        <transactionDetails>ok</transactionDetails>
      </ns1:result>
    </ns1:getHistoryResponse>
  </soapenv:Body>
</soapenv:Envelope>

```

8.1 *getBalanceTypes*

The SDP functions as the server and provides the interface for partners. Partners use it to obtain users' balance types.

Request URI

`http://IP:Port/AccountManagementService/services/AccountManagement/v3`

In the preceding information, *IP* and *Port* indicate the IP address and port number for the SDP to provide Account Management services. Contact the carrier to obtain the IP address and port number.

Message Header

Table 8-1 describes the parameters in the message header of the *getBalanceTypes* interface.



9 Appendix

Table 8-1 getBalanceTypes message header parameters

Parameter	Type	Mandatory or Optional	Description
spld	xsd:string	M	<p>Partner ID.</p> <p>Partner ID automatically allocated by the SDP to the Partner after successful registration.</p> <p>To obtain the Partner ID:</p> <ul style="list-style-type: none">• For a partner, set the authentication mode and password during registration. If the password is forgotten, contact the carrier to retrieve the password.• For a partner, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Access Code, and query the Partner ID.• For a developer, use the registered account to log in to the Developer Portal, choose Home > My Account, and query the Developer ID. <p>[Example]</p> <p>2500110000021</p>




9 Appendix

Parameter	Type	Mandatory or Optional	Description
spPassword	xsd:string	O	<p>Authentication key for the SDP to authenticate partners.</p> <p>The SDP supports authentication by SP ID + Password, SP ID + IP address + Password, or SP ID + IP address. Partners select an authentication mode during registration. If a partner selects authentication by SP ID + Password or SP ID + IP address + Password, this parameter is mandatory in requests sent by this partner.</p> <p>The value is a character string encrypted. The encryption formula is as follows:</p> <ul style="list-style-type: none"> • SHA-256: spPassword = Base64(SHA-256(spld + Password + timeStamp)) • MD5: spPassword = MD5(spld + Password + timeStamp) <p>In the formula:</p> <ul style="list-style-type: none"> • spld and timeStamp: authentication ID and timestamp. • Password: password for partners to access the SDP. <ul style="list-style-type: none"> – For a partner, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the SDP Management Portal, choose Home > Partner > Partner Information, and set a new one. – For a developer, set the authentication mode and password during registration. If the password is forgotten, use the registered account to log in to the Developer Portal, choose Member Center > Account > Registration Information > Invoke Password, and set a new one. <p> NOTE To retain features of earlier versions, the SP uses the MD5 algorithm in the connection to the SDP, which might cause security risks.</p> <p>[Example] e6434ef249df55c7a21a0b45758a39bb</p>



9 Appendix

Parameter	Type	Mandatory or Optional	Description
timeStamp	xsd:string	O	<p>Time stamp (UTC time).</p> <p>The value is required during MD5 encryption for spPassword.</p> <p> NOTE If the spPassword parameter must be set, this parameter is mandatory.</p> <p>[Format] yyyyMMddHHmmss</p> <p>[Example] 20100731064245</p>
serviceId	xsd:string	O	<p>Service ID.</p> <p>To obtain the service ID:</p> <ul style="list-style-type: none"> • For a service partner, use the registered account to log in to the SDP Management Portal to get the ID. • For an API partner, set it blank. • For a developer: <ul style="list-style-type: none"> – If the developer has bought the capability, set the value to none. – If the developer has released the capability service, contact the carrier to obtain the service ID. <p>The bundleId must not be contained during invocation of a service interface developed by service partners and other partners, and must be contained during invocation of a capability interface developed by API partners, other partners, and developers.</p> <p>[Example] 35000001000001</p>



9 Appendix

Parameter	Type	Mandatory or Optional	Description
OA	xsd:string	M	<p>Mobile number or the fake ID of the service originator. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639
FA	xsd:string	O	<p>Mobile number or the fake ID of the charged party. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00. <ul style="list-style-type: none"> Fake ID: Prefix-opcoid-sequence <p>[Example]</p> <ul style="list-style-type: none"> Mobile number: 8612312345678 Fake ID: f-245-11900000007639

getBalanceTypesRequest

Table 8-2 describes the input parameters in the **getBalanceTypesRequest** message.

Table 8-2 getBalanceTypesRequest input parameters

Parameter	Type	Mandatory or Optional	Description
endUserIdentifier	xsd:anyURI	M	<p>This parameter identifies the end user's account. [Format]</p> <ul style="list-style-type: none"> Mobile number: prefix+country code+mobile number <p> NOTE</p> <ul style="list-style-type: none"> The prefix is optional. The prefix can be any one of +, +0, +00, 0, and 00.



9 Appendix

Parameter	Type	Mandatory or Optional	Description
			<ul style="list-style-type: none"> • Fake ID: Prefix-opcoid-sequence [Example] • Mobile number: 8612312345678 • Fake ID: f-245-11900000007639
endUserPin	xsd:string	O	Contains the end user's credentials for authorizing access to the account. [Example] 1212

getBalanceTypesResponse

Table 8-3 describes the parameters in the **getBalanceTypesResponse** message.

Table 8-3 getBalanceTypesResponse parameters

Parameter	Type	Description
result	xsd:string [1unbounded]	Identifies the types of balance. End user accounts may have one or more balances for different types of usage (e.g. Voice, SMS, gaming etc).

Error Code

Table 8-4 describes the error codes that the SDP may return.

Table 8-4 getBalance error codes

Error Code	Description	Cause
SVC0001	Service error.	A service exception occurred in the internal SDP.
	A service error occurred.	An internal SDP service is abnormal.
SVC0901	SPID is null!	The spid value in the request header is blank or does not exist in the SDP.
	SPID %1 is invalid!	The spid value in the request header is in an incorrect format.
	Sp password is null!	The password value in the request header is blank.
	Service ID is null!	The serviceld value in the request header is blank or does not exist in the SDP.



9 Appendix

Error Code	Description	Cause
	Service ID %1 is invalid!	The serviceld value in the request header is in an incorrect format.
	Timestamp is empty in soapheader.	The timeStamp value in the request header is blank.
	SP ip is null!	The IP address in the request header is blank.
	The Created is null.	The timeStamp value in the request header is blank.
	The Nonce is null.	The Nonce value in the request header is blank.
	Sp password is null!	The password value in the request header is blank.
	The PasswordDigest is not accepted.	The password in the cipher text is incorrect.
	Sp ip %1 is not accepted!	The IP address in the request header is incorrect.
	Sp password is not accepted!	The password value in the request header is incorrect.
	The Sp has not logged in.	The Token value in the request header does not exist in the SDP and the Partner needs to log in first.
	The token is not accepted!	The Token format in the request header is incorrect.
	The token is expired!	The Token value in the request header is expired.
	local SP password is null!	An exception occurred in the internal SDP.
	The sp's Status is deregistered.	The Partner is in the deregistered state.
	The sp's Status is pre-deregistered.	The Partner is in the pre-deregistered state.
	SP %1 is in blacklist!	The Partner account is in the blacklist.
	The sp's Status is unknown.	An internal SDP service is abnormal.
	SPID %1 is not exist!	The Partner specified by spId in the request header does not exist in the SDP.
	The service status is configuring.	The service specified by serviceld in the request header is in the configuring state.



9 Appendix

Error Code	Description	Cause
	The service status is suspended.	The service specified by serviceld in the request header is in the paused state.
	The service status is pre-deregistered.	The service specified by serviceld in the request header is in the pre-deregistered state.
	The service status is deregistered.	The service specified by serviceld in the request header is in the deregistered state.
	Service ID %1 is not exist!	The serviceld value in the request header does not exist in the SDP.
	The service status is unknown.	An internal SDP service is abnormal.
	Service %1 is in blacklist!	The serviceld value in the request header in the blacklist.
	The API %1 is not existed.	This Partner does not have the permission for using the API.
	The API status is disabled.	This Partner does not have the permission for using the API.
	SP status is locked.	The Partner is in the locked state.
	The sp's Status is forbidden.	The Partner is in the forbidden state.
	The sp 's status is pause.	The Partner is in the paused state.
SVC0905	AuthToken %1 is invalid	The AuthToken value in the request header sent by the partner is invalid.

Example

Examples of getBalanceTypes messages in typical scenarios are as follows:

- The following is an example of request:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:loc="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
  <soapenv:Header>
    <tns:RequestSOAPHeader xmlns:tns="http://www.huawei.com.cn/schema/common/v2_1">
      <tns:spId>011104</tns:spId>
      <tns:spPassword>557d5fd8fb01089acd744245fc011036</tns:spPassword>
      <tns:timeStamp>20120809114701</tns:timeStamp>
      <tns:serviceId>35000001000119</tns:serviceId>
      <tns:OA>35713111113</tns:OA>
      <tns:FA>35713111113</tns:FA>
    </tns:RequestSOAPHeader>
  </soapenv:Header>
```



9 Appendix

```
<soapenv:Body>
  <loc:getBalanceTypes>
    <loc:endUserIdentifier>35713111113</loc:endUserIdentifier>
    <loc:endUserPin>1212</loc:endUserPin>
  </loc:getBalanceTypes>
</soapenv:Body>
</soapenv:Envelope>
```

- The following is an example of the response:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getBalanceTypesResponse
      xmlns:ns1="http://www.csapi.org/schema/parlayx/account_management/v3_1/local">
      <ns1:result>SMS</ns1:result>
      <ns1:result>GPRS</ns1:result>
      <ns1:result>Voice</ns1:result>
    </ns1:getBalanceTypesResponse>
  </soapenv:Body>
</soapenv:Envelope>
```

9.1 The Currency and Atomic Charging Unit of each OpCo country

Country Name	Currency	Atomic Charging Unit
Afghanistan	AFA	pul
Benin	XOF	N/A
Bissau	CFA	N/A
Cameroon	XAF	NA
Cote D'Ivoire	XOF	NA
Cyprus	Euro	cent
Ghana	GHS	Pesewa(1GHS=100Pesewa)
Guinea	GNF(Guinea Franc)	NA
Liberia	LRD(Liberia Dollar)	NA
N Sudan	SDG	Piaster
Nigeria	NGN	Kobo
Rwanda	Rwandan Franc (RWF)	RWF
SA	ZAR	N/A
Swaziland	SZL	cent
Uganda	Ugandan shilling (Code UGX)	UGX
Yemen	Yemeni Riyal	Fils (1 Riyal = 100 Fils)
Zambia	ZMK	ngwee, 1ZMK = 100Ngwee



9 Appendix

9.2 ISO 4217 Codes for the representation of currencies and funds

ENTITY	CURRENCY	ALPHABETI CCODE	NUMERI CCODE
Afghanistan	Afghani	AFA	4
Benin	CFA Franc BCEAO	XOF	952
Botswana	Pula	BWP	72
Cameroon	CFA Franc BEAC	XAF	950
Congo	CFA Franc BEAC	XAF	950
Cote D'Ivoire	CFA Franc BCEAO	XOF	952
Cyprus	Cyprus Pound	CYP	196
Ethiopia	Ethiopian Birr	ETB	230
Ghana	Cedi	GHC	288
Guinea	Guinea Franc	GNF	324
Guinea-Bissau	Guinea-Bissau Peso	GWP	624
	CFA Franc BCEAO	XOF	952
Liberia	Liberian Dollar	LRD	430
Nigeria	Naira	NGN	566
Rwanda	Rwanda Franc	RWF	646
South Africa	Rand	ZAR	710
Sudan	Sudanese Dinar	SDD	736
Swaziland	Lilangeni	SZL	748
Uganda	Uganda Shilling	UGX	800
Yemen	Yemeni Rial	YER	886
Zambia	Kwacha	ZMK	894

9.3 OpCoID List

MTN OpCo Name	OpCoID Value
Afghanistan	9301
Benin	22901



9 Appendix

MTN OpCo Name	OpCoID Value
Bissau	24501
Botswana	26701
Cameroon	23701
Congo	24201
Cote D'Ivoire	22501
Cyprus	35701
Ghana	23301
Guinea Republic	22401
Liberia	23101
Nigeria	23401
Rwanda	25001
South Africa	2701
Sudan North	21101
Sudan South	24901
Swaziland	26801
Syria	96301
Uganda	25601
Yemen	96701
Zambia	26001

