DL-40 data logger

Low-power logger for remote sensor stations: polls Modbus and SDI-12 sensors and stores data locally during backhaul outages.

Key features

- RS-485 Modbus RTU master (up to 16 devices) and two SDI-12 buses
- 180 days of 1-minute data in flash
- Sub-1 W average draw for solar sites

Technical specifications

Parameter	Value	Notes
Sensor inputs	RS-485 Modbus RTU master, 2 x SDI-12, 4 x 4-20 mA	
Logging interval	1 s to 24 h, 1 minute default	
Storage	180 days at 1-minute interval for 12 channels	Flash, wear levelled
Interfaces to host	RS-232, USB-C, Ethernet	
Operating temperature	-40 °C to +70 °C	
Supply voltage	9 to 28 V DC	
Power consumption	0.4 W average	
Ingress protection	IP20 (mount in enclosure)	
Compliance	CE (EMC 2014/30/EU, RED 2014/53/EU where radio), RoHS 2011/65/EU	Declarations on request
Warranty	24 months	Return to Galway or Pune

Ordering

SKU	Description	Unit	List price EUR
DL-40	DL-40 data logger	each	EUR 890.00

Kestrel Sensing Ltd, Galway, Ireland, manufacturing in Pune, India. ISO 9001, CE, RoHS. Specifications subject to change without notice. Sample company (fictional): sample data created for demonstration.