SP-60 solar power kit

Off-grid power for a sensor station: panel, MPPT controller and sealed battery sized for a 15 W continuous load.

Key features

- 60 W monocrystalline panel with tilt bracket
- 100 Ah / 1.2 kWh LiFePO4 battery rated -20 °C to +60 °C with heater pad
- Seven days autonomy at a 7 W continuous load

Technical specifications

Parameter	Value	Notes
Panel	60 W peak, monocrystalline	
Battery	12.8 V, 100 Ah (1,280 Wh) LiFePO4	Low-temperature charge protection
Autonomy	7 days at 7 W; 3 days at 15 W	No sun
Controller	MPPT 10 A, 12 V output	
Ingress protection	IP65 enclosure	
Operating temperature	-30 °C to +60 °C	
Compliance	CE (EMC 2014/30/EU, RED 2014/53/EU where radio), RoHS 2011/65/EU	Declarations on request
Warranty	24 months	Return to Galway or Pune

Ordering

SKU	Description	Unit	List price EUR
SP-60	SP-60 solar power kit	each	EUR 780.00

Kestrel Sensing Ltd, Galway, Ireland, manufacturing in Pune, India. ISO 9001, CE, RoHS. Specifications subject to change without notice. Sample company (fictional): sample data created for demonstration.