# VS-210  visibility (fog) sensor

Forward-scatter visibility sensor reporting meteorological optical range (MOR) for harbours, airfields, roads and wind farms.

## Key features

- MOR 10 m to 75 km with 1-minute and 10-minute averages
- Heated optics and hood with automatic contamination compensation
- RS-485 Modbus RTU and SDI-12 on the same connector
- Marine-grade coating, tested to salt mist IEC 60068-2-52

## Technical specifications

| Parameter | Value | Notes |
|---|---|---|
| Measurement principle | Forward scatter, 42 degrees, infrared 880 nm | |
| Visibility range (MOR) | 10 m to 75 km | Reported in metres |
| Accuracy | ±10% from 10 m to 10 km; ±20% from 10 km to 75 km | Against reference transmissometer |
| Output interfaces | RS-485 Modbus RTU, SDI-12, 4-20 mA (optional) | Baud 1200 to 115200 |
| Ingress protection | IP67 | IEC 60529 |
| Operating temperature | -40 °C to +60 °C | With heaters enabled |
| Supply voltage | 9 to 30 V DC | |
| Power consumption | 1.8 W typical, 9 W with heaters | Heaters thermostat controlled |
| Corrosion resistance | Salt mist IEC 60068-2-52 severity 3 | Marine coating standard |
| Response time | 60 s (1-minute average) | |
| Compliance | CE (EMC 2014/30/EU, RED 2014/53/EU where radio), RoHS 2011/65/EU | Declarations on request |
| Warranty | 24 months | Return to Galway or Pune |

## Ordering

| SKU | Description | Unit | List price EUR |
|---|---|---|---|
| VS-210 | VS-210 visibility (fog) sensor | each | EUR 2,950.00 |

Kestrel Sensing Ltd, Galway, Ireland, manufacturing in Pune, India. ISO 9001, CE, RoHS. Specifications subject to change without notice. Sample company (fictional): sample data created for demonstration.