GW-4G IoT gateway (LTE-M / 4G)

Industrial gateway that bridges RS-485 Modbus RTU sensors to the cloud over 4G with LTE-M fallback and dual SIM.

Key features

- LTE Cat-4 with LTE-M (Cat-M1) fallback, dual SIM with automatic failover
- RS-485 Modbus RTU to Modbus TCP and MQTT 3.1.1/5 over TLS
- Store-and-forward during backhaul loss

Technical specifications

Parameter	Value	Notes
Cellular	LTE Cat-4, LTE-M (Cat-M1), NB-IoT, 2G fallback	Dual nano-SIM, auto failover
Serial	1 x RS-485 (Modbus RTU), 1 x RS-232	
Protocols	Modbus RTU/TCP, MQTT, HTTPS, SNMP	TLS 1.2
Ingress protection	IP65	Mount in cabinet or sensor enclosure
Operating temperature	-40 °C to +70 °C	
Supply voltage	9 to 36 V DC	
Power consumption	2.0 W typical, 4.5 W peak during transmit	
Compliance	CE (EMC 2014/30/EU, RED 2014/53/EU where radio), RoHS 2011/65/EU	Declarations on request
Warranty	24 months	Return to Galway or Pune

Ordering

SKU	Description	Unit	List price EUR
GW-4G	GW-4G IoT gateway (LTE-M / 4G)	each	EUR 640.00

Kestrel Sensing Ltd, Galway, Ireland, manufacturing in Pune, India. ISO 9001, CE, RoHS. Specifications subject to change without notice. Sample company (fictional): sample data created for demonstration.