VS-210 visibility (fog) sensor

Forward-scatter visibility sensor reporting meteorological optical range (MOR) for harbours, airfields, roads and wind farms.

Key features

- MOR 10 m to 75 km with 1-minute and 10-minute averages
- Heated optics and hood with automatic contamination compensation
- RS-485 Modbus RTU and SDI-12 on the same connector
- Marine-grade coating, tested to salt mist IEC 60068-2-52

Technical specifications

Parameter	Value	Notes
Measurement principle	Forward scatter, 42 degrees, infrared 880 nm	
Visibility range (MOR)	10 m to 75 km	Reported in metres
Accuracy	±10% from 10 m to 10 km; ±20% from 10 km to 75 km	Against reference transmissometer
Output interfaces	RS-485 Modbus RTU, SDI-12, 4-20 mA (optional)	Baud 1200 to 115200
Ingress protection	IP67	IEC 60529
Operating temperature	-40 °C to +60 °C	With heaters enabled
Supply voltage	9 to 30 V DC	
Power consumption	1.8 W typical, 9 W with heaters	Heaters thermostat controlled
Corrosion resistance	Salt mist IEC 60068-2-52 severity 3	Marine coating standard
Response time	60 s (1-minute average)	
Compliance	CE (EMC 2014/30/EU, RED 2014/53/EU where radio), RoHS 2011/65/EU	Declarations on request
Warranty	24 months	Return to Galway or Pune

Ordering

SKU	Description	Unit	List price EUR
VS-210	VS-210 visibility (fog) sensor	each	EUR 2,950.00

Kestrel Sensing Ltd, Galway, Ireland, manufacturing in Pune, India. ISO 9001, CE, RoHS. Specifications subject to change without notice. Sample company (fictional): sample data created for demonstration.