
Linux, day 6

This lab is licensed under Creative Commons BY-NC-SA 4.0. https://creativecommons.org/licenses/by-nc-sa/4.0/deed.en

You are free to share and adapt, but NOT for commercial purposes and you must attribute the source and share your own adaptions under the same license.





Objectives covered

Objective	Summary	Book
1.4	System services	6
1.5	Interface management, name resolution	7
1.7	Configure common system services	6

LAB: Linux networking





- Add a second NIC to your VM (in Virtualbox).
 - You can put it in the NAT network.

- Bring the new NIC under NetworkManager control.
- Configure it using "nmtui".

Solution (RHEL)

- sudo dmesg | grep -i network
- sudo nmcli device set eth1 managed yes
- sudo nmtui
 - Set up the new device, similar to eth0.
 - Devices <u>names may differ</u>, like *enp0s3*.

Solution (Debian)

sudo vi /etc/netplan/00-installer-config.yml
Should only contain these lines:
 network:
 version: 2
 renderer: NetworkManager

- sudo netplan generate; sudo netplan apply
- sudo nmcli device set eth1 managed yes
- sudo ip link eth1 up; sudo nmtui




What will we do today?

- Recap
- Linux networking
- Network services
- Configuring network services
- Closing: homework and Q&A

LAB: FTP Server





- Install the "vsftpd" package on Ubuntu.
 - On Fedora WS, the firewall will block you.
- Check for the latest changes (Is -Irt) in:
 - /lib/systemd/system/
 - /etc/systemd/system/
 - /etc/systemd/system/multi-user.target.wants/

- Enable the "vsftpd" service.
- Again, check for the latest changes (Is -Irt) in:
 - /lib/systemd/system/
 - /etc/systemd/system/
 - /etc/systemd/system/multi-user.target.wants/

- Check the status of the "vsftpd" service.
- Start the "vsftpd" service.
- Check the status of the "vsftpd" service again.
 - Can you FTP into the server?
- Finally, disable and mask the "vsftpd" service.

LAB: NTP Client






- Install, enable and run "chrony".
- Configure "chrony" as NTP client.
 - Find the configuration file, verify the settings.
 - Can you confirm your time is synchronized?

LAB: SSH keys, ssh-agent





Setup

- Ensure that you have two Linux VMs.
- And that you have an account on both.

- Plus, let's take a short sidestep to the whiteboard!
 - What are SSH keys?!

- Double-check that SSHd runs on both servers.
- Generate a new key pair on one of the accounts.
 - Make it type ECDSA, with a password.

- Configure your public key for access on the other VM.
 - Copy it to the other VM,
 - It needs to go into ~/.ssh/authorized_keys.


- Start "eval \$(ssh-agent)".
- Load your private key with "ssh-add" command.
 - This should ask your password once.

- Try SSH-ing to the other VM again.
 - This should not ask your password.

- Reconfigure "sshd_config" on one of the VMs,
 - So it will only allow group "sshusers" to login.
- Give your own account the new group "sshusers"
- Restart the SSH daemon and test that you can login.
 - Also make sure that another user <u>cannot</u>.

Closing





Homework

- Reading:
 - Chapter 5.
 - Chapter 14.

Homework

- Go do:
 - On Ubuntu, setup a httpd webserver.
 - Create a simple "index.html" to serve up.
 - Make sure you can browse to the site:
 - Both from your Fedora VM
 - And from your laptop (setup a port forward!)

Reference materials





Resources

- ifconfig vs ip
- netplan vs networkmanager vs networkd
- Have a plan for netplan
- Bonding with NetworkManager
- Bonding with configuration files
- Bridged network connections

Resources

- Bug in Ubuntu and Network Manager
- Learning to love systemd
- SysVinit and systemd service mgt cheatsheet

Resources

- Does Not Compute:
 - Let's look at some big, expensive servers.
 - Let's check out a blade server (32 CPUs).
- Others:
 - Inside a Google data center
 - Rackmount server anatomy 101