


Linux, day 7

This lab is licensed under Creative Commons BY-NC-SA 4.0.
<https://creativecommons.org/licenses/by-nc-sa/4.0/deed.en>

You are free to share and adapt, but NOT for commercial purposes and you must attribute the source and share your own adaptations under the same license.



Objectives covered

Objective	Summary	Boek
1.1	Basic boot process	5
1.1	Kernel panic	5
1.7	Configure kernel options	14

LAB: The Linux boot process

Fedora: enable boot menu

- Edit `"/etc/default/grub"` and set these (no quotes!):
 - `GRUB_TIMEOUT=5`
 - `GRUB_TIMEOUT_STYLE=menu`
 - `GRUB_TERMINAL=console`
 - `GRUB_TERMINAL_OUTPUT=console`
- Then run:
 - `sudo grub2-mkconfig -o /boot/grub2/grub.cfg`
 - `sudo grub2-mkconfig -o /boot/efi/EFI/fedora/grub.cfg`

Ubuntu: enable boot menu

- Edit *"/etc/default/grub"* and set these (no quotes!):
 - *GRUB_TIMEOUT=5*
 - *GRUB_TIMEOUT_STYLE=menu*
 - *GRUB_TERMINAL=console*
 - *GRUB_TERMINAL_OUTPUT=console*
- Then run:
 - *sudo grub-mkconfig -o /boot/grub/grub.cfg*

Seeing the bootup

- Some Linuxen have "splash screens" or quiet boot.
- Reboot your VM and interrupt the GRUB2 menu.
- Select the default kernel, then press "e" to edit.
 - Remove the words "quiet", "rhgb" and "splash".
 - Continue booting

Logs once the host is up

```
$ dmesg | less
```

```
$ journalctl --list-boots           # Modern
```

```
$ journalctl -b                     # Modern
```

```
$ tail -500 /var/log/messages      # Older
```

```
$ tail -500 /var/log/syslog        # Older
```

LAB: The Linux boot process

() I've lost my root!

- Oh no! We're locked out of our root account!
 - And our system refuses to boot.
- How we fix this, differs per distro...
- For safety, first make a snapshot of your VM.

Again, a warning!!

- For safety, first make a snapshot of your VM.



RHEL, CentOS, Fedora (1)

- Reboot your VM and go into the GRUB2 editor.
- Edit the line with boot parameters:
 - Remove "*quiet*" and "*rhgb*"
 - Add "*init=/bin/sh*"
- Boot up...
- Mount / as writable: "*mount -o rw,remount /*"

RHEL, CentOS, Fedora (2)

- Go into */etc*.
- Make a backup copy of the "*shadow*" file.
- **Either** Run: "*passwd root*"
- **Or** use nano or vi to blank-out the root password.
- Run: "*touch /.autorelabel*"

See: [SELinux and passwd in rescue mode](#)

RHEL, CentOS, Fedora (3)

- Run: *"sync; sync; mount -o ro,remount /"*
- Reboot, or reset the VM
- Test your root account afterwards.
 - The password should be blank/empty,
 - Or the new value you gave with *passwd*.

Debian, Ubuntu, Kali (1)

- Reboot your VM and go into the GRUB2 editor.
- Edit the line with boot parameters:
 - Remove "*quiet*" and "*rhgb*"
 - Add "*init=/bin/bash*"
- Boot up...
- Mount / as writable: "*mount -o rw,remount /*"

Debian, Ubuntu, Kali (2)

- Go into */etc*.
- Make a backup copy of the "*shadow*" file.
- Run: "*passwd root*",
 - Or edit "*/etc/shadow*" with *vi/nano*.
- Run: "*sync; sync; mount -o ro,remount /*"
- Reboot
- Test your new root password afterwards.

LAB: Kernel modules

Assignment

- Shutdown your VM.
- Add a new NIC to your VM (in Virtualbox).
 - You can put it in the NAT network.
 - This time, use another hardware type! Not e1000.

Assignment

- Boot the VM again.
- Check with "*dmesg*" if the hardware was seen.
 - Check if the right driver was loaded.
- Check with "*lsmod*" if you can see the driver.

Closing

Homework

- Reading:
 - Chapters 28, 29 and 30.

Homework

- Go do:
 - Check your VMs: how many kernels do they have?
 - Install a second, or third kernel version.
 - Use GRUB2 to test booting the installed kernel.

Reference materials

Resources

- [Don't use NSCD](#)
- [Anatomy of a Linux DNS lookup](#)
- [The Linux boot process](#)
- [Step by step: Linux boot process explained](#)
- [EFI System Partition](#)
- [Initramfs, Dracut and the Dracut rescue shell](#)

Resources

- [Changing GRUB entries at boot](#)
- [Resetting passwords in single-user-mode](#)
- [SELinux and passwd in rescue mode](#)
- [What is the Linux kernel and what does it do?](#)