

```
# Mount to Google Drive for downloading dataset file
```

```
from google.colab import drive
drive.mount('/content/gdrive/')
```

Mounted at /content/gdrive/

```
# Unzip the dataset file
```

```
!unzip /content/gdrive/MyDrive/deep-learning-recycle-item-classification-main.zip
```

```
Archive: /content/gdrive/MyDrive/deep-learning-recycle-item-classification-main.zip
33ae657e01683187bb19c4351555cd56aa5329d3
  creating: deep-learning-recycle-item-classification-main/
  inflating: deep-learning-recycle-item-classification-main/LICENSE
  inflating: deep-learning-recycle-item-classification-main/README.md
    creating: deep-learning-recycle-item-classification-main/code/
  inflating: deep-learning-recycle-item-classification-main/code/deep-learning-real-life-item-classification.ipynb
  inflating: deep-learning-recycle-item-classification-main/code/deep-learning-real-life-item-classification.pdf
    creating: deep-learning-recycle-item-classification-main/dataset/
  inflating: deep-learning-recycle-item-classification-main/dataset/Dataset.zip
    creating: deep-learning-recycle-item-classification-main/images/
  inflating: deep-learning-recycle-item-classification-main/images/accuracy-validation.png
  inflating: deep-learning-recycle-item-classification-main/images/confusion-matrix.png
  inflating: deep-learning-recycle-item-classification-main/images/item-classification-deep-learning.png
  inflating: deep-learning-recycle-item-classification-main/images/loss-validation.png
```

```
import pandas as pd
import numpy as np
import glob
import os
from datetime import datetime
from packaging import version
```

```
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras.applications import EfficientNetB0
from tensorflow.keras.preprocessing import image_dataset_from_directory
from tensorflow.keras.preprocessing.image import load_img, img_to_array
from tensorflow.keras.callbacks import ModelCheckpoint, History
```

```
from tensorflow.keras.models import Sequential, load_model
from tensorflow.keras.layers import Conv2D, Lambda, MaxPooling2D, Dense, Dropout, Flatten
from tensorflow.keras.preprocessing.image import ImageDataGenerator
from tensorflow.keras.utils import to_categorical
```

```
from skimage.io import imread, imshow
from skimage.transform import resize
from IPython import display
import matplotlib.pyplot as plt
import seaborn as sns
from seaborn import heatmap
from sklearn.metrics import confusion_matrix
```

```
!unzip /content/deep-learning-recycle-item-classification-main/dataset/Dataset.zip
```

```

inflating: Dataset/Train/Non-recyclable/0_51.jpg
inflating: Dataset/Train/Non-recyclable/0_45.jpg
inflating: Dataset/Train/Non-recyclable/0_45.jpg
inflating: Dataset/Train/Non-recyclable/0_79.jpg
inflating: Dataset/Train/Non-recyclable/0_79.jpg
inflating: Dataset/Train/Non-recyclable/0_41.jpg
inflating: Dataset/Train/Non-recyclable/0_41.jpg
inflating: Dataset/Train/Non-recyclable/0_55.jpg
inflating: Dataset/Train/Non-recyclable/0_55.jpg
inflating: Dataset/Train/Non-recyclable/0_69.jpg
inflating: Dataset/Train/Non-recyclable/0_69.jpg
inflating: Dataset/Train/Non-recyclable/0_82.jpg
inflating: Dataset/Train/Non-recyclable/0_82.jpg
inflating: Dataset/Train/Non-recyclable/0_96.jpg
inflating: Dataset/Train/Non-recyclable/0_96.jpg
inflating: Dataset/Train/Non-recyclable/0_264.jpg
inflating: Dataset/Train/Non-recyclable/0_264.jpg
inflating: Dataset/Train/Non-recyclable/0_270.jpg
inflating: Dataset/Train/Non-recyclable/0_270.jpg
inflating: Dataset/Train/Non-recyclable/0_258.jpg
inflating: Dataset/Train/Non-recyclable/0_258.jpg
inflating: Dataset/Train/Non-recyclable/0_476.jpg
inflating: Dataset/Train/Non-recyclable/0_476.jpg
inflating: Dataset/Train/Non-recyclable/0_310.jpg
inflating: Dataset/Train/Non-recyclable/0_310.jpg
inflating: Dataset/Train/Non-recyclable/0_304.jpg
inflating: Dataset/Train/Non-recyclable/0_304.jpg
inflating: Dataset/Train/Non-recyclable/0_462.jpg
inflating: Dataset/Train/Non-recyclable/0_462.jpg
inflating: Dataset/Train/Non-recyclable/0_338.jpg
inflating: Dataset/Train/Non-recyclable/0_338.jpg
inflating: Dataset/Train/Non-recyclable/0_6.jpg

# Define train and test image folder path

train_folder = "/content/Dataset/Train"
test_folder = "/content/Dataset/Test"

from tensorflow.keras.applications.efficientnet import preprocess_input

# Data augmentation for training
train_datagen = ImageDataGenerator(
    preprocessing_function=preprocess_input, # EfficientNetB0-specific preprocessing
    rotation_range=30,
    width_shift_range=0.2,
    height_shift_range=0.2,
    shear_range=0.2,
    zoom_range=0.2,
    horizontal_flip=True,
    fill_mode='nearest'
)

# No augmentation for validation
test_datagen = ImageDataGenerator(preprocessing_function=preprocess_input)

# Load dataset
train_generator = train_datagen.flow_from_directory(
    train_folder,
    target_size=(224, 224),
    batch_size=32,
    class_mode='binary')

Found 999 images belonging to 2 classes.

test_generator = test_datagen.flow_from_directory(
    test_folder,
    target_size=(224, 224),
    batch_size=32,
    class_mode='binary',
    shuffle=False)

Found 1234 images belonging to 2 classes.

from sklearn.utils.class_weight import compute_class_weight
# Compute class weights to address imbalance
class_labels = np.array(train_generator.classes)
class_weights = compute_class_weight(class_weight='balanced', classes=np.unique(class_labels), y=class_labels)
class_weight_dict = {i: class_weights[i] for i in range(len(class_weights))}

```

```
# Load EfficientNetB0 base model (pre-trained on ImageNet)
base_model = EfficientNetB0(weights='imagenet', include_top=False, input_shape=(224, 224, 3))

Downloading data from https://storage.googleapis.com/keras-applications/efficientnetb0\_notop.h5
16705208/16705208 — 0s 0us/step

base_model.trainable = False


model = keras.Sequential([
    base_model,
    keras.layers.GlobalAveragePooling2D(),
    keras.layers.Dense(128, activation='relu'),
    keras.layers.Dropout(0.5),
    keras.layers.Dense(1, activation='sigmoid')
])

from tensorflow.keras.optimizers import Adam
#Compile the model
model.compile(optimizer=Adam(learning_rate=0.0001), loss='binary_crossentropy', metrics=['accuracy'])

# Train model
history = model.fit(
    train_generator,
    epochs=10,
    validation_data=test_generator,
    class_weight=class_weight_dict)

/usr/local/lib/python3.11/dist-packages/keras/src/trainers/data_adapters/py_dataset_adapter.py:121: UserWarning: Your `PyDataset` c
self._warn_if_super_not_called()
Epoch 1/10
32/32 — 208s 6s/step - accuracy: 0.5819 - loss: 0.6742 - val_accuracy: 0.7861 - val_loss: 0.5451
Epoch 2/10
32/32 — 186s 6s/step - accuracy: 0.8917 - loss: 0.3703 - val_accuracy: 0.8379 - val_loss: 0.4809
Epoch 3/10
32/32 — 194s 6s/step - accuracy: 0.9405 - loss: 0.2452 - val_accuracy: 0.8379 - val_loss: 0.4544
Epoch 4/10
32/32 — 188s 6s/step - accuracy: 0.9487 - loss: 0.1903 - val_accuracy: 0.8412 - val_loss: 0.4351
Epoch 5/10
32/32 — 232s 7s/step - accuracy: 0.9443 - loss: 0.1633 - val_accuracy: 0.8355 - val_loss: 0.4291
Epoch 6/10
32/32 — 240s 8s/step - accuracy: 0.9587 - loss: 0.1329 - val_accuracy: 0.8282 - val_loss: 0.4251
Epoch 7/10
32/32 — 191s 6s/step - accuracy: 0.9734 - loss: 0.1166 - val_accuracy: 0.8290 - val_loss: 0.4218
Epoch 8/10
32/32 — 199s 6s/step - accuracy: 0.9754 - loss: 0.1056 - val_accuracy: 0.8193 - val_loss: 0.4237
Epoch 9/10
32/32 — 199s 6s/step - accuracy: 0.9695 - loss: 0.0998 - val_accuracy: 0.8177 - val_loss: 0.4267
Epoch 10/10
32/32 — 237s 8s/step - accuracy: 0.9699 - loss: 0.0943 - val_accuracy: 0.8120 - val_loss: 0.4374

# Plot accuracy and loss
fig, axes = plt.subplots(1, 2, figsize=(12, 5))
axes[0].plot(history.history['accuracy'], label='Train Accuracy')
axes[0].plot(history.history['val_accuracy'], label='Validation Accuracy')
axes[0].set_title('Model Accuracy')
axes[0].legend()
axes[1].plot(history.history['loss'], label='Train Loss')
axes[1].plot(history.history['val_loss'], label='Validation Loss')
axes[1].set_title('Model Loss')
axes[1].legend()
plt.show()
```



```
# Confusion matrix
y_true = test_generator.classes
y_pred = model.predict(test_generator) > 0.5
cm = confusion_matrix(y_true, y_pred)
```




39/39 107s 3s/step

```
# Display confusion matrix with labels and percentages
fig, ax = plt.subplots(figsize=(6, 6))
cm_percent = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis] * 100
sns.heatmap(cm_percent, annot=True, fmt='.2f', cmap='Blues', xticklabels=['Pred Non-Recyclable', 'Pred Recyclable'],
            yticklabels=['Actual Non-Recyclable', 'Actual Recyclable'])
plt.xlabel('Predicted Label')
plt.ylabel('True Label')
plt.title('Confusion Matrix')
```



Text(0.5, 1.0, 'Confusion Matrix')



```
from sklearn.metrics import classification_report
# Classification report
print("Classification Report:")
print(classification_report(y_true, y_pred, target_names=['Non-Recyclable', 'Recyclable']))
```



Classification Report:
precision recall f1-score support

Non-Recyclable	0.72	0.93	0.81	533
Recyclable	0.93	0.72	0.81	701
accuracy			0.81	1234
macro avg	0.83	0.83	0.81	1234
weighted avg	0.84	0.81	0.81	1234

```
# Convert accuracy and loss to percentage
train_acc = [x * 100 for x in history.history['accuracy']]
val_acc = [x * 100 for x in history.history['val_accuracy']]
train_loss = [x * 100 for x in history.history['loss']]
val_loss = [x * 100 for x in history.history['val_loss']]
# Print accuracy and loss values
print("Final Training Accuracy: {:.2f}%".format(train_acc[-1]))
print("Final Validation Accuracy: {:.2f}%".format(val_acc[-1]))
print("Final Training Loss: {:.2f}%".format(train_loss[-1]))
print("Final Validation Loss: {:.2f}%".format(val_loss[-1]))
```

```
↗ Final Training Accuracy: 96.70%
Final Validation Accuracy: 81.20%
Final Training Loss: 9.16%
Final Validation Loss: 43.74%
```