

```
import os


# Create a directory for Kaggle config
os.makedirs("/root/.kaggle", exist_ok=True)

# Upload `kaggle.json`
from google.colab import files
files.upload() # Select and upload the downloaded kaggle.json file

# Move `kaggle.json` to the correct directory
!mv kaggle.json /root/.kaggle/

# Set permissions
!chmod 600 /root/.kaggle/kaggle.json

# Verify Kaggle API works
!kaggle datasets list
```

 Choose Files kaggle.json

- **kaggle.json**(application/json) - 67 bytes, last modified: 3/20/2025 - 100% done
Saving kaggle.json to kaggle.json

ref	title	size
atharvasoundankar/chocolate-sales	Chocolate Sales Data 🇮🇳🍫	14
abdulmalik1518/mobiles-dataset-2025	Mobiles Dataset (2025)	20314
mahmoudehemaly/students-grading-dataset	Student Performance & Behavior Dataset	520428
atharvasoundankar/global-water-consumption-dataset-2000-2024	Global Water Consumption Dataset (2000-2024) 🌍💧	1
adilshamim8/student-depression-dataset	Student Depression Dataset	467028
atharvasoundankar/global-food-wastage-dataset-2018-2024	🌍 Global Food Wastage Dataset (2018-2024) 🗑️	108
adilshamim8/temperature	Global Environmental Trends 2000-2024	22391
parsabrahamsari/wdi-education-health-and-employment-2011-2021	WDI: Education, Health & Employment (2011-2021)	136185
bhargavchirumamilla/netflix-movies-and-tv-shows-till-2025	Netflix Movies and TV shows till 2025	6471165
smayanj/netflix-users-database	Netflix Users Database	362555
atharvasoundankar/global-energy-consumption-2000-2024	Global Energy Consumption (2000-2024) 🔥⚡	251
ricgomes/global-fashion-retail-stores-dataset	Global Fashion Retail Sales	234910595
aniruddhawankhede/mental-heath-analysis-among-teenagers	Mental_Heath_Analysis_Among_Teenagers	177085
atharvasoundankar/global-music-streaming-trends-and-listener-insights	Global Music Streaming Trends & Listener Insights	97474
abdulmoiz12/amazon-stock-data-2025	Amazon Stock Data 2025	160515
brsahan/genomic-data-for-cancer	Genomic Data for Cancer	9134
atharvasoundankar/viral-social-media-trends-and-engagement-analysis	🚀 Viral Social Media Trends & Engagement Analysis	1072
adilshamim8/student-performance-on-an-entrance-examination	Student Performance on an Entrance Examination	4402
anandshaw2001/video-game-sales	Video Game Sales	390286
meharshanali/amazon-stocks-2025	Amazon Stocks 2025	165462


```
!kaggle datasets download -d jaiharish11499/wastedata
```

 Dataset URL: <https://www.kaggle.com/datasets/jaiharish11499/wastedata>
License(s): CC0-1.0

```
import zipfile

with zipfile.ZipFile("wastedata.zip", 'r') as zip_ref:
    zip_ref.extractall("waste_data")
```

```
import os
print(os.listdir("/content/"))
```

 ['.config', 'wastedata.zip', 'waste_data', 'sample_data']

```
train_folder = "/content/waste_data/d/Train"
test_folder = "/content/waste_data/d/Test"
```

```
import pandas as pd
import numpy as np
import glob
import os
from datetime import datetime
from packaging import version

import tensorflow as tf
from tensorflow import keras
from tensorflow.keras.applications import ResNet50
from tensorflow.keras.preprocessing import image_dataset_from_directory
from tensorflow.keras.preprocessing.image import load_img, img_to_array
from tensorflow.keras.callbacks import ModelCheckpoint, History
```

```

from tensorflow.keras.models import Sequential, load_model
from tensorflow.keras.layers import Conv2D, Lambda, MaxPooling2D, Dense, Dropout, Flatten
from tensorflow.keras.preprocessing.image import ImageDataGenerator
from tensorflow.keras.utils import to_categorical

```

```

from skimage.io import imread, imshow
from skimage.transform import resize
from IPython import display
import matplotlib.pyplot as plt
import seaborn as sns
from seaborn import heatmap
from sklearn.metrics import confusion_matrix

```

```

# Data augmentation for training
train_datagen = ImageDataGenerator(
    rescale=1./255,
    rotation_range=30,
    width_shift_range=0.2,
    height_shift_range=0.2,
    shear_range=0.2,
    zoom_range=0.2,
    horizontal_flip=True,
    fill_mode='nearest')

```

```

# No augmentation for validation/test
test_datagen = ImageDataGenerator(rescale=1./255)

```

```

# Load dataset
train_generator = train_datagen.flow_from_directory(
    train_folder,
    target_size=(224, 224),
    batch_size=32,
    class_mode='binary')

```

➡ Found 336 images belonging to 2 classes.

```

test_generator = test_datagen.flow_from_directory(
    test_folder,
    target_size=(224, 224),
    batch_size=32,
    class_mode='binary',
    shuffle=False)

```

➡ Found 64 images belonging to 2 classes.

```

from sklearn.utils.class_weight import compute_class_weight
# Compute class weights to address imbalance
class_labels = np.array(train_generator.classes)
class_weights = compute_class_weight(class_weight='balanced', classes=np.unique(class_labels), y=class_labels)
class_weight_dict = {i: class_weights[i] for i in range(len(class_weights))}

```

```

# Define ResNet model
base_model = ResNet50(weights='imagenet', include_top=False, input_shape=(224, 224, 3))
base_model.trainable = False

```

➡ Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/resnet/resnet50_weights_tf_dim_ordering_tf_kernels/94765736/94765736 0s 0us/step

```

model = keras.Sequential([
    base_model,
    keras.layers.GlobalAveragePooling2D(),
    keras.layers.Dense(128, activation='relu'),
    keras.layers.Dropout(0.5),
    keras.layers.Dense(1, activation='sigmoid')
])

```

```

from tensorflow.keras.optimizers import Adam
#Compile the model
model.compile(optimizer=Adam(learning_rate=0.0001), loss='binary_crossentropy', metrics=['accuracy'])

```

```

# Train model
history = model.fit(
    train_generator,

```


```
epochs=10,
validation_data=test_generator,
class_weight=class_weight_dict)
```

```

/usr/local/lib/python3.11/dist-packages/keras/src/trainers/data_adapters/py_dataset_adapter.py:121: UserWarning: Your `PyDataset` c
self._warn_if_super_not_called()
Epoch 1/10
11/11 ----- 99s 8s/step - accuracy: 0.3282 - loss: 0.8113 - val_accuracy: 0.6719 - val_loss: 0.6813
Epoch 2/10
11/11 ----- 76s 7s/step - accuracy: 0.5233 - loss: 0.7920 - val_accuracy: 0.7812 - val_loss: 0.6284
Epoch 3/10
11/11 ----- 75s 7s/step - accuracy: 0.6214 - loss: 0.7105 - val_accuracy: 0.7812 - val_loss: 0.6395
Epoch 4/10
11/11 ----- 85s 8s/step - accuracy: 0.5802 - loss: 0.6663 - val_accuracy: 0.7344 - val_loss: 0.6497
Epoch 5/10
11/11 ----- 89s 8s/step - accuracy: 0.5389 - loss: 0.6869 - val_accuracy: 0.7656 - val_loss: 0.6288
Epoch 6/10
11/11 ----- 86s 8s/step - accuracy: 0.5986 - loss: 0.7123 - val_accuracy: 0.7656 - val_loss: 0.6144
Epoch 7/10
11/11 ----- 86s 8s/step - accuracy: 0.6071 - loss: 0.7377 - val_accuracy: 0.7344 - val_loss: 0.6293
Epoch 8/10
11/11 ----- 77s 7s/step - accuracy: 0.5792 - loss: 0.7442 - val_accuracy: 0.7500 - val_loss: 0.6267
Epoch 9/10
11/11 ----- 86s 8s/step - accuracy: 0.5945 - loss: 0.6370 - val_accuracy: 0.7500 - val_loss: 0.6207
Epoch 10/10
11/11 ----- 76s 7s/step - accuracy: 0.4807 - loss: 0.7716 - val_accuracy: 0.5938 - val_loss: 0.6740
```

```

# Plot accuracy and loss
fig, axes = plt.subplots(1, 2, figsize=(12, 5))
axes[0].plot(history.history['accuracy'], label='Train Accuracy')
axes[0].plot(history.history['val_accuracy'], label='Validation Accuracy')
axes[0].set_title('Model Accuracy')
axes[0].legend()
axes[1].plot(history.history['loss'], label='Train Loss')
axes[1].plot(history.history['val_loss'], label='Validation Loss')
axes[1].set_title('Model Loss')
axes[1].legend()
plt.show()
```



```


# Confusion matrix
y_true = test_generator.classes
y_pred = model.predict(test_generator) > 0.5
cm = confusion_matrix(y_true, y_pred)
```

```
2/2 ----- 14s 6s/step
```

```

# Display confusion matrix with labels and percentages
fig, ax = plt.subplots(figsize=(6, 6))
cm_percent = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis] * 100
sns.heatmap(cm_percent, annot=True, fmt='.2f', cmap='Blues', xticklabels=['Pred Non-Recyclable', 'Pred Recyclable'],
            yticklabels=['Actual Non-Recyclable', 'Actual Recyclable'])
plt.xlabel('Predicted Label')
plt.ylabel('True Label')
plt.title('Confusion Matrix')
```

Text(0.5, 1.0, 'Confusion Matrix')



```
from sklearn.metrics import classification_report
# Classification report
print("Classification Report:")
print(classification_report(y_true, y_pred, target_names=['Non-Recyclable', 'Recyclable']))
```

Classification Report:

	precision	recall	f1-score	support
Non-Recyclable	0.34	0.93	0.50	14
Recyclable	0.96	0.50	0.66	50
accuracy			0.59	64
macro avg	0.65	0.71	0.58	64
weighted avg	0.83	0.59	0.62	64

```
# Convert accuracy and loss to percentage
train_acc = [x * 100 for x in history.history['accuracy']]
val_acc = [x * 100 for x in history.history['val_accuracy']]
train_loss = [x * 100 for x in history.history['loss']]
val_loss = [x * 100 for x in history.history['val_loss']]
# Print accuracy and loss values
print("Final Training Accuracy: {:.2f}%".format(train_acc[-1]))
print("Final Validation Accuracy: {:.2f}%".format(val_acc[-1]))
print("Final Training Loss: {:.2f}%".format(train_loss[-1]))
print("Final Validation Loss: {:.2f}%".format(val_loss[-1]))
```

Final Training Accuracy: 50.89%
Final Validation Accuracy: 59.38%
Final Training Loss: 70.28%
Final Validation Loss: 67.40%

