

Python

[Learn Python](#)[GUI](#)[PyQt](#)[Machine Learning](#)[Web Development](#)[Django](#)


kmeans elbow method

ninja | July 2, 2017

Find k for kmeans using the elbow method?

The KMeans algorithm can cluster observed data. But how many clusters (k) are there?

The elbow method finds the optimal value for k (#clusters).



Related course:

[Data Science and Machine Learning with Python – Hands On!](#)

Determine optimal k

The technique to determine K, the number of clusters, is called the elbow method.

Downloads

[Free Ebook](#)

[PyQt Examples](#)

Machine Learning

[Machine Learning](#)

[Machine Learning Tasks](#)

[bag of words](#)

[bag of words](#)

[euclidian distance](#)

[Decision tree](#)

[Decision tree](#)

[visual example](#)

[kmeans clustering algorithm](#)

[kmeans clustering centroid](#)

[kmeans elbow method](#)

[kmeans text clustering](#)

[Neural Network](#)

[Neural Network Example](#)

[Linear Regression](#)

[logistic regression](#)


With a bit of fantasy, you can see an elbow in the chart below.

We'll plot:

values for K on the horizontal axis

the distortion on the Y axis (the values calculated with the cost function).

This results in:



When K increases, the centroids are closer to the clusters centroids.

The improvements will decline, at some point rapidly, creating the elbow shape.

That point is the optimal value for K. In the image above, K=3.

Elbow method example

The example code below creates finds the optimal value for k.



[spam filter](#)

[Translate](#)

[Speech
Recognition](#)

[Text to speech](#)

[Deep Learning](#)

```

# clustering dataset
# determine k using elbow method

from sklearn.cluster import KMeans
from sklearn import metrics
from scipy.spatial.distance import cdist
import numpy as np
import matplotlib.pyplot as plt

x1 = np.array([3, 1, 1, 2, 1, 6, 6, 6, 5, 6,
               5, 4, 5, 6, 5, 8, 6, 7, 6, 7,
               5, 4, 5, 6, 5, 8, 6, 7, 6, 7])
x2 = np.array([5, 4, 5, 6, 5, 8, 6, 7, 6, 7,
               5, 4, 5, 6, 5, 8, 6, 7, 6, 7,
               5, 4, 5, 6, 5, 8, 6, 7, 6, 7])

plt.plot()
plt.xlim([0, 10])
plt.ylim([0, 10])
plt.title('Dataset')
plt.scatter(x1, x2)
plt.show()

# create new plot and data
plt.plot()
X = np.array(list(zip(x1, x2))).reshape(len(x1))
colors = ['b', 'g', 'r']
markers = ['o', 'v', 's']

# k means determine k
distortions = []
K = range(1,10)
for k in K:
    kmeanModel = KMeans(n_clusters=k).fit(X)
    kmeanModel.fit(X)
    distortions.append(sum(np.min(cdist(X, kn

# Plot the elbow
plt.plot(K, distortions, 'bx-')
plt.xlabel('k')
plt.ylabel('Distortion')
plt.title('The Elbow Method showing the optimal number of clusters')
plt.show()

```

[Previous Post](#)

[Next Post](#)

Categories: [Machine Learning](#) | [Comments](#)

Leave a Reply

You must be [logged in](#) to post a comment.

Login:



Login with twitter



Login with google

[← Apache Spark](#)

[Web Scraping with Pandas and BeautifulSoup →](#)

© 2017 Python