

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: By default - 1p; A – 2p; B - 4p; C - 3p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. Let L be a list of numbers and given the following PROLOG predicate definition **f(list, integer)**, with the flow model (i, o):

f([], 0).

f([H|T], S):-**f(T, S1)**, S1<H,!, S is H.

f(_|T], S):-**f(T, S1)**, S is S1.

Rewrite the definition in order to avoid the recursive call **f(T, S)** in both clauses. Do NOT redefine the predicate. Justify your answer.

B. Write a PROLOG program that generates the list of all subsets of k elements (all elements being odd numbers) in arithmetic progression. Write the mathematical models and flow models for the predicates used. For example, for $L=[1,5,2,9,3]$ and $k=3 \Rightarrow [[1,5,9],[1,3,5]]$ (not necessarily in this order).

C. An n-ary tree is represented in Lisp as (node subtree1 subtree2 ...). Write a Lisp function to replace all nodes on the given level **k** with a given value **e**. The root level is assumed zero. **A MAP function shall be used.** ***Example*** for the tree (a (b (g)) (c (d (e)) (f))) and **e=h**
(a) k=2 => (a (b (h)) (c (h (e)) (h)))) **(b)** k=4 => (a (b (g)) (c (d (e)) (f)))