

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: By default - 1p; A – 2p; B - 4p; C - 3p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. The following function definition in LISP is given

```
(DEFUN F(L)
  (COND
    ((NULL L) NIL)
    (> (F (CAR L)) 0) (CONS (F (CAR L)) (F (CDR L))))
    (T (F (CAR L)))
  )
)
```

Rewrite the definition in order to avoid the repeated recursive call **(F (CAR L))**. Do NOT redefine the function. Do NOT use SET, SETQ, SETF. Justify your answer.

B. Write a PROLOG program that generates the list of all subsets with at least N elements such that the value of sum of all elements from each subset is divisible with 3, from a list of integers. Write the mathematical models and flow models for the predicates used. For example, for the list $L=[2,3,4]$ and $N=1 \Rightarrow [[3],[2,4],[2,3,4]]$ (not necessarily in this order).

C. Given a nonlinear list, write a Lisp function to return the list with all non-numerical atoms on even levels removed. The superficial level is assumed 1. **A MAP function shall be used.**

Example for the list (a (1 (2 b)) (c (d))) the result is (a (1 (2 b)) ((d)))