

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: By default - 1p; A – 2p; B - 4p; C - 3p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. Let **G** be LISP function and given the following definition

```
(DEFUN F(L)
  (COND
    ((NULL L) 0)
    (> (G L) 2) (+(G L) (F (CDR L))))
    (T (G L))
  )
)
```

Rewrite the definition in order to avoid the repeated call **(G L)**. Do NOT redefine the function. Do NOT use SET, SETQ, SETF. Justify your answer.

B. Write a PROLOG program that generates the list of all permutations with the property the absolute value of difference between two consecutive values from each permutation is ≤ 3 . Write the mathematical models and flow models for the predicates used. For example, for $L=[2,7,5] \Rightarrow [[2,5,7], [7,5,2]]$ (not necessarily in this order).

C. Given a nonlinear list, write a Lisp function to replace all even numerical values with their natural successor. **A MAP function shall be used.**

Example for the list (1 s 4 (2 f (7))) the result is (1 s 5 (3 f (7))).