

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: By default - 1p; A – 2p; B - 4p; C - 3p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. Given the following PROLOG predicate definition **f(integer, integer)**, with the flow model (i, o):

f(20, -1):-!.

f(I,Y):-J is I+1, **f(J,V)**, V>0, !, K is J, Y is K.

f(I,Y):-J is I+1, **f(J,V)**, Y is V-1.

Rewrite the definition in order to avoid the recursive call **f(J,V)** in both clauses. Do NOT redefine the predicate. Justify your answer.

B. Write a PROLOG program that generates the list of all permutations with the property the absolute value of difference between two consecutive values from each permutation is ≤ 3 . Write the mathematical models and flow models for the predicates used. For example, for $L=[2,7,5] \Rightarrow [[2,5,7], [7,5,2]]$ (not necessarily in this order).

C. Given a nonlinear list, write a Lisp function to return the list with all atoms on level **k** removed. The superficial level is assumed 1. **A MAP function shall be used.**

Example for the list (a (1 (2 b)) (c (d)))

a) k=2 => (a ((2 b)) ((d))) **b)** k=1 => ((1 (2 b)) (c (d))) **c)** k=4 => the list does not change

C. Given a nonlinear list, write a Lisp function to return the list with all occurrences of an element **e** removed. **A MAP function shall be used.**

Example **a)** if the list is (1 (2 A (3 A)) (A)) and **e** is A => (1 (2 (3)) NIL)

b) if the list is (1 (2 (3))) and **e** is A => (1 (2 (3)))