

Functional and logic programming

- written exam -

Important:

1. Subjects are graded as follows: By default - 1p; A – 2p; B - 4p; C - 3p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

A. The following function definition in LISP is given

```
(DEFUN F(L)
  (COND
    ((NULL L) 0)
    (> (F (CAR L)) 2) (+ (F (CDR L)) (F(CAR L))))
    (T (+ (F (CAR L)) 1))
  )
)
```

Rewrite the definition in order to avoid the repeated recursive call **F (CAR L)**. Do NOT redefine the function. Do NOT use SET, SETQ, SETF. Justify your answer.

B. Write a PROLOG program that generates the list of all subsets of even sum, using the elements of a list. Write the mathematical models and flow models for the predicates used.
For example, for the list $L=[2, 3, 4] \Rightarrow [[],[2],[4],[2,4]]$ (not necessarily in this order).

C. An n-ary tree is represented in Lisp as (node subtree1 subtree2 ...). Write a Lisp function to determine the number of nodes on level **k**. The root level is assumed zero. **A MAP function shall be used.** ***Example*** for the tree (a (b (g)) (c (d (e)) (f)))
a) k=2 => nr=3 (g d f) **b)** k=4 => nr=0 ()